# **URBAN DESIGN COMMISSION APPLICATION**



City of Madison Planning Division Madison Municipal Building, Suite 017 215 Martin Luther King, Jr. Blvd. P.O. Box 2985 Madison, WI 53701-2985 (608) 266-4635



Date Received _	9/22/25 10:39 a.m.	☐ Initial Submittal
Paid		☐ Revised Submittal

Complete all sections of this application, including the

If you need an interpreter, translator, materials in alternate formats or other accommodations to access these forms, please call the Plannina Division at (608) 266-4635.

5	project requires bo submittals, a com	oth UDC <u>and</u> L pleted <u>Land U</u>	on requested. If your and Use application and are also required to	Si necesit acceder o Yog tias ntaub ni	a interprete, traductor, materiales en diferentes formatos, u otro tipo de ayuda para a estos formularios, por favor llame al (608) 266-4635.  koj xav tau lib tug neeg txhais lus, tus neeg txhais ntawv, los sis xav tau cov tawv ua lwm hom ntawv los sis lwm cov kev pab kom paub txog cov lus qhia hu rau Koog Npaj (Planning Division) (608) 266-4635.		
1. F	Project Information	on					
	Address (list all add	resses on the nr	oject site): 801 S Whitney W	ay Madi	son WI		
			servoir Reconstruction				
	ittle: om wente	rreimouse and ne	servon neconstruction				
2. /	Application Type	(check all that	apply) and Requested Da	te			
-	JDC meeting date	requested No	wember 5th				
	☐ New develop	nent 🗆	Alteration to an existing of	or prev	iously-approved development		
[	☐ Informational		Initial Approval	2	Final Approval		
3. F	Project Type						
[	☐ Project in an U	rban Design Dist	trict	Sign	nage		
[			District (DC), Urban		Comprehensive Design Review (CDR)		
			ed-Use Center District (MXC)		Modifications of Height, Area, and Setback		
L			ment Center District (SEC), I), or Employment Campus				
	District (EC)			Oth	ner		
[	☐ Planned Devel			<b>2</b>	Please specify		
		Development Pla Implementation I		Madison Water Utility Project - Public			
1			dential Building Complex				
			The second second				
4. /	Applicant, Agent,	and Property	Owner Information				
1	Applicant name	Pete Holmgrer	1		mpany Madison Water Utility		
S	Street address	119 E Olin Ave		City/State/Zip Madison, WI 53713			
1	Felephone	608 261 5530		Email pholmgren@madisonwater.org  Company SEH			
ş	Project contact pe	rson <u>Isaac Stei</u> r	meyer				
5	Street address	10 N. Bridge St	reet	Cit	y/State/Zip Chippewa Falls WI 54729		
1	Telephone	715-505-4092		Em	isteinmeyer@sehinc.com		
	Property owner (if	not applicant)					
S	Street address			Cit	y/State/Zip		
1	Felephone	<del></del>	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		ail		
					0*		

# **URBAN DESIGN DEVELOPMENT PLANS CHECKLIST**



The items listed below are minimum application requirements for the type of approval indicated. Please note that the UDC and/or staff may require additional information in order to have a complete understanding of the project.

1. Informa	tional Presentation								
	Letter of Intent (If the project is within an Urban Design District, a summary of how the development proposal addresses the district criteria is required)  Contextual site information, including photographs and layout of adjacent buildings/structures  Site Plan  Two-dimensional (2D) images of proposed buildings or structures.	Providing additional information beyond these minimums may generate a greater level of feedback from the Commission.	Requirements for All Plan Sheets  1. Title block 2. Sheet number 3. North arrow 4. Scale, both written and graphic 5. Date 6. Fully dimensioned plans, scaled at 1" = 40' or larger  ** All plans must be legible, including the full-sized landscape and lighting plans (if required)						
2. Initial A <sub>l</sub>	pproval								
⊠	Locator Map		)						
×	Letter of Intent (If the project is within a Urban Design District, a summary of <a diam<="" href="https://example.com/how/how/how/how/how/how/how/how/how/how&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;&lt;/td&gt;&lt;td&gt;Contextual site information, including photograph&lt;/td&gt;&lt;td&gt;•&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;&lt;/td&gt;&lt;td&gt;Site Plan showing location of existing and pr&lt;br&gt;bike parking, and existing trees over 18" td=""><td></td><td>es, bike lanes, beyond these minimums may generate a</td></a>								es, bike lanes, beyond these minimums may generate a
X	Landscape Plan and Plant List (must be legible		greater level of						
	Building Elevations in <b>both</b> black & white and cand color callouts	color for all building sides, inclu	uding material feedback from the Commission.						
	PD text and Letter of Intent (if applicable)		J						
3. Final Ap	proval								
All the re	equirements of the Initial Approval (see above) Grading Plan	, <u>plus</u> :							
X	Lighting Plan, including fixture cut sheets and	photometrics plan (must be le	egible)						
X	Utility/HVAC equipment location and screening	g details (with a rooftop plan i	if roof-mounted)						
X	Site Plan showing site amenities, fencing, tras	h, bike parking, etc. (if applical	ble)						
NA 🗆	PD text and Letter of Intent (if applicable)								
<b>X</b>	Samples of the exterior building materials								
NA 🗆	Proposed sign areas and types (if applicable)								
4. Signage	Approval (Comprehensive Design Review (CDI	R), Sign Modifications, and Sig	gn Exceptions (per <u>Sec. 31.043(3)</u> )						
	Locator Map								
	Letter of Intent (a summary of how the proposed signal and the proposed signal		, ,						
	Contextual site information, including photogroup project site		·						
	Site Plan showing the location of existing signal driveways, and right-of-ways								
	Proposed signage graphics (fully dimensioned	, scaled drawings, including ma	aterials and colors, and night view)						

Perspective renderings (emphasis on pedestrian/automobile scale viewsheds)

Graphic of the proposed signage as it relates to what the Ch. 31, MGO would permit

Illustration of the proposed signage that meets Ch. 31, MGO compared to what is being requested

### 5. Required Submittal Materials

### Application Form

 A completed application form is required for <u>each</u> UDC appearance. For projects also requiring Plan Commission approval, applicants must also have submitted an accepted application for Plan Commission consideration prior to obtaining any formal action (Initial or Final Approval) from the UDC.

### Letter of Intent

- If the project is within an Urban Design District, a summary of how the development proposal addresses the district criteria is required.
- For signage applications, a summary of how the proposed signage is consistent with the applicable Comprehensive Design Review (CDR) or Signage Modification review criteria is required.
- Development Plans (Refer to checklist on Page 4 for plan details)
- Filing Fee (Refer to Section 7 (below) for a list of application fees by request type)

### Electronic Submittal

- Complete electronic submittals <u>must</u> be received prior to the application deadline before an application will be scheduled
  for a UDC meeting. Late materials will not be accepted. All plans must be legible and scalable when reduced. Individual
  PDF files of each item submitted should be submitted via email to <u>UDCapplications@cityofmadison.com</u>. The email
  must include the project address, project name, and applicant name.
- Email Size Limits. Note that an individual email cannot exceed 20MB and it is the responsibility of the applicant, to present files
  in a manner that can be accepted. Applicants who are unable to provide the materials electronically should contact the Planning
  Division at (608) 266-4635 for assistance.

### Notification to the District Alder

Please provide an email to the District Alder notifying them that you are filing this UDC application. Please send this as
early in the process as possible and provide a copy of that email with the submitted application.

<ol><li>Applicant Declaration</li></ol>
---

- Prior to submitting this application, the applicant is required to discuss the proposed project with Urban Design Commission staff.
   This application was discussed with Jessica Vaughn on 8/19/2025
- The applicant attests that all required materials are included in this submittal and understands that if any required information is not provided by the application deadline, the application will not be placed on an Urban Design Commission agenda for consideration.

Name of applicant Pete Holmgren		Relationship to property Madison Water Utility - Owner	
Authorizing signature of property owner	Eta felan	Date 9/19/2025	

### 7. Application Filing Fees

Fee payments are due by the submittal date. Payments received after the submittal deadline may result in the submittal being scheduled for the next application review cycle. Fees may be paid in-person, via US Mail, or City drop box. If mailed, please mail to: City of Madison Building Inspection, P.O. Box 2984, Madison, WI 53701-2984. The City's drop box is located outside the Municipal Building at 215 Martin Luther King, Jr. Blvd. on the E Doty Street side of the building. Please make checks payable to City Treasurer, and include a completed application form or cover letter indicating the project location and applicant information with all checks mailed or submitted via the City's drop box.

NOTE: NO FEE REQUIRED. THE PROJECT IS A

Please consult the schedule below for the appropriate fee for your request: CITY OF MADISON WATER UTILITY PROJECT.

Urban Design Districts: \$350 (per §33.24(6) MGO).
Minor Alteration in the Downtown Core District (DC) or Urban Mixed-Use District (UMX): \$150 (per §33.24(6)(b) MGO)
Comprehensive Design Review: \$500 (per §31.041(3)(d)(1)(a) MGO)

- Minor Alteration to a Comprehensive Sign Plan: \$100 (per §31.041(3)(d)(1)(c) MGO)
- All other sign requests to the Urban Design Commission, including, but not limited to: appeals from the decisions of the Zoning Administrator, requests for Sign Modifications (of height, area, and setback), and additional sign code approvals: \$300 (per §31.041(3)(d)(2) MGO)
- A filing fee is not required for the following project applications if part of the combined application process involving both Urban Design Commission and Plan Commission:
- Project in the Downtown Core District (DC), Urban Mixed-Use District (UMX), or Mixed-Use Center District (MXC)
- Project in the Suburban Employment Center District (SEC), Campus Institutional District (CI), or Employment Campus District (EC)
- Planned Development (PD): General Development Plan (GDP) and/or Specific Implementation Plan (SIP)
- Planned Multi-Use Site or Residential Building Complex



Madison Water Utility - Unit Well 12 Wellhouse and Reservoir Letter of Intent – Land Use Application and Urban Design Commission September 22, 2025

### **Project Description**

Madison Water Utility is proposing to reconstruct its existing Unit Well 12 (UW 12), located at 801 South Whiteney Way, Madison, WI. The project will enhance UW 12's dual-pressure zone water supply capabilities to serve water to the west side of Madison, providing additional operational flexibility and increased water supply reliability. The project is also needed to address Wisconsin Department of Natural Resources (WDNR) deficiencies at the wellhouse. The project requires demolition and reconstruction of the existing well house and reservoir.

### **Existing Conditions**

The well and reservoir site is located on the north side of the Beltline along South Whitney Way. It is located on the land between the westbound exit ramp and the Beltline itself. The original well and pump house was built in 1957 and was designed by Water Utility engineering staff. The rough limestone in an ashlar pattern is seen on many wells throughout Madison that were built during this era and is recognizable as a Water Utility facility.

### **Proposed Design**

The proposed reconstructed well house includes design features to respect the appearance of the existing structure. A slightly larger footprint is required to house the necessary equipment for UW 12 and meet model WDNR NR811 design standards. The architectural finishes are selected to mimic the existing structure's limestone finish. Stone was chosen to clad the building, and a smooth finish stone is proposed in a more regular pattern. The color of the stone is intended to appear similar to the existing building.

### Site

The site changes around the well house are minimal. The most notable change is the proposed reservoir location and size. A 1.0 million gallon reservoir is proposed versus the existing 150,000 gallon reservoir. The reservoir is proposed to be located to the east of the well house. The driveway will be raised slightly to provide accessibility to the rear doors. Asphalt pavement will generally be replaced in kind. The drive and parking area will be used by service vehicles and allows the vehicles to turn around on the site to exit onto Whitney Way facing the traffic. The existing reservoir location will be graded to match surrounding areas and restored to grass surface. Landscaping and restoration is also proposed.

### **Site Location**

Address: 801 South Whitney Way

### **Land Use Zoning Approval**

The project is being submitted to be re-zoned from CN to PR, as well as to allow for conditional use of the new well house and reservoir.

### **Project Schedule**

September 22, 2025 Urban Design and Plan Commission Application

October X, 2025 PIM (date TBD)

November 5, 2025 Urban Design Commission

November 17, 2025 Plan Commission
November 25, 2025 Common Council
January 2026 Plans out for Bid
February 2026 Bids received

February 2026 Project Approval/Award
March 2026 Contracts Signed
May 2026 Start of Construction
September 2026 Structure Demolition
October 2027 Construction Completed

### **Project Team**

Madison Water Utility Peter Holmgren, PE 119 East Olin Avenue

Madison, WI 53713

Engineer/Architect:

SEH, Inc.

Jeffrey Nussbaum, PE
10 North Bridge Street
Isaac Steinmeyer, PE
Chippewa Falls, WI 54729
Jim Lynch, AIA

### **Building Size**

Existing Wellhouse Building: 1,122 SF

Existing Reservoir: 1,810 SF

Proposed Wellhouse Building: 1,505 SF

Proposed Reservoir: 5,540 SF

### **Auto and Bike Parking Stalls**

There is room for two maintenance vehicles to be parked on site and one handicap stall, for a total of three parking spaces. There are no bike parking stalls proposed. It is not a public building and the only visitors to the facility will be water utility staff.

### Lot Coverage & Useable Open Space

Total Lot Area: 46,090 SF or 1.06 AC

Building and Pavement Area (Existing): 8300 SF

Building and Pavement Area (Proposed): 13,595 SF

Total Open Area (Proposed): 32, 495 SF

## Location/Aerial Map



An aerial view showing the pump house and the reservoir along South Whitney Way. The reservoir is the round building to the northeast of the pump house.

# **Existing Photos**



View from Whitney Way of the Wellhouse



The rear of the existing Wellhouse.



Interior of existing Wellhouse.




Interior of existing Wellhouse.



Existing Reservoir to be removed and replaced.

# CONSTRUCTION DRAWINGS FOR UNIT WELL 12 RECONSTRUCTION FOR MADISON WATER UTILITY MADISON, WISCONSIN









Project O

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

801 S. Whitney Way Madison WI, 53711

training is an instrument of service and shall in the property of Short Eliotit Heraldicision, Inc. 12 in the service of Short Eliotit Heraldicision, Inc. 12 in the service of Short Eliotit Heraldicision, Inc. 12 in the service of Short Eliotit Heraldicision of Short Eliotic Office of Short El

Checked By Drawn By

NR SUBMITTAL

REVISION SCHEDULE

G001

GENERAL STRUCTURAL ABBREVIATIONS, SYMBOLS AND TABLES S001

S002 GENERAL STRUCTURAL NOTES

GENERAL INFORMATION AND ABBREVIATIONS A001

P001 GENERAL PROCESS INFORMATION

HYDRAULIC PROFILE, FLOW SCHEMATIC AND BASIS OF DESIGN P002

MECHANICAL SYMBOLS AND ABBREVIATIONS M001

SYMBOLS, ABBREVIATIONS AND NOTES E001

**CIVIL** 

C101 SITE PLAN

C102 REMOVALS PLAN

C103 GRADING & EROSION CONTROL PLAN

C104 WATER MAIN SYSTEM MAP

## 01 WELLHOUSE

01 S101	FOUNDATION PLAN
01 S102	FLOOR PLAN
01 S103	ROOF FRAMING PLAN
01 S201	REINFORCING ELEVATIONS
01 S301	BUILDING SECTIONS
01 S501	CONCRETE DETAILS

01 S502 PRECAST AND MASONRY DETAILS

01 S503 STRUCTURAL DETAILS

BUILDING DEMOLITION REFERENCE DRAWING 01 A002

01 A003 BUILDING DEMOLITION REFERENCE DRAWING

01 A004 CODE PLAN FLOOR PLAN 01 A101

01 A102 CLERESTORY PLAN

01 A103 ROOF PLAN

EXTERIOR ELEVATIONS 01 A201

01 A301 BUILDING SECTIONS WALL SECTIONS 01 A302 WALL SECTIONS

01 A501 DETAILS

01 A303

01 A601

01 A502 DETAILS

01 P101 WELLHOUSE FLOOR PLAN 01 P301 WELLHOUSE SECTIONS

01 P302 WELLHOUSE SECTIONS 01 P501 WELLHOUSE PROCESS DETAILS WELLHOUSE PROCESS DETAILS 01 P502

01 P503 WELL NO. 12 PROFILE & ASSEMBLY DETAILS

SCHEDULES AND DETAILS

01 M101

DOMESTIC WATER AND GAS PLAN 01 M102 SANITARY WASTE AND VENT PLAN 01 M103

01 M104 MECHANICAL ROOF PLAN 01 M105 FIRE PROTECTION PLAN

01 M201 RISER DIAGRAMS 01 M202 RISER DIAGRAMS

01 M301 MECHANICAL SCHEDULES 01 M302 PLUMBING SCHEDULES

01 M303 MECHANICAL DETAILS MECHANICAL DETAILS 01 M304

ELECTRICAL REMOVAL PLAN 01 E071

01 E101 ELECTRICAL SITE PLAN

01 E201 LIGHTING PLAN

01 E301 POWER AND INSTRUMENTATION PLAN

01 E501 ONE-LINE DIAGRAM ONE-LINE DIAGRAM 01 E502 01 E601 ELECTRICAL SCHEMATICS

01 E701 SCHEDULES 01 E801 ELECTRICAL DETAILS

# 02 RESERVOIR

02 P101

02 P505

02 P506

02 P301 WATER STORAGE TANK SECTION WATER STORAGE TANK ELEVATIONS & SECTIONS 02 P302 WATER STORAGE TANK STRUCTURAL DETAILS 02 P501 WATER STORAGE TANK INLET, OUTLET, & MIXING SYSTEM DETAILS 02 P502 WATER STORAGE TANK ACCESSORY DETAILS 02 P503 02 P504 WATER STORAGE TANK ACCESSORY DETAILS

WATER STORAGE TANK ACCESSORY DETAILS

WATER STORAGE TANK ACCESSORY DETAILS

WATER STORAGE TANK PLAN & SECTION

### SHEET NUMBERING LEGEND

### STRUCTURE IDENTIFIER OR SHEET TYPE

G GENERAL INFORMATION

С SITE WORK

D DETAILS

**SERIES DRAWING NUMBER** 

GENERAL

SHEET

01

P101

PLAN VIEWS 100 200 ELEVATION VIEWS

SECTION VIEWS 300

400 LARGE SCALE VIEWS

500 DETAILS

600 SCHEDULES

900 3D VIEWS

### DISCIPLINE

**G** GENERAL

CIVIL С

S STRUCTURAL ARCHITECTURAL

PROCESS

М MECHANICAL


Ε ELECTRICAL

INSTRUMENTATION / CONTROLS


Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SHEET INDEX



Name	Location	Size	<u>Type</u>	<u>Operator</u>	Purpose	Oper. Press.	Fall Pos.	<u>Notes</u>
V-ZBP-1	Bypass Between Zone 7 and 8 Discharge Piping	12-inch	Butterfly	Electric Actuator	Flow Directional Control water flow to each zone.	< 90 psi	Closed	Closed = One pump feeds each zone, Open = Two pumps feed one zone.
V-Z7-1	Discharge to Zone 7	12-inch	Butterfly	Electric Actuator	Controls Water Flow to Zone 7	< 90 psi	Open	
V-Z8-1	Discharge to Zone 8	12-inch	Butterfly	Electric Actuator	Controls Water Flow to Zone 8	< 90 psi	Open	
V-RF-1	Reservoir Fill Piping	8-inch	Butterfly	Electric Actuator	Controls Water Flow Dist. To Reservoir	< 90 psi	Closed	
V-PSV/PRV-1	Connection between Zone 7 and 8	8-inch	Globe	Solenoid	Move flow from Zone 8 to 7 (PRV) or Zone 7 to 8 (PSV)	< 50 psi	Closed	Set to provide a minimum pressure to each side of the valve.
Standard Proces	ss Valves							
<u>Name</u>	<u>Location</u>	Size	<u>Type</u>	<u>Operator</u>			Notes	
V-AV-1	Unit Well 12 Wellhead	3-inch	Air Release / Vacuum	Pressure		NPT	Threaded	
CV-RW-1	Unit Well 12 Wellhead	12-inch	Swing Check	Counter Weight		F	langed	
V-RW-1	Well 12 Isolation	12-inch	Butterfly	Handwheel		F	langed	
V-HSP1-1	High Lift Pump 1 Suction	8-inch	Butterfly	Handwheel		F	langed	
V-HSP2-1	High Lift Pump 2 Suction	8-inch	Butterfly	Handwheel		Flanged		
CV-HSP1	High Lift Pump 1 Discharge	12-inch	Swing Check	Counter Weight	Flanged			
CV-HSP2	High Lift Pump 2 Discharge	12-inch	Swing Check	Counter Weight		F	langed	
V-HSP1-2	High Lift Pump 1 Discharge	6-inch	Butterfly	Handwheel		F	langed	
V-HSP2-2	High Lift Pump 2 Discharge	6-inch	Butterfly	Handwheel		F	langed	
V-ZBP-3	Isolation (Zone 7/8)	8-inch	Butterfly	Handwheel		F	langed	
V-AR-Z7	Zone 7 Discharge Piping	2-inch	Air Release	Pressure		NPT Threaded		
V-AR-Z8	Zone 8 Discharge Piping	2-inch	Air Release	Pressure		MDT	Threaded	






Madison Water Utility
UNIT WELL 12 RECONSTRUCTION

MADWU 182222 IS

HYDRAULIC PROFILE, FLOW SCHEMATIC AND BASIS OF DESIGN

P002



么 SEH

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

1 S. Whitney Way Idison WI. 53711

ng is an instrument of service and shall properly of Short Eliott Hendrickson, Inc. sofraving, concepts and ideas contained II not be used, reproduced, revised, or

MADWU\_182222

09/22/2025

SEH Project Checked By Drawn By

ecked By Iwn By

Project Status

DNR SUBMITTAL

CITY SUBMITTAL

REVISION SCHE

REV. # DESCRIPTION

SITE PLAN



MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

801 S. Whitney Way Madison WI, 53711

ing is an instrument of service and shall property of Short Elliott Hendrickson, Inc. scrawing, concepts and ideas contained or line be used, reproduced, revised or thout the express written approval of SEH, or distribution of this drawing to meet

MADWU\_182222

09/22/2025

SEH Project Checked By Drawn By

Project Status

DNR SUBMITTAL

CITY SUBMITTAL

CITY SUBMITTAL

REV. # DESCRIPTIO

REMOVALS PLAN



MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

S. Whitney Way ison WI, 53711

strument of service and shall
of Short Elliott Hendrickson, Inc.
concepts and ideas contained
and removaled registed or

cation in derogation of any of t

SEH Project Checked By Drawn By

Project Status

DNR SUBMITTAL

CITY SUBMITTAL

SUBMITTAL 09/22/2025

REV. # DESCRIPTI

GRADING & EROSION CONTROL PLAN



MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

an instrument of service and shall rify of Short Eliott Hendrickson,

MADWU\_182222 KB PAL

09/22/2025

EH Project

SEH Project Checked By Drawn By

Project Status


DNR SUBMITTAL

CITY SUBMITTAL

REVISION SCHEDULE

REV. # DESCRIPTION

WATER MAIN SYSTEM MAP



FOUNDATION PLAN

1/4" = 1'-0"



### PLAN NOTES

- 1. TWE = TOP OF FOUNDATION WALL ELEVATION
- 2. TFE = TOP OF FOOTING ELEVATION = 990.67 U.N.O.
- 3. VERIFY DIMENSIONS, ELEVATIONS, AND MATERIALS WITH ARCHITECTURAL AND PROCESS.
- CONTRACTOR OPTIONS AT MECHANICAL & ELECTRICAL LINES THROUGH FOUNDATION - SEE H/DS1, J/DS1, K/DS1, L/DS1
- 5. 'Fx' DENOTES FOOTING TYPE. REFERENCE SCHEDULE ON THIS SHEET.

	FOOTING S	SCHEDULE
MARK	SIZE	REINFORCING
F1	24" WIDE x 12" DEEP x CONTINUOUS	(2) #5 REBAR, BOTTOM
F2	36" WIDE x 12" DEEP x CONTINUOUS	(3) #5 REBAR, BOTTOM
F3	24" WIDE x 12" DEEP x CONTINUOUS THICKENED SLAB	(2) #5 REBAR, BOTTOM

SEE SHEET S2 FOR LOCATION OF THICKENED SLABS F3.



Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

801 S. Whitney Way Madison WI, 53711

ment of service and shall of Elioti Hendrickson, Inc. copts and ideas contained reproduced, revised, or ses written approved of SEH.

Issue Date 6/30/2025

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL

REVISION SCHEDU

REV.# DESCRIPTION

FOUNDATION PLAN

01 S101



### **PLAN NOTES**

- 1. FFE, FINISHED FLOOR ELEVATION = 994.67'
- 2. TFE, TOP OF FOOTING ELEVATION = 990.67' U.N.O.
- VERIFY ALL DIMENSIONS, ELEVATIONS, AND MATERIALS WITH ARCHITECTURAL AND PROCESS DRAWINGS.
- 4. HOIST, TROLLEY, AND LIFTED LOAD 4,000 POUNDS.
- 5. MASONRY CONTRACTOR SHALL COORDINATE WEELECTRICAL CONTRACTOR TO CUT BLOCK NEATLY FOR OPENINGS NEEDED BY ELECTRICAL CONTRACTOR.
- SEE DETAILS AIDS1 AND BIDS1 FOR STANDARD CONCRETE EQUIPMENT PAD &
   PEDESTAL DETAILS. COORDINATE LOCATIONS AND DIMENSIONS WITH
   PROCESS, MECHANICAL, AND ELECTRICAL.
- 7. FOR CONTRACTION JOINTS (C.J.) OR SAWCUT WITHIN 18 HOURS OF CONCRETE PLACEMENT SEE CIDS1. MAXIMUM SPACING OF CONTRACTION JOINTS TO BE 15-0".
- 8. 'Fx' DENOTES FOOTING TYPE. SEE SHEET S1 FOR FOOTING SCHEDULE.
- 9. 'Lx' INDICATES LINTEL SEE LINTEL SCHEDULE ON SHEET S3.
- 10. D.O. DENOTES DOOR ROUGH OPENING W.O. DENOTES WINDOW ROUGH OPENING
- 11. ALL CMU SURFACES EXPOSED TO VIEW ARE GLAZED FACE.
- 12. BEVEL TOP OF CONCRETE FOUNDATION WALL 3" AT 45 DEG. WHERE EXPOSED TO SHED RAIN WATER. COORDINATE EXTENTS WITH ARCHITECTURAL.

### KEYNOTES:

- 21 PROVIDE ADDITIONAL REINFORCEMENT PER DETAIL D/DS3 AT ALL RE-ENTRANT CORNERS.
- (2) WELL HEAD AND VERTICAL TURBINE PUMP SEE PROCESS. PROVIDE 1/2" EXPANSION JOINT MATERIAL AND CAULK BETWEEN FLOOR SLAB AND CONCRETE PUMP BASE.
- 3 4" ELECTRICAL EQUIPMENT PADS SEE STANDARD DETAIL A/DS1.
- 4 THICKENED SLAB, SEE DETAIL F/DS2. SEE FOOTING SCHEDULE ON SHEET S1 FOR THICKNESS, WIDTH, AND REINFORCING.
- MONORAIL ABOVE SEE DETAIL J/DS2 AND NOTE 4 ON THIS SHEET. COORDINATE FINAL LOCATION W/ PUMP LIFT POINTS.
- $\fbox{6}$  HOUSEKEEPING PAD OR PUMP PEDISTAL REFERENCE TYPICAL DETAIL A/DS1 OR B/DS1.
- Note the second of the se
- 8 PIPE PENETRATION THROUGH CONCRETE CAST-IN-PLACE SLAB ON GRADE. PROVIDE ADDITIONAL REINFORCING PER DETAIL H/DS1, TYP.
- 9 CIP CONCRETE CONTAINMENT CURB.

么 SEH

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

1 S. Whitney Way

wing is an instrument of service and shall the property of Shart Elioti Hendrickson, Inc. This drawing, concepts and ideas contained that not be used, reproduced, revised, or

MADWU 182222

Issue Date 6/30/2025

publication in derogation of any of the SEH Project Checked By Drawn By

\_\_\_\_

# DESCRIPTION

KEV.# DESCRIPTION

FLOOR PLAN

01 S102



### **PLAN NOTES**

- 1. TYPICAL 10" HOLLOWCORE PLANK BEARING ELEVATION = 1008.67'
- SUPERIMPOSED UNIFORM DEAD LOAD: 20 PSF SUPERIMPOSED UNIFORM LIVE LOAD: 20 PSF
- 3. 'Lx' INDICATES LINTEL SEE LINTEL SCHEDULE ON THIS SHEET
- 4. THIS SHEET SHOWS CONCEPTUAL LAYOUT AT OPENINGS IN HOLLOWCORE SLABS. P/C SUPPLIER IS RESPONSIBLE FOR FINAL DESIGN.
- 5. P/C = PRECAST CONCRETE
  H/C = HOLLOWCORE
  H/C PLANK = PRESTRESSED CONCRETE HOLLOWCORE SLABS DESIGNED BY SUPPLIER IN
  ACCORDANCE WITH PCI STANDARDS. SEE SPECIFICATION.
- 6. TYPICAL ANCHORAGE OF EXTERIOR CMU WALLS: INSTALL TO HIC PLANK WITH INJECTION ADHESIVE: PROVIDE SCREEN TUBE AS REQUIRED (IF DOWEL GOES INTO HOLES OF HIC PLANK), LAP REBAR MIN, 32" WITH WALL REINFORCING U.N.O. ON DETAILS, REINFORCING EQUAL TO SIZE AND SPACING SHOWN ON REINFORCING ELEVATIONS.
- 7. HOLLOWCORE PLANK TO BE DESIGNED ASSUMING (1) STRAND CUT.

Project Owner

1 TIE-OFF - SEE DETAIL K/DS2, CONFIRM LOCATION WITH OWNER.

**KEY NOTES** 

- 2 MONORAIL BELOW
- MONORAIL SUPPORT SEE DETAIL J/DS2, SUPPORT REQUIRED AT EACH PLANK.
- 4 LOCATE BUILDING TO CENTER HATCH ON EXISTING WELL HEAD.

	LINTEL SCHEDULE	
MARK	SIZE OR DESIGNATION	NOTES
L1	8" W x 8" DEEP CMU LINTEL W/ (2) #5 REBAR, BOTTOM	
L2	8" W x 16" DEEP CMU LINTEL W/ (2) #5 REBAR, TOP & BOTTOM	
L3	8" W x 8" DEEP CMU LINTEL W/ (1) #5 REBAR, BOTTOM	
L4	2-C8x11.5 W/ 5/16" x 15" BOT. PLATE 8" BEARING EA. END	HOT DIP GALVANIZE SEE M/DS2

- NOTES:

  1. EACH MASONRY LINTEL SHALL BEAR 8" MIN, ON CMU WALL. CONTINUE HORIZ, REINF, TO END OF BEARING.

  2. GROUT AND REINFORCE 2 VERTICAL CORES EACH SIDE OF ALL MASONRY AND STEEL LINTELS U.N.O.

  3. BOTTOM KREBAR TO BE MAINTAINED 2" MIN, CLEAR FROM BOTTOM OF BOND BEAM LINTEL OR GREATER IF REOD FOR FIRE RESISTIVE CONSTRUCTION.

  4. SHORE CMU LINTELS FOR ENTIFIEL EINSTH UNTIL BOND BEAMS ARE IN PLACE AND GROUT IS CURED, ALL BOND BEAM LINTELS SHALL BE CONSTRUCTED OF 8" HIGH BLOCK IN RUNNING BOND, USE POUR-THAU BOND BEAM BLOCK FOR UPPER COURSE(S) IF LINTEL HEIGHT EXCEEDING 8" IS INDICATED.

	VENEER LINTEL SCHEDULE					
MARK	SIZE OR DESIGNATION	NOTES				
VL1	BENT PLATE 7 x 7 x 3/8	HOLES IN VERT LEG AT 12" O.C. FOR 1/2"Ø EXP. ANCHORS TO CMU BOND BEAM				


1. EACH LINTEL SHALL BEAR 8" MIN, ON VENEER EA, SIDE OF OPENING.
2. ALL EXTERIOR LINTELS SHALL BE HOT DIP GALVANIZED - SEE STRUCTURAL NOTES,


MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

MADWU 182222 BAW ALC SEH Project Checked By Drawn By

Issue Date 6/30/2025


ROOF FRAMING PLAN






B SECTION THROUGH CANOPY AT LOUVER ASSEMBLY

S503 1" = 1'-0"





2 - #4
0.44
2 - #4
2 - #5
2 - #6
2 - #5
2 - #6

\* USE LARGEST DIAMETER BAR IN EITHER DIRECTION FOR DETERMINING CORNER BARS.

NOTES:

PROVIDE 2" CLEAR COVER OVER ALL BARS AT OPENINGS

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

Project Status DNR SUBMITTA

ADDITIONAL CORNER BARS:

WHEN SLAB HAS BOTTOM REINFORCEMENT LAYER ONLY, PLACE DIAGONAL BARS AT MID DEPTH.

WHEN SLAB HAS TOP REINFORCEMENT LAYER ONLY, PLACE DIAGONAL BARS WITH TOP REINFORCEMENT.

WHEN SLAB HAS TOP & BOTTOM REINFORCEMENT LAYERS, PLACE DIAGONAL BARS WITH TOP & BOTTOM REINFORCEMENT.


CANOPY CONNECTION PLATE DETAIL


S503 1 1/2" = 1'-9"


SLAB REENTRANT CORNER DETAIL


S503

1/2" = 1'-0"













7'-8"












F SECTION THROUGH CANOPY

S503 1" = 1'-0"









H VENEER SUPPORT DETAIL

STRUCTURAL DETAILS

MADWU 182222 BAW ALC

Issue Date 6/30/2025



MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

BUILDING DEMOLITION REFERENCE DRAWING

CODE INFORMATION
UNIT WELL 12 WATER TREATMENT PLANT
Madison, WI


General Code Information
ITEM
Design code:


Occupancy Type:

Construction type:



Fire barriers shall be permanently identified with stenciling in accessible and concealed locations at intervals not exceeding 30' along the barrier





Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION SEH Project Checked By Drawn By

CODE PLAN

182222 JRL JRL

NOTE: ALL DRAWING SCALES ARE FOR PLANS PRINTED ON 34"x22" SHEETS


MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

Project Status DNR SUBMITTA

182222 JRL JRL

FLOOR PLAN



# TOILET ROOM ENLARGED PLAN

ACCESSIBLE PAPER TOWEL DISPENSER -

ACCESSIBLE TOILET PAPER HOLDER

ACCESSIBLE GRAB BARS

ACCESSIBLE FLOOR —— MOUNTED WATER CLOSET, SEE PLUMBING.

ACCESSIBLE, WALL HUNG LAVATORY, SEE PLUMBING

ACCESSIBLE SOAP DISPENSER



- DOUBLE WYTHE WALL CONSTRUCTION

### GENERAL NOTES:

- 1. SEE STRUCTURAL DRAWINGS FOR ALL DETAILS RELATED TO CMU REINFORCING.
  2. ALL CMU SURFACES EXPOSED TO VIEW SHALL BE BURNISHED FACED UNITS.
  3. PROVIDE BULLNOSE UNITS AT CORNERS AND JAMBS.
  4. PROVIDE UNITEL UNITS OVER OPENINGS.
  5. PROVIDE BURNISHED SILL UNITS AT SILL CONDITIONS. ALL WALLS HAVE COVED BASE STARTER COURSE.
  6. CONSTRUCT WALLS COMMON TO PUMP ROOM SO THAT GOOD SIDE FACES THE PUMP ROOM.
  7. SEE OTHER DRAWINGS FOR EQUIPMENT LOCATIONS AND HOUSE KEEPING PADS.
  8. REFER TO DIVISION 9 SPECIFICATIONS FOR INTERIOR FINISHES.




MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

182222 JRL JRL

SEH Project Checked By Drawn By

CLERESTORY PLAN



### GENERAL NOTES:

- 1. SEE STRUCTURAL DRAWINGS FOR ALL DETAILS RELATED TO CMU REINFORCING.

  2. ALL CMU SURFACES EXPOSED TO VIEW SHALL BE BURNISHED FACED UNITS.

  3. PROVIDE BULLNOSE UNITS AT CORNERS AND JAMBS.

  4. PROVIDE LINTEL UNITS OVER OPENINGS.


  5. PROVIDE BURNISHED SILL UNITS AT SILL CONDITIONS. ALL WALLS HAVE COVED BASE STARTER COURSE.

  6. CONSTRUCT WALLS COMMON TO PUMP ROOM SO THAT GOOD SIDE FACES THE PUMP ROOM.

  7. SEE OTHER DRAWINGS FOR EQUIPMENT LOCATIONS AND HOUSE KEEPING PADS.

  8. REFER TO DIVISION 9 SPECIFICATIONS FOR INTERIOR FINISHES.

  9. ARROWS ON CANOPIES DENOTE 1/4" PITCH DIRECTION TOWARDS ROOF EDGE SCUPPERS



人 SEH

Project Ou

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

S. Whitney Way, Madison

801 S. Whitne Wl, 53711

> 182222 JRL JRL

drawing is an instrument of service and shall in the property of Short Elliott Hendrickson, Inc.

1). This drawing, concepts and ideas contained in shall not be used, reproduced, revised, or ned without the express written approval of SEH.

SEH Project Checked By Drawn By

ject Status

REVISION SCHEDULE

REV. # DESCRIPTION

01 A103

ROOF PLAN

SEH

Project Owner

110,000 0111

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

801 S. Whitney Way, WI, 53711

This drawing is an instrument of service and shall receive the property of Short Elliott Hendrickoun, Inc. (SSEI). The drawing concepts and cleas contained service that not be used, reproduced, revised, and received without the express written approved of SEH. Submission or distribution of this drawing to meet official or regulative requirements for the proposes in connection with the project is not be construed as publication in designation of size of the right of SEH.

SEH Project Checked By Drawn By

> roject Status NR SUBMITTAL

> > DEVISION SCHEDI II E

DESCRIPTION

182222 JRL JRL

\_\_\_\_\_\_

EXTERIOR ELEVATIONS

01 A201

么 SEH

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

Project Status DNR SUBMITTA

182222 JRL JRL

EXTERIOR ELEVATIONS

NOTE: ALL DRAWING SCALES ARE FOR PLANS PRINTED ON 34"x22" SHEETS

В A ROOF DRAIN REFER TO A3 ROOF 1008.67 4 A302 Sim 1 A302 PUMP FLUORIDE 102 104 FIRST FLOOR 994.67 FOUNDATION 990.67

BUILDING SECTION

1/4" = 1'-0"

NOTE: ALL DRAWING SCALES ARE FOR PLANS PRINTED ON 34"x22" SHEETS

A301


MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL

BUILDING SECTIONS

182222 JRL JRL



.

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

This drawing is an instrument of service and shall remain the property of Short Blief Hendrickson, Inc. SSH). This disray, concepts and class concepts and class continued of Services and the services within appropriate of SERVICES. The straining concepts within appropriate of SERVICES and the services within appropriate of SERVICES. Schemisters or distribution of this drawing to meet the services of services and the services of services and the services of services and services are services and services and services are services and services and services are services and services are services and services are services and services and services are services are services and services are services and services are services are services and services are services and services are services and services are services are services and services are services and services are services are services and services are services are services are services are services and services are services are services and services are services are

SEH Project Checked By Drawn By

ect Status SUBMITTAL

REVISION SCHEDULE

DESCRIPTION

182222 JRL JRL

WALL SECTIONS

01 A302


NOTE: ALL DRAWING SCALES ARE FOR PLANS PRINTED ON 34"x22" SHEETS

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

182222 JRL JRL


SEH Project Checked By Drawn By

WALL SECTIONS



2 WALL SECTION
3/4" = 1'-0"

WALL SECTION - ENTRANCE DOOR



MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

182222

JRL JRL

SEH Project Checked By Drawn By

DETAILS

STONE VENEER 2

STONE VENEER 2


- 3" THERMAL INSULATION


1" AIR SPACE


STONE VENEER 2

8 x 8 x 8 BURNISHED CMU BLOCKS











PLAN DETAIL - CORNER CONDITION
11/2" = 1'-0"





FIBERGLASS WINDOW JAMB
A502 1 112" = 1"-0"

NOTE: ALL DRAWING SCALES ARE FOR PLANS PRINTED ON 34"x22" SHEETS

人 SEH

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

g) is an instrument of services and shell properly of Shot Elicial Heriodicans, In 2007. We have been serviced as a service of the seek reproduced, revised, or of the seek reproduced, revised, or of distribution of this drawing to meet guidance requirements for purposes in which the project and the constituted as a service of State of the services where the project of services are serviced as a service of State of the services are serviced as a service of the services and the services are serviced as a service of the services and the services are serviced as a service of the service of the services are serviced as a service of the service of the servic

182222 JRL JRL

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL

REVISION SCHEDULE


DETAILS

01 A502 HM: HOLLOW METAL FRP: FIBER REINFORCED PLASTIC


REMOVABLE

SEE SCHEDULE

В








BURNISHED CMU


BULLNOSE SILL

BACKER ROD AND SEALANT BOTH SIDES OF FRAME


HOLLOW METAL FRAME




A601











FIRE RATED INTERIOR WINDOW

FIRE RATED GLAZING AND FRAME

BACKER ROD AND FIRE


CAULK SEALANT BOTH SIDES OF FRAME


BULLNOSE SILL


BURNISHED CMU

ROOM FINISH SCHEDULE										
ROOM	M FLOOR BASE			WALL FINISH				CEILINGS		REMARKS
NUMBER	ROOM NAME	FLOOR	BASE	NORTH	SOUTH	EAST	WEST	FINISH	MATERIAL	REMARKS
101	CHLORINE	EP	-	BURN	BURN	BURN	BURN	PT	PRECAST	
102	FLUORIDE	EP	-	BURN	BURN	BURN	BURN	PT	PRECAST	
103	TOILET	EP	-	BURN	BURN	BURN	BURN	PT	PRECAST	
104	PUMP	EP	-	BURN	BURN	BURN	BURN	PT	PRECAST	


BURN: BURNISHED CMU EP: EPOXY QUARTZ PT: PAINTED PER SPECIFICATION







A601







FIRE RATED FGL JAMB/SILL
3" = 1-0"


6 PARTITION TYPES M1C/S

TYP. INTERIOR DOOR JAMB














TYP. EXTERIOR DOOR HEAD
3" = 1"-0"

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

182222 JRL JRL

SEH Project Checked By Drawn By

REVISION SCHEDULE

SCHEDULES AND DETAILS

### **KEYNOTES:**

- $\langle 1 \rangle$  DUAL CYLINDER PLATFORM WITH INDICATOR
- GAS CHLORINE FEED SYSTEM SEE DETAIL E/DP1
- 3 EMERGENCY CHLORINE SHUTOFF PANEL
- 4 CHLORINE GAS DETECTOR
- 5 LOSS OF VACCUM DETECTOR
- 6 165 GALON FLUORIDE TANK
- 7 36" x 36" SCALE PLATFORM
- 8 DIGITAL SCALE INDICATOR
- 9 FLUORIDE METERING PUMP SEE DETAIL F/DP1
- (10) 16" HIGH CHEMICAL CONTAINMENT WALL
- (11) CHLORINE ANALYZER ROTATE PIPING AS REQUIRED
- (12) TAP PIPE FOR 1/2" CHLORINE ANALYZER SUPPLY -INSTALL 1/2" BALL VALVE - ROUTE PIPE TO CHLORINE
- (13) FLUORIDE INJECTION POINT SEE DETAIL D/DP1
- (14) CHLORINE INJECTION POINT SEE DETAIL D/DP1
- (15) 12" MAGNETIC FLOW METER (FURNISHED BY OWNER)
- 12" BUTTERFLY VALVE W/ELECTRIC ACTUATOR
- **17** 8" BUTTERFLY VALVE W/ELECTRIC ACTUATOR
- $\langle \overline{\textbf{18}} \rangle$  8" Pressure Sustaining/Pressure reducing valve (V-PSV/PRV-1)
- AIR RELEASE VALVE ROUTE VENT TO NEARBY HUB DRAIN SEE DETAIL A/DP1
- **20** 6" BUTTERFLY VALVE
- ⟨21⟩ 6" EXPANSION JOINT
- (22) 8" EXPANSION JOINT
- **23** 8" BUTTERFLY VALVE
- (24) 16x8 ECCENTRIC REDUCER
- ⟨25⟩ 12" BUTTERFLY VALVE
- 26 12" CHECK VALVE
- (27) AIR/VACUUM VALVE ROUTE VENT TO NEARBY FLOOR DRAIN - SEE DETAIL A/DP1
- 28 12" EXPANSION JOINT
- $\stackrel{\textstyle \langle \overline{\bf 29} \rangle}{}$  Vertical Turbine Well, PUMP, MOTOR and PUMP BASE SEE DP3 FOR DETAILS
- (30) HIGH SERVICE PUMP
- 31> SAMPLE TAP SEE DETAIL B/DP2
- $\stackrel{\left\langle 32\right\rangle}{-}$  4" CONDUIT WITH LONG SWEEP BENDS UNDER FLOOR FOR CHLORINE ANALIZER TUBING
- 4" CONDUIT WITH LONG SWEEP BENDS UNDER FLOOR FOR CHEMICAL FEED TUBING
- (34) 4" CONDUIT WITH LONG SWEEP BENDS UNDER FLOOR FOR ALTERNATE CHLORINE FEED 12" BUTTERFLY VALVE W/HANDWHEEL

- (36) EMERGENCY SHOWER, TYP.
- (37) EXISTING HIGH SERVICE PUMP SALVAGED FROM **EXISTING WELLHOUSE**
- (38) EXISTING UW 12 DEEP WELL TO REMAIN, PROTECT FROM DAMAGE DURING CONSTRUCTION, SEE PUMP BASE DETAIL. -CONTRACTOR TO FIELD VERIFY LOCATION


NOTE: ENCASE BELOW FLOOR PIPING ACCORDING TO DETAIL K/DP1

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

WELLHOUSE FLOOR PLAN

P-UW-12



## **KEYNOTES:**


- 1 HIGH SERVICE WELL SEE DETAILS DP3
- 2 12" EXPANSION JOINT
- 3 AIR/VACUUM VALVE ROUTE VENT TO NEARBY FLOOR DRAIN - SEE DETAIL A/DP1
- 4 12" CHECK VALVE (CV-RW-1)
- 5 12" BUTTERFLY VALVE W/HANDWHEEL
- (6) 12" MAGNETIC FLOW METER (FURNISHED BY OWNER)
- (7) AIR RELEASE VALVE ROUTE VENT TO NEARBY FLOOR DRAIN SEE DETAIL A/DP1
- 8 HIGH SERVICE PUMP (TYP OF 3)
- 9 12" BUTTERFLY VALVE W/ELECTRIC ACTUATOR
- (10) 8" BUTTERFLY VALVE W/ELECTRIC ACTUATOR
- ⟨11⟩ 8" PRESSURE SUSTAINING/PRESSURE REDUCING VALVE
- (V-PSV/PRV-1)
  12" BASE ELBOW AND PEDISTAL
- 8" MAGNETIC FLOW METER (FURNISHED BY OWNERY/M-BP-1)
  12" SWING CHECK VALVE
- 12x6 REDUCING ELBOW
- (16) 6" BUTTERFLY VALVE
- ⟨17⟩ 6" EXPANSION JOINT
- (18) 8" EXPANSION JOINT
- (19) 8" BUTTERFLY VALVE
- (20) 16x8 ECCENTRIC REDUCER
- $\langle \overline{21} \rangle$  tap blind flange for ahu return water See Mechanical
- (22) BASE BEND PEDISTAL SEE DETAIL B/DP1
- (23) THRUST BLOCK AND PIPE ENCASEMENT SEE DETAIL K/DP1, C/DP2
- (24) CONCRETE PUMP BASE SEE DETAIL B/DP3
- SAMPLE TAP SEE DETAIL B/DP2
- (26) 8" PIPING AND FITTINGS
- **⟨27⟩** 16x16 TEE
- (28) 16" FROM RESERVOIR
- (29) TAP TEE FOR PRESSURE GAUGE AND SAMPLE TAP SEE DETAIL D/DP2
- (30) 12" x 16" CONCENTRIC REDUCER


 $\underline{\text{NOTE:}}$  ENCASE BELOW FLOOR PIPING ACCORDING TO DETAIL K/DP1

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

WELLHOUSE SECTIONS





# **KEYNOTES**:

- 1 8" PSV VALVE
- $\fbox{2}$  Tap Pipe for 1/2" Chlorine analyzer supply install 1/2" ball valve
- $\bigcirc$  12" MAGNETIC FLOW METER (FURNISHED BY OWNER)
- 4 12" ACTUATED BUTTERFLY VALVE
- 5 16x12 CONCENTRIC REDUCER
- 6 12" MAGNETIC FLOW METER PROVIDED BY OWNER
- 7 BASE BEND PEDISTAL SEE DETAIL B/DP1
- 8 12x8 ECCENTRIC REDUCER
- $\begin{picture}(40,0)\put(0,0){\line(0,0){10}}\put(0,0){\line(0,0){10}$
- (10) PUMP BASE SEE DETAIL G/DP1

SEH.

Project Owner

1.00000

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

S. Whitney Way ison Wl. 53711

rawing is an instrument of service and shall the property of Short Eliott Hendrickson, Inc. This drawing, concepts and ideas contained shall not be usef, persolucted, revised, or d without the express written approval of SEH.


SEH Project Checked By

DNR SUBMITTAL

# DESCRIPTION

WELLHOUSE SECTIONS

01 P302





Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

s an instrument of service and sha poerty of Short Eliott Hendindson, awing, concepts and ideas contain the used, reproduced, revised, or

Submission or distribution of this drawing to meet difficult or squishty requirement of the purposes in concession with the project in sort to be considered as a publication in decogation of any of the rights of SEt.

SEH Project

Checked By

Drawn By

DD

Project Status DNR SUBMITTAL

DESCRIPTION

WELLHOUSE PROCESS DETAILS



L-1 36/12 900 CFM

L-2 | 36/12 100 CFM



#### KEYNOTES:

- 1. ROUTE Ø6" EA UP THRU ROOF TO ROOF CAP.
- 2. ROUTE CONDENSATE TO NEAREST FLOOR DRAIN.
- 3. DUCTWORK IN PUMP AND CHEMICAL ROOMS TO BE TYPE 3002-H14 ALUMINUM UNLESS NOTED OTHERWISE.
- 4. 14/14 EA FROM 12" AFF TO EXHAUST FAN <u>EF-1</u> MOUNTED IN VERTICAL. 14/14 OUTLET UP THRU ROOF TO GRAVITY VENT <u>GV-1</u>.
- 5. 9/9 EA FROM 12" AFF TO EXHAUST FAN EF-2 MOUNTED IN VERTICAL. 12/12/ OUTLET UP THRU ROOF TO GRAVITY VENT GV-2.
- 6. ROUTE <u>GUH-1</u> EXHAUST AND COMBUSTION AIR UP TO CONCENTRIC ROOF KIT. CORE DRILL OPENING THRU ROOF, FLASH AND SEAL ROOF PENETRATION.
- Ø3" SCHEDULE 40 FLUE VENT/COMBUSTION AIR PIPING TO/FROM GWH-1 AND ROOF TERMINATION. SEAL PENETRATIONS WEATHERTIGHT. PROVIDE ROOF TERMINATION KIT.

SEH.

Project Owner


MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL

MADWU 182222 CAH KML

HVAC PLAN





#### KEYNOTES:

- 1. WATER METERS PROVIDED BY OWNER.
- 2. TRANSITION TO 1" SCHEDULE 80 CPVC AND ROUTE UNDERFLOOR TO WELL PRE-LUBE SYSTEM.
- 3. ALL PIPING, HANGERS AND SUPPORTS IN CHEMICAL ROOMS TO BE CPVC OR EQUIVALENT.
- $4. \quad \text{EXISTING GAS METER AND GAS SERVICE BY GAS COMPANY. METER TO HAVE 60 CFH CAPACITY AT 2 PSIG.} \\$
- 5. 3/4" GAS CONNECTION TO GUH-1 WITH DRIP LEG, PRESSURE REGULATOR, SHUT-OFF VALVE, AND UNION.

SEH.

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

MADWU 182222 CAH KML

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL

DOMESTIC WATER AND GAS PLAN

4" WASTE TO SANITARY SEWER. SEE CIVIL FOR CONTINUATION.

CHLORINE

— — -2" V— — -(UNDERGROUND)

<u>FD-1</u>

FLUORIDE 102

-2" V-

3" VTR

MSB-1

-4" OSD UP TO ROOF

-4" SD UP TO ROOF

CO-21 H

\_\_<u>HD-1</u>\_

PUMP 104



TERMINATE HIGH AS POSSIBLE THRU WALL.

TERMINATE WITH LAMBS
TONGUE 18" ABOVE GRADE.

-4" WASTE TO SANITARY SEWER. SEE CIVIL FOR CONTINUATION. KEYNOTES:

MAINTAIN MINIMUM SEPARATION TO WELL OF 24".

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH.

Project Owner

astrument of service and shall of Short Elliott Hendrickson, In p. concepts and ideas contained, concepts and ideas contained seed, reproduced, revised, or express written approval of SE button of this drawing to meet

MADWU 182222 CAH KML

> Issue Date 6/30/2025

official or regulatory requirement connection with the project is not publication in derogation of any of SEH Project Checked By Drawn By

Project Status
DNR SUBMITTAL

IIIAL


REVISION SCHEDUL

REVISION SCHEDUL

SANITARY WASTE AND VENT PLAN

01 M103

MECHANICAL ROOF PLAN
3/8" = 1"-0"



Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL


MADWU 182222 CAH KML

Issue Date 6/30/2025

MECHANICAL ROOF PLAN




KEYNOTES:





#### GENERAL NOTES:

- FIRE SPRINKLER PIPING LAYOUT AND SIZING SHALL BE DETERMINED BY HYDRAULIC CALCULATION IN ACCORDANCE WITH NFPA 13 PER SPECIFICATION 21 00 00. FINAL HYDRAULIC CALCULATIONS SHALL BE BASED ON ACTUAL FLOW TEST DATA TO BE PERFORMED BY CONTRACTOR.
- SPRINKLER SYSTEM SHALL BE DESIGNED AS REQUIRED BY NFPA 13 FOR R THE OCCUPANCIES IDENTIFIED. CONTRACTOR SHALL BE
  RESPONSIBLE FOR DETERMINING THE ACTUAL NUMBER OF SPRINKLERS AND SPACING REQUIREMENTS TO PROTECT THE AREA IN
  ACCORDANCE WITH NFPA 13 FOR THE OCCUPANCY HAZARD CLASSIFICATION.
- RISER TO SERVE THE ZONE SHALL BE COORDINATED WITH THE CONSTRUCTION; DO NOT OBSTRUCT CORRIDORS, DOORWAYS, ETC. INSTALL
  RISERS AS CLOSE AS PRACTICAL TO ROOM CORNERS, WALLS, ETC. RISER LOCATION SHOWN MAY BE REVISED BY THE CONTRACTOR AS
  REQUIRED.
- THE ARCHITECTURAL BACKGROUND PROVIDED ON THIS SHEET IS FOR GENERAL REFERENCE ONLY. CONTRACTOR SHALL VERIFY ALL BACKGROUNDS WITH THE ARCHITECTURAL SHEETS. REFER TO ARCHITECTURAL DRAWINGS FOR ELEVATED WALKWAYS, STAIRWAYS, BRIDGES, ETC.
- COORDINATE SPRINKLER INSTALLATION IN AREAS WITHOUT CEILINGS. PROVIDE ADDITIONAL SPRINKLERS AS REQUIRED TO AVOID
  OBSTRUCTIONS TO DISCHARGE FORMED BY DUCT WORK, LIGHT FIXTURES, STRUCTURE, WATER TREATMENT EQUIPMENT, MECHANICAL
  EQUIPMENT, ETC.
- 6. PROVIDE SPRINKLER GUARDS ON ALL SPRINKLERS LESS THAN 7"-0" AFF.
- PROVIDE INSPECTORS TEST CONNECTION AT REMOTE POINT FOR EACH ZONE. ROUTE TEST AND DRAIN PIPES TO GRADE. PIPE SHALL TERMINATE WITH SMOOTHER BORE CORROSION RESISTANT OUTLET.
- 8. COORDINATE LOCATION OF FIRE DEPARTMENT CONNECTION WITH CITY OF SOUTH ST. PAUL FIRE DEPARTMENT.
- 9. PROVIDE BALL DRIP VALVE AT BASE OF FIRE DEPARTMENT CONNECTION.
- 10. INSTALL HIGH TEMPERATURE SPRINKLERS IN CLOSE PROXIMITY TO UNIT HEATERS PER NFPA 13.
- 11. SPRINKLER HEADS IN CHEM ROOMS SHALL BE WAX COATED AGAINST CORROSION. ALL PIPING SHALL BE FIELD PAINTED IN ACCORDANCE WITH DIVISION 9.
- SPRINKLER MAINS SHALL BE MINIMUM SCHEDULE 10 STEEL PIPE. BRANCH PIPING SHALL BE MINIMUM SCHEDULE 40 STEEL PIPE. NO THIN
  WALLED PIPING WILL BE ACCEPTED. REFER TO 21 13 13 FOR DETAILS.
- 13. ALL PIPING PENETRATIONS SHALL BE SEALED WITH FIRE STOP.
- 14. AREAS WITH LAY-IN OR GYPSUM CEILINGS SHALL HAVE RECESSED OR SEMI-RECESSED SPRINKLER HEADS.
- 15. AREAS WITHOUT CEILINGS SHALL HAVE UPRIGHT OR PENDANT TYPE SPRINKLER HEADS.
- 16. ALL CHEMICAL ROOM SPACES SHALL HAVE WAX COATED UPRIGHT OR PENDANT TYPE SPRINKLER HEADS.





SPRINK	LER SYSTEM SCH	DULE				
AREA	HAZARD CLASS	MINIMUM DENSITY (GPM/SQ FT)	MINIMUM SPRINKLER HYDRAULIC DESIGN AREA (SQ FT)	HOSE STREAM DEMAND (GPM)	DURATION (MIN)	NOTES
	ORDINARY GROUP 1	0.15	1110	250	90	
	ORDINARY GROUP 2	0.20	150	250	90	



Project Owner

MADISON, WISCONSIN
UNIT WELL 12 RECONSTRUCTION

801 S. Whitney W. Madison WI, 5371

g is an instrument of service and shall property of Short Elliott Hendrickson, In drawing, concepts and ideas contained not be used, reproduced, revised, or hout the express written approval of SE

in derogation of any of th

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL

MADWU 182222 CAH KML

REVISION SCHED


-----


FIRE PROTECTION PLAN

01 M105









MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

Project Owner

MUSIC MUSIC MARKET STATE OF THE STATE OF THE

of without the express written approved of SEH.

\$1.50 \text{ \$\frac{1}{2}\$ \$\frac{1}{

SEH Project Checked By Drawn By Project Status

Project Status DNR SUBMITTAL

DEVISION SCHEDI


Issue Date 6/30/2025

REVISION SCHEDU

RISER DIAGRAMS

01 M201





MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

Project Owner

MADWU 182222 CAH KML

SEH Project Checked By Drawn By Project Status DNR SUBMITTAL

Issue Date 6/30/2025

RISER DIAGRAMS

NOTES:

1) HORIZONTAL ORIENTATION INDOOR UNIT

2) WALL MOUNTED DIGITAL PROGRAMMABLE THERMOSTAT

4. HAIL GUARD

5. OUTDOOR UNIT MOUNTED ON CONCRETE PAD

3) R-454B REFRIGERANT

		DEHUMID	IFIERS SC	HEDULE			
EQUIPMENT		MODEL			EL	ECTRICAL	
NUMBER	MANUFACTURER	NUMBER	CFM	MOISTURE REMOVAL (LB/DAY)	AMPS	V/PH/CY	NOTES
D-1	QUEST	HI-E DRY 195	540	192	12	115/60/1	1,2
		•		•		•	

NOTES:

1) MERV 8 FILTER

2) UNIT MOUNTED HUMIDISTAT

		ELECT	RIC HEATER SCHEDULE	•							
					FAN		ELE	CTRIC HEATER	ELECTRICAL		
EQUIPMENT NUMBER	MANUFACTURER	MODEL NUMBER	SERVES	CFM	HP	RPM	ĸw	AIR TEMP. RISE (F)	V/PH/CY	FLA	NOTES
EUH-1	QMARK	QWD	CHLORINE ROOM	2400	-	-	15	21	460/3/60	20	1,2,3,4
EUH-2	QMARK	QWD	FLUORIDE ROOM	700	-	-	15	23	460/3/60	6	1,2,3,4
EWH-1	QMARK	CWH1202DSAF	TOILET	65	-		1.5	-	208/1/60	7.3	5,6
-	-				-		-	-			-

NOTES:

1) FACTORY DISCONNECT

2) FACTORY WALL MOUNTED THERMOSTAT

3) SWIVEL BRACKET

4) WASHDOWN CONSTRUCTION

5) RECESS WALL MOUNT

6) INTEGRAL THERMOSTAT

			FAN S	SCHEDULE								
EQUIPMENT		MODEL				E.S.P.			М	OTOR		
NUMBER	MANUFACTURER	NUMBER	TYPE	SERVES	CFM	(IN. W.G.)	SONES	WATTS	HP	RPM	V/PH/CY	NOTES
EF-1	GREENHECK	SQ-100-A	INLINE	CHLORINE ROOM	900	0.25	7.1	-	1/4	1283	115/60/1	1,2,3,4
EF-2	GREENHECK	SQ-65-D	INLINE	FLUORIDE ROOM	100	0.25	3.5	-	1/30	1534	115/60/1	1,2,3,4
EF-3	GREENHECK	SP-A190	CEILING	TOILET	140	0.25	1.5	33	-	1254	115/60/1	4,5

1) FACTORY MOUNTED AND WIRED DISCONNECT

2) CORROSION RESISTANT CONSTRUCTION

3) HERESITE COATED

4) SPEED CONTROLLER

5) ROOF CURB AND ROOF CAP

							DIFFUSERS, REGISTERS, GRILLES
	S = SU	IPPLY	GR = RETU	RN (	GE = EXHAUST		
TAG	MANUFACTURER	MODEL No.	TYPE	DAMPER	MOUNTING POSITION	FACE IN INCHES	REMARKS
SG-1	TITUS	300FL	SUPPLY	NO	SIDEWALL	SEE PLAN	RECTANGULAR REGISTER; STEEL; WHITE ENAMIEL; DOUBLE DEFLECTION 3/4" ADJUSTABLE LOUVERS; FRONT BLADES TO BE HORIZONTAL.

1) NECK SIZE SHALL MATCH DUCT CONNECTION SIZE

2) VERIFY MOUNTING TYPE WITH CEILING TYPE

3) DAMPER SHALL BE MOUNTED IN DUCT TAKE-OFF

		GAS FIRE	D UNIT HEATER	SCHEDI	JLE						
EQUIPMENT NUMBER	MANUFACTURER	MODEL NUMBER	SERVES	CFM	INPUT (BTU)	OUTPUT (BTU)	GAS CFH	GAS INLET PRESSURE	HP	V/PH/CY	NOTES
GUH-1	REZNOR	UDAS60	PUMP ROOM	769	60	49.8	60	2 PSIG	3/100	115/60/1	ALL
NOTES:											

1) WALL MOUNTED THERMOSTAT

2) FACTORY MOUNTED AND WIRED DISCONNECT

3) GAS PRESSURE REGULATOR

4) POWER VENTED, SEPARATED COMBUSTION

5) STAINLESS STEEL HEAT EXCHANGER AND BURNER

6) MANUFACTURER'S ROOF CONCENTRIC VENT KIT

							GRAVIT	Y VENTS						
UNIT NO. GV-1	LOCATION ROOF	SERVING CHLORINE ROOM	MODEL NO.	TYPE EXHAUST	CFM	S.P. ("W.G.)	WIDTH (INCHES)	LENGTH (INCHES)	WIDTH (INCHES)		CURB HEIGHT (INCHES)	OVERALL HEIGHT (INCHES)	ACCESSORIES	REMARKS
GV-1	ROOF	CHLORINE ROOM	FGR-1414	EXHAUST	900	0.06	14	14	16-1/2	16-1/2	8	22	ROOF CURB	
GV-2	ROOF	FLUORIDE ROOM	FGR-1212	EXHAUST	100	0.02	12	12	14-1/2	14-1/2	8	22	ROOF CURB	
NOTES:					•							•		•
1)														

			LOUV	ER SC	HEDULE						
EQUIPMENT NUMBER	MANUFACTURER	MODEL NUMBER	SERVES	CFM	WIDTH (IN)	HEIGHT (IN)	NET FREE AREA (FT^2)	VELOCITY (FPM)	MATERIAL	SCREEN	NOTES
WL-1	RUSKIN	ELF6375DX	CHLORINE ROOM	900	36	16	2	450	ALUMINUM	INSECT	1
WL-2	RUSKIN	ELF6375DX	FLUORIDE ROOM	100	36	16	2	50	ALUMINUM	INSECT	1
NOTES:											
1)	KYNAR FINISH. COLOR SELECTED BY ARCHITECT.										

MOTORIZED D	AMPER SCH	EDULE						
MANUFACTURER	MODEL NUMBER	ROOM NUMBER	SERVING	WIDTH	HEIGHT	CFM	POSITION	NOTES
RUSKIN	CD50	CHLORINE ROOM	EF-1	14	14	900	N.C.	1, 2, 3
RUSKIN	CD50	CHLORINE ROOM	WL-1	36	16	900	N.C.	1, 2, 3
RUSKIN	CD50	FLUORIDE ROOM	EF-2	9	9	100	N.C.	1, 2, 3
RUSKIN	CD50	FLUORIDE ROOM	WL-2	36	16	100	N.C.	1, 2, 4
	MANUFACTURER RUSKIN RUSKIN RUSKIN	MANUFACTURER MODEL NUMBER  RUSKIN CD50  RUSKIN CD50  RUSKIN CD50	RUSKIN CD50 CHLORINE ROOM RUSKIN CD50 CHLORINE ROOM RUSKIN CD50 CHLORINE ROOM RUSKIN CD50 FLUORIDE ROOM	MANUFACTURER         MODEL NUMBER         ROOM NUMBER         SERVING           RUSKIN         CD50         CHLORINE ROOM         EF-1           RUSKIN         CD50         CHLORINE ROOM         WL-1           RUSKIN         CD50         FLUORIDE ROOM         EF-2	MANUFACTURER         MODEL NUMBER         ROOM NUMBER         SERVING         WIDTH           RUSKIN         CD50         CHLORINE ROOM         EF-1         14           RUSKIN         CD50         CHLORINE ROOM         WL-1         36           RUSKIN         CD50         FLUORIDE ROOM         EF-2         9	MANUFACTURER         MODEL NUMBER         ROOM NUMBER         SERVING         WIDTH         HEIGHT           RUSKIN         CD50         CHLORINE ROOM         EF-1         14         14           RUSKIN         CD50         CHLORINE ROOM         WL-1         36         16           RUSKIN         CD50         FLUORIDE ROOM         EF-2         9         9	MANUFACTURER         MODEL NUMBER         ROOM NUMBER         SERVING         WIDTH         HEIGHT         CFM           RUSKIN         CD50         CHLORINE ROOM         EF-1         14         14         900           RUSKIN         CD50         CHLORINE ROOM         WL-1         36         16         900           RUSKIN         CD50         FLUORIDE ROOM         EF-2         9         9         100	MANUFACTURER         MODEL NUMBER         ROOM NUMBER         SERVING         WIDTH         HEIGHT         CFM         POSITION           RUSKIN         CD50         CHLORINE ROOM         EF-1         14         14         900         N.C.           RUSKIN         CD50         CHLORINE ROOM         WL-1         36         16         900         N.C.           RUSKIN         CD50         FLUORIDE ROOM         EF-2         9         9         100         N.C.

1) ALUMINUM, LOW LEAKAGE, OPPOSED BLADE TYPE.

2) 120 V NEMA 4X ACTUATOR, POWER OPEN - SPRING RETURN.

3) PROVIDE BAKED ENAMEL COATING FOR CORROSION PROTECTION.

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION


MADWU 182222 CAH KML

SEH Project Checked By Drawn By


Project Status DNR SUBMITTAL


MECHANICAL SCHEDULES

















5 CONDENSATE DRAIN






3 EXHAUST DUCT DETAIL NOT TO SCALE



OVERFLOW STORM DRAIN TERMINATION



9 PIPE SLEEVE THROUGH WALL NOT TO SCALE

מינים מינים

01 M303

Project Owner

SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL


REVISION SCHEDULE


MADWU 182222 CAH KML

REVISION SCHEDULE


.# DESCRIPTION


MECHANICAL DETAILS






CEILING EXHAUST FAN NOT TO SCALE





- NOTES:
  1. TYPICAL FOR NON-INSULATED PIPING AND CONDUIT.
  2. TYPICAL FOR MASONRY OR CONCRETE WALL.
  3. FOR WALL PENETRATION WITH FIRE RATINGS GREATER THAN (1) HOUR, USE THUNDERLINE "PYRO-PAC" SEALS OR EQUAL.
  4. WHERE PIPING EXPOSED AT FINISHED WALL, FLUSH MOUNT SLEEVE, AND PROVIDE AN ESCUTCHEON PLATE.

# PIPE PENETRATION THRU EXTERIOR WALLS




S WATER METER INSTALLATION NOT TO SCALE

- NOTES:


  1. LOCATE ROOF DRAINS AT LOW POINTS OF ROOF, AS SHOWN ON PLAN.

  2. ALL ROOF FLASHING WORK AND MATERIALS ARE THE RESPONSIBILITY OF THE ROOFING CONTRACTOR.

  3. ROOFING CONTRACTOR MAY USE AN ALTERNATE FLASHING ARRANGEMENT PROVIDED IT HAS BEEN SUBMITTED TO AND APPROVED BY THE ARCHITECT.




ROOF DRAIN




DUCT PENETRATION THROUGH ROOF

M304 NOT TO SCALE



GAS PRESSURE REGULATOR ASSEMBLY
NOT TO SCALE



MADWU 182222 CAH KML SEH Project Checked By Drawn By

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

Project Owner

MECHANICAL DETAILS

Project Owner

 ALL CONDUIT SHOWN IS APPROXIMATE. IT IS THE ELECTRICAL CONTRACTOR'S RESPONSIBILITY TO COORDINATE WITH ALL OTHER TRADES AND UTILITIES TO AVOID CONFLICTS WITH NEW WORK AND EXISTING CONDITIONS PRIOR TO INSTALLATION. B. ALL HANDHOLE LOCATIONS AND QUANTITIES ARE APPROXIMATE ELECTRICAL CONTRACTOR SHALL VERIFY EXACT HANDHOLE LOCATIONS PRIOR TO INSTALLATION. ELECTRICAL CONTRACTOR SHALL DETERMINE IF ADDITIONAL HANDHOLES ARE REQUIRED DUE TO SITE CONDITIONS OR PULLING REQUIREMENTS. PROVIDE AND INSTALL IF ADDITIONAL LIMINATIONS OR DEVIAINED FOR AND INSTALL IF ADDITIONAL

- HANDHOLES ARE INDEED REQUIRED. C. COORDINATE ALL ELECTRICAL SERVICE REQUIREMENTS INCLUDING, BUT NOT LIMITED TO, UTILITY TRANSFORMER, PRIMARY AND SECONDARY CONDUIT AND WIRING, AND METERING WITH ELECTRICAL UTILITY. SEE SPECIFICATION SECTION 26 00 00 FOR MORE INFORMATION.
- SEE ONE-LINE DIAGRAMS FOR CONDUIT/WIRE REQUIREMENTS. SEE SHEETS E501 AND E502.
- E. SEE DETAIL 5/E801 FOR DIRECT BURIED CONDUIT DETAILS.
- UTILITY TO PROVIDE CONNECTIONS BETWEEN EXISTING CONNECTION CABINET AND NEW C.T. CABINET CT-1.
  PROVIDE CONNECTION BETWEEN C.T. CABINET CT-1 AND SERVICE DISCONNECT DIS-1.
  EMBED CONDUIT IN TANK PLASTER COATING AND RUN UP TANK. SEE PROCESS SHEETS XXX FOR REFERENCE.

MADISON. WISCONSIN UNIT WELL 12 RECONSTRUCTION

MADWU 182222

JAM DDH

SEH Project Checked By Drawn By

ELECTRICAL SITE PLAN

E101

WHITNEY WAY

Ś

**ELECTRICAL - SITE PLAN** 

E101

SCALE: 1"=20'

#### LIGHTING GENERAL NOTES

- A. ALL RECESSED LIGHTING FIXTURES IN LAY-IN CEILING GRIDS SHALL BE INSTALLED WITH A 6'-0" LONG FLEXIBLE METAL CONDUIT.
- B. ALL MOUNTING HEIGHTS ARE FOR LIGHTING FIXTURES ARE TO THE BOTTOM OF THE FIXTURE UNLESS OTHERWISE NOTED.
- C. REFER TO SPECIFICATION SECTION 26 05 19 FOR MINIMUM CONDUCTOR SIZE ADJUSTMENTS FOR VOLTAGE DROP.
- D. CIRCUIT NUMBERS SHOWN AT LIGHT FIXTURE LOCATIONS CORRESPOND TO PANELBOARD BREAKERS. SEE PANELBOARD SCHEDULES ON SHEET E701.
- E. ALL EMERGENCY LIGHT FIXTURES SHALL BE FED FROM AN UNSWITCHED LEG OF ROOM LIGHTING CIRCUIT.
- F. WIRE FOR CIRCUIT CONDUCTORS NOT SHOWN. PROVIDE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUIT AND SWITCHING CONNECTIONS SHOWN.
- G. SEE LIGHT FIXTURE SCHEDULE ON THIS SHEET.

#### KEYNOTES ()

 INTER-LOCK EXHAUST FAN WITH ROOM LIGHTING. REFER TO SCHEMATIC 4/E601 FOR ADDITIONAL INFORMATION.

PROJECT NORTH

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

1 S. Whitney Way Idison WI, 53711

g is an instrument of service and shall property of Short Elliott Hendrickson, Inc. drawing, concepts and ideas contained

connection with the project is not publication in derogation of any of SEH Project Checked By Drawn By

Project Status DNR SUBMITTAL

K SUBMITTAL


REVISION SCHEDULE

182222 JAM NDS

LIGHTING PLAN

01 E201









#### POWER GENERAL NOTES

- A. PROVIDE HOUSE KEEPING PADS FOR ALL FLOOR AND GRADE MOUNTED ELECTRICAL EQUIPMENT. MINIMUM REQUIREMENTS: 4" HIGH, 4" WIDER AND LONGER THAN EQUIPMENT TO BE PLACED ON IT, 4% AIR ENTRAINED, POLYFIBER REINFORCED CONCRETE.
- B. REFER TO SPECIFICATION SECTION 26 05 19 FOR MINIMUM CONDUCTOR SIZE ADJUSTMENTS FOR VOLTAGE DROP.
- C. CIRCUIT NUMBERS SHOWN AT GENERAL RECEPTACLE, ELECTRICAL EQUIPMENT, AND MECHANICAL EQUIPMENT LOCATIONS CORRESPOND TO PANELBOARD BREAKERS. SEE PANELBOARD SCHEDULES ON SHEET E701.
- D. SEE ONE-LINE DIAGRAMS FOR CONDUIT AND WIRING REQUIREMENTS. SEE SHEETS E501 AND E502.
- E. SEE PANELBOARD SCHEDULES ON SHEET E701 FOR CONDUIT AND WIRING REQUIREMENTS.
- F. SEE MECHANICAL PLANS AND SCHEDULES FOR ALL HVAC AND PLUMBING POWER REQUIREMENTS AND DETAILS.

#### KEYNOTES ()

- 1. WALL MOUNT TRANSFORMER ABOVE LP-1.
- SALVAGED PUMP.

SEH

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

182222 JAM NDS

Issue Date 06/30/2025

POWER AND INSTRUMENTATION PLAN

EXISTING CONNECTION CABINET SERVICE DISCONNECT DIS-1 1200A, 480V, 3-PHASE, 4-WIRE FUSED, SERVICE ENTRANCE RATED 1200A C.T. CABINET CT-1 PP-1, 1200A 480V, 3-PHASE, 4-WIRE, 42SCCR, NEMA 1 CUSTOMER METERING & PHASE MONITORS 100a 3-PH, 4-W, 208Y/120V PANEL LP-1 POWER 1-LINE

NOT TO SCALE

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

Project Owner

SEH.

KEYNOTES (

no instrument of service and shall enjoy and shall shall see contained on the service and shall see contained and seas contained and seas contained and seas contained and seas contained to the services underne commont of SFH.

182222 JAM NDS

Issue Date 06/30/2025

is drawing is an instrument of service and shall main the propenty of Short Eliott Hendrickon, in EPI, This drawing, concepts and ideas contained rest shall not be used, reproduced, revised, or anised without the express withen approval of SEPdemission or distribution of this drawing to meet foolial or regulatory requirements or for purposes in mencifoun with the protest is not be construed as bit-cation in derogation of any of the rights of SEPI.

SEH Project Checked By Drawn By Project Status DNR SUBMITTAL

MITTAL

REVISION SCHEDU

ONE-LINE DIAGRAM

01 E501

6/30/2025 3:46:20 PM		
II FULL SCALE		
E 1. PKIN IED /		
IENDED 10 BE		

	1200			,			SCP-12 CC	ONTROL PANEL											
E902P-1;34*2#126 E901C-1; E901C-2 E901C-3 E901C-3	E502P-2:347-2412, #136  MFR SUPPLIED CABLE  MP E502C-1:1"2-PR#168	E902P-3:34*2#12.#126	E902P-4:34"-2#12,#126	E902P-6.34**2#12,#12G	ESOZP-6:34".2#126 FM ESOZO-6:1"-LPR#16S	ESO2P7:34".2#126 FM ESO2C 6: 1"1.PR#16S	ESD2P 8.34"-2#12,#126  WV ESD2C 7: 1"2-PR#16S	ESODRO 34"-2#12 #126  WV ESOZRO 8.1"-2 PR#16S	ESOZP-10:34*72#12 #12G  WV ESOZO 9:1*2 PP#16S	ESO2P-11:34*-2#12.#156 WV ESO2P-10:1*-2-PR#-168	ESOZP-12:34*-2#12.#15G WV ESSZC-11:1"-2.P14#16S	(E) E502C-12:347:2#14	(E) E5020-13:3/4"2#14	(E) E502C-14:34*2#14 (F) E502C-15:34*2#14	DC E602C-16:34F-2#14	DC E502C-17:3(#-2#14	DC E502C-18:34°2#14	DC ESOZ-19:34*2#14	DC ESOXC-21:34*2#14
120VAC POWER FROM LP1 SERVICE DISCONNECT DIS-1 VFD-WP-1 VFD-HSP-1 VFD-HSP-2	120VAC POWER FROM LP1 MP-FL-1 FLOURDE METERING PUMP	120VAC POWER PANEL 90-LP1 AZ-CL2-1 CHLORNE ANALYZER	120VAC POWER PANEL 90.LP1 FM-WP-19-1 FLOW METER	120VAC POWER PANEL 90-LP1 FM-Z7-1 FLOW METER	120VAC POWER PANEL 90-LP1 FM-28-1 FLOW METER	120VAC POWER PANEL 90.1P1 FM-8P-1 FLOW METER	120VAC POWER PANEL LP1 MV-212-1 MOTORIZED VALVE	120VAC POWER PANEL LP1 MV-ZBP-1 MOTORIZED VALVE	120VAC POWER PANEL LP1 MV-Z7-1 MOTORIZED VALVE	120VAC POWER PANEL LP1 MV-28-1 MOTORIZED VALVE	120VAC POWER PANEL LP1 MV-29-1 MOTORIZED VALVE	LE-R-HH	LE-R-H	LE-R-L LE-R-LL	DC-1 DOOR CONTACT	DC-2 DOOR CONTACT	DC-3 DOOR CONTACT	DC-4 DOOR CONTACT	DC-8 DOOR CONTACT
PLC 1-LINE DT TO SCALE																_	_		-

MADISON, WISCONSIN

UNIT WELL 12 RECONSTRUCTION

801 S. Whitney Way

Madison WI. 53711

Project Owner

rg is an instrument of service and shall properly of Short Elech Tendidoson, Inc. 1997 (1997)

publication in derogation of any of the rig SEH Project Checked By Drawn By

EVICION COLIFFINE


182222 JAM NDS

Issue Date 06/30/2025

EVISION SCHEDULE


ONE-LINE DIAGRAM

01 F502




WELL PUMP SCHEMATIC

ROT TO SCALE



CHEM ROOM EXHAUST FAN/LIGHTING INTER-LOCK



BOOSTER PUMP SCHEMATIC

BOOSTER PUMP SCHEMATIC

SCHEMATIC SYMBOLS - LOCATIONS AND CONNECTIONS DEVICE AT PLC DEVICE AT MFR CP CONNECTION POINT

EXTERNAL CONNECTION POINT

ELECTRICAL SCHEMATICS

Project Owner

MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

182222 JAM NDS


MOUN MAIN DE	ATION: PUMP 104 ITING: FLUSH NE EVICE: 200.0 A M AMPS: 200 AMPS	EMA1 AIN CB				A.I.C.	OLTAGE: RATING: SPECIAL:	10,000			RICAL			
CONDUIT/ WIRE	LOAD DESC	RIPTION	BKR	Р	скт	PHASE	A kVA	PHASE	B kVA	скт	Р	BKR	LOAD DESCRIPTION	CONDUIT/ WIRE
E502P-2	FL. METER PU	MP	20 A	1	1	0.2	0.4			2	1	20 A	S1 LIGHT FIXTURES	3/4" - 2#12, #12G
E502P-3	CHLORINE AIT		20 A	1	3			0.0	0.0	4	1	20 A	V1E LIGHT FIXTURES	3/4" - 2#12, #12G
E502P-4	FM-WP-19-1		20 A	1	5	0.0	0.0			6	1	20 A	WW1 LIGHT FIXTURES	3/4" - 2#12, #12G
E502P-5	FM-Z7-1		20 A	1	7			0.0	0.0	8	1	20 A	FACP	3/4" - 2#12, #12G
E502P-6	FM-Z8-1		20 A	1	9	0.0	0.0			10	1	20 A	SCP-12	3/4" - 2#12, #12G
E502P-7	FM-BP-1		20 A	1	11			0.0	0.0	12	_		00105	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
E502P-8	MV-Z12-1		20 A	1	13	0.0	0.0			14	2	20 A	SPARE	
E502P-9	MV-ZBP-1		20 A	1	15			0.0	0.0	16	1	20 A	SPARE	
E502P-10	MV-Z7-1		20 A	1	17	0.0	0.0			18	1	20 A	SPARE	
E502P-11	MV-Z8-1		20 A	1	19			0.0	0.0	20	1	20 A	SPARE	
E502P-12	MV-Z9-1		20 A	1	21	0.0	0.0			22	1	20 A	SPARE	
3/4" - 2#12, #12G	EF-1		20 A	1	23			0.0	0.0	24	1	20 A	SPARE	
3/4" - 2#12, #12G	EF-2		20 A	1	25	0.0	0.0			26	1	20 A	SPARE	
3/4" - 2#12, #12G	EF-3		20 A	1	27			0.0	0.0	28	1	20 A	SPARE	
3/4" - 2#12, #12G	GUH-1		20 A	1	29	0.0	0.0			30	1	20 A	SPARE	
					31			0.0	0.0	32	1	20 A	SPARE	
3/4" - 2#12, #12G	EWH-1		20 A	2	33	0.0	0.0			34	1	20 A	SPARE	
3/4" - 2#12. #12G	DEH-1		20 A	1	35			0.0		36	1		SPACE	
. , , , , , , , , , , , , , , , , , , ,					37	0.0				38	1		SPACE	
	SPD		20 A	3	39			0.0		40	1		SPACE	
					41	0.0	0.0			42	1	20 A	SCP-12	E502P-1
			TO	AL I	OAD:	1 k	VA	0 k	VA					
			TOT	AL A	MPS:	5	Α	0.3	3 A	1				
OAD CLASSIFICATIO	N	CONN	ECTED			DEMAN	ID	ES1	IMATED				PANEL TOTALS	
ITES		41:	3 VA			125.00	%	5	16 VA					
teceptacle			) VA			100.00			60 VA	_			CONNECTED LOAD:	768 VA
осоршого			, ,,,			100.00	,,,			-			ESTIMATED DEMAND:	
					1					-+			CONNECTED CURRENT:	
					+								EST. DEMAND CURRENT:	
										-+			EST. DEMIAND CURRENT:	2.4 M
					-									

182222 JAM NDS


SCHEDULES

01 E701

NOTES:



2 GROUNI E801 NOT TO SCALE





4" WIDER THAN EQUIP. SUPPORT TYP. EACH SIDE

KEYNOTES 🔷 NOT USED.

- 1. ABOVE PAD DETAILS APPLY FOR SUPPORT OF ALL EQUIPMENT UNLESS INDICATED OTHERWISE ON
- BEFORE EQUIPMENT SUPPORT PADS ARE POURED, THE PAD SIZES SHALL BE REVIEWED AND APPROVED.
- 6" MIN. PAD EDGE DIMENSION TO EQUIP. ANCHOR BOLTS (A.B.) APPLIES FOR ALL EQUIP. SUPPORT PADS THIS PROJECT.
- PROVIDE AN ADDITIONAL LAYER OF #4@12" E.W. W/ 1-1/2" CL. T&B FOR EACH 8" ADDIT. PAD THICKNESS EXCEEDING THE 3-1/2" THICKNESS.
- 5. L = T-2", BUT L NEED NOT EXCEED 6".








1. BACKFILL OF SELECT COMMON FILL COMPACTED IN LIFTS OF 6" (DEPTH VARIES)






Project Owner


MADISON, WISCONSIN UNIT WELL 12 RECONSTRUCTION

SEH Project Checked By Drawn By

182222 JAM NDS

ELECTRICAL DETAILS







MADWU 182222

WATER STORAGE TANK SECTION



Project Owner

Madison Water Utility
UNIT WELL 12 RECONSTRUCTION

801 S. Whitney Way Addison WI, 53711

This drawing is an instrument of service and shall nemate the property of Short Elbot Hendridson, Inc., (SEH). This drawing, concepts and beles contribute making shall not be used, reproduced, revised, or relabed without the express within approval of SEH.

Submission or distribution of this diversity or submission or distribution of this diversity or produced in the contribution or with the project is not be construed as much project in the project is not be construed as much project in the project in the project in the construed as much project in the c

SEH Project Checked By Drawn By


MADWU 182222 |S

roject Status NR SUBMITTAL

REVISION SCHEDULE

REV.# DESCRIPTION

WATER STORAGE TANK ELEVATIONS. SECTIONS



2'-6" STANDARD C.I.P. CIRCUMFERENTIAL STRIP


HORIZONTAL PROJECTION

– REINF. AS REQ'D

CIRCUMFERENTIAL DOME JOINT REINFORCING

1" CL. MIN.

7 1" GALV. DOVETAIL



RADIAL DOME JOINT REINFORCEMENT

NO 163.


1. SPLICE CIRCUMFERENTIAL JOINT REINFORCING BETWEEN RADIAL JOINTS.


2. RADIAL DIMENSIONS ARE HORIZONTAL PROJECTIONS.

3. DOME PANELS, DOME RING AND DOME SLOTS SHALL RECEIVE A LIGHT BROOM FINISH.

DOME SECTOR

NOT TO SCALE





NOTE:

1. WALL PANELS SHALL RECEIVE A HORIZONTAL
RAKE FINISH FOR THE BOTTOM 1'-0" OF THE
PANEL AND A HORIZONTAL LIGHT BROOM FINISH
FOR THE REST OF THE PANEL.


Project Owner


Madison Water Utility
UNIT WELL 12 RECONSTRUCTION

MADWU 182222 |S

Issue Date 6/30/2025

WATER STORAGE TANK STRUCTURAL DETAILS







Project Owner

Madison Water Utility
UNIT WELL 12 RECONSTRUCTION

ris drawing is an instrument of service and shall make the property of Short EBLM Head Sacon, Inc. EML, This Starelle, corespond and beas combined may be a sharp of the service of the service of the makes without the property of SEM, whether without the service service of SEM, whether the service of the service of SEM, whether the service of the service of SEM, whether the service of the service of the service of the managine with the service of the service of the managine with the service of the service of the managine with the service of the service of the managine with the service of service of the service of the service of service of the service of service service

MADWU 182222

SEH Project Checked By Drawn By


Project Status DNR SUBMITTAL

\_\_\_\_


# DESCRIPTION

NEV. # DECONE NON

WATER STORAGE TANK INLET, OUTLET, & MIXING SYSTEM DETAILS









Project Owner

Madison Water Utility

WHITIMPILSEZIRECONSTRUCTION

ris drawing is an instrument of service and shall main the property of Short Elbott Hendrickson. EHH. This drawing, concepts and kiess contain annis shall not be used, reproduced, revised, or tabled without the express written approved of S ubmission or distribution of this drawing to meet

submission or distribution of this drawing to meet flictal or regulatory requirements or for purposes consection with the project is not be construed as utilication in derogation of any of the rights of SE

SEH Project Checked By Drawn By


DNR SUBMITTAL

# DESCRIPTION

Issue Date 6/30/2025

REV. # DESCRIPTION

WATER STORAGE TANK ACCESSORY DETAILS





remain the property of Short Elliott Hendrickson, Inc. (SEH). This drawing, concepts and ideas contained herein shall not be used, reproduced, revised, or retained without the express written approval of SEH. Submission or distribution of this drawing to meet official or regulatory requirements or for purposes in connection with the project is not to be construed as publication in derogation of any of the rights of SEH. MADWU\_182222


09/22/2025


REVISION SCHEDULE DESCRIPTION

06/30/2025

LANDSCAPE PLAN

WAGNER 749-14






PERENNIAL PLANTING DETAIL

SHRUB PLANTING

32 93-01

32 93-02

32 9333.13-08




PRUNE ONLY TO REMOVE DAMAGED OR BROKEN BRANCHES. TREE STAKING (ONLY 1 OF 3 @ 120 DEG. SHOWN FOR CLARITY). STEEL STAKES & FLEXIBLE GUYING MATERIAL. FLAG GUYS FOR TREE WRAP TO FIRST BRANCH (MAPLES AND OTHER THIN BARKED DECIDUOUS TREES). PLACE WRAP IN LATE FALL AND REMOVE EARLY SPRING. - 4' X 4" A.M. LEONARD RIGID PLASTIC MESH TREE GUARD, BG48 TREE WATERING BAG. INSTALL SAME DAY TREE IS PLANTED. BAG SHALL BE FILLED ONCE PER WEEK THROUGH THE MAINTENANCE PERIOD. (1/2 - 2/3)OF TREE CROWN OF ROOT BALL 1" ABOVE FINISHED GRADE LEAVING HEIGHT TRUNK FLARE VISIBLE AT TOP OF ROOT BALL. 3" DEEP MULCH IN 6'-0" DIAMETER RING. DO NOT PLACE MULCH IN CONTACT WITH TREE TRUNK. NO MOUNDING. PROVIDE MULCH WEEDING A MINIMUM OF ONCE PER MONTH, DEPTH OF OR AS NEEDED TO PREVENT WEED ESTABLISHMENT, **ROOT BALL** THROUGH MAINTENANCE PERIOD. ROUGHEN EDGES OF PLANTING PIT. PLANTING MIXTURE BACKFILL TAMP PLANTING MIX AROUND BASE TO STABILIZE TREE ROOT BALL REMOVE ALL TWINE, ROPE, WIRE, BURLAP AND PLASTIC WRAP FROM TOP HALF OF ROOT BALL. IF WIRE BASKET, CUT IN (4) PLACES AROUND THE ROOT BALL AND FOLD DOWN 8" INTO PLANTING PIT. EXCAVATE TREE PIT TO BE AT ROOT BALL ON UNEXCAVATED OR COMPACTED PEDESTAL LEAST 2 TIMES WIDER THAN TO PREVENT SETTLING **ROOT BALL** 

TREE WITH STRONG CENTRAL LEADER (DO NOT CUT LEADER)

32 9343-01



TREE PLANTING





# PLANTING NOTES:

- 1. THE LAYOUT OF ALL PLANTING BEDS AND INDIVIDUAL TREES SHALL BE STAKED BY THE CONTRACTOR IN ADVANCE OF INSTALLATION. FLAGGING, STAKES, OR PAINT MAY BE USED TO DELINEATE LOCATIONS AS SCALED FROM THE PLANS. THE LANDSCAPE ARCHITECT WILL REVIEW THESE LOCATIONS WITH THE CONTRACTOR AND MAKE MINOR ADJUSTMENTS AS NECESSARY.
- 2. THE CONTRACTOR IS RESPONSIBLE FOR INDEPENDENTLY DETERMINING THE PLANT MATERIAL QUANTITIES REQUIRED BY THE LANDSCAPE PLANS. REPORT ANY DISCREPANCIES TO THE LANDSCAPE ARCHITECT.
- 3. AREAS UNDER PLANTING BEDS SHALL NOT CONTAIN COMPACTED AGGREGATE TO ALLOW FOR PROPER DRAINAGE AND GROWTH OF PLANT MATERIAL. REMOVE AGGREGATE AND PERFORM SUBSOILING AS NECESSARY TO OBTAIN LOOSE, FREE DRAINING SUBGRADE BELOW PLANTING BEDS. UNDESIRABLE CONDITIONS SHALL BE BROUGHT TO THE ATTENTION OF THE LANDSCAPE ARCHITECT PRIOR TO BEGINNING OF WORK. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO ENSURE PROPER SURFACE AND SUBSURFACE DRAINAGE IN ALL AREAS.
- 4. ALL SEED AREAS SHALL RECEIVE A MINIMUM OF 6" DEPTH OF TOPSOIL
- 5. ALL PLANTING BEDS SHALL RECEIVE 18" DEPTH OF PREPARED SOIL
- 6. NEW SEEDED AREAS TO BE TREATED WITH HERBICIDE TO KILL ALL EXISTING GROUNDCOVER. THERE SHALL BE A MINIMUM OF TWO (2) APPLICATIONS SEPARATED BY 10 DAYS. IF ALL EXISTING GROUNDCOVER VEGETATION IS NOT KILLED WITHIN 10 DAYS OF 2ND APPLICATION, A 3RD APPLICATION IS REQUIRED.
- 7. ALL DISTURBED AREAS OUTSIDE THE LIMITS OF WORK SHALL BE RESTORED TO ORIGINAL OR BETTER CONDITION AT NO ADDITIONAL COST TO THE OWNER.
- 8. SHOVEL CUT EDGE TYPICAL OF ALL PLANTING BEDS UNLESS OTHERWISE INDICATED.
- 9. ALL PLANTING BEDS AND PLANTED TREES SHALL BE MULCHED WITH 3" DEEP SHREDDED HARDWOOD MULCH PER PLANTING DETAILS. MULCH SHALL BE CONSIDERED INCIDENTAL TO PLANT MATERIALS
- 10. NO PLANT MATERIAL SUBSTITUTIONS WILL BE ACCEPTED UNLESS APPROVAL BY THE LANDSCAPE ARCHITECT. ALL PLANT MATERIAL AND SEED SHALL BE PROVIDED FROM A NURSERY (WITHIN 200 MILES) WITH A SIMILAR PLANT HARDINESS ZONE AS PROJECT LOCATION.
- 11. CONTRACTOR IS RESPONSIBLE FOR ON-GOING MAINTENANCE OF ALL NEWLY INSTALLED MATERIALS UNTIL TIME OF OWNER ACCEPTANCE. ANY ACTS OF VANDALISM OR DAMAGE WHICH MAY OCCUR PRIOR TO OWNER ACCEPTANCE SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR
- 12. PROVIDE 1 YEAR WARRANTY ON ALL PLANT MATERIAL.
- 13. LAWN SEED SHALL BE ESTABLISHED BY THE CONTRACTOR TO A DENSE, GREEN CONSISTENT LAWN VOID OF ANY BARE OR PATCHY AREAS LARGER THAN 3"X3"
- 14. SEED PRIOR TO OCT. 15. IF SEEDED AFTER OCT. 15, MAINTAIN AND ESTABLISH LAWN UNTIL SPRING REVIEW
- 15. THE CONTRACTOR SHALL VERIFY ALL EXISTING UTILITIES, INCLUDING IRRIGATION LINES PRIOR TO DIGGING. CONSULT DIGGERS HOTLINE.
- 16. THE CONTRACTOR IS RESPONSIBLE FOR ALL PERMITS, FEES AND LICENSES NECESSARY FOR THE INSTALLATION OF THIS PLAN.
- 17. DRAWINGS ARE INTENDED FOR THE INSTALLATION OF PLANT MATERIAL

Project Owner

STRUCTION ISIN RECONS

MADISON, WISC UNIT WELL remain the property of Short Elliott Hendrickson, Inc. (SEH). This drawing, concepts and ideas contained retained without the express written approval of SEH. Submission or distribution of this drawing to meet

official or regulatory requirements or for purposes in connection with the project is not to be construed as publication in derogation of any of the rights of SEH. MADWU\_182222

**Project Status** DNR SUBMITTAL

CITY SUBMITTAL

Checked By

Drawn By

**REVISION SCHEDULE** 

Issue Date

06/30/2025

09/22/2025

DESCRIPTION

LANDSCAPE DETAILS

MOLLY WAGNER 749-14

# <u>Tabulation of Points and Credits</u> Developed site area: 38,513 sf x 5pt/300sf = 642 points required

Use the table to indicate the quantity and points for all existing and proposed landscape elements.

DI ATE ATE	Minimum Size at	<b>D</b> : 4		Existing caping		roposed caping
Plant Type/ Element	Installation	Points	Quantity	Points Achieved	Quantity	Points Achieved
Overstory deciduous tree	2½ inch caliper measured diameter at breast height (dbh)	35		(5) trees ins street fronta (2) trees ins general land	ge trees, talled as	245
Tall evergreen tree (i.e. pine, spruce)	5-6 feet tall	35			(6)	210
Ornamental tree	1 1/2 inch caliper	15		(2) ornamen		105
Upright evergreen shrub (i.e. arborvitae)	3-4 feet tall	10		frontage trees, (5) trees installed as general landscaping		
Shrub, deciduous	#3 gallon container size, Min. 12"-24"	3			(66)	198
Shrub, evergreen	#3 gallon container size, Min. 12"-24"	4			(6)	24
Ornamental grasses/ perennials	#1 gallon container size, Min. 8"-18"	2			(44)	88
Ornamental/ decorative fencing or wall	n/a	4 per 10 lineal ft.				
Existing significant specimen tree	Minimum size: 2 ½ inch caliper dbh. *Trees must be within developed area and cannot comprise more than 30% of total required points.	14 per caliper inch dbh. Maximum points per tree: 200	(2) 20" cal. (1) 18" cal. evergreen tree	812 total points, 192 points (30% of development requirement) applied to developed site area		
Landscape furniture for public seating and/or transit connections	* Furniture must be within developed area, publically accessible, and cannot comprise more than 5% of total required points.	5 points per "seat"				
Sub Totals				192		870

Total	Number of Points Provided	1062
Total	Number of Points Provided	1002

12/2019

<sup>\*</sup> As determined by ANSI, ANLA- American standards for nursery stock. For each size, minimum plant sizes shall conform to the specifications as stated in the current American Standard for Nursery Stock.

CONSIN 12 RECONSTRUCTION MADISON. WISC UNIT WELL

remain the property of Short Elliott Hendrickson, Inc. (SEH). This drawing, concepts and ideas contained herein shall not be used, reproduced, revised, or retained without the express written approval of SEH. Submission or distribution of this drawing to meet official or regulatory requirements or for purposes in connection with the project is not to be construed as

publication in derogation of any of the rights of SEH.

Checked By Project Status

DNR SUBMITTAL

Issue Date

6/30/2025

SITE LIGHTING PHOTOMETRIC

Luminaire Total
Watts Watts Qty Description t.0 t.0DRIVEWAY & PARKING t.o t.o/ PROPOSED WATER t.0 t.1 t.3 t.. WELL BUILDING 1.6 5.3 5.1 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 
 0.0
 0.2
 0.9
 4.

 5.0
 5.0
 5.0
 5.0
 5.0
 5.0

 0.0
 0.2
 1.0
 6.

 LED WALLPACK — (TYP. OF 3) **.** 5.0 5.1 5.4 5.9 b.o b.o \tau.o b.o b.o b.o b.o b.o b 5.0 <del>0.1</del> 5.2 5.4 1.5 <del>9</del>.4 <del>1.1</del> 5.6 5.2 5.1 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 
 5.0
 5.1
 5.2
 5.7
 5.5
 5.0
 5.3
 5.1
 5.1
 5.0
 5.0
 5.0
 5.0
 5.0
 PROPERTY BOUNDARY b.0 b.0 b.1 b.1 b.2 b.2 b.2 b.1 b.1 b.0 b.0 b.0 b.0 b.0 b.0 b.0 b.0 b.0 $\frac{1}{2}$  5.0  $\frac{1}{2}$  6.0  $au_{0}$   $au_$ 

SITE PHOTOMETRIC PLAN SCALE: 1"=20'



# **HLWPC2**

Wallpack® Full Cutoff LED














#### Mechanical

- Heavy grade A360 cast aluminum (aluminum with <1% copper)</li>
- Exterior parts are protected by a zinc-infused Super Durable TGIC thermoset powder coat finish that provides superior resistance to corrosion and weathering
- · Mounts to a standard junction box
- · Wet location listed
- · IP65 rated housing, down light only
- ¾" painted threaded entry(¾" 14 NPT) on each side and on top, accepts ¾" and ½" conduit
- 34" threaded plugs are painted on each side
- Vibration tested to 1.5G per ANSI C136.31.

#### Electrical

- Certified by UL or CSA
- Rated for -40°C (-40°F) minimum ambient
- A programmable electronic driver with 0-10V control leads
- Available in: 120-277V 50/60 Hz and 347-480V 50/60 Hz,
- Standard: 3000K, 4000K and 5000K CCT (>70 CRI)
- Optional >80 CRI (3000K, 4000K and 5000K CCT)
- Internally mounted emergency battery backup for operation in an ambient temperature ranging from -20°C (-4°F) to 30°C (86°F), available with P10 thru P40 performance packages, non CEC compliant
- All surge protection meets ANSI/IEEE C62.41.2 10kV/10kA
- Standard surge protection is 20kV/10kA per ANSI C136.2
- Optional surge protection is 10kV/5kA per ANSI C136.2

#### Ontica

- Light engine housing is IP66 rated
- Acrylic optical system
- Type V: E (entry), M (medium), R (rectangle) & W (wide)
- Asymmetric

#### **Controls**

- Field adjustable output (AO)
- Button style photocontrol (PE)
- Motion sensor & ambient photocontrol combination for mounting low (8-15') (MASL) and high (15-30') (MASH) mounting heights

#### **Certification and Standards**

- · Luminaire is CSA listed, US and Canada
- Suitable for operation in an ambient temperature up to 40°C/104°F per UL or CSA certification
- Design lights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at <a href="www.designlights.org/QPL">www.designlights.org/QPL</a> to confirm which versions are qualified.
- · LM-79 compliant
- The projected LED Lumen Maintenance shall be based only on IES LM-80-08 and TM-21


#### Warranty


5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: <a href="https://www.acuitybrands.com/support/warranty/terms-and-conditions">www.acuitybrands.com/support/warranty/terms-and-conditions</a>.


**Note:** Actual performance may differ as a result of end-user environment and application.


All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.













#### **ORDERING INFORMATION**

#### Example: HLWPC2 P20 40K MVOLT T3M BZSDP

Series	Lumen Package	Color Temperature	Voltage	<b>Optics</b>	Color	CRI
HLWPC2 Wallpack Full Cutoff LED	1 LEM Package P10 3,100 lm P20 5,600 lm 2 LEM Package P30 7,800 lm P40 9,900 lm P50 11,700 lm (Nominal Lumens, 4000K)	AMB True Amber 30K 3,000 K CCT 40K 4,000 K CCT 50K 5,000 K CCT	120 120 volts 208 208 volts 240 240 volts 277 277 volts 347 347 volts 480 480 volts HVOLT 347/480 volts MVOLT 120-277 volts	T2S Type 2 Short T2M Type 2 Medium T3S Type 3 Short T3M Type 3 Medium T4M Type 4 Medium TFTM Forward Throw Medium ASYDF Asymmetric Diffuse SYMDF Symmetric Diffuse	BKSDP Black BZSDP Bronze GYSDP Grey WHSDP White	Blank 70 CRI (STD) 80CRI 80 CRI


Options	s:				
Adjust	able/Programmable Options	Contr	ol - Photocontrol Options	Fuse	Option
AO	Field Adjustable Output	PE	Button Style Photocontrol	SF	Single Fuse
		P3	N.E.M.A. Twistlock Receptacle Mount -3 PIN	DF	Double Fuse
Circuit	<u>Options</u>	P7	N.E.M.A. Twistlock Receptacle Mount -7 PIN		
2CI	2 Independent Circuits	PCLL	DTL Long Life Twistlock Photocontrol for Solid State	Safe	ty Option
		PSC	Shorting Cap	EM	Integral Emergency Battery
Contro	l - Motion Sensor Options			TP	Tamper Resistant Hardware
MASL <sup>1,2</sup>	Motion / Ambient Sensor, 8-15' Mounting Height Ambient Sensor Enabled at 5 FC			Sura	e Protection Option - 20kV/10kA is Standard
MASH <sup>1,2</sup>	Motion / Ambient Sensor, 15-30' Mounting Height Ambient Sensor Enabled at 5 FC			10KV	10kV/5kA Surge Protection, in place of 20kV/10kA

#### Notes


- 1 MASL and MASH sensors are not allowed with P10 lumen package option selected.
- 2 MASL and MASH options reduce luminaire light output to roughly 30% (not full OFF) when no motion is detected. When motion is detected, light output temporarily increases to 100%.

### **Options Location**


Motion/Ambient Sensor mount options for Low (8-15') (MASL) and Height (15-30') (MASH) applications




N.E.M.A. Twistlock Receptacle P3 and P7 Options, P7 Shown



Internal Emergency Battery Test Button - EM Option









#### **Driver & LEM Configuration Based on Circuit Options**

Number of	Number of LEMs &		rcuit (std.)	Two Circuit (2Cl option)		
Drivers / 0	Circuit	LEMs	Drivers	LEMs	Drivers	
	P10	1	1	-	-	
Lumen	P20	1	1	2	2	
Maintenance	P30	2	1	2	2	
Factor	P40	2	1	2	2	
	P50	2	1	-	-	



#### **SPD Based on Circuit Options**

Number of LEMs &			Sinlge Ci	rcuit (std.)		Two Circuit (2Cl option)					
Drivers / C	Circuit	LEMs	Drivers	No. of SPDs	SPD	LEMs	Drivers	No. of SPDs	SPD		
Lumen	P10	1	1	1	20kV/10kA	-	-	-	-		
	P20	1	1	1	20kV/10kA	2	2	2	10kV/5kA		
Maintenance	P30	2	1	1	20kV/10kA	2	2	2	10kV/5kA		
Factor	P40	2	1	1	20kV/10kA	2	2	2	10kV/5kA		
	P50	2	1	1	20kV/10kA	-	-	-	-		



#### **Projected LED Lumen Maintenance**

Data references the extrapolated performance projections for the platform noted in a 25°C ambient, based on 6,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

To calculate LLF, use the lumen maintenance factor that corresponds to the desired number of operating hours below. For other lumen maintenance values, contact factory.

The italicized data is extrapolated beyond the TM-21 standard.

E = (LM) x (CU) x (LAT) x (LLD)LM and CU are obtained from published photometry.

Operating H (Standar		0	25,000	30,000	36,000	45,000	50,000	60,000	75,000	100,000
Lumen Maintenance Factor	P10	1	0.98	0.97	0.96	0.96	0.95	0.95	0.94	0.92
	P20	1	0.97	0.95	0.94	0.93	0.92	0.90	0.88	0.85
	P30	1	0.98	0.97	0.96	0.96	0.95	0.95	0.94	0.92
	P40	1	0.97	0.95	0.94	0.93	0.92	0.90	0.88	0.85

Operating F (2Cl Option		0	25,000	30,000	36,000	45,000	50,000	60,000	75,000	100,000
	P10	1	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Lumen	P20	1	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Maintenance Factor	P30	1	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98
	P40	1	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97

#### **Lumen Ambient Temperature (LAT) Multipliers**

Use these factors to determine relative lumen output for average ambient temperatures from  $0-40^{\circ}\text{C}$  (32-104°F).

#### **Single Circuit Application**

Amt	oient	P10	P20	P30	P40	P50
0°C	32°F	1.02	1.03	1.03	1.04	1.05
10°C	50°F	1.01	1.02	1.02	1.03	1.03
20°C	68°F	1.01	1.01	1.01	1.01	1.01
25°C	77°F	1.00	1.00	1.00	1.00	1.00
30°C	86°F	0.99	0.99	0.99	0.99	0.99
40°C	104°F	0.98	0.97	0.98	0.97	0.97

#### Optional Two Independent Circuit (2CI) Application

optional in	o illacpellac	(2.	., rippiicacio	<b></b>
Amt	ient	P20	P30	P40
0°C	32°F	1.02	1.02	1.02
10°C	50°F	1.01	1.01	1.02
20°C	68ºF	1.00	1.01	1.01
25°C	77°F	1.00	1.00	1.00
30°C	86°F	0.99	0.99	0.99
40°C	104°F	0.98	0.98	0.98

#### **Electrical Load**

#### **Single Circuit Application**

			Current (A)					
LEDs	Drive Current (mA)	System Watts/ Circuit	120	208	240	277	247	480
P10	700	28	0.23	0.13	0.12	0.10	0.08	0.06
P20	1400	47	0.41	0.24	0.20	0.18	0.14	0.10
P30	1050	71	0.63	0.37	0.32	0.29	0.22	0.18
P40	1420	95	0.78	0.45	0.40	0.35	0.27	0.20
P50	1720	115	0.95	0.55	0.48	0.42	0.33	0.24

#### Optional Two Independent Circuit (2CI) Application

					Curre	nt (A)		
LEDs	Drive Current (mA)	System Watts/ Circuit	120	208	240	277	247	480
P10	-	-	-	-	-	-	-	-
P20	700	22	0.10	0.06	0.05	0.04	-	-
P30	1000	32	0.14	0.08	0.07	0.06	-	-
P40	1250	47	0.18	0.10	0.09	0.08	-	-
P50	-	-	-	-	-	-	-	-



# **HLWPC2**

# Wallpack® Full Cutoff LED



### **Operating Characteristics**

LED	Distribution	System		30K (3	000K, 70	CRI)			40K (4	1000K, 70	CRI)			50K (5	000K, 70	(CRI)	
Package	DISTRIBUTION	Watts	Lumens	LPW	В	U	G	Lumens	LPW	В	U	G	Lumens	LPW	В	U	G
	T2S	28	2,904	104	1	0	1	3,128	112	1	0	1	3,168	113	1	0	1
	T2M	28	2,887	103	1	0	1	3,110	111	1	0	1	3,149	112	1	0	1
	T3S	28	2,964	106	1	0	1	3,194	114	1	0	1	3,234	116	1	0	1
P10	T3M	28	2,801	100	1	0	1	3,017	108	1	0	1	3,055	109	1	0	1
PIU	T4M	28	2,858	102	1	0	1	3,079	110	1	0	1	3,118	111	1	0	1
	TFTM	28	2,979	106	1	0	1	3,209	115	1	0	1	3,250	116	1	0	1
	SYMDF	28	2,771	99	1	0	1	2,986	107	1	0	1	3,023	108	1	0	1
	ASYDF	28	2,756	98	1	0	1	2,969	106	1	0	1	3,007	107	1	0	1
	T2S	47	5,303	113	1	0	1	5,713	122	1	0	1	5,785	123	1	0	1
	T2M	47	5,272	112	1	0	2	5,680	121	1	0	2	5,751	122	1	0	2
	T3S	47	5,414	115	1	0	2	5,832	124	1	0	2	5,906	126	1	0	2
P20	T3M	47	5,115	109	1	0	2	5,510	117	1	0	2	5,580	119	1	0	2
F20	T4M	47	5,220	111	1	0	2	5,623	120	1	0	2	5,694	121	1	0	2
	TFTM	47	5,440	116	1	0	2	5,861	125	1	0	2	5,935	126	1	0	2
	SYMDF	47	5,062	108	2	0	2	5,453	116	2	0	2	5,522	117	2	0	2
	ASYDF	47	5,033	107	1	0	1	5,422	115	2	0	1	5,491	117	2	0	1
	T2S	71	7,319	103	2	0	2	7,884	111	2	0	2	7,984	112	2	0	2
	T2M	71	7,276	102	2	0	2	7,838	110	2	0	2	7,937	112	2	0	2
	T3S	71	7,472	105	1	0	2	8,049	113	2	0	2	8,151	115	2	0	2
P30	T3M	71	7,059	99	2	0	2	7,604	107	2	0	2	7,700	108	2	0	2
rsu	T4M	71	7,203	101	2	0	2	7,760	109	2	0	2	7,858	111	2	0	2
	TFTM	71	7,508	106	1	0	2	8,088	114	2	0	2	8,190	115	2	0	2
	SYMDF	71	6,985	98	2	0	2	7,525	106	3	0	3	7,620	107	3	0	3
	ASYDF	71	6,946	98	2	0	2	7,483	105	2	0	2	7,578	107	2	0	2
	T2S	95	9,320	98	2	0	2	10,041	106	2	0	2	10,168	107	2	0	2
	T2M	95	9,266	98	2	0	2	9,982	105	2	0	3	10,108	106	2	0	3
	T3S	95	9,515	100	2	0	2	10,251	108	2	0	2	10,381	109	2	0	2
P40	T3M	95	8,989	95	2	0	2	9,684	102	2	0	2	9,807	103	2	0	2
P40	T4M	95	9,174	97	2	0	2	9,883	104	2	0	3	10,008	105	2	0	3
	TFTM	95	9,561	101	2	0	2	10,300	108	2	0	2	10,431	110	2	0	2
	SYMDF	95	8,896	94	3	0	3	9,583	101	3	0	3	9,705	102	3	0	3
	ASYDF	95	8,846	93	2	0	2	9,530	100	2	0	2	9,650	102	2	0	2
	T2S	115	10,972	95	2	0	2	11,820	103	2	0	2	11,969	104	2	0	2
	T2M	115	10,908	95	2	0	3	11,751	102	2	0	3	11,900	103	2	0	3
	T3S	115	11,202	97	2	0	2	12,067	105	2	0	2	12,220	106	2	0	2
P50	T3M	115	10,582	92	2	0	2	11,400	99	2	0	3	11,544	100	2	0	3
P30	T4M	115	10,799	94	2	0	3	11,634	101	2	0	3	11,781	102	2	0	3
	TFTM	115	11,256	98	2	0	2	12,126	105	2	0	2	12,279	107	2	0	2
	SYMDF	115	10,472	91	3	0	3	11,282	98	3	0	3	11,424	99	3	0	3
	ASYDF	115	10,414	91	2	0	2	11,219	98	3	0	2	11,361	99	3	0	2

Use the following to scale 70CRI to 80CRI.

CCT	Multiplier
3000K	0.909
4000K	0.886
5000K	0.865

All IES files available on product web page





### **Operating Characteristics (continued)**

LED De elseve	Distribution	System	30K	+ 2Cl Op	tion (300	00K, 70 C	RI)	40K	+ 2Cl Op	tion (400	0K, 70 CI	RI)	50K	+ 2CI Op	tion (500	OOK, 70 C	RI)
LED Package	Distribution	Watts	Lumens	LPW	В	U	G	Lumens	LPW	В	U	G	Lumens	LPW	В	U	G
	T2S	49	5,015	102	1	0	1	5,402	110	1	0	1	5,471	112	1	0	1
	T2M	49	4,985	102	1	0	2	5,371	110	1	0	2	5,439	111	1	0	2
	T3S	49	5,120	104	1	0	1	5,515	113	1	0	2	5,585	114	1	0	2
P20	T3M	49	4,837	99	1	0	2	5,210	106	1	0	2	5,276	108	1	0	2
P20	T4M	49	4,936	101	1	0	2	5,317	109	1	0	2	5,385	110	1	0	2
	TFTM	49	5,144	105	1	0	2	5,542	113	1	0	2	5,612	115	1	0	2
	SYMDF	49	4,786	98	2	0	2	5,156	105	2	0	2	5,222	107	2	0	2
	ASYDF	49	4,760	97	1	0	1	5,127	105	1	0	1	5,192	106	1	0	1
	T2S	70	6,769	97	1	0	1	7,293	104	2	0	2	7,385	106	2	0	2
	T2M	70	6,730	96	2	0	2	7,250	104	2	0	2	7,342	105	2	0	2
	T3S	70	6,911	99	1	0	2	7,445	106	1	0	2	7,539	108	1	0	2
P30	T3M	70	6,529	93	2	0	2	7,033	100	2	0	2	7,123	102	2	0	2
130	T4M	70	6,663	95	2	0	2	7,178	103	2	0	2	7,269	104	2	0	2
	TFTM	70	6,945	99	1	0	2	7,481	107	1	0	2	7,576	108	2	0	2
	SYMDF	70	6,461	92	2	0	2	6,960	99	2	0	2	7,049	101	2	0	2
	ASYDF	70	6,425	92	2	0	2	6,922	99	2	0	2	7,009	100	2	0	2
	T2S	89	8,370	94	2	0	2	9,017	101	2	0	2	9,131	103	2	0	2
	T2M	89	8,321	93	2	0	2	8,964	101	2	0	2	9,078	102	2	0	2
	T3S	89	8,545	96	2	0	2	9,205	103	2	0	2	9,322	105	2	0	2
P40	T3M	89	8,073	91	2	0	2	8,696	98	2	0	2	8,807	99	2	0	2
1 40	T4M	89	8,238	93	2	0	2	8,875	100	2	0	2	8,987	101	2	0	2
	TFTM	89	8,586	96	2	0	2	9,250	104	2	0	2	9,367	105	2	0	2
	SYMDF	89	7,989	90	3	0	3	8,606	97	3	0	3	8,715	98	3	0	3
	ASYDF	89	7,944	89	2	0	2	8,558	96	2	0	2	8,666	97	2	0	2

Use the following to scale 70CRI to 80CRI.

CCT	Multiplier
3000K	0.909
4000K	0.886
5000K	0.865

All IES files available on product web page

LED		System	AMB (Wavelength)					LED		System AMB (Wavelength)					
Package	Distribution	Watts	Lumens	LPW	В	U	G	Package	Package Distribution		Lumens	LPW	В	U	G
	T2S	28	1,061	38	0	0	1		T2S	28	1,975	71	0	0	1
	T2M	28	1,054	38	0	0	1	]	T2M	28	1,964	70	0	0	1
	T3S	28	1,083	39	0	0	1	]	T3S	28	2,016	72	0	0	1
P10	T3M	28	1,023	37	0	0	1	P30	T3M	28	1,905	68	0	0	1
PIU	T4M	28	1,044	37	0	0	1	1 130	T4M	28	1,944	69	0	0	1
	TFTM	28	1,088	39	0	0	1	]	TFTM	28	2,026	72	0	0	1
	SYMDF	28	1,012	36	1	0	1	]	SYMDF	28	1,885	67	1	0	1
	ASYDF	28	1,007	36	0	0	1	]	ASYDF	28	1,875	67	0	0	1



# **HLWPC2**

# Wallpack® Full Cutoff LED



### **Options Matrix**

Parameters		LED					0pt	ions (Start	with SF, DI	F, 2CI or EM	if being u	sed)				
Parameter	is .	AMB	PE	P3	P7	PSC	PCLL	MASH	MASL	SF	DF	TP	10kV	A0	2CI	EM
	P10	Y	Y	Y	Y	Y	Υ	N	N	Y	Υ	Υ	Υ	Y	N	Y
1500 (	P20	N	Y	Υ	Y	Y	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ
LED Performance Package	P30	Υ	Υ	Υ	Y	Y	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ
Package	P40	N	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ
	P50	N	Y	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ	N	Υ
	AS	Υ	N	Υ	Υ	Υ	Υ	Υ	Υ	N	N	Υ	Υ	Υ	Υ	Υ
	AH	Υ	N	Y	Y	Υ	N	N	N	N	N	Y	Υ	Υ	N	N
	12	Υ	Υ	Υ	Y	Υ	Υ	Υ	Υ	Υ	N	Y	Υ	Υ	Υ	Υ
Voltage	20	Υ	Y	Y	Y	Υ	Υ	Υ	Y	N	Υ	Υ	Υ	Υ	Υ	Υ
voitage	24	Υ	Y	Y	Y	Υ	Y	Υ	Y	N	Y	Υ	Υ	Y	Υ	Υ
	27	Υ	Y	Y	Y	Y	Υ	Υ	Y	Υ	N	Y	Υ	Y	Υ	Υ
	34	Υ	Y	Y	Y	Y	Υ	N	N	Y	N	Υ	Υ	Y	N	N
	48	Y	N	Υ	Y	Υ	Υ	N	N	N	Y	Υ	Υ	Y	N	N
	PE	Υ		N	N	N	N	N	N	Υ	Υ	Υ	Υ	Υ	N	Υ
	P3	Y	N		N	М	Υ	N	N	Y	Υ	Υ	Υ	N	N	N
	P7	Y	N	N		М	Υ	N	N	Y	Y	Υ	Υ	N	N	N
	PSC	Y	N	М	М		N	N	N	Y	Y	Υ	Υ	N	N	N
	PCLL	Υ	N	Y	Y	N		N	N	Y	Y	Υ	Υ	N	N	N
	MASH	Y	N	N	N	N	N		N	Y	Y	Υ	Υ	N	N	N
Options	MASL	Y	N	N	N	N	N	N		Υ	Υ	Υ	Υ	N	N	N
Options	SF	Υ	Y	Y	Y	Y	Υ	Υ	Y		N	Υ	Υ	Y	Υ	Υ
	DF	Y	Y	Y	Y	Y	Υ	Υ	Y	N		Υ	Υ	Y	Υ	Y
	TP	Υ	Y	Y	Y	Υ	Υ	Υ	Υ	Υ	Υ		Υ	Υ	Υ	Υ
	10kV	Y	Y	Y	Y	Y	Υ	Υ	Y	Υ	Υ	Y		Υ	М	М
	A0	Υ	Y	N	N	N	N	N	N	Y	Υ	Υ	Υ		N	N
	2CI	P30	N	N	N	N	N	N	N	Y	Υ	Y	М	N		N
	EM	Υ	Υ	N	N	N	N	N	N	Υ	Υ	Υ	М	N	N	

#### Notes

I = Included with option

M = Must have: one of these must be installed for the luminaire to operate

N = Combination Not available

 ${\rm P30} = {\rm Valid\ Option\ Combination,\ not\ available\ with\ P10\ Performance\ Packabe}$ 


 $Y = Valid\ Option\ Combination$ 






#### **Photometric Diagrams**

To see complete photometric reports or download .ies files for this product, visit the Holophane's Wallpack FCO LED homepage. Isofootcandle plots for the HLWPC2 P30 40K. Distance are in units of mounting height (12"). Grid is 10'x10'.





#### **HLWPC2 P30 40K XX T2S**







HLWPC2 P30 40K XX T2M







HLWPC2 P30 40K XX ASYDF







**HLWPC2 P30 40K XX T3S** 







HLWPC2 P30 40K XX T3M







HLWPC2 P30 40K XX SYMDF











**HLWPC2 P30 40K XX TFTM** 





#### **Coverage Pattern**



#### **Control Options**

#### **Button Style Photocontrol**

PE



#### N.E.M.A. Receptacle

P3



#### **Motion & Ambient Combined Sensor**

#### MASL/MASH



MASL and MASH options reduce luminaire light output to roughly 30% (not full OFF) when no motion is detected. When motion is detected, light output increases to 100%.

#### Field Adjustable Output Module

The Field Adjustable Output (AO) module is an onboard device that adjusts the light output and input voltage to meet specific requirements, allowing a single fixture configuration to be flexibly applied in many different applications. The AO option is available on the HLWPC2 series.



I	P10 - AS and AH									
AO Position	% Lumens	% Wattage								
8	100%	100%								
7	94%	95%								
6	83%	82%								
5	71%	69%								
4	59%	57%								
3	46%	45%								
2	34%	33%								
1	21%	21%								

P30 - AS and AH								
AO Position	% Lumens	% Wattage						
8	100%	100%						
7	95%	94%						
6	84%	80%						
5	73%	67%						
4	61%	54%						
3	48%	42%						
2	35%	30%						
1	21%	18%						

P20 - AS and AH								
AO Position	% Lumens	% Wattage						
8	100%	100%						
7	95%	94%						
6	84%	80%						
5	73%	67%						
4	61%	54%						
3	48%	42%						
2	35%	30%						
1	21%	18%						

	P40 - AS and AH								
AO Position	% Lumens	% Wattage							
8	100%	100%							
7	95%	95%							
6	85%	82%							
5	74%	68%							
4	62%	55%							
3	49%	43%							
2	36%	30%							
1	21%	17%							

P50 - AS and AH								
AO Position	% Lumens	% Wattage						
8	100%	100%						
7	96%	95%						
6	86%	81%						
5	75%	68%						
4	64%	55%						
3	51%	42%						
2	37%	29%						
1	22%	17%						

