

DIAGRAM 1: DIMENSIONS OF AREA

NOTES:

1. ALL WORK IN THE PUBLIC RIGHT-OF-WAY SHALL BE APPROVED BY THE CITY ENGINEER'S OFFICE.

2. ALL CURBS SHALL BE 6" HIGH. THE AREA BETWEEN THE CURB AND SIDEWALK AND GROUND AT LEAST 18" FROM THE CURB TO THE CENTER OF THE DRIVEWAY SHALL BE PAVED WITH 4" CONCRET. THE DRIVEWAY SHALL BE PAVED WITH 4" CONCRET. THE DRIVEWAY SHALL BE PAVED WITH 4" CONCRET. THE DRIVEWAY SHALL BE PAVED WITH 4" CONCRET.

3. THE APPLICANT SHALL REMOVE ALL TREES AND CLIMBING VINES FROM THE AREA TO BE PAVED. THE APPLICANT SHALL BE RESPONSIBLE FOR THE COST OF REMOVAL AND REPLANTING. THE APPLICANT SHALL BE RESPONSIBLE FOR THE COST OF REMOVAL AND REPLANTING.

- 20.5' is a shared driveway
 - Patio enclosed by a plastic chain barrier
 - 7 - wheel stops of 72" will be placed outside of chained barrier*
 - 12 - 6' wood picnic tables will be spaced out within enclosed area*
- *See diagram 2



