

- SITE PLAN KEYNOTES**
- 1 EXISTING CONCRETE AND ASPHALT PAVEMENT TO BE REMOVED
  - 2 EXISTING VEGETATION TO INCLUDE TREES AND SHRUBS TO BE REMOVED
  - 3 EXISTING MISC. SITE AMENITIES TO BE REMOVED (BOLLARDS, LIGHT POLES, SIGNS, ETC.)
  - 4 SAW CUT EXISTING PAVEMENT FOR A CLEAN MATCH LINE
  - 5 EXISTING CONCRETE RETAINING WALL TO REMAIN
  - 6 REMOVE EXISTING SIDEWALK
  - 7 REMOVE EXISTING CURB RETURNS
  - 8 EXISTING CURB TO BE SAWCUT FOR NEW DRIVEWAY ENTRANCE
  - 9 EXISTING DRIVEWAY APRON TO BE REMOVED, SAW CUT EXISTING CURB AND INFILL WITH NEW CURB & GUTTER
  - 10 EXISTING CURB AND PAVEMENT TO BE REMOVED TO INSTALL NEW CURB INLET
  - 11 INSTALL TREE PROTECTION AS SHOWN IN DETAIL ON SHEET C504

- UTILITY QUALITY SERVICE LEVELS**
- QUALITY LEVELS OF UTILITIES ARE SHOWN IN THE PARENTHESES WITH THE UTILITY TYPE AND WHEN APPLICABLE, SIZE. THE QUALITY LEVELS ARE BASED ON THE CI / ASCE 38-02 STANDARD.
- QUALITY LEVEL (D) INFORMATION IS DERIVED FROM EXISTING UTILITY RECORDS OR ORAL RECOLLECTIONS.
- QUALITY LEVEL (C) INFORMATION IS OBTAINED BY SURVEYING AND PLOTTING VISIBLE ABOVE-GROUND UTILITY FEATURES AND USING PROFESSIONAL JUDGMENT IN CORRELATING THIS INFORMATION WITH QUALITY D INFORMATION.
- QUALITY LEVEL (B) INFORMATION IS OBTAINED THROUGH THE APPLICATION OF APPROPRIATE SURFACE GEOPHYSICAL METHODS TO DETERMINE THE EXISTENCE AND APPROXIMATE HORIZONTAL POSITION OF SUBSURFACE UTILITIES.
- QUALITY LEVEL (A) IS HORIZONTAL AND VERTICAL POSITION OF UNDERGROUND UTILITIES OBTAINED BY ACTUAL EXPOSURE OR VERIFICATION OF PREVIOUSLY EXPOSED SUBSURFACE UTILITIES, AS WELL AS THE TYPE, SIZE, CONDITION, MATERIAL, AND OTHER CHARACTERISTICS.

**UTILITY WARNING**

THE UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND/OR RECORDS OBTAINED. THE SURVEYOR MAKES NO GUARANTEE THAT THE UTILITIES OR SUBSURFACE FEATURES SHOWN COMPRISE ALL SUCH ITEMS IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UTILITIES OR SUBSURFACE FEATURES SHOWN ARE IN THE EXACT LOCATION INDICATED EXCEPT WHERE NOTED AS QUALITY LEVEL A.

  
 TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

**LEGEND**

FEATURES	EXISTING	PROPOSED
Spot Elevation	X 1225.25	X 1225.25
Contour Elevation	1225.25	1225.25
Fence (Barbed, Field, Hog)	—	—
Fence (Chain Link)	—	—
Fence (Wood)	—	—
Fence (Silt)	—	—
Tree Line	—	—
Tree Stump	—	—
Deciduous Tree \ Shrub	—	—
Coniferous Tree \ Shrub	—	—
Communication	—	—
Overhead Communication	—	—
Fiber Optic	—	—
Underground Electric	—	—
Overhead Electric	—	—
Gas Main with Size	—	—
High Pressure Gas Main with Size	—	—
Water Main with Size	—	—
Sanitary Sewer with Size	—	—
Duct Bank	—	—
Test Hole Location for SUE w/D	—	—
Sanitary Manhole	—	—
Storm Sewer with Size	—	—
Storm Manhole	—	—
Single Storm Sewer Intake	—	—
Double Storm Sewer Intake	—	—
Fire Hydrant	—	—
Fire Hydrant on Building	—	—
Water Main Valve	—	—
Water Service Valve	—	—
Well	—	—
Utility Pole	—	—
Guy Anchor	—	—
Utility Pole with Light	—	—
Utility Pole with Transformer	—	—
Street Light	—	—
Yard Light	—	—
Electric Box	—	—
Electric Transformer	—	—
Traffic Sign	—	—
Communication Pedestal	—	—
Communication Manhole	—	—
Communication Handhole	—	—
Fiber Optic Manhole	—	—
Fiber Optic Handhole	—	—
Gas Valve	—	—
Gas Manhole	—	—
Gas Apparatus	—	—
Fence Post or Guard Post	—	—
Underground Storage Tank	—	—
Above Ground Storage Tank	—	—
Sign	—	—
Satellite Dish	—	—
Mailbox	—	—
Sprinkler Head	—	—
Irrigation Control Valve	—	—
Soil Boring	—	—
Elevation	EL. 1225.25	EL. 1225.25

**eua**  
**epstein uhen : architects**  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 319 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 6010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608.838.0444

**PROJECT INFORMATION**

**HILDALE SHOPPING CENTER**

**HILDALE**

702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30


**EXISTING SITE & DEMOLITION PLAN**

**C 100**

© Epstein Uhen Architects, Inc.

V:\Projects\2020\120.0311.30\CADD\120.0311.30\120.0311.30\120.0311.30\_ARCH\_FULL\_BLEED\_ET (3000)X (4200) INCHES





- SITE PLAN KEYNOTES**
- 1 EXISTING STORM SEWER STRUCTURE TO BE REMOVED
  - 2 EXISTING STORM SEWER PIPE TO BE REMOVED
  - 3 EXISTING WATER PIPE TO BE REMOVED
  - 4 EXISTING WATER PIPE / LATERAL TO BE REMOVED
  - 5 EXISTING SANITARY STRUCTURE TO BE REMOVED
  - 6 EXISTING SANITARY PIPE / LATERAL TO BE REMOVED
  - 7 EXISTING GAS PIPE TO BE REMOVED AND CAPPED PER DIRECTION OF THE UTILITY PROVIDER
  - 8 EXISTING BURIED ELECTRIC TO BE REMOVED PER DIRECTION OF THE UTILITY PROVIDER

**UTILITY QUALITY SERVICE LEVELS**

QUALITY LEVELS OF UTILITIES ARE SHOWN IN THE PARENTHESES WITH THE UTILITY TYPE AND WHEN APPLICABLE, SIZE. THE QUALITY LEVELS ARE BASED ON THE CI / ASCE 38-02 STANDARD.

QUALITY LEVEL (D) INFORMATION IS DERIVED FROM EXISTING UTILITY RECORDS OR ORAL RECOLLECTIONS.

QUALITY LEVEL (C) INFORMATION IS OBTAINED BY SURVEYING AND PLOTTING VISIBLE ABOVE-GROUND UTILITY FEATURES AND USING PROFESSIONAL JUDGMENT IN CORRELATING THIS INFORMATION WITH QUALITY D INFORMATION.

QUALITY LEVEL (B) INFORMATION IS OBTAINED THROUGH THE APPLICATION OF APPROPRIATE SURFACE GEOPHYSICAL METHODS TO DETERMINE THE EXISTENCE AND APPROXIMATE HORIZONTAL POSITION OF SUBSURFACE UTILITIES.

QUALITY LEVEL (A) IS HORIZONTAL AND VERTICAL POSITION OF UNDERGROUND UTILITIES OBTAINED BY ACTUAL EXPOSURE OR VERIFICATION OF PREVIOUSLY EXPOSED SUBSURFACE UTILITIES, AS WELL AS THE TYPE, SIZE, CONDITION, MATERIAL, AND OTHER CHARACTERISTICS.

**UTILITY WARNING**

THE UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND/OR RECORDS OBTAINED. THE SURVEYOR MAKES NO GUARANTEE THAT THE UTILITIES OR SUBSURFACE FEATURES SHOWN COMPRISE ALL SUCH ITEMS IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UTILITIES OR SUBSURFACE FEATURES SHOWN ARE IN THE EXACT LOCATION INDICATED EXCEPT WHERE NOTED AS QUALITY LEVEL A.

CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED BOTH PUBLIC AND PRIVATE PRIOR TO THE START OF WORK BEING DONE ONSITE.

  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

**LEGEND**

FEATURES	EXISTING	PROPOSED
Spot Elevation	X 1225.25	X 1225.25
Contour Elevation	~ 1225.25	~ 1225.25
Fence (Barbed, Field, Hog)	—	—
Fence (Chain Link)	—	—
Fence (Wood)	—	—
Fence (Silt)	—	—
Tree Line	—	—
Tree Stump	—	—
Deciduous Tree \ Shrub	—	—
Coniferous Tree \ Shrub	—	—
Communication	—	—
Overhead Communication	—	—
Fiber Optic	—	—
Underground Electric	—	—
Overhead Electric	—	—
Gas Main with Size	—	—
High Pressure Gas Main with Size	—	—
Water Main with Size	—	—
Sanitary Sewer with Size	—	—
Duct Bank	—	—
Test Hole Location for SUE w/ID	—	—
(*) Denotes the survey quality service level for utilities		
Sanitary Manhole	—	—
Storm Sewer with Size	—	—
Storm Manhole	—	—
Single Storm Sewer Intake	—	—
Double Storm Sewer Intake	—	—
Fire Hydrant	—	—
Fire Hydrant on Building	—	—
Water Main Valve	—	—
Water Service Valve	—	—
Well	—	—
Utility Pole	—	—
Guy Anchor	—	—
Utility Pole with Light	—	—
Utility Pole with Transformer	—	—
Street Light	—	—
Yard Light	—	—
Electric Box	—	—
Electric Transformer	—	—
Traffic Sign	—	—
Communication Pedestal	—	—
Communication Manhole	—	—
Fiber Optic Manhole	—	—
Fiber Optic Handhole	—	—
Gas Valve	—	—
Gas Manhole	—	—
Gas Apparatus	—	—
Fence Post or Guard Post	—	—
Underground Storage Tank	—	—
Above Ground Storage Tank	—	—
Sign	—	—
Satellite Dish	—	—
Mailbox	—	—
Sprinkler Head	—	—
Irrigation Control Valve	—	—
Soil Boring	—	—
Elevation	EL. 1225.25	EL. 1225.25

**eua**  
**epstein uhen : architects**  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 319 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 6010 VOGES ROAD  
 MADISON, WISCONSIN 53718  
 608.838.0444

**PROJECT INFORMATION**  
**HILDALE SHOPPING CENTER**  


702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**


PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**EXISTING UTILITY DEMOLITION PLAN**

**C 101**  
 © Epstein Uhen Architects, Inc.

V:\Projects\2020\120.0311.30\CADD\120.0311.30\_P110.dwg ANDREW BERGMANN, UTILITY DEMOLITION PLAN, 20230310, 4:24 PM, ARCH.PLOT BLEED E1 (30.00 X 42.00 INCHES)





**eua**  
**epstein uhen : architects**  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 339 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 6010 VOGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

**PROJECT INFORMATION**

**HILLDALE SHOPPING CENTER**



702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**EXISTING EASEMENTS**

**C 102**

© Epstein Uhen Architects, Inc.

**LEGEND**


FEATURES	EXISTING	PROPOSED
Spot Elevation	X 1225.25	X 1225.25
Contour Elevation	~ 1225.25	~ 1225.25
Fence (Barbed, Field, Hog)	—	—
Fence (Chain Link)	—	—
Fence (Wood)	—	—
Fence (Silt)	—	—
Tree Line	—	—
Tree Stump	—	—
Deciduous Tree \ Shrub	—	—
Coniferous Tree \ Shrub	—	—
Communication	—	—
Overhead Communication	—	—
Fiber Optic	—	—
Underground Electric	—	—
Overhead Electric	—	—
Gas Main with Size	—	—
High Pressure Gas Main with Size	—	—
Water Main with Size	—	—
Sanitary Sewer with Size	—	—
Duct Bank	—	—
Test Hole Location for SUE w/ID	—	—
(*) Denotes the survey quality service level for utilities		
Sanitary Manhole	—	—
Storm Sewer with Size	—	—
Storm Manhole	—	—
Single Storm Sewer Intake	—	—
Double Storm Sewer Intake	—	—
Fire Hydrant	—	—
Fire Hydrant on Building	—	—
Water Main Valve	—	—
Water Service Valve	—	—
Well	—	—
Utility Pole	—	—
Guy Anchor	—	—
Utility Pole with Light	—	—
Utility Pole with Transformer	—	—
Street Light	—	—
Yard Light	—	—
Electric Box	—	—
Electric Transformer	—	—
Traffic Sign	—	—
Communication Pedestal	—	—
Communication Manhole	—	—
Communication Handhole	—	—
Fiber Optic Manhole	—	—
Fiber Optic Handhole	—	—
Gas Valve	—	—
Gas Manhole	—	—
Gas Apparatus	—	—
Fence Post or Guard Post	—	—
Underground Storage Tank	—	—
Above Ground Storage Tank	—	—
Sign	—	—
Satellite Dish	—	—
Mailbox	—	—
Sprinkler Head	—	—
Irrigation Control Valve	—	—
Soil Boring	—	—
Elevation	EL. 1225.25	EL. 1225.25

**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**

WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120.0311.30\CADD\120.0311.30\_P110.dwg ANDREW BERGMANN, EXISTING EASEMENTS, 2023/03/10, 4:24 PM, ARCH PLOT BLEED E1 (30.00 X 42.00 INCHES)





**SITE INFORMATION**

TOTAL SITE AREA: 221,647 SF / 5.09 ACRES  
 EXISTING IMPERVIOUS AREA: 184,807 SF  
 NEW IMPERVIOUS AREA: 27,403 SF (12.36% LOT COVERAGE)  
 REDEVELOPED IMPERVIOUS AREA: 173,193 SF  
 REMOVED IMPERVIOUS AREA: 19,614 SF  
 NET IMPERVIOUS AREA: 192,596 SF

**PARKING STALL COUNT**

TOTAL EXISTING SITE PARKING: 296 STALLS  
 TOTAL PROPOSED SITE PARKING: 234 STALLS  
 TOTAL HANDICAP PARKING: 8 STALLS (3 VAN)  
 TOTAL ELECTRIC VEHICLE PARKING: 3 STALLS

PROPOSED REDUCTION OF 62 PARKING STALLS

**BIKE PARKING COUNT**

PARKING CALC'S FOR BUILDING 100, BUILDING 200, BUILDING 300, AND BUILDING 500

BUILDING 500 - RESIDENTIAL  
 125 STALLS TOTAL (UNIT PLUS GUESTS)  
 103 STALLS LONG TERM 90% (IN BUILDING)  
 22 EXTERIOR BIKE STALLS BY BUILDING 500

BUILDINGS 100, 200 & 300 - RETAIL / RESTAURANT  
 RETAIL = (99,785 SF) / 2,000 SF PER BIKE STALL = 50 STALLS  
 RESTAURANT = (13,075 SF) / (15 SF PER PERSON) \* 0.5 = 44 STALLS  
 94 BIKE

**FIRE LANE:**

SEVERAL ROADS WILL ACT AS THE FIRE LANE ON THIS PROJECT, SEE SHEET C 204 FOR MORE INFORMATION.

**NOTE:**

CONTRACTOR SHALL FIELD VERIFY ALL EXISTING UTILITIES ON AND ADJACENT TO THE SITE PRIOR TO THE START OF THE PROJECT.

RADII ARE FROM FACE OF CURB

DIMENSIONS ARE FROM FACE OF CURB



**eppstein uhen : architects**

milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350



33 BOYLSTON ST. STE 300  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900



**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

**PROJECT INFORMATION**

**HILLCDALE SHOPPING CENTER**



702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**



**SHEET INFORMATION**

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**OVERALL SITE PLAN**

**C 200**


© Eppstein Uhen Architects, Inc.



TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120\_0311\_30\CADD\120\_0311\_30\PSD\06.mxd MAKE WHOLE OVERALL SITE PLAN\_20230310\_4:44 PM\_ARCH FULL BLEED E1 (30.00 X 42.00 INCHES)





**SITE PLAN KEYNOTES**

1. PROPOSED ASPHALT PAVEMENT
2. PROPOSED PERMEABLE PAVERS
3. A.D.A. ACCESSIBLE PARKING SPACE WITH LOADING ZONE. PROVIDE APPROPRIATE STRIPING AND PAVEMENT MARKINGS.
4. PROPOSED RETAINING WALL - CAST IN PLACE BY OTHERS
5. PROPOSED TRANSFORMER LOCATION. EXACT DIMENSIONS TBD.
6. PROPOSED REFUSE AND RECYCLING COMPACTORS
7. EXISTING MG&E EASEMENT AND DUCT BANK
8. REJECT CURB
9. PROPOSED SIDEWALK, 5' THICK
10. PROPOSED BOLLARDS
11. PROPOSED CROSSWALK
12. PROPOSED ELECTRIC EASEMENT
13. 30" MOUNTABLE CURB AND GUTTER, SEE DETAIL 2 ON C 504
14. PROPOSED 7" THICK CONCRETE LOADING AREA. SEE DETAIL ON C 504
15. BIORETENTION AREA, SEE DETAIL ON C 503
16. DRIVEWAY APRON, SEE DETAIL ON C 504
17. POUR NEW CURB AND GUTTER TO INFILL PREVIOUS DRIVEWAY APRON
18. PARKING OVERHANG OF 24"
19. 12" CONCRETE RIBBON CURB, SEE DETAIL ON SHEET C 504
20. CONCRETE STEPS AND RAILINGS BY OTHERS

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

**PROJECT INFORMATION**  
**HILLDALE SHOPPING CENTER**  
  
 702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**


PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**SITE PLAN**  
**C 201**

**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\06.dwg MAKE WHOLE SITE PLAN, 2023/03/10, 4:48 PM, ARCH FULL BLEED ET (30.00 X 42.00 INCHES)





**SITE PLAN KEYNOTES**

1. PROPOSED ASPHALT PAVEMENT
2. PROPOSED PERMEABLE PAVERS
3. A.D.A. ACCESSIBLE PARKING SPACE WITH LOADING ZONE. PROVIDE APPROPRIATE STRIPING AND PAVEMENT MARKINGS.
4. PROPOSED RETAINING WALL - CAST IN PLACE BY OTHERS
5. PROPOSED TRANSFORMER LOCATION. EXACT DIMENSIONS TBD.
6. PROPOSED REFUSE AND RECYCLING COMPACTORS
7. EXISTING MG&E EASEMENT AND DUCT BANK
8. REJECT CURB
9. PROPOSED SIDEWALK, 5" THICK
10. PROPOSED BOLLARDS
11. PROPOSED CROSSWALK
12. PROPOSED ELECTRIC EASEMENT
13. 12" CONCRETE RIBBON CURB, SEE DETAIL ON SHEET C 504
14. CONCRETE STEPS AND RAILINGS BY OTHERS
15. CONCRETE PAVEMENT



**eppstein uhen : architects**

milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350  
madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350



33 BOYLSTON ST. STE 3000  
CHESTNUT HILL, MA 02467  
P 617.232.8900



5010 VOEGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

**PROJECT INFORMATION**

**HILLCREST SHOPPING CENTER**



702 N Midvale Blvd  
Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**



**SHEET INFORMATION**

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

**SITE PLAN**

**C 202**


© Eppstein Uhen Architects, Inc.



TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE 1-800-242-8511 TOLL FREE**  
WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\06.mxd W:\HILL SITE PLAN\_20230310\_10.48 PM\_ARCH FULL BLEED ET (30.00 X 42.00 INCHES)





**SITE PLAN KEYNOTES**

1. PROPOSED ASPHALT PAVEMENT
2. PROPOSED PERMEABLE PAVERS
3. A.D.A. ACCESSIBLE PARKING SPACE WITH LOADING ZONE. PROVIDE APPROPRIATE STRIPING AND PAVEMENT MARKINGS.
4. PROPOSED RETAINING WALL, TYPE TBD
5. PROPOSED TRANSFORMER LOCATION. EXACT DIMENSIONS TBD.
6. PROPOSED REFUSE AND RECYCLING COMPACTORS
7. EXISTING MG&E EASEMENT AND DUCT BANK
8. REJECT CURB
9. PROPOSED SIDEWALK, 5" THICK
10. PROPOSED BOLLARDS
11. PROPOSED CROSSWALK
12. PROPOSED ELECTRIC EASEMENT
13. PROPOSED DRIVEWAY
14. A PORTION OF THE EXISTING RETAINING WALL TO REMAIN
15. CONCRETE PAVEMENT



**eppstein uhen : architects**

milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350  
madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350



33 BOYLSTON ST. STE 3000  
CHESTNUT HILL, MA 02467  
P 617.232.8900



**SNYDER ASSOCIATES**  
5010 VOGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

**PROJECT INFORMATION**

**HILLDALE SHOPPING CENTER**



702 N Midvale Blvd  
Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**



**SHEET INFORMATION**

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

**SITE PLAN**

**C 203**


© Eppstein Uhen Architects, Inc.




 TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\04.mxd MAKE WHAL SITE PLAN\_20230310\_4:50 PM\_ARCH FULL BLEED CT (30.00 X 42.00 INCHES)





- EXISTING HYDRANT LOCATION
- PROPOSED HYDRANT LOCATION
- 26' WIDE FIRE LANE AERIAL APPARATUS
- 20' WIDE FIRE LANE
- HOSE LAY

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**S**  
**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILLDALE SHOPPING CENTER**

702 N Midvale Blvd  
 Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

FIRE ACCESS PLAN

**C 204**

© Eppstein Uhen Architects, Inc.


TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN

**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**

WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120.0311.30\CADD\120.0311.30\FIRE ACCESS PLAN\_20230310\_458 PM\_ARCH FULL BLEED.rvt (80.00 X 42.00 INCHES)





**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**S**  
**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILLDALE SHOPPING CENTER**  


702 N Midvale Blvd  
 Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

GRADING PLAN  
**C 300**  
 © Eppstein Uhen Architects, Inc.

**SITE INFORMATION**  
 TOTAL SITE AREA: 221,647 SF / 5.09 ACRES  
 EXISTING IMPERVIOUS AREA: 184,807 SF  
 NEW IMPERVIOUS AREA: 27,403 SF (12.36% LOT COVERAGE)  
 REDEVELOPED IMPERVIOUS AREA: 173,193 SF  
 REMOVED IMPERVIOUS AREA: 19,614 SF  
 NET IMPERVIOUS AREA: 192,596 SF


 TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\06.dwg ALEXANDER KEEFE OVERALL GRADING PLAN, 2023/03/13, 4:15 PM, ARCH/FULL BLEED E1 (30.00 X 42.00 INCHES)



1 2 3 4 5 6 7

E  
D  
C  
B  
A



**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 TIC = TOP OF CURB  
 TW = TOP OF WALL  
 BW = BOTTOM OF WALL  
 BC = BACK OF CURB  
 (XXX.XX) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOO AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4" OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24" O.C.

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILDALE SHOPPING CENTER**  
 702 N Midvale Blvd  
 Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**CALL DIGGERS HOTLINE**  
 1-800-242-8511  
 TOLL FREE

TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN

WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE


GRADING PLAN  
**C 301**  
 © Eppstein Uhen Architects, Inc.

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\04.dwg ALEXANDER KEEFE GRADING PLAN 2023/03/10, 4:18 PM ARCH FULL BLEED E1 (90.00 X 42.00 INCHES)



1 2 3 4 5 6 7

E  
D  
C  
B  
A



**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 T/C = TOP OF CURB  
 TW = TOP OF WALL  
 BW = BOTTOM OF WALL  
 BC = BACK OF CURB  
 (XXX.XX) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOO AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4" OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24" O.C.

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 300  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILDALE SHOPPING CENTER**  
 702 N Midvale Blvd  
 Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**CALL DIGGERS HOTLINE**  
 1-800-242-8511  
 TOLL FREE


TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN

WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

GRADING PLAN  
**C 302**  
 © Eppstein Uhen Architects, Inc.

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\04.dwg ALEXANDER KEEFE GRADING PLAN 2023/03/10 4:29 PM ARCH FULL BLEED E1 (90.00 X 42.00 INCHES)





**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 T/C = TOP OF CURB  
 TW = TOP OF WALL  
 BW = BOTTOM OF WALL  
 BC = BACK OF CURB  
 (XXX.XX) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOO AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4" OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24" O.C.

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 300  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILLDALE SHOPPING CENTER**

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

702 N Midvale Blvd  
 Madison, WI 53705

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**CALL DIGGERS HOTLINE**  
 1-800-242-8511  
 TOLL FREE

WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

GRADING PLAN  
**C 303**  
 © Eppstein Uhen Architects, Inc.



1 2 3 4 5 6 7

E  
D  
C  
B  
A



**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 T.C. = TOP OF CURB  
 T.W. = TOP OF WALL  
 B.W. = BOTTOM OF WALL  
 B.C. = BACK OF CURB  
 (XXX.XX) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOO AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4" OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24" O.C.

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

**PROJECT INFORMATION**  
**HILDALE SHOPPING CENTER**

702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**


PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

**GRADING PLAN**  
**C 304**  
 © Eppstein Uhen Architects, Inc.

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\06.dwg ALEXANDER KEEFE, GRADING PLAN, 2023/03/10, 4:25 PM, ARCH FULL BLEED E1 (90.00 X 42.00 INCHES)





**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 T/C = TOP OF CURB  
 TW = TOP OF WALL  
 BW = BOTTOM OF WALL  
 BC = BACK OF CURB  
 (XXX.XX) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOO AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4" OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24" O.C.

**eua**  
**eppstein uhen : architects**  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

**HILLDALE**

**PROJECT INFORMATION**  
**HILLDALE SHOPPING CENTER**  
 702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30



**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

**GRADING PLAN**  
**C 305**  
 © Eppstein Uhen Architects, Inc.


V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\mg ALEXANDER KEEFE GRADING PLAN 20230310.427 PM ARCH FULL BLEED E1 (90.00 X 42.00 INCHES)



V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\04.dwg ALEXANDER KEEFE GRADING PLAN, 2023/03/10, 4:34 PM, ARCH FULL BLEED E1 (90.00 X 42.00 INCHES)



**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 T/C = TOP OF CURB  
 TW = TOP OF WALL  
 BW = BOTTOM OF WALL  
 BC = BACK OF CURB  
 (XXX.XX) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOO AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4" OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24" O.C.



**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
 WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street Milwaukee, Wisconsin 53202 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202 Madison, Wisconsin 53703 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 300 CHESTNUT HILL, MA 02467 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD MADISON, WISCONSIN 53718 608-838-0444

**PROJECT INFORMATION**  
**HILDALE SHOPPING CENTER**  
 702 N Midvale Blvd  
 Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL


**KEY PLAN**

**SHEET INFORMATION**

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**GRADING PLAN**  
**C 306**  
 © Eppstein Uhen Architects, Inc.





**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 T/C = TOP OF CURB  
 TW = TOP OF WALL  
 BW = BOTTOM OF WALL  
 BC = BACK OF CURB  
 (XXX.XX) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOO AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4 OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24' O.C.

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILDDALE SHOPPING CENTER**  
 702 N Midvale Blvd  
 Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE

GRADING PLAN  
**C 307**  
 © Eppstein Uhen Architects, Inc.

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\06.dwg ALEXANDER KEETE GRADING PLAN 2023/03/10 4:37 PM ARCH FULL BLEED E1 (90.00 X 42.00 INCHES)



1 2 3 4 5 6 7

E  
D  
C  
B  
A

BUILDING  
400  
FFE 902.00

BUILDING  
100  
FFE 901.00

BUILDING  
400  
FFE 902.00

FFE 901.00

BUILDING  
100  
FFE 900.00



**NOTES:**  
 H.P. = HIGH POINT FOR DRAINAGE  
 L.P. = LOW POINT FOR DRAINAGE  
 T.C. = TOP OF CURB  
 T.W. = TOP OF WALL  
 B.W. = BOTTOM OF WALL  
 B.C. = BACK OF CURB  
 (XXX.X) = EXISTING SPOT ELEVATION  
 ALL SPOT ELEVATIONS ARE AT THE EDGE OF PAVEMENT (FLAG OF CURB)  
 HATCHED CURB AND GUTTER DEPICTS REJECT CURB LOCATIONS  
 ALL LANDSCAPE AND SOD AREAS SHALL HAVE POSITIVE DRAINAGE  
 CONTRACTOR SHALL PROVIDE CONTROL JOINTS, CONSTRUCTION JOINTS AND EXPANSION JOINTS IN SLAB ON GRADE, SIDEWALKS AND DRIVEWAYS.  
 CONTROL JOINT MAXIMUM DISTANCE: SIDEWALKS - 8' O.C., ALL OTHERS 10' O.C.  
 SAW CUT CONTROL JOINTS SHALL BE A MINIMUM OF 1/4" OF THE CONCRETE THICKNESS.  
 EXPANSION JOINT MINIMUM DISTANCE: SIDEWALKS - 24' O.C., ALL OTHERS 40' O.C.  
 DOWEL ALL EXPANSION JOINTS - 24' O.C.

LANDSCAPE BACKGROUND FOR REFERENCE ONLY. SEE LANDSCAPE PLANS FOR DETAILS.

THIS IS A FLUSH CONDITION. SEE LANDSCAPING PLANS FOR PAVEMENT TYPES

THIS IS A FLUSH CONDITION. SEE LANDSCAPING PLANS FOR PAVEMENT TYPES

KELAB DRIVE



**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**

TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN

WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

**eua**

**eppstein uhen : architects**

milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350

madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**

33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**

5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

**PROJECT INFORMATION**

**HILDALE SHOPPING CENTER**

702 N Midvale Blvd  
 Madison, WI 53705

**HILDALE**

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

**GRADING PLAN**  
**C 308**

V:\Projects\2020\120.0311.30\CADD\120.0311.30\PSD\06.dwg ALEXANDER KEEFE, GRADING PLAN, 2023/03/10, 4:38 PM, ARCH FULL BLEED E1 (90.00 X 42.00 INCHES)

1 2 3 4 5 6 7

© Eppstein Uhen Architects, Inc.





eppstein uhen : architects

milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350  
madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350




33 BOYLSTON ST. STE 3000  
CHESTNUT HILL, MA 02467  
P 617.232.8900



SNYDER ASSOCIATES  
5010 VOEGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

PROJECT INFORMATION

HILDALE SHOPPING CENTER



702 N Midvale Blvd  
Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN


SHEET INFORMATION

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

EROSION CONTROL PLAN

C 309

© Eppstein Uhen Architects, Inc.



**NOTES:**

- \*ALL SILT FENCE MUST BE INSTALLED BY THE CONTRACTOR AND INSPECTED BY THE CITY PRIOR TO ANY SITE WORK.
- \*SITE EROSION CONTROL MEASURES MUST BE IN PLACE AT ALL TIMES. SHOULD DEVICES BE REMOVED FOR WORK ACCESS, THEY SHALL BE REINSTALLED AT THE END OF EACH WORK DAY UNTIL PAVEMENTS HAVE BEEN INSTALLED AND ALL LANDSCAPE AREAS HAVE BEEN MULCHED AND SOOLED. SEEDING AREAS MUST EXHIBIT MINIMUM OF 70% SOIL COVERAGE.
- \*REFER TO THE EROSION CONTROL PLAN NOTES AND DETAIL SHEETS FOR MORE INFORMATION.

**CONSTRUCTION SEQUENCE**



- \*INSTALL EROSION/SEDIMENT CONTROL MEASURES
- \*INSTALL STORMWATER MANAGEMENT SEDIMENT BASINS
- \*INSTALL STORM SEWER
- \*INSTALL STRUCTURES
- \*INSTALL PAVEMENTS
- \*INSTALL LAWN/LANDSCAPE
- \*FLUSH STORM SEWER
- \*REMOVE EROSION CONTROL MEASURES ONLY AFTER ALL PAVEMENTS HAVE BEEN INSTALLED AND ALL SOILS HAVE BEEN STABILIZED

**NOTE FOR GRADING CONTRACTOR:**

ANY PROPERTY IRONS THAT ARE DISTURBED IN THE GRADING PROCESS SHALL BE RESET BY A LICENSED LAND SURVEYOR AT NO ADDITIONAL COST TO THE OWNER.

**NOTES:**

- ENGINEER TO OBTAIN RIGHT-OF-WAY EXCAVATION PERMIT PRIOR TO BEGINNING SITE WORK.
- CONSTRUCTION FENCING TO BE INSTALLED AROUND ENTIRE CONSTRUCTION SITE. COORDINATE WITH OWNER FOR FENCING AND GATE LOCATION AND APPROPRIATE SIGNAGE LOCATION.
- PLAN PREPARED FROM TOPOGRAPHIC SURVEY BY:  
SNYDER & ASSOCIATES  
5010 VOEGES ROAD  
MADISON, WI 53718  
608-838-0444 EXT. 234
- CONTRACTOR SHALL LOCATE ALL UTILITIES WHICH MAY AFFECT THIS WORK NOTIFY THE OWNER OF ANY POTENTIAL CONFLICTS.
- CONTRACTOR SHALL VERIFY ALL EXISTING AND PROPOSED ELEVATIONS PRIOR TO START OF CONSTRUCTION. VERIFY CRITICAL ELEVATIONS TO ENSURE CONFORMANCE WITH GRADING PLAN, PARTICULARLY WITH WALK AND/OR PAVEMENTS TO REMAIN. MEET EXISTING GRADES ALONG STREETS, PROPERTY LINES, AND DRIVEWAY ENTRANCES. RESTORE ALL EXISTING PAVEMENTS THAT REMAIN TO THEIR ORIGINAL, IF NOT BETTER CONDITION. NOTIFY OWNER OF ANY CONFLICTS.
- AREAS NOT PAVED AND TO BE LANDSCAPED SHALL RECEIVE MINIMUM OF 4" DEPTH COMPACTED TOPSOIL.
- CONTRACTOR SHALL COORDINATE GRADING AND INSTALLATION OF DRIVES IN R.O.W. WITH APPROPRIATE GOVERNMENT AGENCIES. OBTAIN APPROPRIATE PERMITS FOR GRADING AND DRAINAGE IN ALL R.O.W.
- REFER TO OWNERS SPECIFICATIONS FOR CURB, APPROACH, AND CONCRETE PROFILES AS WELL AS ADDITIONAL SITE STANDARDS RELATED TO THIS PROJECT.
- EXCAVATOR IS RESPONSIBLE FOR ALL EROSION CONTROL INSPECTIONS



TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN

**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**

WIS. STATUTE 182.0175 (1974)  
REQUIRES MIN. OF 3 WORK DAYS  
NOTICE BEFORE YOU EXCAVATE

V:\Projects\2020\120.0311.30\CAD\120.0311.30\PSD\04.dwg ALEXANDER KEEFE, EROSION CONTROL PLAN, 2023/03/10, 4:42 PM, ARCH FULL BLEED ET (30.00 X 42.00 INCHES)



1

2

3

4

5

6

7


E

D

C

B


A



**LEGEND**

- SANITARY SEWER PIPES & STRUCTURES
- STORM SEWER PIPES & STRUCTURES
- WATER PIPES & STRUCTURES

 TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
WIS. STATUTE 182.0175 (1974)  
 REQUIRES MIN. OF 3 WORK DAYS  
 NOTICE BEFORE YOU EXCAVATE



**eppstein uhen : architects**

milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350



33 BOYLSTON ST. STE. 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900



**SNYDER ASSOCIATES**  
5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

**PROJECT INFORMATION**

**HILLDALE SHOPPING CENTER**



**702 N Midvale Blvd  
 Madison, WI 53705**

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**


PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

**OVERALL UTILITY PLAN**

**C 400**


V:\Projects\2020\120.0311.30\CADD\120.0311.30\P400.dwg ALEXANDER KEEFE OVERALL UTILITY PLAN, 2023/03/10, 4:59 PM, A701 FULL BLEED E1 (80.000 X 42.000 INCHES)






SANITARY SEWER PLAN VIEW

SCALE: 1" = 20'




SANITARY SEWER PROFILE VIEW




SANITARY SEWER PLAN VIEW

SCALE: 1" = 20'




SANITARY SEWER PROFILE VIEW



SANITARY SEWER PLAN VIEW

SCALE: 1" = 20'



SANITARY SEWER PROFILE VIEW



epstein uhen : architects

milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350  
madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350



33 BOYLSTON ST. STE 300  
CHESTNUT HILL, MA 02467  
P 617.232.8900



5010 VOEGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

PROJECT INFORMATION

HILDALE SHOPPING CENTER



702 N Midvale Blvd  
Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

SANITARY SEWER PLAN & PROFILE

C 401

V:\Projects\2020\120.0311.30\CAD\120.0311.30\DWG\ANDREW.BERGAMANN\_SANITARY\_SEWER\_PLAN\_AND\_PROFILE\_20230310\_4:14 PM\_ARCH\_FULL\_BLEED.rvt (30.00 X 42.00 INCHES)





eppstein uhen : architects

Milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
Telephone 414.271.5350  
Madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
Telephone 608.442.5350



33 BOYLSTON ST. STE 300  
CHESTNUT HILL, MA 02467  
P 617.232.8900



5010 VOGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

PROJECT INFORMATION

HILDALE SHOPPING CENTER



702 N Midvale Blvd  
Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

**CALL DIGGERS HOTLINE**  
1-800-242-8511  
TOLL FREE

TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN



WIS. STATUTE 182.0175 (1974)  
REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

UTILITY PLAN


C 402

© Eppstein Uhen Architects, Inc.



V:\Projects\2020\120.0311.30\CADD\120.0311.30\_P40.dwg ANDREW BERGMANN UTILITY PLAN 20230310 4:15 PM ARCH FULL BLEED E1 (0.00 X 42.00 INCHES)





**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 3000  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILDALE SHOPPING CENTER**

702 N Midvale Blvd  
 Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL


KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30


UTILITY PLAN  
**C 403**  
 © Eppstein Uhen Architects, Inc.

TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE



V:\Projects\2020\120.0311.30\CADD\120.0311.30\PLANS\UTILITY PLAN\_20230310\_10.4.19 PM\_ARCH FULL BLEED E1 (80.00 X 42.00 INCHES)





**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street  
 Milwaukee, Wisconsin 53202  
 telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202  
 Madison, Wisconsin 53703  
 telephone 608.442.5350

**WS DEVELOPMENT**  
 33 BOYLSTON ST. STE 300  
 CHESTNUT HILL, MA 02467  
 P 617.232.8900

**S**  
**SNYDER ASSOCIATES**  
 5010 VOEGES ROAD  
 MADISON, WISCONSIN 53718  
 608-838-0444

PROJECT INFORMATION  
**HILDALE SHOPPING CENTER**  
  
 702 N Midvale Blvd  
 Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL


KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30

UTILITY PLAN  
**C 404**  
 © Eppstein Uhen Architects, Inc.

TO OBTAIN LOCATION OF PARTICIPANTS' UNDERGROUND FACILITIES BEFORE YOU DIG IN WISCONSIN  
**CALL DIGGERS HOTLINE**  
**1-800-242-8511**  
**TOLL FREE**  
 WIS. STATUTE 182.0175 (1974) REQUIRES MIN. OF 3 WORK DAYS NOTICE BEFORE YOU EXCAVATE



V:\Projects\2020\120.0311.30\CADD\120.0311.30\PLANS\UTILITY PLAN\_20230310\_10.415 PM\_ARCH FULL BLEED E1 (80.00 X 42.00 INCHES)




STRUCTURE TABLE					
STRUCTURE NAME	RIM EL	STRUCTURE TYPE	INVERTS IN	INVERTS OUT	FRAME/GRATE
EX SA 1	896.06	ECCENTRIC MH	W = 888.95		R 1550-0054
EX SA 2	896.67	ECCENTRIC MH	N = 888.17		R 1550-0054
SA-1	901.89	ECCENTRIC MH		E = 890.27	R 1550-0054
SA-2	897.95	ECCENTRIC MH	NW = 889.03	S = 888.93	R 1550-0054
SA-3	901.25	ECCENTRIC MH	W = 891.21	E = 891.11	R 1550-0054
SA-4	898.90	ECCENTRIC MH	W = 889.40	SE = 889.30	R 1550-0054
SA-5	902.27	ECCENTRIC MH	N = 891.84	E = 891.84	R 1550-0054
SA-6	898.68	ECCENTRIC MH			R 1550-0054

SANITARY PIPE TABLE								
PIPE NAME	PIPE TYPE	SIZE (IN.)	FROM	TO	LENGTH (FT)	START INV	END INV	SLOPE
SAP-1	PVC	8	SA-1	EX SA 1	220	890.27	888.95	0.60%
SAP-2	PVC	8	SA-2	EX SA 2	190	888.93	888.17	0.40%
SAP-3	PVC	8	SA-3	SA-4	171	891.11	889.40	1.00%
SAP-4	PVC	8	SA-4	SA-2	68	889.30	889.03	0.40%
SAP-5	PVC	8	SA-5	SA-3	63	891.84	891.21	1.00%
SAP-6	PVC	6			31	890.87	890.24	2.00%
SAP-7	PVC	6			107	892.21	890.07	2.00%
SAP-8	PVC	4			7	892.09	891.85	3.40%
SAP-9	PVC	4			5	892.19	892.09	2.00%
SAP-10	PVC	4			19	892.56	892.19	2.00%
SAP-11	PVC	6			92	891.58	889.75	2.00%
SAP-12	PVC	6			22	892.12	891.58	2.45%
SAP-13	PVC	6			16	892.27	892.03	1.50%
SAP-14	PVC	4			5	892.22	892.12	2.00%
SAP-15	PVC	4			16	892.55	892.22	2.00%
SAP-16	PVC	6			29	889.38	888.81	2.00%
SAP-17	PVC	4			17	892.89	889.53	20.15%
SAP-18	PVC	4			5	892.99	892.89	2.08%
SAP-19	PVC	4			3	893.06	892.99	2.20%
SAP-20	PVC	4			22	893.50	893.06	1.99%
SAP-21	PVC	6			38	892.61	891.84	2.00%
SAP-22	PVC	4			11	892.76	892.44	2.93%
SAP-23	PVC	4			4	892.84	892.76	2.00%
SAP-24	PVC	4			9	893.02	892.84	2.00%

STRUCTURE TABLE					
STRUCTURE NAME	RIM EL	STRUCTURE TYPE	INVERTS IN	INVERTS OUT	FRAME/GRATE
EX STMH 1	898.58	CONC MH	NW = 889.50 S = 890.53		R 1550-0054
EX STMH 2	901.22	CONC MH	SW = 892.71	E = 891.21	R 1550-0054
EX STMH 3	899.33	CONC MH	W = 889.90 SW = 893.39	SE = 889.88	R 1550-0054
OUTLET 1	896.25	OUTLET STRUCTURE		E = 892.25	48" HAALA GRATE
ROOF DRAIN 1	894.31	ROOF DRAIN		N = 893.15	
ROOF DRAIN 2	893.24	ROOF DRAIN		E = 892.01	
ROOF DRAIN 3	895.91	ROOF DRAIN		S = 894.48	
STMH-39	901.19	CONC MH	NW = 896.67	E = 896.67	R-2040
STMH 1	896.22	CONC MH	S = 891.93 W = 891.93	N = 891.93	R 1550-0054
STMH 2	895.91	CONC MH	W = 892.27	N = 892.27	R 1550-0054
STMH 3	898.51	CONC MH	N = 892.53	E = 892.53	R 1550-0054
STMH 4	900.12	2' X 3' CI	W = 892.58	S = 892.58	R-3067 TYPE R
STMH 5	900.59	CONC MH	W = 893.14	E = 893.14	R-2040
STMH 7	901.13	CONC MH	W = 896.29	E = 896.29	R-2040
STMH 9	901.13	CONC MH W/INLET	N = 897.06	SE = 897.06	R-3067 TYPE R
STMH 10	901.29	CONC MH	NW = 897.42	S = 897.42	R-2040
STMH 11	902.31	2' X 3' CI	N = 897.67	SE = 897.67	R-3067 TYPE R
STMH 11A	902.33	2' X 3' CI	N = 897.72	S = 897.72	R-3067 TYPE R
STMH 12	904.84	2' X 3' CI		S = 900.02	R-3067 TYPE R
STMH 16	901.25	48" CONC MH W/INLET	S = 896.24 W = 894.11	NE = 894.11	R-3067 TYPE R
STMH 17	905.02	CONC MH W/INLET	S = 899.94 W = 897.91	E = 897.91	R-3067 TYPE R
STMH 18	909.36	2' X 3' CI	S = 901.73	E = 901.73	R-3067 TYPE R
STMH 19	909.63	2' X 3' CI	E = 903.58	N = 903.58	R-3067 TYPE R
STMH 20	908.87	2' X 3' CI		W = 903.64	R-3067 TYPE R
STMH 21	904.92	2' X 3' CI		N = 900.46	R-3067 TYPE R
STMH 22	901.79	2' X 3' CI		N = 897.00	R-3067 TYPE R
STMH 27	898.20	CONC MH W/INLET		NE = 892.89	R-3067 TYPE R
STMH 28	894.95	CONC MH	N = 891.47	S = 891.47	R 1550-0054
STMH 32	899.31	2' X 3' CI	SW = 893.45	NE = 893.45	R-3067 TYPE R
STMH 33	897.47	72" CONC MH	SW = 892.80 N = 892.80 NE = 892.80	SE = 892.80	R 1550-0054
STMH 34	896.87	CONC MH	S = 891.30 W = 891.80	N = 891.30	R 1550-0054
STMH 35	901.36	CONC MH	N = 894.42	W = 894.42	R 1550-0054
STMH 36	895.80	CONC MH	NW = 892.49	S = 892.49	R 1550-0054
STMH 37	901.55	CONC MH	SW = 893.83	E = 893.58	R-2040
STMH 38	900.84	CONC MH		NE = 894.64	R 1550-0054
TD 1	896.55	ACO DRAIN MINNIKCLASSIK K50		SW = 892.86	GRATE A
TD 2	901.01	ACO DRAIN MINNIKCLASSIK K50		N = 891.80	GRATE A
UG INLET 1	900.63	CONC MH	S = 892.96		R-2040
UG INLET 2	901.70	CONC MH	E = 894.17		R-2040
UG OUTLET 1	897.14	CONC MH		S = 892.95	R-2040
UG OUTLET 2	904.09	CONC MH		NE = 894.20	R-2040

STORM PIPE TABLE								
PIPE NAME	PIPE TYPE	SIZE (IN.)	FROM	TO	LENGTH (FT)	START INV	END INV	SLOPE
STP-1	HDPE	12	STMH 7		205	896.29	894.75	0.75%
STP-2	HDPE	12	STMH-39	STMH 7	51	896.67	896.29	0.75%
STP-2A	HDPE	12	STMH 9	STMH-39	52	897.06	896.67	0.75%
STP-3	HDPE	12	STMH 10	STMH 9	48	897.42	897.06	0.75%
STP-4	HDPE	12	STMH 11	STMH 10	25	897.67	897.42	1.00%
STP-4A	HDPE	12	STMH 11A	STMH 11	5	897.72	897.67	1.00%
STP-5	HDPE	12	STMH 12	STMH 11A	115	900.02	897.72	2.00%
STP-7	RCP	18	STMH 34	EX STMH 1	155	891.30	890.53	0.50%
STP-8	RCP	12	ROOF DRAIN 2	STMH 34	21	892.01	891.80	1.00%
STP-9	RCP	18	STMH 1	STMH 34	125	891.93	891.30	0.50%
STP-10	RCP	12	OUTLET 1	STMH 1	24	892.25	891.93	1.31%
STP-11	RCP	15	STMH 2	STMH 1	68	892.27	891.93	0.50%
STP-12	RCP	15	STMH 3	STMH 2	53	892.53	892.27	0.50%
STP-13	HDPE	15	STMH 4	STMH 3	10	892.58	892.53	0.50%
STP-14	HDPE	15	STMH 5	STMH 4	112	893.14	892.58	0.50%
STP-15	HDPE	15	STMH 37	STMH 5	87	893.58	893.14	0.50%
STP-16	HDPE	12	UG OUTLET 2	STMH 37	73	894.20	893.83	0.50%
STP-17	RCP	30	EX STMH 3	EX STMH 1	38	889.88	889.50	1.00%
STP-20	RCP	12	TD 2		15	891.80	891.49	2.00%
STP-21	RCP	24	EX STMH 2	EX STMH 3	215	891.21	889.90	0.61%
STP-22	RCP	12	STMH 22	STMH 16	38	897.00	896.24	1.99%
STP-24	RCP	12	STMH 16	EX STMH 2	24	894.11	892.71	5.73%
STP-26	RCP	12	STMH 17	STMH 16	100	897.91	894.11	3.81%
STP-27	RCP	12	STMH 21	STMH 17	26	900.46	899.94	2.00%
STP-28	RCP	12	STMH 18	STMH 17	76	901.73	897.91	5.00%
STP-29	RCP	12	STMH 19	STMH 18	37	903.58	901.73	5.00%
STP-30	RCP	12	STMH 20	STMH 19	6	903.64	903.58	1.00%
STP-37	RCP	12	STMH 28		87	891.47	890.79	0.78%
STP-38	RCP	12	STMH 36	STMH 28	130	892.49	891.47	0.78%
STP-39	RCP	12	STMH 33	STMH 36	41	892.80	892.49	0.76%
STP-40	RCP	12	TD 1	STMH 33	12	892.86	892.80	0.50%
STP-41	RCP	12	STMH 27	STMH 33	17	892.89	892.80	0.50%
STP-42	RCP	12	UG OUTLET 1	STMH 33	28	892.95	892.80	0.52%
STP-43	HDPE	15	STMH 35	UG INLET 2	50	894.42	894.17	0.50%
STP-44	HDPE	15	ROOF DRAIN 3	STMH 35	12	894.48	894.42	0.50%
STP-45	HDPE	12	ROOF DRAIN 1	UG INLET 1	37	893.15	892.96	0.50%
STP-46	RCP	12	STMH 38	STMH 32	119	894.64	893.45	1.00%
STP-47	RCP	12	STMH 32	EX STMH 3	6	893.45	893.39	1.00%



eppstein uhen : architects

milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350

madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350




33 BOYLSTON ST. STE 3000  
CHESTNUT HILL, MA 02467  
P 617.232.8900



SNYDER ASSOCIATES  
5010 VOEGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

PROJECT INFORMATION

HILLDALE SHOPPING CENTER



702 N Midvale Blvd  
Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30



UTILITY PLAN

C 405

© Eppstein Uhen Architects, Inc.



1

2

3

4

5

6

7

SANITARY SEWER NOTES


- THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING UTILITIES PRIOR TO THE START OF CONSTRUCTION.
- THE PROPOSED IMPROVEMENTS SHALL BE CONSTRUCTED ACCORDING TO WISCONSIN ADMINISTRATIVE CODE, SECTION SPS 382-384, LATEST EDITION, THE STANDARD SPECIFICATIONS FOR SEWER CONSTRUCTION IN WISCONSIN, LATEST EDITION, AND THE LOCAL ORDINANCES AND SPECIFICATIONS.
- BEFORE PROCEEDING WITH ANY UTILITY CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE EACH EXISTING LATERAL OR POINT OF CONNECTION AND VERIFY THE LOCATION AND ELEVATION OF ALL UTILITIES. IF ANY EXISTING UTILITIES ARE NOT AS SHOWN ON THE DRAWINGS, THE CONTRACTOR SHALL NOTIFY THE ENGINEER IMMEDIATELY FOR POSSIBLE REDESIGN.
- ALL CONNECTIONS TO EXISTING PIPES AND MANHOLES SHALL BE CORED CONNECTIONS.
- PROPOSED SANITARY SEWER, WATER MAIN, AND INTERNALLY CONNECTED STORM SEWER SHOWN ON THIS PLAN SHALL TERMINATE AT POINT FIVE (5) FEET FROM THE EXTERIOR BUILDING WALL. STORM SEWER CONNECTING TO EXTERIOR DOWN SPOUTS SHALL BE PER DETAILS ON THE ARCHITECTURAL PLANS. THE EXACT LOCATION OF ALL DOWN SPOUTS SHALL BE PER THE ARCHITECTURAL PLANS.
- MATERIALS FOR SANITARY SEWER SHALL BE AS FOLLOWS:  
SANITARY SEWER SHALL BE PVC IN ACCORDANCE WITH ASTM 3034, SDR-35 AND BEDDED WITH CLASS C BEDDING.  
BEDDING: 3/8" TO 1 1/2" CLEAR STONE  
COVER: 3/4" TO 1 1/2" CLEAR STONE  
  
TRACER WIRE SHALL BE INSTALLED WITH ALL NEW LATERALS.  
TRACER WIRE BOXES SHALL BE PROVIDED AND LOCATED 3'5" BEHIND THE BACK OF CURB. "SEWER" SHALL BE STAMPED IN THE LID OF THE ACCESS BOX.  
TRACER WIRE SHALL EXTEND TO THE RIGHT OF WAY.  
ALL LATERAL ENDS SHALL BE MARKED WITH A TREATED 4" X 4" POST AND THE TOP OF THE POST SHALL BE PAINTED GREEN. LATERAL END SHALL BE CAPPED WITH A GLUED ON CAP.  
  
LATERALS ARE NOT ALLOWED TO BE CONNECTED DIRECTLY INTO A MANHOLE.  
  
ALL SANITARY MANHOLE CASTINGS SHALL BE NEENAH R-1550 WITH TYPE B NON-ROCKING LIDS AND CONCEALED PICK HOLES.  
  
SANITARY MANHOLES SHALL HAVE EXTERNAL CHIMNEY SEALS.  
  
ALL MANHOLE JOINTS SHALL BE WRAPPED WITH GATOR WRAP OR APPROVED EQUAL EXCAVATED MATERIAL FROM THE TRENCH NOT SUITABLE FOR BACKFILL AS DEEMED BY THE PUBLIC SERVICES DIRECTOR SHALL BE HAULED OFF-SITE AND SELECT TRENCH BACKFILL WILL BE REQUIRED.  
  
ALL SANITARY SEWER MAINS WILL BE REQUIRED TO BE TELEVISED. 2 COPIES OF THE TELEVISING REPORT AND DVD SHALL BE PROVIDED TO THE PUBLIC SERVICES DIRECTOR. MANDRELL TESTING IS ALSO REQUIRED ON ALL SANITARY SEWER. LOW PRESSURE AIR TESTS ARE REQUIRED ON ALL SANITARY SEWER CONSTRUCTION.  
  
ALL MANHOLES INSTALLED OUTSIDE OF THE RIGHT-OF-WAY SHALL HAVE A RIM ELEVATION A MINIMUM OF 1' ABOVE THE PROPOSED GROUND AND BE MARKED WITH A TREATED 4" X 4" POST AND HAVE A SIGN WITH THE WORDS "SANITARY SEWER" ATTACHED TO THE POST.  
  
LATERAL DEPTH AT THE RIGHT-OF-WAY SHALL NOT EXCEED 12' WITHOUT PROPER JUSTIFICATION. VARIANCES FROM THIS MAP BE APPROVED BY THE PUBLIC SERVICES DIRECTOR.  
  
ADJUSTMENT RINGS SHALL HAVE A MINIMUM HEIGHT OF 4" AND A MAXIMUM HEIGHT OF 12". ADJUSTMENT RINGS SHALL BE POLYETHYLENE PLASTIC UNLESS OTHERWISE APPROVED. MAINTAIN A MINIMUM SEPARATION OF 6" OF HORIZONTAL SEPARATION BETWEEN WATER MAIN AND SANITARY SEWER.  
SANITARY MANHOLES SHALL BE CONSTRUCTED WITH STEPS.
- EXTREME CAUTION MUST BE FOLLOWED REGARDING THE COMPACTION OF ALL UTILITY TRENCHES. MECHANICALLY COMPACTED GRANULAR BACKFILL IS REQUIRED UNDER AND WITHIN 5 FEET OF ALL PAVEMENT INCLUDING SIDEWALKS. FLOODING OF BACKFILL MATERIAL IS NOT ALLOWED. THE COST OF THIS GRANULAR MATERIAL AND ITS COMPACTION IS CONSIDERED INCIDENTAL AND SHALL BE INCLUDED IN THE COST OF THE PROPOSED UTILITY.
- PRIOR TO FINAL PAVING OPERATIONS, THE UTILITY CONTRACTOR SHALL ADJUST ALL MANHOLE AND INLET RIMS AND VALVE BOXES TO FINISHED GRADE.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE OWNER WITH A SET OF MARKED-UP PRINTS SHOWING ALL CHANGES MADE DURING THE CONSTRUCTION PROCESS. ANY CHANGES TO THE DRAWINGS OR ADDITIONAL ITEMS MUST BE REPORTED TO THE OWNER.
- TRACER WIRE SHALL BE INSTALLED ON ALL BURIED NON-METALLIC SANITARY SEWERS, PRIVATE SANITARY INTERCEPTOR MAIN SEWERS, STORM BUILDING SEWERS, AND PRIVATE STORM INTERCEPTOR MAIN SEWERS THAT DISCHARGE TO MUNICIPAL MAINS. TRACER WIRE SHALL BE A MINIMUM OF 18-GAUGE, INSULATED, SINGLE-CONDUCTOR COPPER WIRE OR EQUIVALENT. TRACER WIRE COLOR SHALL BE BLUE FOR POTABLE WATER, GREEN FOR SANITARY SEWER, AND BROWN FOR STORM SEWER.

WATER MAIN NOTES

- THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING UTILITIES PRIOR TO THE START OF CONSTRUCTION.
- THE PROPOSED IMPROVEMENTS SHALL BE CONSTRUCTED ACCORDING TO WISCONSIN ADMINISTRATIVE CODE, SECTION SPS 382-384, LATEST EDITION, THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN, LATEST EDITION, AND THE LOCAL ORDINANCES AND SPECIFICATIONS.
- BEFORE PROCEEDING WITH ANY UTILITY CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE EACH EXISTING LATERAL OR POINT OF CONNECTION AND VERIFY THE LOCATION AND ELEVATION OF ALL UTILITIES. IF ANY EXISTING UTILITIES ARE NOT AS SHOWN ON THE DRAWINGS, THE CONTRACTOR SHALL NOTIFY THE ENGINEER IMMEDIATELY FOR POSSIBLE REDESIGN.
- PROPOSED SANITARY SEWER, WATER MAIN, AND INTERNALLY CONNECTED STORM SEWER SHOWN ON THIS PLAN SHALL TERMINATE AT POINT FIVE (5) FEET FROM THE EXTERIOR BUILDING WALL. STORM SEWER CONNECTING TO EXTERIOR DOWN SPOUTS SHALL BE PER DETAILS ON THE ARCHITECTURAL PLANS. THE EXACT LOCATION OF ALL DOWN SPOUTS SHALL BE PER THE ARCHITECTURAL PLANS.
- MATERIALS FOR WATER SERVICE SHALL BE AS FOLLOWS:  
WATER MAIN SHALL BE DUCTILE IRON AND BEDDED WITH TYPE 3 EMBEDMENT (SAND OR SAND SCREENINGS)  
  
WATER MAIN SHALL BE INSTALLED WITH TRACER WIRE. TRACER WIRE SHALL SURFACE AT ALL HYDRANTS IN A CONDUIT OR A TRACER WIRE ACCESS BOX.  
  
ALL MAINS SHALL BE A MINIMUM OF 8" IN DIAMETER WITH THE EXCEPTION OF HYDRANT LEADS THAT SHALL BE 6".  
  
WATER MAINS SHALL HAVE A MINIMUM COVER OF 6.5'.  
ALL WATER MAINS ARE REQUIRED TO BE LOOPED.  
  
MECHANICAL JOINT FITTINGS WITH MEGA-LUGS ARE REQUIRED FOR ALL DIRECTIONAL CHANGE FITTINGS AND WATER MAIN ENDS. ALL BOLTS SHALL BE STAINLESS STEEL. ALL FITTINGS SHALL BE "MADE IN AMERICA" CERTIFIED.  
  
CORPORATION STOPS SHALL BE MUELLER H15008.  
  
WATER VALVES SHALL BE AMERICAN FLOW CONTROL SERIES 2500 RESILIENT WEDGE GATE VALVE.  
  
WATER MAINS SHALL BE A MINIMUM OF 4' OFF THE FLAG OF THE CURB.  
  
FIRE HYDRANTS SHALL BE LOCATED 3'5" BEHIND THE BACK OF CURB AND HYDRANT VALVES SHALL BE PLACED IN THE STREET.  
  
A FIRE HYDRANT WILL BE REQUIRED AT THE END OF ALL DEAD END LINES.  
  
FIRE HYDRANTS SHALL BE WATEROUS PACER WB67 WITH A STORZ NOZZLE.  
  
CURB BOXES SHALL BE BINGHAM AND TAYLOR BUFFALO TYPE AND INSTALLED WITH THE EXTENSION ROD AND GUIDE RING.  
  
CURB VALVES SHALL BE MUELLER H15209.  
  
CURB BOXES SHALL BE LOCATED 3'5" BEHIND THE BACK OF CURB.  
  
ALL LATERAL/WATER SERVICE ENDS SHALL BE MARKED WITH A TREATED 4" X 4" POST AND THE TOP OF THE POST SHALL BE PAINTED BLUE.  
  
EXCAVATED MATERIAL FROM THE TRENCH NOT SUITABLE FOR BACKFILL AS DEEMED BY THE PUBLIC SERVICES DIRECTOR SHALL BE HAULED OFF-SITE AND SELECT AND SELECT TRENCH BACKFILL WILL BE REQUIRED.  
  
PROVIDE A 2" THICK STYROFOAM INSULATION BETWEEN WATER MAIN AND ALL STORM SEWER CROSSINGS.  
  
WATER MAINS SHALL UNDERGO A PRESSURE AND LEAKAGE TEST. SERVICES SHALL BE TESTED TO THE CURB STOP. SERVICES OF 4" AND LARGER WITH JOINTED PIPE SHALL BE TESTED AGAINST THE VALVE WITH A SECOND TEST OUT TO THE PLUG. THE SECOND TEST MAY BE SHORTER DURATION AS APPROVED BY THE PUBLIC SERVICES DIRECTOR.  
  
A SIGN SHALL BE INSTALLED ADJACENT TO ANY VALVES LOCATED OUTSIDE OF THE RIGHT-OF-WAY WITH THE TEXT "WATER VALVE". SIGNS SHALL BE MOUNTED TO A TREATED 4"x4" WOOD POST.  
  
WATER SERVICES 4" OF DIAMETER OR GREATER SHALL HAVE VALVES LOCATED IN THE STREET.
- EXTREME CAUTION MUST BE FOLLOWED REGARDING THE COMPACTION OF ALL UTILITY TRENCHES. MECHANICALLY COMPACTED GRANULAR BACKFILL IS REQUIRED UNDER AND WITHIN 5 FEET OF ALL PAVEMENT INCLUDING SIDEWALKS. FLOODING OF BACKFILL MATERIAL IS NOT ALLOWED. THE COST OF THIS GRANULAR MATERIAL AND ITS COMPACTION IS CONSIDERED INCIDENTAL AND SHALL BE INCLUDED IN THE COST OF THE PROPOSED UTILITY.

STORM WATER DRAINAGE NOTES :

- THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING UTILITIES PRIOR TO THE START OF CONSTRUCTION.
- UNLESS OTHERWISE INDICATED, USE REINFORCED, PRECAST, CONCRETE MAINTENANCE HOLES AND CATCHBASINS CONFORMING TO ASTM C478, FURNISHED WITH WATER STOP RUBBER GASKETS AND PRECAST BASES. JOINTS FOR ALL PRECAST MAINTENANCE HOLE SECTIONS SHALL HAVE CONFINED, RUBBER "O"-RING GASKETS IN ACCORDANCE WITH ASTM C923. THE INSIDE BARREL DIAMETER SHALL NOT BE LESS THAN 48 INCHES.
- ALL JOINTS AND CONNECTIONS TO CATCHBASINS OR MANHOLES SHALL BE WATERTIGHT. USE RESILIENT RUBBER SEALS, WATERSTOP GASKETS, OR APPROVED EQUAL. CEMENT MORTAR JOINTS ARE NOT ALLOWED.
- INSTALL CATCHBASIN CASTINGS WITH SPECIFIED TOP ELEVATION AT THE FRONT RIM.
- USE HDPE SOLID WALL PIPE WHEN CALLED OUT ON THE PLANS.
- PVC PIPE, USE SOLID-CORE, SDR-35, ASTM D3034 POLYVINYL CHLORIDE (PVC) PIPE FOR DESIGNATED PVC STORM SEWER SERVICES 4 TO 15-INCHES IN DIAMETER. USE SOLID-CORE, SDR-35, ASTM F679 POLYVINYL CHLORIDE (PVC) PIPE FOR DESIGNATED PVC STORM SEWER SERVICES 18 TO 27-INCHES IN DIAMETER. JOINTS FOR ALL STORM SEWER SHALL HAVE PUSH-ON JOINTS WITH ELASTOMERIC GASKETS. USE OF SOLVENT CEMENT JOINTS IS ALLOWED FOR BUILDING SERVICES. SOLVENT CEMENT JOINTS IN PVC PIPE MUST INCLUDE USE OF A PRIMER WHICH IS OF CONTRASTING COLOR TO THE PIPE AND CEMENT. PIPE WITH SOLVENT CEMENT JOINTS SHALL BE JOINED WITH PVC CEMENT CONFORMING TO ASTM D2564. LAY ALL PVC PIPE ON A CONTINUOUS GRANULAR BED. INSTALLATION MUST COMPLY WITH ASTM D2321.
- TESTING: TEST ALL PORTIONS OF STORM SEWER THAT ARE WITHIN 10 FEET OF BUILDINGS, WITHIN 10 FEET OF BURIED WATER, LINES, WITHIN 50 FEET OF WATER WELLS, OR THAT PASS THROUGH SOIL OR WATER IDENTIFIED AS BEING CONTAMINATED. TEST ALL FLEXIBLE STORM SEWER LINES FOR DEFLECTION AFTER THE SEWER LINE HAS BEEN INSTALLED AND BACKFILL HAS BEEN IN PLACE FOR AT LEAST 30 DAYS. NO PIPE SHALL EXCEED A DEFLECTION OF 5%. IF THE TEST FAILS, MAKE NECESSARY REPAIRS AND RETEST.
- INSTALL DETECTABLE UNDERGROUND MARKING TAPE DIRECTLY ABOVE ALL PVC, POLYETHYLENE, AND OTHER NONCONDUCTIVE UNDERGROUND UTILITIES AT A DEPTH OF 457 MM (18 INCHES) BELOW FINISHED GRADE, UNLESS OTHERWISE INDICATED. BRING THE TAPE TO THE SURFACE AT VARIOUS LOCATIONS IN ORDER TO PROVIDE CONNECTION POINTS FOR LOCATING UNDERGROUND UTILITIES. INSTALL BLUE RHINO TRIVIEW FLEX TEST STATIONS, OR APPROVED EQUAL, WITH BLACK CAPS AT EACH SURFACE LOCATION.
- TRACER WIRE: LOCATING REQUIREMENTS - A MEANS TO LOCATE BURIED UNDERGROUND EXTERIOR NON METALLIC SEWERS/MAINS MUST BE PROVIDED WITH TRACER WIRE OR OTHER METHODS IN ORDER TO BE LOCATED IN ACCORD WITH THE PROVISIONS OF THESE CODE SECTIONS AS PER 182.0719(2R) OF THE STATUTES.
- THE MINIMUM DEPTH OF COVER FOR BUILDING AND CANOPY ROOF DRAIN LEADERS WITHOUT INSULATION IS 5 FEET. INSULATE ROOF DRAIN LEADERS AT LOCATIONS WHERE THE DEPTH OF COVER IS LESS THAN 5 FEET. PROVIDE A MINIMUM INSULATION THICKNESS OF 2 INCHES. THE INSULATION MUST BE AT LEAST 4 FEET WIDE AND CENTERED ON THE PIPE. INSTALL THE INSULATION BOARDS 6 INCHES ABOVE THE TOPS OF THE PIPES ON MECHANICALLY COMPACTED AND LEVELED PIPE BEDDING MATERIAL. USE HIGH DENSITY, CLOSED CELL, RIGID BOARD MATERIAL EQUIVALENT TO DOW STYROFOAM HI-40 PLASTIC FOAM INSULATION.
- CLEANOUTS: INSTALL CLEANOUTS ON ALL ROOF DRAINS IN ACCORDANCE WITH S.P.S 382.35 (3)(C)1.). THE DISTANCE BETWEEN CLEANOUTS IN HORIZONTAL PIPING SHALL NOT EXCEED 100 FEET FOR PIPES 10-INCHES AND UNDER IN SIZE. CLEANOUTS SHALL BE OF THE SAME NOMINAL SIZE AS THE PIPES THEY SERVE. INSTALL A METER BOX FRAME AND SOLID LID (NEENAH R-1914-A, OR APPROVED EQUAL) OVER ALL CLEANOUTS.
- INSTALL ALL PIPE WITH THE ASTM IDENTIFICATION NUMBERS ON THE TOP FOR INSPECTION. COMMENCE PIPE LAYING AT THE LOWEST POINT IN THE PROPOSED SEWER LINE. LAY THE PIPE WITH THE BELL END OR RECEIVING GROOVE END OF THE PIPE POINTING UPGRADE. WHEN CONNECTING TO AN EXISTING PIPE, UNCOVER THE EXISTING PIPE IN ORDER TO ALLOW ANY ADJUSTMENTS IN THE PROPOSED LINE AND GRADE BEFORE LAYING ANY PIPE. DO NOT LAY PIPES IN WATER OR WHEN THE TRENCH CONDITIONS ARE UNSUITABLE FOR SUCH WORK.



eppstein uhen : architects

milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350

madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350




33 BOYLSTON ST. STE 3000  
CHESTNUT HILL, MA 02467  
P 617.232.8900



5010 VOEGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

PROJECT INFORMATION

HILDDALE SHOPPING CENTER



702 N Midvale Blvd  
Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
	3/13/2023	CITY SUBMITTAL

KEY PLAN

SHEET INFORMATION

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

UTILITY NOTES

C 500

1

2

3


4

5


6

7







**1** SANITARY MANHOLE DETAIL  
C 501 NOT TO SCALE




**4** BOOT CONNECTION DETAIL  
C 501 NOT TO SCALE




**7** WATER VALVE BOX DETAIL  
C 501 NOT TO SCALE




**10** BUTRESS DETAIL  
C 501 NOT TO SCALE




**2** SANITARY SEWER CLEANOUT  
C 501 NOT TO SCALE




**5** SEWER LATERAL DETAIL  
C 501 NOT TO SCALE




**8** WATER MAIN CONNECTION DETAIL  
C 501 NOT TO SCALE




**11** WATER SERVICE INSTALLATION DETAIL  
C 501 NOT TO SCALE




**3** SANITARY SEWER BEDDING DETAIL  
C 501 NOT TO SCALE



**6** STANDARD HYDRANT DETAIL  
C 501 NOT TO SCALE



**9** OFFSET & RODDING DETAIL  
C 501 NOT TO SCALE



**12** NOT USED  
C 501 NOT TO SCALE

**eua**  
 eppstein uhen : architects  
 milwaukee 333 East Chicago Street Milwaukee, Wisconsin 53202 Telephone 414.271.5350  
 madison 309 West Johnson Street, Suite 202 Madison, Wisconsin 53703 Telephone 608.442.5350  
 WS DEVELOPMENT  
 33 BOYLSTON ST. STE. 3000 CHESTNUT HILL, MA 02467 P 617.232.8900  
 SNYDER ASSOCIATES  
 5010 VOEGES ROAD MADISON, WISCONSIN 53718 608-838-0444  
 PROJECT INFORMATION  
**HILDALE SHOPPING CENTER**  
 HILDALE


702 N Midvale Blvd  
 Madison, WI 53705  
 ISSUANCE AND REVISIONS  

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL


  
 KEY PLAN

SHEET INFORMATION  
 PROJECT MANAGER SJA  
 PROJECT NUMBER 120.0311.30  
 UTILITY DETAILS  
**C 501**  
 © Eppstein Uhen Architects, Inc.






**1** CONSTRUCTION ENTRANCE DETAIL  
NOT TO SCALE




**4** SEDIMENT LOG DETAIL  
NOT TO SCALE



**6** NOT USED  
NOT TO SCALE




**2** SILT FENCE DETAIL  
NOT TO SCALE



**5** CONCRETE WASHOUT DETAILS  
NOT TO SCALE

**7** NOT USED  
NOT TO SCALE



**3** INLET PROTECTION DETAIL  
NOT TO SCALE



**7** NOT USED  
NOT TO SCALE

**EROSION CONTROL NOTES**

1. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING COPIES OF ALL PERMITS, INCLUDING WISDNR WPDES (DISCHARGE PERMIT IF APPLICABLE), COUNTY AND LOCAL EROSION CONTROL PERMIT. CONTRACTOR IS RESPONSIBLE FOR ABIDING BY ALL PERMIT REQUIREMENTS AND RESTRICTIONS.
2. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO LAND DISTURBING ACTIVITIES.
3. ALL INSTALLATION AND MAINTENANCE OF EROSION CONTROL PRACTICES SHALL BE IN ACCORDANCE WITH THE APPLICABLE WISCONSIN DEPARTMENT OF NATURAL RESOURCES (WDNR) TECHNICAL STANDARD, (FOUND AT: <http://dnr.wisconsin.gov/topic/water/erosioncontrol.htm>) OR THE WISCONSIN CONSTRUCTION SITE BEST MANAGEMENT PRACTICE HANDBOOK IF A TECHNICAL STANDARD IS NOT AVAILABLE.
4. ALL EROSION CONTROL FACILITIES SHALL BE MAINTAINED THROUGHOUT THE DURATION OF THE PROJECT AND WARRANTY PERIOD IN CONFORMANCE WITH ALL APPLICABLE PERMITS ISSUED FOR THE PROJECT.
5. ALL EROSION AND SEDIMENTATION CONTROL PRACTICES SHALL BE INSPECTED WEEKLY AND WITHIN 24 HOURS AFTER EVERY PRECIPITATION EVENT THAT PRODUCES 0.5 INCHES OF RAIN OR MORE DURING A 24 HOUR PERIOD. REPAIRS SHALL BE MADE IMMEDIATELY TO EROSION CONTROL PRACTICES AS NECESSARY.
6. TEMPORARY STOCKPILE SHALL BE STABILIZED IF NOT REMOVED IN 10 DAYS. PERIMETER CONTROL ON THE DOWNHILL SIDE SHALL BE IN PLACE AT ALL TIMES (SILT FENCE OR APPROVED EQUAL).
7. TEMPORARY SEED MIXTURE SHALL CONFORM TO 630.2.1.5.1.4 OF THE WISDOT STANDARD SPECIFICATIONS USE WINTER WHEAT OR RYE FOR FALL PLANTINGS STARTED AFTER SEPTEMBER 1.
8. DISTURBED AREAS THAT CANNOT BE STABILIZED WITH A DENSE GROWTH OF VEGETATION BY SEEDING AND MULCHING DUE TO TEMPERATURE OR TIMING OF CONSTRUCTION, SHALL BE STABILIZED BY APPLYING ANIONIC POLYACRYLAMIDE (PAM) IN ACCORDANCE WITH WDNR TECHNICAL STANDARD 1050.
9. SEDIMENT SHALL BE REMOVED FROM THE SEDIMENT BASINS TO MAINTAIN A THREE FOOT DEPTH OF TREATMENT, MEASURED BELOW THE NORMAL WATER ELEVATION. SEDIMENT WILL BE REMOVED FROM THE DIVERSION DITCHES WHEN IT REACHES HALF THE HEIGHT OF THE DITCH. SEDIMENT WILL BE REMOVED FROM BEHIND THE SILT FENCE AND DITCH CHECKS WHEN IT REACHES HALF THE HEIGHT OF THE FENCE/BARRIER. THE SILT FENCE AND DITCH CHECKS SHALL BE REPAIRED AS NECESSARY TO MAINTAIN A BARRIER.
10. ALL WATER FROM CONSTRUCTION DEWATERING SHALL BE TREATED IN ACCORDANCE WITH WDNR TECHNICAL STANDARD 1061 PRIOR TO DISCHARGE TO WATERS OF THE STATE, WETLANDS, OR OFFSITE.
11. THE CONTRACTOR IS RESPONSIBLE FOR INSTALLATION OF ANY ADDITIONAL EROSION CONTROL MEASURES NECESSARY TO PREVENT EROSION AND SEDIMENTATION. ALL DISTURBED AREAS ARE TO DRAIN TO APPROVED SEDIMENT CONTROL MEASURES AT ALL TIMES DURING SITE DEVELOPMENT UNTIL FINAL STABILIZATION IS ACHIEVED. DEPENDING ON HOW THE CONTRACTOR GRADES THE SITE, IT MAY BE NECESSARY TO INSTALL TEMPORARY EROSION CONTROL AND/OR SEDIMENT TRAPS IN VARIOUS LOCATIONS THROUGHOUT THE PROJECT. TEMPORARY SEDIMENT TRAPS SHALL BE DESIGNED, INSTALLED, AND MAINTAINED IN ACCORDANCE WITH WDNR TECHNICAL STANDARD 1063.
12. TRACKED MATERIAL TO ADJACENT STREETS SHALL BE COLLECTED AT THE END OF EACH WORKING DAY OR AS REQUIRED BY THE LOCAL MUNICIPALITY.
13. DUST CONTROL SHALL BE PROVIDED AS NECESSARY IN ACCORDANCE WITH WDNR TECHNICAL STANDARD 1068.
14. FINAL STABILIZATION OF LANDSCAPED AREAS SHALL BE IN ACCORDANCE WITH THE APPROVED LANDSCAPE PLAN.
15. ALL SEEDED AREAS WILL BE FERTILIZED, RESEED AS NECESSARY, AND MULCHED ACCORDING TO SPECIFICATIONS IN THE APPROVED LANDSCAPE PLAN TO MAINTAIN A VIGOROUS DENSE VEGETATIVE COVER.
16. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL EROSION CONTROL FACILITIES AND MEASURES NECESSARY TO CONTROL EROSION AND SEDIMENTATION AT THE PROJECT SITE. THESE FACILITIES AND MEASURES MAY OR MAY NOT BE SHOWN ON THE DRAWINGS AND THEIR ABSENCE ON THE DRAWINGS DOES NOT ALLEVIATE THE CONTRACTOR FROM PROVIDING THEM. ANY MEASURES AND FACILITIES SHOWN ON THE DRAWINGS ARE THE MINIMUM ACTIONS REQUIRED.
17. ERODED MATERIAL THAT HAS LEFT THE CONSTRUCTION SITE SHALL BE COLLECTED AND RETURNED TO THE SITE BY THE CONTRACTOR.
18. AFTER FINAL VEGETATION IS ESTABLISHED, REMOVE ALL EROSION CONTROL FACILITIES. RESTORE AREAS DISTURBED BY THE REMOVALS.
19. KEEP A COPY OF THE CURRENT EROSION CONTROL PLAN ON SITE THROUGHOUT THE DURATION OF THE PROJECT.
20. COMPLETE AND STABILIZE SEDIMENT BASINS/TRAPS PRIOR TO MASS LAND DISTURBANCE TO CONTROL RUNOFF DURING CONSTRUCTION. REMOVE SEDIMENT AS NEEDED TO MAINTAIN 3 FEET OF DEPTH TO THE OUTLET, AND PROPERLY DISPOSE OF SEDIMENT REMOVED DURING MAINTENANCE. CONSTRUCT AND MAINTAIN THE SEDIMENT BASIN PER WDNR TECHNICAL STANDARDS.
21. PROPERLY DISPOSE OF ALL WASTE AND UNUSED BUILDING MATERIALS (INCLUDING GARBAGE, DEBRIS, CLEANING WASTES, OR OTHER CONSTRUCTION MATERIALS) AND DO NOT ALLOW THESE MATERIALS TO BE CARRIED BY RUNOFF INTO THE RECEIVING CHANNEL.
22. MAKE PROVISIONS FOR WATERING DURING THE FIRST 8 WEEKS FOLLOWING SEEDING OR PLANTING OF DISTURBED AREAS WHENEVER MORE THAN 7 CONSECUTIVE DAYS OF DRY WEATHER OCCUR.

**epstein uhen : architects**  
milwaukee 333 East Chicago Street Milwaukee, Wisconsin 53202 telephone 414.271.5350  
madison 309 West Johnson Street, Suite 202 Madison, Wisconsin 53703 telephone 608.442.5350

**WS DEVELOPMENT**  
33 BOYLSTON ST. STE 3000 CHESTNUT HILL, MA 02467 P 617.232.8900

**SNYDER ASSOCIATES**  
5010 VOGES ROAD MADISON, WISCONSIN 53718 608-838-0444

**PROJECT INFORMATION**  
**HILDALE SHOPPING CENTER**

702 N Midvale Blvd  
Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
1	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30










**EROSION CONTROL NOTES & DETAILS**

**C 502**

© Epstein Uhen Architects, Inc.

V:\Projects\2020\120.0311.30\CADD\120.0311.30\_PSD0.mxd ALEXANDER KEEFE, EROSION CONTROL NOTES & DETAILS, 2023/03/10, 2:48 PM, ARCH PULL BLEED ET (30.00 X 42.00 INCHES)





**eua**  
appstein uhen : architects

milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350

madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350

**WS DEVELOPMENT**

33 BOYLSTON ST. STE 3000  
CHESTNUT HILL, MA 02467  
P 617.232.8900

**SNYDER ASSOCIATES**  
5010 VOGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

PROJECT INFORMATION  
**HILLDALE SHOPPING CENTER**

**HILLDALE**

702 N Midvale Blvd  
Madison, WI 53705

ISSUANCE AND REVISIONS

#	DATE	DESCRIPTION
3	13/2023	CITY SUBMITTAL

PROJECT MANAGER SJA











PROJECT NUMBER 120.0311.30

**STORM WATER DETAILS**

**C 503**

© Eppstein Uhen Architects, Inc.





**eua**  
eppstein uhen : architects  
milwaukee 333 East Chicago Street  
Milwaukee, Wisconsin 53202  
telephone 414.271.5350  
madison 309 West Johnson Street, Suite 202  
Madison, Wisconsin 53703  
telephone 608.442.5350

**WS DEVELOPMENT**  
33 BOYLSTON ST. STE 300  
CHESTNUT HILL, MA 02467  
P 617.232.8900

**SNYDER ASSOCIATES**  
5010 VOGES ROAD  
MADISON, WISCONSIN 53718  
608-838-0444

**PROJECT INFORMATION**  
**HILDALE SHOPPING CENTER**

**HILDALE**

702 N Midvale Blvd  
Madison, WI 53705

**ISSUANCE AND REVISIONS**

#	DATE	DESCRIPTION
3	3/13/2023	CITY SUBMITTAL

**KEY PLAN**

**SHEET INFORMATION**

PROJECT MANAGER SJA  
PROJECT NUMBER 120.0311.30

**SITE DETAILS**  
**C 504**

© Eppstein Uhen Architects, Inc.

V:\Projects\2023\120.0311.30\CADD\120.0311.30\PSD\mgp\_alexander\_keefe\_site\_details\_20230310\_249.plt ARCH\FULL BLEED ET (31.00 X 42.00 INCHES)



PROJECT INFORMATION	
ENGINEERED PRODUCT MANAGER	
ADS SALES REP	
PROJECT NO.	



# BUILDING 300

## MADISON, WI

### SC-740 STORMTECH CHAMBER SPECIFICATIONS

1. CHAMBERS SHALL BE STORMTECH SC-740.
2. CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
3. CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
4. CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
5. THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
6. CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS (<1 MIN) AASHTO DESIGN TRUCK LIVE LOAD ON MINIMUM COVER 2) MAXIMUM PERMANENT (75-YR) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
7. REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 550 LBS/FT/%. THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
8. ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER, THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE AS FOLLOWS:
  - THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.
  - THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PIPE.
  - THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
9. CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

### IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-740 SYSTEM

1. STORMTECH SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
2. STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
3. CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS 3 BACKFILL METHODS:
  - STONESHOOTER LOCATED OFF THE CHAMBER BED.
  - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
  - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
4. THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
5. JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
6. MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
7. EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4-2" (20-50 mm).
8. THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
9. ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.

### NOTES FOR CONSTRUCTION EQUIPMENT


1. STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
2. THE USE OF CONSTRUCTION EQUIPMENT OVER SC-740 CHAMBERS IS LIMITED:
  - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
  - NO RUBBER TIRED LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
  - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
3. FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

**USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.**

CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.



PROPOSED LAYOUT		PROPOSED ELEVATIONS		*INVERT ABOVE BASE OF CHAMBER				
				PART TYPE	ITEM ON LAYOUT	DESCRIPTION	INVERT*	MAX FLOW
60	STORMTECH SC-740 CHAMBERS	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED):	904.70					
10	STORMTECH SC-740 END CAPS	MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC):	898.70					
12	STONE ABOVE (in)	MINIMUM ALLOWABLE GRADE (UNPAVED NO TRAFFIC):	898.20	PREFABRICATED EZ END CAP	A	24" BOTTOM PREFABRICATED EZ END CAP, PART#: SC740ECEZ / TYP OF ALL 24" BOTTOM CONNECTIONS AND ISOLATOR PLUS ROWS	0.10"	
12	STONE BELOW (in)	MINIMUM ALLOWABLE GRADE (TOP OF RIGID CONCRETE PAVEMENT):	898.20	FLAMP	B	INSTALL FLAMP ON 24" ACCESS PIPE / PART#: SC74024RAMP		
40	STONE VOID	MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT):	898.20	MANIFOLD	C	12" x 12" TOP MANIFOLD, ADS N-12	12.50"	
5927	INSTALLED SYSTEM VOLUME (CF) (PERIMETER STONE INCLUDED) (COVER STONE INCLUDED) (BASE STONE INCLUDED)	TOP OF STONE:	897.70	NYLOPLAST (INLET W/ ISO PLUS ROW)	D	30" DIAMETER (24.00" SUMP MIN)		5.7 CFS IN
		TOP OF SC-740 CHAMBER:	896.70	NYLOPLAST (OUTLET)	E	30" DIAMETER (DESIGN BY ENGINEER)		2.0 CFS OUT
		12" x 12" TOP MANIFOLD INVERT:	895.24	UNDERDRAIN	F	6" ADS N-12 DUAL WALL PERFORATED HDPE UNDERDRAIN		
		12" BOTTOM CONNECTION INVERT:	894.30					
2374	SYSTEM AREA (SF)	24" ISOLATOR ROW PLUS INVERT:	894.21					
237.6	SYSTEM PERIMETER (ft)	BOTTOM OF SC-740 CHAMBER:	894.20					
		UNDERDRAIN INVERT:	893.20					
		BOTTOM OF STONE:	893.20					



- ISOLATOR ROW PLUS (SEE DETAIL)
- PLACE MINIMUM 12.50' OF ADSPLUS125 WOVEN GEOTEXTILE OVER BEDDING STONE AND UNDERNEATH CHAMBER FEET FOR SCOUR PROTECTION AT ALL CHAMBER INLET ROWS
- BED LIMITS

**NOTES**

- MANIFOLD SIZE TO BE DETERMINED BY SITE DESIGN ENGINEER. SEE TECH NOTE #6.32 FOR MANIFOLD SIZING GUIDANCE.
- DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THE SITE DESIGN ENGINEER MUST REVIEW ELEVATIONS AND IF NECESSARY ADJUST GRADING TO ENSURE THE CHAMBER COVER REQUIREMENTS ARE MET.
- THIS CHAMBER SYSTEM WAS DESIGNED WITHOUT SITE-SPECIFIC INFORMATION ON SOIL CONDITIONS OR BEARING CAPACITY. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THE SOIL AND PROVIDING THE BEARING CAPACITY OF THE INSITU SOILS. THE BASE STONE DEPTH MAY BE INCREASED OR DECREASED ONCE THIS INFORMATION IS PROVIDED.
- **NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.

**StormTech®**  
Chamber System

888-892-2694 | WWW.STORMTECH.COM

4640 TRUEMAN BLVD  
HILLIARD, OH 43026  
1-800-733-7473

0 10' 20'

BUILDING 300  
MADISON, WI

DATE: \_\_\_\_\_  
DRAWN: LO  
PROJECT #: \_\_\_\_\_  
CHECKED: N/A

SHEET  
**2 OF 6**

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.




## ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS

MATERIAL LOCATION		DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT
D	<b>FINAL FILL:</b> FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	ANY SOIL/ROCK MATERIALS, NATIVE SOILS, OR PER ENGINEER'S PLANS. CHECK PLANS FOR PAVEMENT SUBGRADE REQUIREMENTS.	N/A	PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.
C	<b>INITIAL FILL:</b> FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	GRANULAR WELL-GRADED SOIL/AGGREGATE MIXTURES, <35% FINES OR PROCESSED AGGREGATE.  MOST PAVEMENT SUBBASE MATERIALS CAN BE USED IN LIEU OF THIS LAYER.	AASHTO M145 <sup>1</sup> A-1, A-2-4, A-3  OR  AASHTO M43 <sup>1</sup> 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10	BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN). DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN).
B	<b>EMBEDMENT STONE:</b> FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	CLEAN, CRUSHED, ANGULAR STONE	AASHTO M43 <sup>1</sup> 3, 357, 4, 467, 5, 56, 57	NO COMPACTION REQUIRED.
A	<b>FOUNDATION STONE:</b> FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	CLEAN, CRUSHED, ANGULAR STONE	AASHTO M43 <sup>1</sup> 3, 357, 4, 467, 5, 56, 57	PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. <sup>2,3</sup>

**PLEASE NOTE:**

- THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
- STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
- WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.
- ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.




**NOTES:**

- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- SC-740 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 550 LBS/FT/%. THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.

<b>BUILDING 300</b>	MADISON, WI	DRAWN: LO	CHECKED: N/A
	DATE:	PROJECT #:	DESCRIPTION
	DATE	DRW	CHK
<b>StormTech®</b> Chamber System		888-892-2694   WWW.STORMTECH.COM	
4640 TRUEMAN BLVD HILLIARD, OH 43026 1-800-733-7473		THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.	
SHEET <b>3 OF 6</b>			





**SC-740 ISOLATOR ROW PLUS DETAIL**  
NTS

**INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
- A. INSPECTION PORTS (IF PRESENT)
    - A.1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
    - A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
    - A.3. USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
    - A.4. LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
    - A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
  - B. ALL ISOLATOR PLUS ROWS
    - B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
    - B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
      - i) MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
      - ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - B.3. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JETVAC PROCESS
- A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45" (1.1 m) OR MORE IS PREFERRED
  - B. APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
  - C. VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.


**NOTES**

1. INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
2. CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.


<b>BUILDING 300</b>	MADISON, WI	DATE:	DRAWN: LO	CHECKED: N/A
		PROJECT #:		
DATE	DRW	CHK	DESCRIPTION	
		888-892-2694   WWW.STORMTECH.COM		
4640 TRUEMAN BLVD HILLIARD, OH 43026 1-800-733-7473				
THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.				
SHEET		4 OF 6		



**UNDERDRAIN DETAIL**



**SC-740 TECHNICAL SPECIFICATION**




**NOMINAL CHAMBER SPECIFICATIONS**

SIZE (W X H X INSTALLED LENGTH)	51.0" X 30.0" X 85.4"	(1295 mm X 762 mm X 2169 mm)
CHAMBER STORAGE	45.9 CUBIC FEET	(1.30 m <sup>3</sup> )
MINIMUM INSTALLED STORAGE*	74.9 CUBIC FEET	(2.12 m <sup>3</sup> )
WEIGHT	75.0 lbs.	(33.6 kg)

\*ASSUMES 6" (152 mm) STONE ABOVE, BELOW, AND BETWEEN CHAMBERS

PRE-FAB STUB AT BOTTOM OF END CAP WITH FLAMP END WITH "BR"  
 PRE-FAB STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"  
 PRE-FAB STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"  
 PRE-CORED END CAPS END WITH "PC"



PART #	STUB	A	B	C
SC740EPE06T / SC740EPE06TPC	6" (150 mm)	10.9" (277 mm)	18.5" (470 mm)	---
SC740EPE06B / SC740EPE06BPC	---	---	---	0.5" (13 mm)
SC740EPE08T / SC740EPE08TPC	8" (200 mm)	12.2" (310 mm)	16.5" (419 mm)	---
SC740EPE08B / SC740EPE08BPC	---	---	---	0.6" (15 mm)
SC740EPE10T / SC740EPE10TPC	10" (250 mm)	13.4" (340 mm)	14.5" (368 mm)	---
SC740EPE10B / SC740EPE10BPC	---	---	---	0.7" (18 mm)
SC740EPE12T / SC740EPE12TPC	12" (300 mm)	14.7" (373 mm)	12.5" (318 mm)	---
SC740EPE12B / SC740EPE12BPC	---	---	---	1.2" (30 mm)
SC740EPE15T / SC740EPE15TPC	15" (375 mm)	18.4" (467 mm)	9.0" (229 mm)	---
SC740EPE15B / SC740EPE15BPC	---	---	---	1.3" (33 mm)
SC740EPE18T / SC740EPE18TPC	18" (450 mm)	19.7" (500 mm)	5.0" (127 mm)	---
SC740EPE18B / SC740EPE18BPC	---	---	---	1.6" (41 mm)
SC740ECEZ*	24" (600 mm)	18.5" (470 mm)	---	0.1" (3 mm)

ALL STUBS, EXCEPT FOR THE SC740ECEZ ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2694.

\* FOR THE SC740ECEZ THE 24" (600 mm) STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 1.75" (44 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL

BUILDING 300

MADISON, WI

DRAWN: LO

CHECKED: N/A

DATE:

PROJECT #:

DESCRIPTION

CHK

DATE

DRW

**StormTech®**  
 Chamber System

888-892-2694 | WWW.STORMTECH.COM

4640 TRUJMAN BLVD  
 HILLIARD, OH 43026  
 1-800-733-7473

**ADS**

SHEET


5 OF 6

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.



# NYLOPLAST DRAIN BASIN

NTS



## NOTES

- 8-30" (200-750 mm) GRATES/SOLID COVERS SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- 12-30" (300-750 mm) FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- DRAIN BASIN TO BE CUSTOM MANUFACTURED ACCORDING TO PLAN DETAILS
- DRAINAGE CONNECTION STUB JOINT TIGHTNESS SHALL CONFORM TO ASTM D3212 FOR CORRUGATED HDPE (ADS & HANCOR DUAL WALL) & SDR 35 PVC
- FOR COMPLETE DESIGN AND PRODUCT INFORMATION: [WWW.NYLOPLAST-US.COM](http://WWW.NYLOPLAST-US.COM)
- TO ORDER CALL: 800-821-6710

A	PART #	GRATE/SOLID COVER OPTIONS		
8" (200 mm)	2808AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
10" (250 mm)	2810AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
12" (300 mm)	2812AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
15" (375 mm)	2815AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
18" (450 mm)	2818AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
24" (600 mm)	2824AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
30" (750 mm)	2830AG	PEDESTRIAN AASHTO H-20	STANDARD AASHTO H-20	SOLID AASHTO H-20

BUILDING 300  
MADISON, WI

DRAWN: LO

DATE:

CHECKED: N/A

DESCRIPTION	DATE	DRW	CHK

**Nyloplast**<sup>®</sup>

770-932-2443 | [WWW.NYLOPLAST-US.COM](http://WWW.NYLOPLAST-US.COM)

4640 TRUEMAN BLVD  
HILLIARD, OH 43026  
1-800-733-7473



THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.







PROJECT INFORMATION	
ENGINEERED PRODUCT MANAGER	
ADS SALES REP	
PROJECT NO.	



# BUILDING 500

## MADISON, WI

### SC-740 STORMTECH CHAMBER SPECIFICATIONS

1. CHAMBERS SHALL BE STORMTECH SC-740.
2. CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
3. CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
4. CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
5. THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
6. CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS (<1 MIN) AASHTO DESIGN TRUCK LIVE LOAD ON MINIMUM COVER 2) MAXIMUM PERMANENT (75-YR) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
7. REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 550 LBS/FT/%. THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
8. ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER, THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE AS FOLLOWS:
  - THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.
  - THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PIPE.
  - THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
9. CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

### IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-740 SYSTEM

1. STORMTECH SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
2. STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
3. CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS 3 BACKFILL METHODS:
  - STONESHOOTER LOCATED OFF THE CHAMBER BED.
  - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
  - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
4. THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
5. JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
6. MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
7. EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4-2" (20-50 mm).
8. THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
9. ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.

### NOTES FOR CONSTRUCTION EQUIPMENT


1. STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
2. THE USE OF CONSTRUCTION EQUIPMENT OVER SC-740 CHAMBERS IS LIMITED:
  - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
  - NO RUBBER TIRED LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
  - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
3. FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

**USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.**

CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.



PROPOSED LAYOUT		PROPOSED ELEVATIONS		*INVERT ABOVE BASE OF CHAMBER				
				PART TYPE	ITEM ON LAYOUT	DESCRIPTION	INVERT*	MAX FLOW
44	STORMTECH SC-740 CHAMBERS	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED):	903.45					
8	STORMTECH SC-740 END CAPS	MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC):	897.45					
12	STONE ABOVE (in)	MINIMUM ALLOWABLE GRADE (UNPAVED NO TRAFFIC):	896.95	PREFABRICATED EZ END CAP	A	24" BOTTOM PREFABRICATED EZ END CAP, PART#: SC740ECEZ / TYP OF ALL 24" BOTTOM CONNECTIONS AND ISOLATOR PLUS ROWS	0.10"	
6	STONE BELOW (in)	MINIMUM ALLOWABLE GRADE (TOP OF RIGID CONCRETE PAVEMENT):	896.95	FLAMP	B	INSTALL FLAMP ON 24" ACCESS PIPE / PART#: SC74024RAMP		
40	STONE VOID	MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT):	896.95	MANIFOLD	C	12" x 12" TOP MANIFOLD, ADS N-12	12.50"	
4110	INSTALLED SYSTEM VOLUME (CF) (PERIMETER STONE INCLUDED) (COVER STONE INCLUDED) (BASE STONE INCLUDED)	TOP OF STONE:	896.45	NYLOPLAST (INLET W/ ISO PLUS ROW)	D	30" DIAMETER (24.00" SUMP MIN)		5.7 CFS IN
		TOP OF SC-740 CHAMBER:	895.45	NYLOPLAST (OUTLET)	E	30" DIAMETER (DESIGN BY ENGINEER)		2.0 CFS OUT
		12" x 12" TOP MANIFOLD INVERT:	893.99	UNDERDRAIN	F	6" ADS N-12 DUAL WALL PERFORATED HDPE UNDERDRAIN		
		12" BOTTOM CONNECTION INVERT:	893.05					
1811	SYSTEM AREA (SF)	24" ISOLATOR ROW PLUS INVERT:	892.96					
213.8	SYSTEM PERIMETER (ft)	BOTTOM OF SC-740 CHAMBER:	892.95					
		UNDERDRAIN INVERT:	892.45					
		BOTTOM OF STONE:	892.45					



- ISOLATOR ROW PLUS (SEE DETAIL)
- PLACE MINIMUM 12.50' OF ADSPLUS125 WOVEN GEOTEXTILE OVER BEDDING STONE AND UNDERNEATH CHAMBER FEET FOR SCOUR PROTECTION AT ALL CHAMBER INLET ROWS
- BED LIMITS

**NOTES**

- MANIFOLD SIZE TO BE DETERMINED BY SITE DESIGN ENGINEER. SEE TECH NOTE #6.32 FOR MANIFOLD SIZING GUIDANCE.
- DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THE SITE DESIGN ENGINEER MUST REVIEW ELEVATIONS AND IF NECESSARY ADJUST GRADING TO ENSURE THE CHAMBER COVER REQUIREMENTS ARE MET.
- THIS CHAMBER SYSTEM WAS DESIGNED WITHOUT SITE-SPECIFIC INFORMATION ON SOIL CONDITIONS OR BEARING CAPACITY. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THE SOIL AND PROVIDING THE BEARING CAPACITY OF THE INSITU SOILS. THE BASE STONE DEPTH MAY BE INCREASED OR DECREASED ONCE THIS INFORMATION IS PROVIDED.
- **NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.

**BUILDING 500**  
MADISON, WI

DATE: \_\_\_\_\_ DRAWN: LO

PROJECT #: \_\_\_\_\_ CHECKED: N/A

DATE	DRW	CHK	DESCRIPTION

**StormTech®**  
Chamber System

888-892-2694 | WWW.STORMTECH.COM

4640 TRUEMAN BLVD  
HILLIARD, OH 43026  
1-800-733-7473

SHEET  
**2 OF 6**

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.




## ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT
D	<b>FINAL FILL:</b> FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	N/A	PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.
C	<b>INITIAL FILL:</b> FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	AASHTO M145 <sup>1</sup> A-1, A-2-4, A-3  OR AASHTO M43 <sup>1</sup> 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10	BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN). DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN).
B	<b>EMBEDMENT STONE:</b> FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	AASHTO M43 <sup>1</sup> 3, 357, 4, 467, 5, 56, 57	NO COMPACTION REQUIRED.
A	<b>FOUNDATION STONE:</b> FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	AASHTO M43 <sup>1</sup> 3, 357, 4, 467, 5, 56, 57	PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. <sup>2,3</sup>

**PLEASE NOTE:**

1. THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
2. STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
3. WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.
4. ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.



**NOTES:**

1. CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
2. SC-740 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
3. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
4. PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
5. REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 550 LBS/FT/%. THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.

**BUILDING 500**  
MADISON, WI

DATE: \_\_\_\_\_ DRAWN: LO

PROJECT #: \_\_\_\_\_ CHECKED: N/A

**StormTech®**  
Chamber System

888-892-2694 | WWW.STORMTECH.COM


4640 TRUEMAN BLVD  
HILLIARD, OH 43026  
1-800-733-7473

**ADS**

SHEET  
**3 OF 6**

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.





**SC-740 ISOLATOR ROW PLUS DETAIL**

NTS

**INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
  - A. INSPECTION PORTS (IF PRESENT)
    - A.1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
    - A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
    - A.3. USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
    - A.4. LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
    - A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
  - B. ALL ISOLATOR PLUS ROWS
    - B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
    - B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
      - i) MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
      - ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - B.3. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JETVAC PROCESS
  - A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45" (1.1 m) OR MORE IS PREFERRED
  - B. APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
  - C. VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.


**NOTES**

- 1. INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- 2. CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.


<b>BUILDING 500</b>		MADISON, WI	
DATE:		DRAWN: LO	
PROJECT #:		CHECKED: N/A	
<b>StormTech®</b>		888-892-2694   WWW.STORMTECH.COM	
Chamber System			
4640 TRUEMAN BLVD HILLIARD, OH 43026 1-800-733-7473			
THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.			
SHEET		4 OF 6	



**UNDERDRAIN DETAIL**



**SC-740 TECHNICAL SPECIFICATION**




**NOMINAL CHAMBER SPECIFICATIONS**

SIZE (W X H X INSTALLED LENGTH)	51.0" X 30.0" X 85.4"	(1295 mm X 762 mm X 2169 mm)
CHAMBER STORAGE	45.9 CUBIC FEET	(1.30 m <sup>3</sup> )
MINIMUM INSTALLED STORAGE*	74.9 CUBIC FEET	(2.12 m <sup>3</sup> )
WEIGHT	75.0 lbs.	(33.6 kg)

\*ASSUMES 6" (152 mm) STONE ABOVE, BELOW, AND BETWEEN CHAMBERS

PRE-FAB STUB AT BOTTOM OF END CAP WITH FLAMP END WITH "BR"  
 PRE-FAB STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"  
 PRE-FAB STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"  
 PRE-CORED END CAPS END WITH "PC"



PART #	STUB	A	B	C
SC740EPE06T / SC740EPE06TPC	6" (150 mm)	10.9" (277 mm)	18.5" (470 mm)	---
SC740EPE06B / SC740EPE06BPC	---	---	---	0.5" (13 mm)
SC740EPE08T / SC740EPE08TPC	8" (200 mm)	12.2" (310 mm)	16.5" (419 mm)	---
SC740EPE08B / SC740EPE08BPC	---	---	---	0.6" (15 mm)
SC740EPE10T / SC740EPE10TPC	10" (250 mm)	13.4" (340 mm)	14.5" (368 mm)	---
SC740EPE10B / SC740EPE10BPC	---	---	---	0.7" (18 mm)
SC740EPE12T / SC740EPE12TPC	12" (300 mm)	14.7" (373 mm)	12.5" (318 mm)	---
SC740EPE12B / SC740EPE12BPC	---	---	---	1.2" (30 mm)
SC740EPE15T / SC740EPE15TPC	15" (375 mm)	18.4" (467 mm)	9.0" (229 mm)	---
SC740EPE15B / SC740EPE15BPC	---	---	---	1.3" (33 mm)
SC740EPE18T / SC740EPE18TPC	18" (450 mm)	19.7" (500 mm)	5.0" (127 mm)	---
SC740EPE18B / SC740EPE18BPC	---	---	---	1.6" (41 mm)
SC740ECEZ*	24" (600 mm)	18.5" (470 mm)	---	0.1" (3 mm)

ALL STUBS, EXCEPT FOR THE SC740ECEZ ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2694.

\* FOR THE SC740ECEZ THE 24" (600 mm) STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 1.75" (44 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL

BUILDING 500  
 MADISON, WI

DATE: \_\_\_\_\_  
 PROJECT #: \_\_\_\_\_  
 DRAWN: LO  
 CHECKED: N/A

DATE	DRW	CHK	DESCRIPTION

**StormTech®**  
 Chamber System  
 888-892-2694 | WWW.STORMTECH.COM

4640 TRUEMAN BLVD  
 HILLIARD, OH 43026  
 1-800-733-7473




THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.



# NYLOPLAST DRAIN BASIN

NTS



## NOTES

- 8-30" (200-750 mm) GRATES/SOLID COVERS SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- 12-30" (300-750 mm) FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- DRAIN BASIN TO BE CUSTOM MANUFACTURED ACCORDING TO PLAN DETAILS
- DRAINAGE CONNECTION STUB JOINT TIGHTNESS SHALL CONFORM TO ASTM D3212 FOR CORRUGATED HDPE (ADS & HANCOR DUAL WALL) & SDR 35 PVC
- FOR COMPLETE DESIGN AND PRODUCT INFORMATION: [WWW.NYLOPLAST-US.COM](http://WWW.NYLOPLAST-US.COM)
- TO ORDER CALL: 800-821-6710

A	PART #	GRATE/SOLID COVER OPTIONS		
8" (200 mm)	2808AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
10" (250 mm)	2810AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
12" (300 mm)	2812AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
15" (375 mm)	2815AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
18" (450 mm)	2818AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
24" (600 mm)	2824AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
30" (750 mm)	2830AG	PEDESTRIAN AASHTO H-20	STANDARD AASHTO H-20	SOLID AASHTO H-20

BUILDING 500  
MADISON, WI

DRAWN: LO

DATE:

PROJECT #:

CHECKED: N/A

Nyloplast®

770-932-2443 | WWW.NYLOPLAST-US.COM

4640 TRUEMAN BLVD  
HILLIARD, OH 43026  
1-800-733-7473



SHEET

6 OF 6

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.