# PBMVC 9/26/06 ITEM E



# Department of Transportation Traffic Engineering & Parking Divisions

Madison Municipal Building 215 Martin Luther King, Jr. Boulevard P.O. Box 2986 Madison, Wisconsin 53701-2986 PH: 608 266 4761

TTY: 608 267 9623 FAX: 608 267 1158

August 17, 200₹ 6

# Re: 2006 Draft Traffic Signal Priority List

The schedule for the 2006 Traffic Signal Priority List (TSPL) is planned as follows:

August 22 Initial discussion with the Pedestrian/Bicycle/Motor Vehicle

Commission introducing the 2006 Traffic Signal Priority List schedule.

September 26 Opportunity offered at Pedestrian/Bicycle/Motor Vehicle
Commission (PBMVC) meeting for comments (written or oral) from
interested residents to be presented. Room 260, Madison Municipal
Building, 215 Martin Luther King Jr. Blvd, at 5 p.m.

PBMVC review/discussion of 2006 Traffic Signal Priority List.

Additional data needs to be identified.

November 28 Final 2006 Signal Priority List and Action Plan reviewed and adopted by PBMVC.

Please note the September 26 meeting is your opportunity to offer comments on specific intersections.

Signal warrants are the framework for analyzing and comparing the need for traffic signal control at intersections. Madison's Priority List is an annual effort to evaluate relative needs for traffic signal control at major unsignalized intersections. While all of the data on the Priority List is valuable, additional factors are also considered and evaluated before decisions to install signals are made. For example, an intersection with volumes somewhat below the minimum volumes to meet a signal warrant may still be a prime candidate for signals if volumes are expected to increase significantly in the immediate future. On the flip side, intersections with volumes above the threshold for traffic signals may not be recommended for signals when accident rates or congestion are expected to worsen with signal control.

A copy of last years 2005 TSPL is enclosed along with the detailed descriptions of the signal warrants. This information is also available on our web page: http://www.cityofmadison.com/transp/trindex.html

Brian Smith, Traffic Engineer (261-9625), can respond to your questions or comments regarding technical aspects of the priority list.

Sincerely,

David Dryer, P.E. City Traffic Engineer and Parking Manager

Enclosures

ð

## CRITERIA FOR TRAFFIC SIGNALS

#### INTRODUCTION

Difficult deliberations often precede the decision to install a new traffic signal. The Manual on Uniform Traffic Control Devices (MUTCD) lists eight different ways that a traffic signal can be "justified." These eight different ways will be called "criteria" in this report. In the MUTCD, the criteria are called warrants. Regardless of the terminology, the eight criteria provide a nationally used, systematic method to evaluate the need for traffic signals. Meeting just one of these eight criteria can be justification for installing signals. However, many other factors need to be considered. Addressing travel needs by alternative means without installing signals may be desirable at some locations even when one or more of the eight signal criteria are met.

#### **PROCESS**

The City Traffic Engineering Division will use the eightcriteria published as warrants in the *MUTCD*. Traffic will be counted, typically by automatic machine methods that segregate traffic for each approach. Locations that appear close to meeting one or more criteria will receive more intense study, including manual counts that segregate traffic by type (motor vehicle, bicycle, pedestrian) and movement (left turn, right turn, straight through); vehicle delay study; field review of existing intersection conditions; etc.

## Special Considerations:

- (1) When a manual count has been made, on-street bicycle traffic will be included in vehicle volumes before comparing to the criteria.
- (2) Pedestrian volume will generally include those crossing at the intersection and within one-half block of the intersection. The adequacy of alternative pedestrian crossings (safety, travel route, etc.) to meet pedestrian needs will be considered.
- (3) Where "side street" right-turn traffic exceeds 25% of approach volume, all or a portion of right-turn traffic will be deducted before the volumes are compared to the criteria.
- (4) Intersection topography and geometry will be considered.
- (5) The effect and influence of nearby roadway features will be considered. Such features would include driveways, intersections, railroad crossings, etc.
- (6) Future traffic, especially in a growing area, will be considered.
- (7) Traffic redirection resulting from a signal will be considered. This especially includes the impact on neighborhood streets of installing and not installing the signal.
- (8) Benefits to land uses having access to a potential signalized intersection need to be considered.
- (9) The effects of new signals for travel along an arterial highway need to be considered.

# PRIORITY LIST AND COMMENTARY

A rank order priority list will be prepared for review by the Pedestrian/Bicycle/Motor Vehicle Commission. Staff will prepare commentary on those intersections of most interest to the Commission. The commentary will cover special consideration items listed earlier and other issues.

Contract to the second section of

#### TRAFFIC SIGNAL WARRANTS: PARAPHRASED DESCRIPTION

#### Warrant #1-A: Minimum Vehicular Volume

The "side street" traffic volume is the principal reason for signals under this warrant. Typical <u>minimum</u> volume thresholds needed for at least <u>8 hours:</u>

Main Street: 600 vehicles each hour Side Street: 200 vehicles each hour

## Warrant #1-B: Interruption of Continuous Traffic

The high volume on the major street and lack of traffic bunching does not allow enough gaps for side street traffic. Typical minimum volume thresholds needed for at least 8 hours:

Main Street: 900 vehicles each hour Side Street: 100 vehicles each hour

#### Warrant #1-C: Combination of Warrants

For <u>exceptional</u> cases, warrants 1-A and 1-B are each over 80% of the minimum threshold volumes.

#### Warrant #2: Four-hour Volumes

Traffic volumes for four hours fall above the threshold lines on the warrant chart. Traffic concentrated within a four-hour period justifies signal control.

## Warrant #3-A: Peak-hour Delay

The side street traffic needs to wait too long on average during a one-hour period. Typical minimum thresholds:

- · Five vehicle-hours of delay for a two-lane side street approach, and
- Side street volume exceeds 150 vehicles during the same hour, and
- Total intersection traffic exceeds 800 vehicles during the same hour.

#### Warrant #3-B: Peak-hour Volume

Traffic volumes for one hour fall above the threshold lines on the warrant chart. Traffic concentrated within a one-hour period justifies signal control.

#### Warrant #4: Minimum Pedestrian Volume

The high volume and lack of traffic bunching on the major street does not allow enough gaps for pedestrians to cross. Typical <u>minimum</u> volume thresholds needed are as follows:

- 100 pedestrians crossing each hour for any four hours.
- The frequency of gaps in major street traffic average less than one per minute.

M:\DESIGN\Traffic\SIG\_PRIO\2001\To mike simle\CRITERIA FOR TRAFFIC SIGNALS.doc

Page 3



The study location must be suitable for maintaining existing platoons of vehicles created by nearby signals.

## Warrant #5: School Crossing

The high volume and lack of traffic bunching on the major street does not allow enough gaps for students to cross. Adequate gaps occur less frequently than once a minute or once each signal cycle when adjacent signals create gaps.

# Warrant #6: Coordinated Signal System

Traffic signal control is needed to keep traffic bunched (i.e., to keep platoons from getting too spread out). Traffic bunching or platooning is helpful in reducing speeding and allowing gaps at non-signalized intersections.

## Warrant #7: Crash Experience

Traffic signal control is determined to be the safer control type. Other measures to maintain safety have not proven effective. This is one of the most controversial warrants to justify signal control. Typical minimum thresholds:

- Five or more accidents in the past 12 months of a type that could theoretically have been prevented if signal control had been in operation.
- Warrants 1-A, 1-B or 4 are at least 80% met.
- Progressive traffic flow would not be significantly affected.

## Warrant #8: Roadway Network Warrant

Signals are needed to keep traffic on the major streets. Typical minimum thresholds:

- Vehicle volume of 1000 vehicles during the peak hour.
- Projected volumes will meet warrants 1, 2, or 3 within five years.

To request a copy of the section on Traffic Signal Warrants in the 2000 edition of the MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, call Brian Smith at 261-9625.

# 2005 TRAFFIC SIGNAL PRIORITY LIST

		1,	n accer	rdanco i	with ori				GNAL I		commissio	n and a-	nama = = =	ouncil				
		uance v	WILLI CIT	teria au	lopeu i	by the t	anspor	tation c		on and co		ouncii T		Γ -	T	<del></del> -		
		Overall WARRANT 1-A						WARR	ANT 1-E	3	# With	#						
		%	Major	r Street	Minor	Street	Majo	r Street	Mino	r Street	Property	With			Peak	Peak		
	Location	Below	#	%	#	%	#	%	#	%	Damage	Personal	Crash	Pedestrian	Hour	Hour	4 Hour	
	Side Street Stop Controlled Intersections Stu	Warrant	Hrs.	Met eting the	Hrs. e Minim	Met	Hrs.	Met Peguirer	Hrs.	Met either M	Only	Injuries	Rate	Warrant	Warrant A	Warrant B	Warrant	Comments
1	Edgewood & Monroe	-23	14	171	0	39	10	114	1	77	1	o warran	0.17	N				
2	Manchester & McKee (PD)	-24	17	225	2+	38	16	150	8+	76	,	1	0.17	N N	-	N Y	N-1 HRS	ABCE
3	Gammon, McKenna & New Washburn	-30	16	208	0	35	12	139	1	70	1		0.13	N N	-		N-2 HRS	EF
4	Bedford & Northshore	-32	14	144		35	9	100	7+	68	,		0.12	N	-	N N	N-0 HRS.	5-
5	Franklin & Johnson	-33	17	263	0	34	14	175	0	67	0		0	N N	_	N N	N-3 HRS	DE
6	Nakoma, Seminole, Yuma	-34	8	110	0	49	2	66	5+	111	0	0	0	N	N-1.08	N N	N-0 HRS	
7	Old Sauk & Westfield	-35	12	143	0	35	5	95	1	70	0	1	0,18	N	N-0.84	N N	N-0 HRS	ļr L
8	Milwaukee & Schenk	-35	15	170	0	33	9	113	2	65	0	'	0.10	N	11-0.04	N N	N-0 BRS	ļ.
9	Segoe & Sheboygan	-36	6	96	1+	67	0	64	11+	133	1	0	0.23	N	- -	N N	N-1 HRS	AEF
10	Marshall, Ridge & University	-38	18	615	0	31	17	410		62	1 1	0	0.05	N	- -	N-0 HRS	N-U FIRS	i
11	High Point & Star Grass	-38	5	100	2+	50	1	62	8	237	0	0	0.55	N		N-U ARS	N-2 HRS	ADEF
12	Atwood, Miller & Waubesa	-39	15	158	0	31	13	105		61	0	1	0.13	N	-	N N	N-2 HRS N-0 HRS	AE
13	Butler & Gorham	-39	17	209	0	31	14	139	1	61	0	0	0	N	_	N	N-0 ARS N-1 HRS	R
14	Fordem & Sherman	-39	14	132	0	48	7	89	7	72	1	1	0.36	"	_	N	N-1 HRS	ACE
15	Knickerbocker & Monroe	-39	12	197	o	31	12	131	0	61	0	0	0	N	_	N	N-0 HRS	ADE
16	Elderberry & Junction	-39	14	217	0	31	12	145	0	61	0	0	0	N	_	N	N-0 HRS	F
17	Mineral Point & Yellowstone	-39	16	359	0	30	14	240	0	61	2	4	0.51	N	N-1.59	N	N-0 HRS	ABEF
18	Gammon, Longmeadow & Stonefield	-40	14	139	0	34	8	93	3	67	0	0	0	N	_ ]	N	N-2 HRS	DE
19	Haywood & Park	-40	18	423	o	30	18	282	0	60	0	0	0	N ]	N-0.70	N	N-0 HRS	ADE
20	Appleton & Fish Hatchery	-40	16	281	0	30	15	187	1	60	0	1	0.1	N	_	N	N-0 HRS	AEF
21	Norman & University (MS)	-42	16	325	0	29	16	216	1	58	0	0	0 .	N	-	N	N-1 HRS	ACE
22	Carver & Fish Hatchery (D)	-42	17	504	0	29	16	336	1	58	0	0	0	N	N-0.47	N	N-0 HRS	D
23	Milwaukee & Waubesa	-44	11	128	0	38	3	84	3	72	0	0	0	N	-	N	N-0 HRS	
24	Old Middleton & Rosa	-44	11	110	2	56	5	73	6+	42	1	0	0.2	N	-	N	N-2 HRS	
25	Ray-O-Vac & Schroeder	-44	9	96	0	46	0	64	5	92	1	0	0.23	N	-	N	N-0 HRS	
26	Northport & School	-45	16	248	0	28	15	165	0	55	0	1	0.1	N	-	N	N-0 HRS	BE
27	Cottage Grove (BB) & Thompson	-47	12	133	0	37	4	83	4	70	0	1	0.19	N	-	N	N-0 HRS	
28	Johnson, Randall & Engineering Drive	-47	13	146	0	53	5	97	5+	42	0	0	0	-	-	N	N-0 HRS	ABCDEF
29	Milwaukee & Oak	-48	9	119	0	37	2	79	4	73	0	0	0	N	N-0.94	N	N-0 HRS	F
30	Odana & Medical Circle	-48	14	220	0	26	11	147	0	52	0	0	0	N	-	N	N-0 HRS	D
31	Hammersley & Whitney Way	-50	14	144	1	42	6	96	4+	54	2	0	0.34	N	-	Υ	N-1 HRS	
32	Colony & Gammon	-50	15	155	0	26	12	136	1	50	0	0	0	N	-	N	N-0 HRS	Ę
33	Gammon & Tree	-51	14	215	0	30	11	148	1	49	0	1	0.13	N	-	N	N-0 HRS	ΕF
34	Monona (BB), Panther & Tompkins	-52	16	259	0	24	14	173	0	48	1	0	0.12	N	-	N	N-0 HRS	ABEF
35	DickInson & East Washington	-52	19	777	0	24	18	518	0	58	0	0	0	N		N	N-0 HRS	AE
36	Sherman & Trailsway	-53	13	142	0	25	8	105	0	47	0	0	0	N	-	N	N-0 HRS	
37	Bassett & Dayton	-54	2	84	0	44	0	58	6+	88	0	0	0	N	-	N	N-1 HRS	E
38	Commercial & Nakoosa	-54	0	46	7+	114	0	33	8+	178	0	0	0	N	-	N	N-0 HRS	
39	Hughes & Park	-55	17	303	0	23	16	202	0	45	0	1	0.08	N	-	N	N-0 HRS	ACDEF
40	Heartland & Old Sauk	-55	4	67	4+	68	1	45	6+	300	0	2	0.5	N		N	N-2 HRS	
41	Gilman & Wisconsin	-57	0	65	2	54	0	43	8+	108	0	1	0.09	N	-	N		E
42	Milwaukee & Wittwer	-57	16	149	0	27	7	103	3	43	0	0	0	N	-	N	N-1 HRS	
43	Packers & Sixth	-61	17	213	0	21	13	131	0	39	1	0	0.12	N	-	N		E
44	Odana Lane & Odana Rd	-61	14	149	0	20	11	99	0	40	0	0	0	N	-	N	N-0 HRS	
45	Prairie & Raymond	-61	14	177	0	24	6	86	2	53	2	1	0.45	N		N	N-1 HRS	F
46 47	Blount & Williamson Plaza & Watts	-62	16	232	0	19	13	154	2	38	0	0	0	N	-	N	1	AEF
	1	-64	4	98 121	0	38 28	0 5	65	2	60	1	0	0.3	N	-	N	N-0 HRS	
	IMain & Woheter																	
48 49	Main & Webster Carroll & Doty	-65 -66	11 11	144	0	34	ნ 5	80 96	0 1	55 37	0	0	0	N	-	Y	ł	EF E

		]	l				1				i	CRASHES	<u> </u>	1	1	1	1	ı
		Overail		WARR	ANT 1-A	i.		WARR	ANT 1-B		# With	#						1
		%	Major	Street	Minor	r Street	Maio	r Street	i	Street	Property	With			Dools	, n		İ
	·	Below	#	%	#	%	#	%	#	%	Damage	Personal	Crash	Pedestrian	Peak Hour	Peak Hour	4 Mann	
	Location	Warrant	Hrs.	Met	Hrs.	Met	Hrs.	Met	Hrs.	Met	Only	injuries	Rate	Warrant	Warrant A	!	4 Hour	0
51	Big Sky, Mineral Point & Tree	-68	16	400	0	16	16	267	0	32	0	0	0	N	Wallall A	Warrant B	Warrant	Comments
52	Gorham & Henry	-69	16	229	0	16	15	153	0	31	0	1	0.08		-	N ·	N-0 HRS	ACEF
53	Mineral Point & Owens	-70	15	181	0	15	11	121	0	30	0		0.00	N	-	N 	N-0 HRS	E
54	Gilbert & Whitney	-73	16	192	0	13	12	128	0	27	0	0	-	N	-	· N	N-0 HRS	ABE
55	Aberg & Huxley	-74	11	133	0	23	2	78	0		1		0	N	-	N	N-0 HRS	ADEF
56	Few & Williamson	-75	15	171	0	18	10	114	0	48 25	0		0.21	N	<u> </u>	N	N-0 HRS	F
57	Packers & Schlimgen	-75	19	412		13	18	274	0		1	0	0 .	N	-	N	N-0 HRS	AE
58	Johnson & Sixth	-75	9	92	0	31	2		1+	25	0	0	0	N	-	N	N-0 HRS	CEF
59	MLK Jr. & Wilson	-76	4	69	0	39	0	62		63	0	0	0	N	-	N	N-0 HRS	
60	American Pkwy & American Family Dr	-78	5	153	0			46	4	78	0	0	0	. N	-	N	N-0 HRS	
	Kelab & Segoe	-79	8	99	0	14	3	60	2	62	0	1 1	0.17	N		N	N-0 HRS	<u> </u>
i	Blue Ridge & Old Sauk	-79 -80	9	161	0	22	0	66	0	44	0	0	0	N	-	N	N-0 HRS	EF
	Cottage Grove (BB) & Mc Lean	-80	6			20	2	70	0	42	0	0	0	N	-	N	N-0 HRS	
1	Cottage Grove & Ellen	-81	6	89 83	0	31	1	59	2	61	0	0	0	N	-	N	N-0 HRS	
	Blackhawk, Erdman & University (MS)	-82	=		0	29	2	70	6	49	0	0	. 0	N	-	N	N-0 HRS	
	Carroll & Dayton	-82	19 9	671	0	9	17	447	0	18	0	0	0	N	-	N	N-0 HRS	ADEF
1 1	East Pass, Maple Grove & Westin	l f	-	110	0	18	1	74	oʻ	27	.0	0	0 (	N	-	N	N-0 HRS	EF
	Scott & Packers (CV)	-83	0	47	0	43	0	31	4	86	0	0	0	N	- [	N	N-0 HRS	
-	Hammersley & McKenna	-84	13	130	0	15	4	87	0	29	0	0	0	N	- ]	N	N-0 HRS	
1 1	Milwaukee & Swanton	-85	11	153	0	7	8	102	0	15	0	0	0	N	N-1.00	N	N-0 HRS	F
	Roth & Sherman	-85	10	108	0	15	2	72	0	31	0 .	1	0.14	N	N-2.5	N	N-0 HRS	AEF
1 1	Cottage Grove & McClellan (BB)	-86	14	121	0	7	11	107	0	14	0	0	0	N	-	N	N-0 HRS	F
1	Corporate Dr & Blettner	-90	8	135	0	10	1	64	. 0	31	0	0	0	N	-	, N	N-0 HRS	
	Buckeye (AB) & Thompson	-95	3	68	0	30	0	45	3	60	0	0	0	N	-	N	N-0 HRS	
i i	Mineral Point (S) & South Point	-95	3	53	0	30	0	30	6	75	1	0	0.34	N	- 1	į	N-0 HRS	
1 1	Mayfield & Sherman	-98		99	0	3	3	, 66	0	6	0	0	0	N	-	N	N-0 HRS	
<del>                                     </del>	ALL-WAY STOP INTERSECTIONS STUDIED	-132	1	64	0	4	0	40	0	13.	. 0	0	0	N		N	N-0 HRS	!
	Highland, Regent & Speedway	07		1		. 1		<del>- 1</del>	<u> </u>						·			
1 1	Raymond & Whitney	27	13	141	11	127	5	94	16	254	1	0	0.14	N	-	Υ	Y-9 HRS	BC '
	-	17	10	117	11	127	4	80	8+	234	0	1	0.21	N	Y-10.85	Y	Y-7 HRS	F
1 1	Beltline Frontage and Todd Drive (south of Beltline) Old Middleton & Old Sauk	4	8	104	10	113	2	69	16	225	0	0	0	N	_ [	N i	N-3 HRS	1
1		-17	11	119	4	83	3	79	8+	165	0	0	0	· N	-	Y	Y-1 HRS	BF
	Beltline Frontage and Todd Drive (north of Beltline) Swanton & Thompson	-18	3	82	8+	245	0	55	8+	491	0	0	0	14		_ Y	N-3 HRS	
I I	High Point & Midtown	-22	2	78	8+	153	0	52	8+	307	a	0	0	N	-	Y		С
1 1		-34	6	69	6+	97	1	52	+8	216	0	0	0	И	-	Y	N-3 HRS	
	American Pkwy, Hoepker & Rattman	-45	2	74	. 6+	81	0	44	8+	180	0	0	0	N	-	Υ	N-3 HRS	
1 1	Milwaukee-Sprecher	-45	4	94	2	56	0	55	8÷	143	0	0	0	N	-	N	N-0 HRS	
<u> </u>	Buckeye (AB) & Vondron	-50	5	70	3	70	0	50	7+	124	0	1	0.23	N	_	N	N-0 HRS	
	TWO-WAY STOP INTERSECTIONS STUDIED AND MEETING THE MINIMUM NUMERAL REQUIREMENTS OF EITHER WARRANT 1-B.																	
	Sam's Club Driveway & Watts Road	32	12	267	9+	117	10	132	10	300	3	1	0.50	N		Υ	Y-9 HRS	BCDF
l I	Carroll & Gorham	17	17	239	0	59	15	159	11	117	0	2	0.32	N	-	Υ	1	EF .
1 1	McKee (PD) & Muir Field	16	15	172	4-8	78	13	116	8+	119	0	0	0	N	-	Y	Y-5 HRS	
4 /	Anderson & Hoffman  A: Eight-Hour Vehicular Volume: Condition A-Minimum Vehi	11	13	96	9+	149	11	111	13	176	4	0	0.48	N		Y		\EF

Warrant 1-A: Eight-Hour Vehicular Volume: Condition A-Minimum Vehicular Volume

Warrant 1-B: Eight0Hour Vehicular Volume; Condition B-Interruption of Continuous Traffic

Y=Yes N=No

Accident Rate: Number of accidents "preventable" with traffic signals per million entering vehicles.

Peak Hour Warrant A: Total vehicle hours of delay is listed for intersections where delay data was collected.

4-Hour Warrant: Number of hours shown are those that exceed the volume thresholds.

The intersections that do not meet the minimum numerical Warrant are listed in order of "closeness" to meeting either Warrant 1-A or Warrant 1-B.

Both the Major and Minor street volumes must meet 100% of the minimum Warrant in order to be classified as "meeting the minimum numerical Warrant."

Key to Comments:

Last Updated 12/8/2005

A = Signal coordination problems

B = Geometric problems

C = Intersection reconstruction needs to be considered.

D = Part of cost could be assessed to benefitting property owners.

E = Coordination with adjacent signals is necessary.

F = "Side Street" volumes adjusted for high right-turn percentage.

<sup>\*</sup> Projected 4-Way volumes with Watts Road extention expected in 2003 used for High Point-Watts