



TYPICAL FINISHED SECTION  
 DILORETO AVENUE  
 STATION 15+50 to STATION 19+00  
 NOT TO SCALE

- ① POINT REFERRED TO ON PROFILE
- ② BITUMINOUS UPPER LAYER
- ③ BITUMINOUS LOWER LAYER
- ④ 4" GRADATION 2 CRUSHED STONE
- ⑤ 6" GRADATION 1 CRUSHED STONE
- ⑥ TYPE 'A' CONCRETE CURB & GUTTER
- ⑦ FILL, INCIDENTAL
- ⑧ 4' TOPSOIL, SEED & MAT
- ⑨ 5' CONCRETE SIDEWALK
- ⑩ MIN. 2' SELECT FILL

SEE CROSS SECTION SHEETS FOR  
 CROSS SLOPES AND TOP OF  
 CURB ELEVATIONS.

\*CITY OF MADISON MINIMUM PAVEMENT DESIGN  
 1) ALL PAVEMENT ON DILORETO AVE SHALL BE TYPE 'B' PER STANDARD SPECIFICATIONS  
 2) ALL PAVEMENT ON PORTAGE RD SHALL BE TYPE 'C' PER STANDARD SPECIFICATIONS

TYPE	CRUSHED AGG, BASE COURSE		ASPHALTIC CONCRETE PAVEMENT			
	LOWER LAYER GRADATION 1	UPPER LAYER GRADATION 2	LOWER LAYER		UPPER LAYER	
			TYPE	THICKNESS	TYPE	THICKNESS
A	6"	4"	E-0,3	1,75"	E-0,3	1,75"
B	6"	4"	E-1	2,50"	E-1	1,75"
C	6"	4"	E-3	3,50"	E-3	1,75"