



CALL DIGGER'S HOTLINE  
1-800-242-8511  
TOLL FREE  
TELEFAX: 1-800-338-3860  
TDC (FOR HEARING IMPAIRED):  
1-800-542-2289  
WS. STATUTE 182.0175 (1979)  
REQUIRES MINIMUM OF 3 WORKING DAYS  
NOTICE BEFORE YOU EXCAVATE.



GRAPHIC SCALE FEET  
0 5 10 20

EXISTING CONDITIONS LEGEND

- EXISTING POST
- EXISTING SIGN (TYPE NOTED)
- EXISTING CURB INLET
- EXISTING SANITARY MANHOLE
- EXISTING FIRE HYDRANT
- EXISTING WATER MAIN VALVE
- EXISTING CURB STOP
- EXISTING DOWN GUY
- EXISTING ELECTRIC MANHOLE
- EXISTING TRANSFORMER
- EXISTING UTILITY POLE
- EXISTING TELEPHONE PEDESTAL
- EXISTING DECIDUOUS TREE
- EXISTING UNDERGROUND TELEPHONE
- EXISTING CHAIN LINK FENCE
- EXISTING GENERAL FENCE
- EXISTING WOOD FENCE
- EXISTING GAS LINE
- EXISTING UNDERGROUND ELECTRIC LINE
- EXISTING OVERHEAD GENERAL UTILITIES
- EXISTING SANITARY SEWER LINE (SIZE NOTED)
- EXISTING STORM SEWER LINE (SIZE NOTED)
- EXISTING WATER MAIN (SIZE NOTED)
- EXISTING ASPHALT PAVEMENT
- EXISTING CONCRETE

PROPOSED UTILITY LEGEND

- STORM SEWER PIPE
- SANITARY SEWER PIPE (GRAVITY)
- WATER MAIN
- WATER VALVE
- GAS MAIN
- ELECTRIC SERVICE
- TELEPHONE SERVICE

- PROPOSED ASPHALT PAVEMENT
- PROPOSED CONCRETE

UTILITY NOTES:

1. PRIVATE WATER MAIN AND SERVICES SHALL BE DUCTILE IRON (AWWA C-151, CLASS 52) OR APPROVED EQUAL MATERIAL THAT CONFORMS TO COMM 84.30(4)(d).
2. PRIVATE SANITARY SEWER AND LATERALS SHALL BE POLYVINYL CHLORIDE (PVC) ASTM D3034 - SDR 35 OR APPROVED EQUAL MATERIAL THAT CONFORMS TO COMM 84.30(2)(c).
3. A MEANS TO LOCATE BURIED UNDERGROUND EXTERIOR NON METALLIC SEWERS/MAINS AND WATER SERVICES/MAINS MUST BE PROVIDED WITH TRACER WIRE OR OTHER METHODS IN ORDER TO BE LOCATED PER COMM 82.10(11)(h) AND COMM 82.40(8)(k).
4. EXTERIOR WATER SUPPLY PIPING SETBACKS AND CROSSINGS SHALL BE IN ACCORDANCE WITH COMM 82.40(8)(b.).
5. NO PERSON MAY ENGAGE IN WORK AT PLUMBING IN THE STATE UNLESS LICENSED TO DO SO BY THE DEPARTMENT OF COMMERCE PER S.145.06.
6. SITE CONTRACTOR SHALL LEAVE SANITARY AND WATER LATERALS FIVE (5) FEET SHORT (HORIZONTALLY) FROM THE BUILDING. BUILDING PLUMBER SHALL VERIFY SIZE AND EXACT LOCATION OF PROPOSED SANITARY AND WATER LATERALS.
7. CONTRACTOR SHALL FIELD VERIFY THE SIZE, TYPE, LOCATION, AND ELEVATION OF EXISTING UTILITIES PRIOR TO INSTALLING ANY ON-SITE UTILITIES OR STRUCTURES. CONTACT ENGINEER PRIOR TO INSTALLATION IF DISCREPANCY EXISTS WITHIN THESE PLANS.
8. PROPOSED UTILITY SERVICE LINES AS SHOWN ARE APPROXIMATE. COORDINATE THE EXACT LOCATIONS WITH THE PLUMBING DRAWINGS. COORDINATE THE LOCATIONS WITH THE PLUMBING CONTRACTOR AND/OR OWNER'S CONSTRUCTION REPRESENTATIVE PRIOR TO INSTALLATION OF ANY NEW UTILITIES.
9. CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE RELOCATION OF ANY UTILITIES ENCOUNTERED AND REPLACEMENT OF ANY UTILITIES DAMAGED WITHIN INFLUENCE ZONE OF NEW CONSTRUCTION. CONTACT ENGINEER IF THE EXISTING UTILITIES VARY APPRECIABLY FROM THE PLANS.
10. ALL WATER MAIN AND SERVICES SHALL BE INSTALLED AT A MINIMUM DEPTH OF 6.5' FROM TOP OF FINISHED GROUND ELEVATION TO TOP OF MAIN.
11. CLEAN OUT ALL EXISTING AND PROPOSED STORM INLETS AND CATCH BASINS AT THE COMPLETION OF CONSTRUCTION.
12. EXISTING WATER AND SANITARY LATERALS MUST BE PROPERLY ABANDONED PER CITY REQUIREMENTS.
13. CONTRACTOR SHALL OBTAIN ANY NECESSARY WORK IN RIGHT-OF-WAY, EXCAVATION, UTILITY CONNECTION, PLUGGING, ABANDONMENT, AND DRIVEWAY CONNECTION PERMITS PRIOR TO CONSTRUCTION.
14. THE DEVELOPER SHALL INSTALL THE 3M™ ELECTRONIC MARKER SYSTEM (EMS) 4" EXTENDED RANGE 5" BALL MARKERS-WASTEWATER (MODEL #1404-XR) FOR EACH SANITARY AND STORM SEWER LATERALS. THE CITY SHALL SUPPLY ALL THE REQUIRED MARKERS TO THE DEVELOPER OR ITS CONTRACTOR (GENERALLY REQUIRES 2 PER LATERAL) AND THE CONTRACTOR SHALL INSTALL THEM PER THE MANUFACTURER'S REQUIREMENTS OR AS DIRECTED BY THE CITY ENGINEER.

PROPOSED STORM PIPE TABLE

| PIPE NAME | PIPE TYPE | SIZE (IN) | FROM     | TO  | LENGTH (FT) | START INV | END INV | SLOPE |
|-----------|-----------|-----------|----------|-----|-------------|-----------|---------|-------|
| P-1       | RCP       | 10        | EX CI #2 | S-1 | 61          | 858.13    | 858.74  | 1.00% |
| P-2       | RCP       | 10        | S-1      | S-2 | 7           | 858.74    | 858.81  | 1.00% |
| P-3       | RCP       | 10        | S-1      | S-3 | 18          | 858.74    | 858.92  | 1.00% |
| P-4       | PVC       | 10        | EX CI #2 | S-1 | 30          | 858.13    | 858.43  | 1.00% |

PROPOSED STORM STRUCTURE TABLE

| STRUCTURE NAME | STRUCTURE TYPE | FRAME | COVER        | RIM/TC | INVERT |
|----------------|----------------|-------|--------------|--------|--------|
| EX CI #2       | CURB INLET     | -     | -            | 860.88 | 857.98 |
| S-1            | 48" CONC STMH  | R1550 | TYPE B LID   | 862.25 | 858.74 |
| S-2            | 60" CONC CB    | R2578 | TYPE C GRATE | 862.15 | 855.81 |
| S-3            | 60" CONC CB    | R2578 | TYPE C GRATE | 862.15 | 855.92 |

UTILITY PLAN  
2620 MONROE STREET  
CITY OF MADISON  
DANE COUNTY, WISCONSIN

REVISIONS

| NO. | DATE | REMARKS |
|-----|------|---------|
|     |      |         |
|     |      |         |
|     |      |         |