NEIGHBORHOOD HOUSE

29 S. MILLS STREET MADISON, WI 53715

	SHEET INDEX - LUA		
ARCHITI	ECTURAL		
Tl	TITLE SHEET		
A1.0	PARKING LEVEL FLOOR PLAN		
A1.1	FIRST FLOOR PLAN		
A1.2	SECOND FLOOR PLAN		
A1.3	THIRD FLOOR PLAN		
A1.4	FOURTH FLOOR PLAN		
A1.5	FIFTH FLOOR PLAN		
A1.6	SIXTH FLOOR PLAN		
A1.7	OVERALL ROOF PLAN		
	'		
A2.1	BUILDING ELEVATIONS		
A2.2	BUILDING ELEVATIONS		
CIVIL	T		
-	ALTA/NSPS LAND TITLE SURVEY		
C 1.1	NOTES & LEGEND		
C2.0	DEMOLITION PLAN		
C3.0	OVERALL SITE PLAN		
C3 .1	DETAILED SITE PLAN		
C4.0	DETAILED SITE PLAN GRADING PLAN		
C4.0 C5.0	GRADING PLAN		
C4.0 C5.0 C6.0	GRADING PLAN UTILITY PLAN		
C4.0	GRADING PLAN UTILITY PLAN DETAILS		



LOCATION MAP

APPROVALS	NAME	DATE
DESIGN		
<u>CONSTRUCTION</u>		
DEVELOPMENT		
MANAGEMENT		
OWNER		

A Compan
2450 Rimrock Road

Suite 100

Madison, WI 53713

Telephone: 608-258-5580

Fax: 608-258-5599

www.alexandercompany.com

LAND USE

APPLICATION

NOT FOR CONSTRUCTION


10-12-23 LAND USE APPLICATION
11-28-23 LAND USE APPLICATION - REV 1

DRAWN: Author APPR: Checker

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

TITLE SHEET




- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. FOR COMPLETE UNIT LAYOUT AND DIMENSIONING SEE ENLARGED UNIT PLANS.
- 3. FOR INTIERIOR FINISHES SEE FINISH SCHEDULE AND FINISH LEGEND ON SHEET A8.1
- 4. FOR DOOR TYPE DESCRIPTIONS SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._

GENERAL WALL KEY:

NEW INTERIOR WALL

NEW MASONRY WALL



WALL TAG INDICATES WALL TYPE, REFERENCE SHEET A0.1 FOR WALL TYPE CONSTRUCTION

UNIT INTERIOR WALL TYPES ARE INDICATED ON ENLARGED UNIT PLANS

FOR WALL TYPE DESCRIPTIONS SEE PARTITION SCHEDULE ON SHEET A0.1, WALL TYPES INDICATED ON THIS SHEET TO BE FRAMED PRIOR TO UNIT PARTITIONS. FOR WALL TYPES WITHIN UNITS, REFER TO ENLARGED UNIT PLAN SHEETS

DIMENSION NOTES:

- 1. ALL WALLS ARE DIMENSIONED TO FACE OF FINISH UNLESS NOTED OTHERWISE.
- 2. NOTIFY ARCHITECT IF +/- DIMENSION VARIES BY 6" OR MORE.
- 3. DIMENSIONS IN KITCHENS AND BATHROOMS MUST BE WITHIN 1/2".

FLOOR PLAN KEYNOTES

PARKING SUMMARY		
SIZE	TYPE	QTY
9' x 18'	STANDARD	(1)
9' x 18'	HC	

BICYCLE I	PARKING SUM	MARY
SIZE	TYPE	QTY
2' x 8'	BICYCLE	70

LAND USE **APPLICATION** NOT FOR CONSTRUCTION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100


10-12-23 LAND USE APPLICATION 11-28-23 LAND USE APPLICATION - REV 1

DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

PARKING LEVEL FLOOR PLAN



- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. FOR COMPLETE UNIT LAYOUT AND DIMENSIONING SEE ENLARGED UNIT PLANS.
- 3. FOR INTIERIOR FINISHES SEE FINISH SCHEDULE AND FINISH LEGEND ON SHEET A8.1
- 4. FOR DOOR TYPE DESCRIPTIONS SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._

GENERAL WALL KEY:

NEW INTERIOR WALL

NEW MASONRY WALL



WALL TAG INDICATES WALL TYPE, REFERENCE SHEET A0.1 FOR WALL TYPE CONSTRUCTION

UNIT INTERIOR WALL TYPES ARE INDICATED ON ENLARGED UNIT PLANS

FOR WALL TYPE DESCRIPTIONS SEE PARTITION SCHEDULE ON SHEET A0.1, WALL TYPES INDICATED ON THIS SHEET TO BE FRAMED PRIOR TO UNIT PARTITIONS. FOR WALL TYPES WITHIN UNITS, REFER TO ENLARGED UNIT PLAN SHEETS

DIMENSION NOTES:

- 1. ALL WALLS ARE DIMENSIONED TO FACE OF FINISH UNLESS NOTED OTHERWISE.
- 2. NOTIFY ARCHITECT IF +/- DIMENSION VARIES BY 6" OR MORE.
- 3. DIMENSIONS IN KITCHENS AND BATHROOMS MUST BE WITHIN 1/2".

FLOOR PLAN KEYNOTES

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100

LAND USE **APPLICATION** NOT FOR CONSTRUCTION


10-12-23 LAND USE APPLICATION 11-28-23 LAND USE APPLICATION - REV 1

DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

FIRST FLOOR PLAN




- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. FOR COMPLETE UNIT LAYOUT AND DIMENSIONING SEE ENLARGED UNIT PLANS.
- 3. FOR INTIERIOR FINISHES SEE FINISH SCHEDULE AND FINISH LEGEND ON SHEET A8.1
- 4. FOR DOOR TYPE DESCRIPTIONS SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._

GENERAL WALL KEY:

NEW INTERIOR WALL

NEW MASONRY WALL



WALL TAG INDICATES WALL TYPE, REFERENCE SHEET A0.1 FOR WALL TYPE CONSTRUCTION

UNIT INTERIOR WALL TYPES ARE INDICATED ON ENLARGED UNIT PLANS

FOR WALL TYPE DESCRIPTIONS SEE PARTITION SCHEDULE ON SHEET A0.1, WALL TYPES INDICATED ON THIS SHEET TO BE FRAMED PRIOR TO UNIT PARTITIONS. FOR WALL TYPES WITHIN UNITS, REFER TO ENLARGED UNIT PLAN SHEETS

DIMENSION NOTES:

- 1. ALL WALLS ARE DIMENSIONED TO FACE OF FINISH UNLESS NOTED OTHERWISE.
- 2. NOTIFY ARCHITECT IF +/- DIMENSION VARIES BY 6" OR MORE.
- 3. DIMENSIONS IN KITCHENS AND BATHROOMS MUST BE WITHIN 1/2".

FLOOR PLAN KEYNOTES

LAND USE **APPLICATION** NOT FOR CONSTRUCTION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100


10-12-23 LAND USE APPLICATION 11-28-23 LAND USE APPLICATION - REV 1

DRAWN: Author APPR: Checker

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

SECOND FLOOR PLAN




- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. FOR COMPLETE UNIT LAYOUT AND DIMENSIONING SEE ENLARGED UNIT PLANS.
- 3. FOR INTIERIOR FINISHES SEE FINISH SCHEDULE AND FINISH LEGEND ON SHEET A8.1
- 4. FOR DOOR TYPE DESCRIPTIONS SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._

GENERAL WALL KEY:

NEW INTERIOR WALL

NEW MASONRY WALL



WALL TAG INDICATES WALL TYPE, REFERENCE SHEET A0.1 FOR WALL TYPE CONSTRUCTION

UNIT INTERIOR WALL TYPES ARE INDICATED ON ENLARGED UNIT PLANS

FOR WALL TYPE DESCRIPTIONS SEE PARTITION SCHEDULE ON SHEET A0.1, WALL TYPES INDICATED ON THIS SHEET TO BE FRAMED PRIOR TO UNIT PARTITIONS. FOR WALL TYPES WITHIN UNITS, REFER TO ENLARGED UNIT PLAN SHEETS

DIMENSION NOTES:

- 1. ALL WALLS ARE DIMENSIONED TO FACE OF FINISH UNLESS NOTED OTHERWISE.
- 2. NOTIFY ARCHITECT IF +/- DIMENSION VARIES BY 6" OR MORE.
- 3. DIMENSIONS IN KITCHENS AND BATHROOMS MUST BE WITHIN 1/2".

FLOOR PLAN KEYNOTES

LAND USE **APPLICATION** NOT FOR CONSTRUCTION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100

10-12-23 LAND USE APPLICATION


11-28-23 LAND USE APPLICATION - REV 1

DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

THIRD FLOOR PLAN




- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. FOR COMPLETE UNIT LAYOUT AND DIMENSIONING SEE ENLARGED UNIT PLANS.
- 3. FOR INTIERIOR FINISHES SEE FINISH SCHEDULE AND FINISH LEGEND ON SHEET A8.1
- 4. FOR DOOR TYPE DESCRIPTIONS SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._

GENERAL WALL KEY:

NEW INTERIOR WALL

NEW MASONRY WALL



WALL TAG INDICATES WALL TYPE, REFERENCE SHEET A0.1 FOR WALL TYPE CONSTRUCTION

UNIT INTERIOR WALL TYPES ARE INDICATED ON ENLARGED UNIT PLANS

FOR WALL TYPE DESCRIPTIONS SEE PARTITION SCHEDULE ON SHEET A0.1, WALL TYPES INDICATED ON THIS SHEET TO BE FRAMED PRIOR TO UNIT PARTITIONS. FOR WALL TYPES WITHIN UNITS, REFER TO ENLARGED UNIT PLAN SHEETS

DIMENSION NOTES:

- 1. ALL WALLS ARE DIMENSIONED TO FACE OF FINISH UNLESS NOTED OTHERWISE.
- 2. NOTIFY ARCHITECT IF +/- DIMENSION VARIES BY 6" OR MORE.
- 3. DIMENSIONS IN KITCHENS AND BATHROOMS MUST BE WITHIN 1/2".

FLOOR PLAN KEYNOTES

LAND USE **APPLICATION** NOT FOR CONSTRUCTION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100

10-12-23 LAND USE APPLICATION

11-28-23 LAND USE APPLICATION - REV 1

DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

FOURTH FLOOR PLAN




- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. FOR COMPLETE UNIT LAYOUT AND DIMENSIONING SEE ENLARGED UNIT PLANS.
- 3. FOR INTIERIOR FINISHES SEE FINISH SCHEDULE AND FINISH LEGEND ON SHEET A8.1
- 4. FOR DOOR TYPE DESCRIPTIONS SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._

GENERAL WALL KEY:

NEW INTERIOR WALL

NEW MASONRY WALL



WALL TAG INDICATES WALL TYPE, REFERENCE SHEET A0.1 FOR WALL TYPE CONSTRUCTION

UNIT INTERIOR WALL TYPES ARE INDICATED ON ENLARGED UNIT PLANS

FOR WALL TYPE DESCRIPTIONS SEE PARTITION SCHEDULE ON SHEET A0.1, WALL TYPES INDICATED ON THIS SHEET TO BE FRAMED PRIOR TO UNIT PARTITIONS. FOR WALL TYPES WITHIN UNITS, REFER TO ENLARGED UNIT PLAN SHEETS

DIMENSION NOTES:

- 1. ALL WALLS ARE DIMENSIONED TO FACE OF FINISH UNLESS NOTED OTHERWISE.
- 2. NOTIFY ARCHITECT IF +/- DIMENSION VARIES BY 6" OR MORE.
- 3. DIMENSIONS IN KITCHENS AND BATHROOMS MUST BE WITHIN 1/2".

FLOOR PLAN KEYNOTES

LAND USE **APPLICATION** NOT FOR CONSTRUCTION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100

10-12-23 LAND USE APPLICATION


11-28-23 LAND USE APPLICATION - REV 1

DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

FIFTH FLOOR PLAN





- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. FOR COMPLETE UNIT LAYOUT AND DIMENSIONING SEE ENLARGED UNIT PLANS.
- 3. FOR INTIERIOR FINISHES SEE FINISH SCHEDULE AND FINISH LEGEND ON SHEET A8.1
- 4. FOR DOOR TYPE DESCRIPTIONS SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._

GENERAL WALL KEY:

NEW INTERIOR WALL

NEW MASONRY WALL





WALL TAG INDICATES WALL TYPE, REFERENCE SHEET A0.1 FOR WALL TYPE CONSTRUCTION

UNIT INTERIOR WALL TYPES ARE INDICATED ON ENLARGED UNIT PLANS

FOR WALL TYPE DESCRIPTIONS SEE PARTITION SCHEDULE ON SHEET A0.1, WALL TYPES INDICATED ON THIS SHEET TO BE FRAMED PRIOR TO UNIT PARTITIONS. FOR WALL TYPES WITHIN UNITS, REFER TO ENLARGED UNIT PLAN SHEETS

DIMENSION NOTES:

- ALL WALLS ARE DIMENSIONED TO FACE OF FINISH UNLESS NOTED OTHERWISE.
- 2. NOTIFY ARCHITECT IF +/- DIMENSION VARIES BY 6" OR MORE.
- 3. DIMENSIONS IN KITCHENS AND BATHROOMS MUST BE WITHIN 1/2".

FLOOR PLAN KEYNOTES

LAND USE APPLICATION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100

NOT FOR CONSTRUCTION

10-12-23 LAND USE APPLICATION

11-28-23 LAND USE APPLICATION - REV 1


DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

SIXTH FLOOR PLAN

A1.6



GENERAL ROOF PLAN NOTES:

- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. REFER TO DEMOLITION PLANS FOR EXISTING CONDITIONS AND ADDITIONAL INFORMATION.

ROOF PLAN KEYNOTES

A COXENCE COMPANY

2450 Rimrock Road
Suite 100
Madison, WI 53713
Telephone: 608-258-5580
Fax: 608-258-5599
www.alexandercompany.com

LAND USE

APPLICATION

NOT FOR CONSTRUCTION

10-12-23 LAND USE APPLICATION
11-28-23 LAND USE APPLICATION - REV 1

DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

OVERALL ROOF PLAN

A1.7



2 WEST ELEVATION - 18% GLAZING A2.1 SCALE: 3/32" = 1'-0"



1 NORTH ELEVATION - 15% GLAZING

A2.1 SCALE: 3/32" = 1'-0"

11/29/2023 7:55:32 AM C:\TempRevit\29 S Mills_v23_cdq64PWJ.rvt

GENERAL ELEVATION NOTES:

- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. THE CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH THE EXISTING CONDITIONS. NO ALLOWANCE WILL BE MADE FOR THE CONTRACTOR'S FAILURE TO DETERMINE THE FULL EXTENT OF WORK
- TO BE PERFORMED.

 3. FOR EXTERIOR WALL ASSEMBLIES (EX1, EX2, ETC), SEE SHEET ____
- 4. FOR DOOR TYPE DESCTIPTIONS, SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._
- 5. FOR WINDOW TYPE DESCTIPTIONS, SEE WINDOW ELEVATIONS AND SCHEDULES ON SHEETS A10.1 TO A10.

ELEVATION KEYNOTES

LAND USE APPLICATION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100

NOT FOR CONSTRUCTION

10-12-23 LAND USE APPLICATION

11-28-23 LAND USE APPLICATION - REV 1

EXTERIOR MATERIAL KEY:

7/8" CORRUGATED METAL SIDING SLATE GRAY EXPOSED FASTENERS



CEMENT BOARD MOUNTAIN SAGE EXPOSED FASTENERS




T8 METAL PLANKWALL BURNT WOOD CONCEALED FASTENERS



THIN BRICK
GEORGIAN RED IRONSPOT
CONCEALED FASTENERS

<u>BIRD GLASS -</u> <u>PATTERN APPLIED FILM TO INTERIOR:</u>



PROJECT # 23-814

BUILDING ELEVATIONS

DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE

29 S. MILLS STREET

MADISON, WI 53715

A2.1

162' - 9 1/4" 6TH FLOOR 152' - 6 3/4" 5TH FLOOR 142' - 3 3/8" 4TH FLOOR 132' - 0" 3RD FLOOR 121' - 9" 2ND FLOOR 110' - 4" FINAL LOUVER LAYOUT TO BE COORDINATED WITH GAS METERS MECHANICAL DESIGN 1ST FLOOR 100' - 0" PARKING LEVEL

EAST ELEVATION - 17% GLAZING A2.2 | SCALE: 3/32" = 1'-0"

11/29/2023 7:55:58 AM C:\TempRevit\29 S Mills_v23_cdq64PWJ.rvt



GENERAL ELEVATION NOTES:

- 1. FOR SYMBOL AND ABBREVIATION DESCRIPTIONS SEE SHEET G1.1
- 2. THE CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH THE EXISTING CONDITIONS. NO ALLOWANCE WILL BE MADE FOR THE CONTRACTOR'S FAILURE TO DETERMINE THE FULL EXTENT OF WORK
- TO BE PERFORMED. 3. FOR EXTERIOR WALL ASSEMBLIES (EX1, EX2, ETC), SEE SHEET ____
- 4. FOR DOOR TYPE DESCTIPTIONS, SEE DOOR AND HARDWARE SCHEDULES ON SHEETS A9.0 TO A9._
- 5. FOR WINDOW TYPE DESCTIPTIONS, SEE WINDOW ELEVATIONS AND SCHEDULES ON SHEETS A10.1 TO

ELEVATION KEYNOTES

LAND USE **APPLICATION**

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com

Suite 100

NOT FOR CONSTRUCTION

10-12-23 LAND USE APPLICATION

11-28-23 LAND USE APPLICATION - REV 1

EXTERIOR MATERIAL KEY:



7/8" CORRUGATED METAL SIDING SLATE GRAY EXPOSED FASTENERS.



CEMENT BOARD MOUNTAIN SAGE EXPOSED FASTENERS




T8 METAL PLANKWALL **BURNT WOOD** CONCEALED FASTENERS



THIN BRICK GEORGIAN RED IRONSPOT CONCEALED FASTENERS

BIRD GLASS -**PATTERN APPLIED FILM TO INTERIOR:**



BUILDING

PROJECT # 23-814


DRAWN: DZ APPR: CDQ

NEIGHBORHOOD HOUSE

29 S. MILLS STREET

MADISON, WI 53715

ELEVATIONS



SANITARY SEWER STRUCTURES

STRUCT. ID RIM ELEVATION INVERT ELEVATION PIPE SIZE PIPE TYPE

852.56

854.54

SAN-4

845.41

846.04

PVC

ST0-5

ST0-9

STO-10

851.33

851.46

853.03

848.97

843.88

ALTA/NSPS LAND TITLE SURVEY

ALL OF LOT 1, BLOCK 1, TRIANGLE PLAT, PART OF THE SOUTHWEST 1/4 OF SECTION 23, TOWNSHIP 07 NORTH, RANGE 09 EAST MADISON, DANE COUNTY, WISCONSIN.

NOTE TO THE CLIENT, INSURER, AND LENDER - WITH REGARD TO TABLE A, ITEM 11, INFORMATION FROM THE SOURCES CHECKED ABOVE WILL BE COMBINED WITH OBSERVED EVIDENCE

ASSESSMENT OF THE LOCATION OF THE UTILITIES. WHERE ADDITIONAL OR MORE DETAILED INFORMATION IS REQUIRED, THE CLIENT IS ADVISED THAT EXCAVATION MAY BE NECESSARY.

THERE ARE NO PROPOSED CHANGES IN THE STREET RIGHT-OF-WAY LINES. THERE IS NO OBSERVED EVIDENCE OF RECENT STREET OR SIDEWALK CONSTRUCTION OR REPAIRS AT THE

PAGE 21 AS DOCUMENT No. 1220391, BUT DELETING ANY COVENANT, CONDITION OR RESTRICTION INDICATING A PREFERENCE, LIMITATION OR DISCRIMINATION BASED ON RACE, COLOR,

MODIFICATION AND/OR AMENDMENT BY INSTRUMENT: AMENDED URBAN RENEWAL PLAN FOR THE TRIANGLE URBAN RENEWAL AREA, PROJECT No. WIS. R-2; RECORDING INFORMATION:

OF THE CITY OF MADISON, A PUBLIC BODY CORPORATE AND POLITIC OF THE STATE OF WISCONSIN AND MADISON NEIGHBORHOOD CENTERS, A NON-STOCK, NON-PROFIT CORPORATION:

RECORDS, BUT DELETING ANY COVENANT, CONDITION OR RESTRICTION INDICATING A PREFERENCE, LIMITATION OR DISCRIMINATION BASED ON RACE, COLOR, RELIGION, SEX, HANDICAP, FAMILIAL

) AMENDED URBAN RENEWAL PLAN FOR THE TRIANGLE URBAN RENEWAL AREA, PROJECT No. WIS. R-2 RECORDED AUGUST 13, 1963 IN VOLUME 396 OF MISC, ON PAGE 79 AS DOCUMENT No.

OF UTILITIES PURSUANT TO SECTION 5.E.IV. TO DEVELOP A VIEW OF THE UNDERGROUND UTILITIES. HOWEVER, LACKING EXCAVATION, THE EXACT LOCATION OF UNDERGROUND

FEATURES CANNOT BE ACCURATELY, COMPLETELY, AND RELIABLY DEPICTED. IN ADDITION, IN SOME JURISDICTIONS, 811 OR OTHER SIMILAR UTILITY LOCATE REQUESTS FROM SURVEYORS MAY BE IGNORED OR RESULT IN AN INCOMPLETE RESPONSE, IN WHICH CASE THE SURVEYOR SHALL NOTE ON THE PLAT OR MAP HOW THIS AFFECTED THE SURVEYOR'S

<u>LEGEND</u>

CITY OF MADISON

VERIZON WIRELESS

CHARTER COMMUNICATIONS

MIDWEST FIBER NETWORKS

TIME OF THE SURVEY.

• 1" IRON PIPE FOUND CURB INLET — – CENTERLINE 2" • 2" IRON PIPE FOUND DOWNSPOUT 1¼" REBAR FOUND GAS REGULATOR/METER ---- PROPERTY LINE ¾" REBAR FOUND ····· CHORD LINE BENCHMARK ELECTRIC MANHOLE — SETBACK LINE - · - · - EASEMENT LINE FINISHED FLOOR SHOT LOCATION ELECTRIC METER ELECTRIC TRANSFORMER BOLLARD —×——×— FENCE LINE AIR CONDITION UNIT CONCRETE CURB & GUTTER SANITARY MANHOLE LIGHT POLE CLEAN OUT POWER POLE --- EDGE OF GRAVEL TELEPHONE PEDESTAL HYDRANT WATER VALVE DECIDUOUS TREE CURB STOP/SERVICE VALVE HANDICAP PARKING — ST — STORM SEWER ROUND CASTED INLET ——— PARCEL BOUNDARY

SQUARE CASTED INLET

MADISON GAS AND ELECTRIC

AT&T DISTRIBUTION

THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE; THEREFORE IT IS NOT PLOTTED HEREON.

THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.

THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.

THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.

THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON

THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.

THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.

THIS ITEM MAY AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.

THIS ITEM MAY AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.

CERTIFICATE OF COMPLETION OF IMPROVEMENTS RECORDED JUNE 22, 1967 IN VOLUME 465, PAGE 564 AS DOCUMENT No. 1187686.

STATUS OR NATIONAL ORIGIN TO THE EXTENT SUCH COVENANTS, CONDITIONS OR RESTRICTIONS VIOLATE 42 USC 3604(c).

FEBRUARY 2, 1965 IN VOLUME 422 OF MISC, PAGE 101 AS DOCUMENT No. 1123151.

RECORDED: JANUARY 14, 1965 IN VOLUME 421, PAGE 1; INSTRUMENT NO.: 1121965.

RELIGION, SEX, HANDICAP. FAMILIAL STATUS OR NATIONAL ORIGIN TO THE EXTENT SUCH COVENANTS, CONDITIONS OR RESTRICTIONS VIOLATE 42 USC 3604(c).

— - - - — SECTION LINE — E — UNDERGROUND ELECTRIC EDGE OF WOODS OR BRUSH --- - RIGHT-OF-WAY LINE ///////// BUILDING ---855-- INDEX CONTOUR -854 INTERMEDIATE CONTOUR BITUMINOUS PAVEMENT CONCRETE PAVEMENT GRAVEL ----- EDGE OF PAVEMENT

---- EDGE OF BITUMINOUS ----- PAVEMENT STRIPING END OF FLAGGED UTILITIES () DENOTES RECORDED AS MEASUREMENTS DEPICTING THE SAME LINE ON THE GROUND AS RETRACED BY THIS SURVEY

CREATE THE VISION TELL THE STOR

jsdinc.com

MADISON REGIONAL OFFICE 161 HORIZON DRIVE, SUITE 101 VERONA, WISCONSIN 53593


P. 608.848.5060

THE ALEXANDER **COMPANY**

CLIENT ADDRESS: 2450 RIMROCK ROAD, SUITE 100 MADISON, WI 53713

NEIGHBORHOOD HOUSE COMMUNITY CENTER REDEVELOPMENT

PROJECT LOCATION: 31 SOUTH MILLS STREET CITY OF MADISON DANE COUNTY, WI



CMD 06/19/23

ALTA/NSPS LAND TITLE

SURVEY

PROJECT NO:

TODD J

S-2614

DEFOREST,

MODIFICATIONS

IMPROVEMENT OF THE LAND.

SURVEYOR'S CERTIFICATE

Website: www.jsdinc.com

BENCHMARKS

*JSD DOES NOT GUARANTEE THE BENCHMARK ELEVATIONS LISTED ON THIS

MAP ARE ACCURATE AND SHOULD BE VERIFIED PRIOR TO CONSTRUCTION

CORNER OF SITE.

CORNER OF SITE.

DESCRIPTION

1-1/4" REBAR AT SOUTH WEST

3/4" REBAR AT SOUTH EAST

ELEVATION

i) NEIGHBORHOOD HOUSE COMMUNITY CENTER, INC.,

ii) FIRST BUSINESS BANK, iii) CITY OF MADISON, A MUNICIPAL CORPORATION,

iii) FIRST AMERICAN TITLE INSURANCE COMPANY,

THIS IS TO CERTIFY THAT THIS MAP OR PLAT AND THE SURVEY ON WHICH IT IS BASED WERE MADE IN ACCORDANCE WITH THE 2021 MINIMUM STANDARD DETAIL REQUIREMENTS FOR ALTA/NSPS LAND TITLE SURVEYS, JOINTLY ESTABLISHED AND ADOPTED BY ALTA AND NSPS AND INCLUDES ITEMS 1, 2, 3, 4, 5, 6a, 7a, 7b(1), 7c, 8, 9, 10, 11a, 12, 13, 14, 16, 17, 18, 19, 20 OF TABLE A THEREOF. THE FIELD WORK WAS COMPLETED ON JUNE 9-16, 2023.

TODD J. BUHR, S-2614 PROFESSIONAL LAND SURVEYOR Email: todd.buhr@jsdinc.com

GENERAL NOTES

- REFER TO THE EXISTING CONDITIONS SURVEY FOR EXISTING CONDITIONS NOTES AND LEGENDS.
- ALL WORK IN THE ROW AND/OR PUBLIC EASEMENTS SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR SEWER & WATER CONSTRUCTION IN WISCONSIN AND MUNICIPAL REQUIREMENTS.
- EXISTING GRADE SPOT ELEVATIONS SHOWN FOR INFORMATIONAL PURPOSES. DURING CONSTRUCTION MATCH EXISTING GRADES AT CONSTRUCTION LIMITS.
- NO SITE GRADING OUTSIDE OR DOWNSLOPE OF PROPOSED SILT FENCE LOCATION. NO LAND DISTURBANCE BEYOND PROPERTY LINES.
- JSD SHALL BE HELD HARMLESS AND DOES NOT WARRANT ANY DEVIATIONS BY THE OWNER/CONTRACTOR FROM THE APPROVED CONSTRUCTION PLANS THAT MAY RESULT IN DISCIPLINARY 1.4. ACTIONS BY ANY OR ALL REGULATORY AGENCIES.

DEMOLITION NOTES

- THIS PLAN INDICATES ITEMS ON THE PROPERTY INTENDED FOR DEMOLITION BASED ON THE CURRENT SITE DESIGN THAT HAVE BEEN IDENTIFIED BY A REASONABLE OBSERVATION OF THE EXISTING CONDITIONS THROUGH FIELD SURVEY RECONNAISSANCE, "DIGGER'S HOTLINE" LOCATION, AND GENERAL "STANDARD OF CARE". THERE MAY BE ADDITIONAL ITEMS THAT CAN NOT BE IDENTIFIED BY A REASONABLE ABOVE GROUND OBSERVATION, OF WHICH THE ENGINEER WOULD HAVE NO KNOWLEDGE OR MAY BE A PART OF ANOTHER DESIGN DISCIPLINE. IT IS THE CONTRACTOR'S/BIDDER'S RESPONSIBILITY TO REVIEW THE PLANS, INSPECT THE SITE AND PROVIDE THEIR OWN DUE DILIGENCE TO INCLUDE IN THEIR BID WHAT ADDITIONAL ITEMS, IN THEIR OPINION, MAY BE NECESSARY FOR DEMOLITION. ANY ADDITIONAL ITEMS IDENTIFIED BY THE CONTRACTOR/BIDDER SHALL BE IDENTIFIED IN THE BID AND REPORTED TO THE ENGINEER OF RECORD. JŚD TAKES NO RESPONSIBILITY FOR ITEMS ON THE PROPERTY THAT COULD NOT BI LOCATED BY A REASONABLE OBSERVATION OF THE PROPERTY OR OF WHICH THEY WOULD HAVE NO KNOWLEDGE
- CONTRACTOR SHALL KEEP ALL STREETS AND PRIVATE DRIVES FREE AND CLEAR OF ALL CONSTRUCTION RELATED DIRT, DUST AND DEBRIS.
- TREES WITHIN THE CONSTRUCTION LIMITS SHALL BE REMOVED UNLESS SPECIFICALLY CALLED 2.5. OUT FOR PROTECTION. ALL TREES TO BE REMOVED SHALL BE REMOVED IN THEIR ENTIRETY AND STUMPS SHALL BE GROUND TO PROPOSED SUBGRADE.
- ALL LIGHT POLES TO BE REMOVED SHALL BE REMOVED IN THEIR ENTIRETY, INCLUDING BASE AND ALL APPURTENANCES. SALVAGE FOR RELOCATION. COORDINATE RELOCATION AND/OR ABANDONMENT OF ALL ELECTRIC LINES WITH ELECTRICAL ENGINEER AND OWNER PRIOR TO DEMOLITION.
- ABANDONED/REMOVED ITEMS SHALL BE DISPOSED OF OFF SITE UNLESS OTHERWISE NOTED.
- CONTRACTOR TO REPLACE ALL SIDEWALK AND CURB AND GUTTER ABUTTING THE PROPERTIES WHICH IS DAMAGED BY THE CONSTRUCTION. OR ANY SIDEWALK AND CURB AND GUTTER THAT THE CITY ENGINEER DETERMINES NEEDS TO BE REPLACED BECAUSE IT IS NOT AT A DESIRABLE GRADE REGARDLESS OF WHETHER THE CONDITION EXISTED PRIOR TO BEGINNING CONSTRUCTION.
- PRIOR TO CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR: EXAMINE ALL SITE CONDITIONS RELATIVE TO THE CONDITIONS INDICATED ON THE ENGINEERING DRAWINGS. ANY DISCREPANCIES ARE TO BE REPORTED IMMEDIATELY TO THE ENGINEER AND RESOLVED PRIOR TO THE START OF CONSTRUCTION.
- VERIFYING UTILITY ELEVATIONS AND NOTIFYING ENGINEER OF ANY DISCREPANCIES. NO WORK SHALL BE PERFORMED UNTIL THE DISCREPANCIES ARE RESOLVED.
- NOTIFYING ALL UTILITIES PRIOR TO THE REMOVAL OF ANY UNDERGROUND UTILITIES.
- 7.4. NOTIFYING THE DESIGN ENGINEER AND LOCAL CONTROLLING MUNICIPALITY 48 HOURS PRIOR TO 3.6. EXTERIOR CONCRETE SURFACES SHALL BE BROOM FINISHED. THE START OF CONSTRUCTION TO ARRANGE FOR APPROPRIATE CONSTRUCTION INSPECTION.
- ANY SANITARY SEWER, SANITARY SEWER SERVICES, WATER MAIN, WATER SERVICES, STORM SEWER, OR OTHER UTILITIES, WHICH ARE DAMAGED BY THE CONTRACTORS, SHALL BE REPAIRED TO THE 4. PAVEMENT MARKING SPECIFICATIONS OWNER'S SATISFACTION AT THE CONTRACTOR'S EXPENSE.
- CONTRACTOR IS RESPONSIBLE FOR SITE SAFETY DURING THE CONSTRUCTION OF THESE IMPROVEMENTS.
- RELOCATION WITH RESPECTIVE UTILITY COMPANY. COORDINATION REQUIRED PRIOR TO CONSTRUCTION.
- ALL DEMOLITION SHALL BE IN ACCORDANCE WITH THE APPROVED MUNICIPALITY RECYCLING PLAN.
- ANY CONTAMINATED SOILS SHALL BE REMOVED IN ACCORDANCE WITH FEDERAL AND STATE REGULATIONS TO AN APPROVED LANDFILL.
- ALL EXISTING UTILITIES TO BE FIELD LOCATED AND FLAGGED BY CONTRACTOR.
- NOTIFY ENGINEER IMMEDIATELY IF ANY DISCREPANCIES OCCUR IN THE LOCATION SHOWN OR PROPOSED IMPROVEMENTS IMPACTING EXISTING FIBER OPTIC LINE LOCATION.
- SPECIFICATIONS FOR WATER AND SEWER CONSTRUCTION IN WISCONSIN, LATEST ADDITION, AND CITY OF MADISON SPECIFICATIONS.
- WATER ABANDONMENT SHALL BE IN ACCORDANCE WITH SECTION 4.14.0 OF THE STANDARD SPECIFICATIONS FOR WATER AND SEWER CONSTRUCTION IN WISCONSIN, LATEST ADDITION, AND CITY OF MADISON SPECIFICATIONS.
- ALL PERIMETER EROSION CONTROL DEVICES SHALL BE INSTALLED PRIOR TO THE START OF DEMOLITION ACTIVITIES. CONTRACTOR SHALL KEEP ALL STREETS AND PAVEMENT FREE AND CLEAR 4. ANY WORK WITHIN RIGHT-OF-WAY SHALL BE PROPERLY PERMITTED AND COORDINATED WITH THE OF ALL CONSTRUCTION RELATED DIRT, DUST AND DEBRIS.
- BUILDING REMOVALS SHALL BE BY A QUALIFIED CONTRACTOR. CONTRACTOR TO FOLLOW ALL DEMOLITION REGULATIONS, DISCONNECT ALL UTILITIES, OBTAIN ALL APPLICABLE PERMITS AND 5. DISPOSE OF ALL BUILDING MATERIALS IN APPROPRIATE LANDFILLS. DEMOLISHED MATERIALS SHALL NOT BE BURIED ON SITE. IF ENCOUNTERED, ANY CONTAMINATED SOILS SHALL BE REMOVED TO A LANDFILL IN ACCORDANCE WITH APPROPRIATE STATE AND FEDERAL REGULATIONS.
- CONTRACTOR TO REMOVE EXISTING UTILITY PIPE OR PROVIDE PIPE BACK-FILLING AFTER REMOVAL OF EXISTING UTILITIES WITHIN BUILDING FOOTPRINT USING "LOW DENSITY CONCRETE/FLOWABLE FILL". 7.
- RESTORATION OF THE EXISTING ROADWAY RIGHT-OF-WAYS ARE CONSIDERED INCIDENTAL AND SHOULD BE PART OF THE COST OF THE UNDERGROUND IMPROVEMENTS, DEMOLITION AND REMOVAL. 8 THIS INCLUDES CURB & GUTTER, SIDEWALK, TOPSOIL, SEEDING AND MULCHING.

CONSTRUCTION SEQUENCING

- INSTALL PERIMETER SILT FENCE, INLET PROTECTION AND TEMPORARY CONSTRUCTION ENTRANCE. STRIP AND STOCKPILE TOPSOIL, INSTALL SILT FENCE AROUND PERIMETER OF STOCKPILE.
- INSTALL UTILITY PIPING AND STRUCTURES, IMMEDIATELY INSTALL INLET PROTECTION.
- INSTALL FOUNDATIONS AND BASEMENT.

CONTROL REQUIREMENTS.

- COMPLETE FINAL GRADING, INSTALLATION OF GRAVEL BASE COURSES, PLACEMENT OF CURBS, PAVEMENTS, WALKS, ETC.
- PLACE TOPSOIL AND IMMEDIATELY STABILIZE DISTURBED AREAS WITH EROSION CONTROL MEASURES AS INDICATED ON PLANS.
- EROSION CONTROLS SHALL NOT BE REMOVED UNTIL SITE IS FULLY STABILIZED OR 70% VEGETATIVE COVER IS ESTABLISHED.
- CONTRACTOR MAY MODIFY SEQUENCING AFTER ITEM NO. 1 AS NEEDED TO COMPLETE CONSTRUCTION F EROSION CONTROLS ARE MAINTAINED IN ACCORDANCE WITH THE CONSTRUCTION SITE EROSION

PAVING NOTES

- GENERAL
- ALL PAVING SHALL CONFORM TO "STATE OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY & STRUCTURE CONSTRUCTION. LATEST EDITION, APPLICABLE CITY OF MADISON ORDINANCES AND THE GEOTECHNICAL REPORT PREPARED BY FIRM DATED DATE.
- 1.2. ALL PAVING DIMENSIONS ARE TO FACE OF CURB UNLESS SPECIFIED OTHERWISE.
- 1.3. SURFACE PREPARATION NOTIFY ENGINEER/OWNER OF UNSATISFACTORY CONDITIONS. DO NOT BEGIN PAVING WORK UNTIL DEFICIENT SUBBASE AREAS HAVE BEEN CORRECTED AND ARE READY
- ANY REQUIRED REPLACEMENT OF PUBLIC CURB AND GUTTER SHALL MATCH EXISTING AND MEET MUNICIPALITY REQUIREMENTS.
- 2. ASPHALTIC CONCRETE PAVING SPECIFICATIONS
- CODES AND STANDARDS THE PLACING, CONSTRUCTION AND COMPOSITION OF THE ASPHALTIC BASE COURSE AND ASPHALTIC CONCRETE SURFACE COURSE SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTIONS 450, 455, 460 AND 465 OF THE STATE OF WISCONSIN STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, CURRENT EDITION. HEREAFTER, THIS PUBLICATION WILL BE REFERRED TO AS STATE HIGHWAY SPECIFICATIONS.
- WEATHER LIMITATIONS APPLY TACK COATS WHEN AMBIENT TEMPERATURE IS ABOVE 50° F (10° C) AND WHEN TEMPERATURE HAS NOT BEEN BELOW 35° F (1° C) FOR 12 HOURS IMMEDIATELY PRIOR TO APPLICATION. DO NOT APPLY WHEN BASE IS WET OR CONTAINS EXCESS OF MOISTURE. CONSTRUCT ASPHALTIC CONCRETE SURFACE COURSE WHEN ATMOSPHERIC TEMPERATURE IS ABOVE 40° F (4° C) AND WHEN BASE IS DRY AND WHEN WEATHER IS NOT RAINY. BASE COURSE MAY BE PLACED WHEN AIR TEMPERATURE IS ABOVE 30° F $(-1^{\circ} C)$.
- GRADE CONTROL ESTABLISH AND MAINTAIN REQUIRED LINES AND ELEVATIONS FOR EACH COURSE DURING CONSTRUCTION.
- CRUSHED AGGREGATE BASE COURSE THE TOP LAYER OF BASE COURSE SHALL CONFORM TO SECTIONS 301 AND 305, STATE HIGHWAY SPECIFICATIONS.
- BINDER COURSE AGGREGATE THE AGGREGATE FOR THE BINDER COURSE SHALL CONFORM TO SECTIONS 460 AND 315, STATE HIGHWAY SPECIFICATIONS.
- 2.6. SURFACE COURSE AGGREGATE THE AGGREGATE FOR THE SURFACE COURSE SHALL CONFORM TO SECTIONS 460 AND 465, STATE HIGHWAY SPECIFICATIONS.
- ASPHALTIC MATERIALS THE ASPHALTIC MATERIALS SHALL CONFORM TO SECTION 455 AND 460, STATE HIGHWAY SPECIFICATIONS.
- 3. CONCRETE PAVING SPECIFICATIONS
- CONCRETE PAVING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTIONS 415 AND 416 OF THE STATE HIGHWAY SPECIFICATIONS.
- 3.2. CONCRETE PAVEMENT SHALL BE REINFORCED WITH NOVOMESH 950 (OR EQUAL) FIBER REINFORCEMENT AT A RATE OF 5 LBS/CUBIC YARD. 3.3. CURING COMPOUNDS SHALL CONFORM TO SECTION 415 OF THE STATE HIGHWAY SPECIFICATIONS.
- 3.4. CONTRACTOR SHALL PROVIDE CONTROL JOINTS AND CONSTRUCTION JOINTS OF ONE-QUARTER CONCRETE THICKNESS AT AN EQUAL RATIO OF LENGTH TO WIDTH WHEREVER POSSIBLE WITH A MAXIMUM LENGTH BETWEEN JOINTS OF 8' ON CENTER.
- 3.5. CONTRACTOR SHALL PROVIDE EXPANSION JOINTS IN SIDEWALKS AT A MAXIMUM 24' ON CENTER.
- ALL CONCRETE SURFACES TO BE SEALED WITH TYPE TK-26UV CONCRETE SEALANT
- 4.1. USE 4" WIDE, HIGH VISIBILITY YELLOW LATEX PAINT FOR STALL LINES.
- 4.2. MARK AND STRIPE ADA PARKING SPACES APPROPRIATELY.

PAINTED WITH LATEX PAINT PER SPECIFICATIONS.

- CONTRACTOR TO COORDINATE PRIVATE UTILITY REMOVAL / ABANDONMENT AND NECESSARY 4.3. ALL PAVEMENT MARKINGS INCLUDING: STOP BARS, CROSSWALKS, DIRECTIONAL ARROWS, PARKING STALL LINES, ADA STALL MARKINGS, NO PARKING ZONES, DROP-OFF/PICK-UP ZONES SHALL BE
 - 4.4. 2' x 4' TRUNCATED DOME WARNING DETECTION FIELD SHALL BE PLACED AT ALL ADA RAMPS.

GRADING AND SEEDING NOTES

STANDARD 1059 AND CITY OF MADISON ORDINANCE.

- EXISTING FIBER OPTIC LINE TO BE CLEARLY MARKED PRIOR TO ANY EXCAVATION. CONTRACTOR TO 1. ALL PROPOSED GRADES SHOWN ARE FINISHED GRADES. CONTRACTOR SHALL VERIFY ALL GRADES, MAKE SURE ALL AREAS DRAIN PROPERLY AND SHALL REPORT ANY DISCREPANCIES TO THE ENGINEER
- SEWER ABANDONMENT SHALL BE IN ACCORDANCE WITH SECTION 3.2.24, OF THE STANDARD 2. CONTRACTOR SHALL ASSUME SOLE RESPONSIBILITY FOR COMPUTATIONS OF ALL GRADING QUANTITIES. PROFESSIONAL SERVICES, INC. ATTEMPTS TO PROVIDE A COST BALANCE EARTHWORK, GRADING DESIGN IS BASED ON MANY FACTORS, INCLUDING SAFETY, AESTHETICS, AND COMMON ENGINEERING STANDARDS OF CARE. THEREFORE, NO GUARANTEE CAN BE MADE FOR A BALANCED SITE.
 - PARKING LOT AND DRIVEWAY ELEVATIONS ARE PAVEMENT GRADES, NOT TOP OF CURB GRADES, UNLESS OTHERWISE NOTED.
 - APPROPRIATE OFFICIALS PRIOR TO COMMENCEMENT OF ANY CONSTRUCTION ACTIVITIES. ALL GRADING WITHIN RIGHT-OF-WAY IS SUBJECT TO APPROVAL BY SAID OFFICIALS. CONTRACTOR SHALL PROVIDE NOTICE TO THE MUNICIPALITY IN ADVANCE OF ANY SOIL DISTURBING
 - ACTIVITIES, IN ACCORDANCE WITH MUNICIPAL REQUIREMENTS. 6. ALL DISTURBED AREAS SHALL BE SODDED AND/OR SEEDED AND MULCHED IMMEDIATELY FOLLOWING
 - GRADING ACTIVITIES. SOD/SEED MIX TO BE IN ACCORDANCE WITH LANDSCAPE PLAN. CONTRACTOR SHALL CHISEL-PLOW OR DEEP TILL WITH DOUBLE TINES ALL STORMWATER MANAGEMENT
 - FACILITIES JUST PRIOR TO SODDING AND/OR SEEDING AND MULCHING TO PROMOTE INFILTRATION.
 - CONTRACTOR SHALL WATER ALL NEWLY SODDED/SEEDED AREAS DURING THE SUMMER MONTHS WHENEVER THERE IS A 7 DAY LAPSE WITH NO SIGNIFICANT RAINFALL.
 - 9. CONTRACTOR TO DEEP TILL ALL COMPACTED PERVIOUS SURFACES PRIOR TO SODDING AND/OR SEEDING AND MULCHING.
 - 10. ALL SLOPES 20% OR GREATER SHALL BE TEMPORARY SEEDED, MULCHED, OR OTHER MEANS OF COVER PLACED ON THEM WITHIN 2 WEEKS OF DISTURBANCE.
- CONDUCT ROUGH GRADING EFFORTS AND INSTALL CHECK DAMS WITHIN DRAINAGE DITCHES AS 11. ALL EXPOSED SOIL AREAS THAT WILL NOT BE BROUGHT TO FINAL GRADE OR ON WHICH LAND DISTURBING ACTIVITIES WILL NOT BE PERFORMED FOR A PERIOD GREATER THAN 30 DAYS AND REQUIRE VEGETATIVE COVER FOR LESS THAN 1 YEAR, REQUIRE TEMPORARY SEEDING FOR EROSION CONTROL. SEEDING FOR EROSION CONTROL SHALL BE IN ACCORDANCE WITH WDNR TECHNICAL

UTILITY NOTES

- 1. ALL EXISTING UTILITIES ARE SHOWN FOR INFORMATIONAL PURPOSES ONLY AND ARE NOT GUARANTEED TO BE ACCURATE OR ALL INCLUSIVE. THE CONTRACTOR IS RESPONSIBLE FOR MAKING HIS OWN DETERMINATION AS TO THE TYPE AND LOCATIONS OF UNDERGROUND UTILITIES AS MAY BE NECESSARY TO AVOID DAMAGE THERETO. CONTRACTOR/OWNER SHALL CALL "DIGGER'S HOTLINE" PRIOR TO ANY CONSTRUCTION.
- EXAMINING ALL SITE CONDITIONS RELATIVE TO THE CONDITIONS INDICATED ON THE ENGINEERING DRAWINGS. ANY DISCREPANCIES ARE TO BE REPORTED TO THE ENGINEER AND RESOLVED PRIOR TO
- THE START OF CONSTRUCTION. · OBTAINING ALL PERMITS INCLUDING PERMIT COSTS, TAP FEES, METER DEPOSITS, BONDS, AND
- ALL OTHER FEES REQUIRED FOR PROPOSED WORK TO OBTAIN OCCUPANCY. VERIFYING ALL ELEVATIONS, LOCATIONS AND SIZES OF SANITARY, WATER AND STORM LATERALS
- AND CHECK ALL UTILITY CROSSINGS FOR CONFLICTS. NOTIFY ENGINEER OF ANY DISCREPANCY. NO WORK SHALL BE PERFORMED UNTIL THE DISCREPANCY IS RESOLVED.
- NOTIFYING ALL UTILITIES PRIOR TO INSTALLATION OF ANY UNDERGROUND IMPROVEMENTS NOTIFYING THE DESIGN ENGINEER AND MUNICIPALITY 48 HOURS PRIOR TO THE START OF CONSTRUCTION TO ARRANGE FOR APPROPRIATE CONSTRUCTION OBSERVATION.
- COORDINATING ALL CONSTRUCTION WITH OTHER CONTRACTORS INVOLVED WITH CONSTRUCTION OF THE PROPOSED DEVELOPMENT AND FOR REPORTING ANY ERRORS OR DISCREPANCIES BETWEEN THESE PLANS AND PLANS PREPARED BY OTHERS.
- 3. ALL UTILITY WORK SHALL BE DONE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN - AND ALL STATE AND LOCAL CODES AND SPECIFICATIONS. IT IS THE CONTRACTORS RESPONSIBILITY TO DETERMINE WHICH SPECIFICATIONS AND CODES APPLY, AND TO COORDINATE ALL CONSTRUCTION ACTIVITIES WITH THE APPROPRIATE LOCAL AND STATE
- SPECIFICATIONS SHALL COMPLY WITH THE CITY OF MADISON SPECIAL PROVISIONS.

OWNER'S SATISFACTION AT THE CONTRACTOR'S EXPENSE.

PRIOR TO CONSTRUCTION. THE PRIME CONTRACTOR IS RESPONSIBLE FOR:

- LENGTHS OF ALL UTILITIES ARE TO CENTER OF STRUCTURES OR FITTINGS AND MAY VARY SLIGHTLY FROM PLAN. LENGTHS SHALL BE VERIFIED IN THE FIELD DURING CONSTRUCTION.
- CONTRACTOR IS RESPONSIBLE FOR SITE SAFETY DURING THE CONSTRUCTION OF IMPROVEMENTS. 7. CONTRACTOR SHALL INSTALL A PEDESTRIAN FENCE AROUND ALL EXCAVATIONS TO BE LEFT OPEN
- OVER NIGHT AS REQUIRED IN CONSTRUCTION SITES WHERE THE POTENTIAL FOR PEDESTRIAN INJURY
- CONTRACTOR SHALL ADJUST AND/OR RECONSTRUCT ALL UTILITY COVERS (SUCH AS MANHOLE COVERS, 8. PAVED SURFACES ADJACENT TO CONSTRUCTION SITE VEHICLE ACCESS SHALL BE SWEPT AND/OR — — GRADE BREAK VALVE BOX COVERS, ETC.) TO MATCH THE FINISHED GRADES OF THE AREAS EFFECTED BY THE
- ANY ERRORS OR DISCREPANCIES BETWEEN THESE PLANS AND PLANS PREPARED BY OTHERS. OR OTHER UTILITIES, WHICH ARE DAMAGED BY THE CONTRACTORS, SHALL BE REPAIRED TO THE
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE ENGINEER WITH AS-BUILT CONDITIONS OF THE DESIGNATED IMPROVEMENTS IN ORDER THAT THE APPROPRIATE DRAWINGS CAN BE PREPARED. IF ENGINEER AS WORK PROGRESSES.
- 12. STORM SEWER SPECIFICATIONS -

PIPE - REINFORCED CONCRETE PIPE (RCP) SHALL MEET THE REQUIREMENTS OF ASTM CLASS III (MINIMUM) C-76 WITH RUBBER GASKET JOINTS CONFORMING TO ASTM C-443. HIGH DENSITY DUAL-WALL POLYETHYLENE CORRUGATED PIPE SHALL BE AS MANUFACTURED BY ADS OR EQUAL WITH WATER TIGHT JOINTS, AND SHALL MEET THE REQUIREMENTS OF AASHTO DESIGNATION M-294 TYPE

INLETS - INLETS SHALL BE CONSTRUCTED IN ACCORDANCE WITH FILE. NO. 28 OF THE "STANDARD SPECIFICATIONS", OR APPROVED EQUAL WITH A 1'-8" X 2'-6" MAXIMUM OPENING. CURB FRAME & GRATE SHALL BE NEENAH R-3067 WITH TYPE R GRATE, OR EQUAL.

BACKFILL AND BEDDING - STORM SEWER SHALL BE CONSTRUCTED WITH GRAVEL BACKFILL AND CLASS B" BEDDING IN ALL PAVED AREAS AND TO A POINT 5 FEET BEYOND THE EDGE OF PAVEMENT. TRENCHES RUNNING PARALLEL TO AND LESS THAN 5 FEET FROM THE EDGE OF PAVEMENT SHALL ALSO REQUIRE GRAVEL BACKFILL. LANDSCAPED AREAS MAY BE BACKFILLED WITH EXCAVATED MATERIAL IN CONFORMANCE WITH SECTION 8.43.5 OF THE "STANDARD SPECIFICATIONS".

MANHOLE FRAMES AND COVERS - MANHOLE FRAMES AND COVERS SHALL BE AS SHOWN ON SHEET

FIELD TILE CONNECTION - ALL FIELD TILE ENCOUNTERED DURING CONSTRUCTION SHALL BE INCLUDED IN THE UNIT PRICE(S) FOR STORM SEWER. TILE LINES CROSSED BY THE TRENCH SHALL BE REPLACED WITH THE SAME MATERIAL AS THE STORM SEWER.

13. WATER MAIN SPECIFICATIONS -

PIPE - DUCTILE IRON PIPE SHALL BE CLASS 52 CONFORMING TO AWWA C151 AND CHAPTER 8.18.0 THE "STANDARD SPECIFICATIONS". POLYVINYL CHLORIDE (PVC) PIPE SHALL MEET THE 17. STABILIZATION PRACTICES: REQUIREMENTS OF AWWA STANDARD C-900, CLASS 150, DR-18, WITH CAST IRON O.D. AND INTEGRAL ELASTOMERIC BELL AND SPIGOT JOINTS. NON-METALLIC WATER MAINS SHALL BE INSTALLED WITH BLUE INSULATION TRACER WIRE AND CONFORM WITH SPS 382.30(11)(h).

VALVES AND VALVE BOXES - GATE VALVES SHALL BE AWWA GATE VALVES MEETING THE REQUIREMENTS OF AWWA C-500 AND CHAPTER 8.27.0 OF THE "STANDARD SPECIFICATIONS". GATE 17.2. VALVES AND VALVE BOXES SHALL CONFORM TO LOCAL PLUMBING ORDINANCES.

HYDRANTS - HYDRANTS SHALL CONFORM TO THE SPECIFICATIONS OF THE CITY OF MADISON. THE DISTANCE FROM THE GROUND LINE TO THE CENTERLINE OF THE LOWEST NOZZLE AND THE LOWEST CONNECTION OF THE FIRE DEPARTMENT SHALL BE NO LESS THAN 18-INCHES AND NO GREATER THAN 23-INCHES (SEE DETAIL).

BEDDING AND COVER MATERIAL - PIPE BEDDING AND COVER MATERIAL SHALL BE SAND, CRUSHED STONE CHIPS OR CRUSHED STONE SCREENINGS CONFORMING TO CHAPTER 8.43.2 OF THE "STANDARD

BACKFILL - BACKFILL MATERIAL AND INSTALLATION SHALL BE IN ACCORDANCE WITH CHAPTER 2.6.0 OF THE "STANDARD SPECIFICATIONS". GRAVEL BACKFILL IS REQUIRED IN ALL PAVED AREAS AND TO A POINT 5 FEET BEYOND THE EDGE OF PAVEMENT, TRENCHES RUNNING PARALLEL TO AND LESS THAN 5 FFFT FROM THE FDGE OF PAVEMENT SHALL ALSO REQUIRE GRAVEL BACKELL LANDSCAPED AREAS MAY BE BACKFILLED WITH EXCAVATED MATERIAL IN CONFORMANCE WITH SECTION 8.43.5 OF THE "STANDARD SPECIFICATIONS".

. SANITARY SEWER SPECIFICATIONS -

ADEQUATE SIDE SUPPORT."

PIPE - SANITARY SEWER PIPE MATERIAL SHALL BE POLYVINYL CHLORIDE (PVC) MEETING REQUIREMENTS OF ASTM D 3034, SDR-35, WITH INTEGRAL BELL TYPE FLEXIBLE ELASTOMERIC JOINTS, MEETING THE REQUIREMENTS OF ASTM D-3212.

BEDDING AND COVER MATERIAL - BEDDING AND COVER MATERIAL SHALL CONFORM TO THE APPROPRIATE SECTIONS OF THE "STANDARD SPECIFICATION" WITH THE FOLLOWING MODIFICATION: "COVER MATERIAL SHALL BE THE SAME AS USED FOR BEDDING AND SHALL CONFORM TO SECTION 8.43.2 (A). BEDDING AND COVER MATERIAL SHALL BE PLACED IN A MINIMUM OF THREE SEPARATE LIFTS, OR AS REQUIRED TO INSURE ADEQUATE COMPACTING OF THESE MATERIALS, WITH ONE LIFT OF BEDDING MATERIAL ENDING AT OR NEAR THE SPRINGLINE OF THE PIPE. THE CONTRACTOR SHALL TAKE CARE TO COMPLETELY WORK BEDDING MATERIAL UNDER THE HAUNCH OF THE PIPE TO PROVIDE

BACKFILL - BACKFILL MATERIAL AND INSTALLATION SHALL BE IN ACCORDANCE CHAPTER 2.6.0 OF THE "STANDARD SPECIFICATIONS." GRAVEL BACKFILL IS REQUIRED IN ALL PAVED AREAS AND TO A POINT 5 FEET BEYOND THE EDGE OF PAVEMENT. TRENCHES RUNNING PARALLEL TO AND LESS THAN 5 FEET FROM THE EDGE OF PAVEMENT SHALL ALSO REQUIRE GRAVEL BACKFILL. LANDSCAPED AREAS MAY BE BACKFILLED WITH EXCAVATED MATERIAL IN CONFORMANCE WITH SECTION 8.43.5 OF THE "STANDARD SPECIFICATIONS.

MANHOLES - MANHOLES SHALL BE CONSTRUCTED IN ACCORDANCE WITH FILE NOS. 12, 13 AND 15 OF THE "STANDARD SPECIFICATIONS" AND ALL SPECIAL PROVISIONS OF THE CITY OF MADISON. MANHOLE FRAMES AND COVERS - MANHOLE FRAMES AND COVERS SHALL BE AS SHOWN ON SHEET

- 15. WATERMAIN AND SANITARY SEWER SHALL BE INSULATED WHEREVER THE DEPTH OF COVER IS LESS THAN 6 FEET. INSULATION AND INSTALLATION OF INSULATION SHALL BE CONFORMING WITH CHAPTER 4.17.0 "INSULATION" OF THE STANDARD SPECIFICATIONS FOR SEWER AND WATER CONSTRUCTION IN WISCONSIN 6TH EDITION UPDATED WITH ITS LATEST ADDENDUM (TYP.).
- 16. ALL NON-METALLIC UTILITY PIPES (SANITARY SEWER, STORM SEWER, AND WATER PIPING) SHALL BE INSTALLED IN CONJUNCTION WITH TRACER WIRE AS REQUIRED BY SPS 382.30(11)(H), SPS 382.36(7)(C)10., AND SPS 382.40(8)(K). COLOR OF TRACER WIRE SHALL BE: SANITARY SEWER -GREEN, STORM SEWER - BROWN, WATER - BLUE, NON-POTABLE WATER - PURPLE.

EROSION CONTROL NOTES

- CONTRACTOR IS RESPONSIBLE TO NOTIFY ENGINEER OF RECORD AND OFFICIALS OF ANY CHANGES TO PROPERTY LINE THE EROSION CONTROL AND STORMWATER MANAGEMENT PLANS. ENGINEER OF RECORD AND APPROPRIATE CITY OF MADISON OFFICIALS MUST APPROVE ANY CHANGES PRIOR TO DEVIATION FROM - - - - RIGHT-OF-WAY THE APPROVED PLANS.
- 2. ALL EROSION CONTROL MEASURES SHALL BE CONSTRUCTED AND MAINTAINED BY THE CONTRACTOR IN ACCORDANCE WITH THE WISCONSIN DEPARTMENT OF NATURAL RESOURCES (WDNR) TECHNICAL STANDARDS (REFERRED TO AS BMP'S) AND CITY OF MADISON ORDINANCE. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN A COPY OF THESE STANDARDS. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY ADDITIONAL EROSION CONTROL MEASURES WHICH MAY BE NECESSARY TO MEET --- BUILDING SETBACK LINE UNFORESEEN FIELD CONDITIONS.
- 5. INSTALL PERIMETER EROSION CONTROL MEASURES (SUCH AS CONSTRUCTION ENTRANCES, SILT FENCE AND EXISTING INLET PROTECTION) PRIOR TO ANY SITE WORK, INCLUDING GRADING OR DISTURBANCE OF EXISTING SURFACE COVER, ÁS SHOWN ON PLAN. MODIFICATIONS TO THE APPROVED EROSION CONTROL DESIGN IN ORDER TO MEET UNFORESEEN FIELD CONDITIONS IS ALLOWED IF MODIFICATIONS PRIOR TO DEVIATION OF THE APPROVED PLAN.
- ADDITIONAL EROSION CONTROL MEASURES, AS REQUESTED BY STATE INSPECTORS, LOCAL INSPECTORS, COUNTY INSPECTORS AND/OR ENGINEER OF RECORD SHALL BE INSTALLED WITHIN 24 HOURS OF
- INSPECTIONS AND MAINTENANCE OF ALL EROSION CONTROL MEASURES SHALL BE ROUTINE (ONCE PER WEEK MINIMUM) TO ENSURE PROPER FUNCTION OF EROSION CONTROLS AT ALL TIMES. EROSION CONTROL MEASURES ARE TO BE IN WORKING ORDER AT THE END OF EACH WORK DAY.
- EVENTS EXCEEDING 0.5 INCHES. ANY DAMAGED EROSION CONTROL MEASURES SHALL BE REPAIRED OR REPLACED IMMEDIATELY UPON INSPECTION. 7. CONSTRUCTION ENTRANCES SHALL BE INSTALLED AT ALL LOCATIONS OF VEHICLE INGRESS/EGRESS -------960------------PROPOSED 5 FOOT CONTOUR POINTS. ADDITIONAL LOCATIONS OTHER THAN AS SHOWN ON THE PLANS MUST BE PRIOR APPROVED
- BY THE MUNICIPALITY. CONSTRUCTION ENTRANCES SHALL BE 50' LONG AND NO LESS THAN 12" THICK BY USE OF 3" CLEAR STONE. CONSTRUCTION ENTRANCES SHALL BE MAINTAINED BY THE CONTRACTOR IN A CONDITION WHICH WILL PREVENT THE TRACKING OF MUD OR DRY SEDIMENT ONTO ADJACENT PUBLIC STREETS AFTER EACH WORKING DAY OR MORE FREQUENTLY AS REQUIRED.
- SCRAPED TO REMOVE ACCUMULATED SOIL, DIRT AND/OR DUST AFTER THE END OF EACH WORK DAY AND AS REQUESTED BY THE CITY OF MADISON. THE PRIME CONTRACTOR IS RESPONSIBLE FOR COORDINATING ALL CONSTRUCTION WITH OTHER 9. INLET PROTECTION SHALL BE IMMEDIATELY FITTED AT THE INLET OF ALL INSTALLED STORM SEWER AND SILT FENCE SHALL BE IMMEDIATELY FITTED AT ALL INSTALLED CULVERT INLETS TO PREVENT SEDIMENT . BOULDER WALL CONTRACTORS INVOLVED WITH CONSTRUCTION OF THE PROPOSED DEVELOPMENT AND FOR REPORTING
- DEPOSITION WITHIN STORM SEWER SYSTEMS. 10. ANY SANITARY SEWER, SANITARY SEWER SERVICES, WATER MAIN, WATER SERVICES, STORM SEWER, 10. INSTALL EROSION CONTROLS ON THE DOWNSTREAM SIDE OF STOCKPILES. IF STOCKPILE REMAINS ACCORDANCE WITH BEST MANAGEMENT PRACTICES IS REQUIRED. IF DISTURBANCE OCCURS BETWEEN NOVEMBER 15TH AND MAY 15TH, THE MULCHING SHALL BE PERFORMED BY HYDRO-MULCHING WITH A
- REQUIRED. ANY CHANGES TO THE DRAWINGS OR ADDITIONAL ITEMS MUST BE REPORTED TO THE 11. DITCH CHECKS AND APPLICABLE EROSION NETTING/MATTING SHALL BE INSTALLED IMMEDIATELY AFTER COMPLETION OF GRADING EFFORTS WITHIN DITCHES/SWALES TO PREVENT SOIL TRANSPORTATION.
 - 12. EROSION CONTROL FOR UTILITY CONSTRUCTION (STORM SEWER, SANITARY SEWER, WATER MAIN, ETC.): A. PLACE EXCAVATED TRENCH MATERIAL ON THE HIGH SIDE OF THE TRENCH. BACKFILL, COMPACT, AND STABILIZE THE TRENCH IMMEDIATELY AFTER PIPE CONSTRUCTION. DISCHARGE TRENCH WATER INTO A SEDIMENTATION BASIN OR FILTERING TANK IN ACCORDANCE WITH THE DEWATERING TECHNICAL STANDARD NO. 1061 PRIOR TO RELEASE INTO THE STORM SEWER, RECEIVING STREAM, OR DRAINAGE DITCH.
 - 13. ALL SLOPES 4:1 OR GREATER SHALL BE STABILIZED WITH CLASS I, TYPE B EROSION MATTING OR APPLICATION OF A WISCONSIN DEPARTMENT OF TRANSPORTATION (WISDOT) APPROVED POLYMER SOIL STABILIZATION TREATMENT OR A COMBINATION THEREOF, AS REQUIRED WITHIN 7 DAYS OF REACHING FINAL GRADE AND/OR AS SOON AS CONDITIONS ALLOW. DRAINAGE SWALES SHALL BE STABILIZED WITH CLASS II, TYPE B EROSION MATTING. EROSION MATTING AND/OR NETTING USED ONSITE SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S GUIDELINES AND WDNR TECHNICAL STANDARDS
 - 14. CONTRACTOR SHALL TAKE ALL NECESSARY STEPS TO CONTROL DUST ARISING FROM CONSTRUCTION OPERATIONS. REFER TO WDNR TECHNICAL STANDARD 1068.
 - 15. EROSION CONTROL MEASURES SHALL NOT BE REMOVED UNTIL ALL LAND DISTURBING CONSTRUCTION HAS BEEN ESTABLISHED WITH A DENSITY OF AT LEAST 70% FOR UNPAVED AREAS AND AREAS NOT COVERED BY PERMANENT STRUCTURES OR THAT EMPLOY EQUIVALENT PERMANENT STABILIZATION
 - 16. CONTRACTOR/OWNER SHALL FILE A NOTICE OF TERMINATION UPON COMPLETION OF THE PROJECT IN ACCORDANCE WITH WDNR REQUIREMENTS AND/OR PROPERTY SALE IN ACCORDANCE WITH WDNR REQUIREMENTS.

 - STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS PRACTICABLE IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY OR PERMANENTLY CEASED. NO MORE THAN SEVEN (7) DAYS SHALL PASS AFTER THE CONSTRUCTION ACTIVITY IN THAT
 - THE INITIATION STABILIZATION MEASURES BY THE SEVENTH (7) DAY AFTER CONSTRUCTION ACTIVITY HAS CEASED IS PRECLUDED BY SNOW COVER. IN THAT EVENT, STABILIZATION SHALL BE INITIATED AS SOON AS PRACTICABLE. CONSTRUCTION ACTIVITY WILL RESUME ON A PORTION OF THE SITE WITHIN FOURTEEN (14) DAYS FROM WHEN ACTIVITY CEASED, (I.E. THE TOTAL TIME PERIOD THAT THE CONSTRUCTION
 - ACTIVITY IS TEMPORARILY CEASED IS LESS THAN FOURTEEN (14) DAYS. IN THAT EVENT, STABILIZATION MEASURES DO NOT HAVE TO BE INITIATED ON THAT PORTION OF THE SITE BY THE SEVENTH (7) DAY AFTER CONSTRUCTION ACTIVITY HAS TEMPORARILY CEASED. STABILIZATION MEASURES SHALL BE DETERMINED BASED ON SITE CONDITIONS AT THE TIME OF CONSTRUCTION ACTIVITY HAS CEASED, INCLUDING BUT NOT LIMITED TO WEATHER
 - CONDITIONS AND LENGTH OF TIME MEASURE MUST BE EFFECTIVE. THE FOLLOWING ARE ACCEPTABLE STABILIZATION MEASURES: • PERMANENT SEEDING; IN ACCORDANCE WITH APPROVED CONSTRUCTION SPECIFICATION TEMPORARY SEEDING; MAY CONSIST OF SPRING OATS(100LBS/ACRE) AND/OR WHEAT
 - OR CEREAL RYE (150LB/ACRE) HYDRO-MULCHING WITH A TACKIFIER GEOTEXTILE EROSION MATTING

PORTION OF THE SITE HAS CEASED UNLESS:

CITY TRAFFIC ENGINEERING NOTES

THE RIGHT-OF-WAY IS THE SOLE JURISDICTION OF THE CITY OF MADISON AND IS SUBJECT TO

STREET TREE REMOVAL(S) PRIOR TO A TREE REMOVAL PERMIT BEING ISSUED.

CHANGE AT ANY TIME PER THE RECOMMENDED PLAN BUY TRAFFIC ENGINEERING AND CITY

CITY FORESTRY NOTES

ENGINEERING DEPARTMENT.

SODDING

ALL PROPOSED STREET TREE REMOVALS WITHIN THE RIGHT OF WAY SHALL BE REVIEWED BY CITY FORESTRY BEFORE THE PLAN COMMISSION MEETING. STREET TREE REMOVALS REQUIRE APPROVAL AND A TREE REMOVAL PERMIT ISSUED BY CITY FORESTRY. ANY STREET TREE REMOVALS REQUESTED AFTER THE DEVELOPMENT PLAN IS APPROVED BY THE PLAN COMMISSION OR THE BOARD OF PUBLIC WORKS AND CITY FORESTRY WILL REQUIRE A MINIMUM OF A 72-HOUR REVIEW PERIOD WHICH SHALL INCLUDE THE NOTIFICATION OF THE ALDERPERSON WITHIN WHO'S DISTRICT IS AFFECTED BY THE

- AS DEFINED BY THE SECTION 107.13 OF CITY OF MADISON STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION: NO EXCAVATION IS PERMITTED WITHIN 5 FEET OF THE TRUNK OF THE STREET TREE OR WHEN CUTTING ROOTS OVER 3 INCHES IN DIAMETER. IF EXCAVATION IS NECESSARY, THE CONTRACTOR SHALL CONTACT MADISON CITY FORESTRY (266-4816) PRIOR TO EXCAVATION. CITY OF MADISON FORESTRY PERSONNEL SHALL ASSESS THE IMPACT TO THE TREE AND TO ITS ROOT SYSTEM PRIOR TO WORK COMMENCING. TREE PROTECTION SPECIFICATIONS CAN BE FOUND ON THE FOLLOWING WEBSITE: <u>HTTPS://WWW.CITYOFMADISON.COM/BUSINESS/PW/SPECS.CFM</u>
- CONTRACTOR SHALL TAKE PRECAUTIONS DURING CONSTRUCTION TO NOT DISFIGURE, SCAR, OR IMPAIR THE HEALTH OF ANY STREET TREE. CONTRACTOR SHALL OPERATE EQUIPMENT IN A MANNER AS TO NOT DAMAGE THE BRANCHES OF THE STREET TREE(S). THIS MAY REQUIRE USING SMALLER EQUIPMENT AND LOADING AND UNLOADING MATERIALS IN A DESIGNATED SPACE AWAY FROM TREES ON THE CONSTRUCTION SITE. ANY DAMAGE OR INJURY TO EXISTING STREET TREES (EITHER ABOVE OR BELOW GROUND) SHALL BE REPORTED IMMEDIATELY TO CITY FORESTRY AT 266-4816. PENALTIES AND REMEDIATION SHALL BE REQUIRED.

SECTION 107.13(G) OF CITY OF MADISON STANDARD SPECIFICATIONS FOR PUBLIC WORKS

CONSTRUCTION ADDRESSES SOIL COMPACTION NEAR STREET TREES AND SHALL BE FOLLOWED BY

CONTRACTOR. THE STORAGE OF PARKED VEHICLES, CONSTRUCTION EQUIPMENT, BUILDING MATERIALS,

REFUSE, EXCAVATED SPOILS OR DUMPING OF POISONOUS MATERIALS ON OR AROUND TREES AND

- ROOTS WITHIN FIVE (5) FEET OF THE TREE OR WITHIN THE PROTECTION ZONE IS PROHIBITED. 5. ON THIS PROJECT, STREET TREE PROTECTION ZONE FENCING IS REQUIRED. THE FENCING SHALL BE ERECTED BEFORE THE DEMOLITION, GRADING OR CONSTRUCTION BEGINS. THE FENCE SHALL INCLUDE THE ENTIRE WIDTH OF TERRACE AND, EXTEND AT LEAST 5 FEET ON BOTH SIDES OF THE OUTSIDE EDGE OF THE TREE TRUNK. DO NOT REMOVE THE FENCING TO ALLOW FOR DELIVERIES OR
- EQUIPMENT ACCESS THROUGH THE TREE PROTECTION ZONE. 6. STREET TREE PRUNING SHALL BE COORDINATED WITH MADISON FORESTRY AT A MINIMUM OF TWO WEEKS PRIOR TO THE START OF CONSTRUCTION FOR THIS PROJECT. CONTACT CITY FORESTRY AT (608) 266-4816. ALL PRUNING SHALL FOLLOW THE AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI) A300 - PART 1 STANDARDS FOR PRUNING.

FORESTRY AT (608) 266-4816 TO SCHEDULE INSPECTION AND APPROVAL OF NURSERY TREE STOCK

7. AT LEAST ONE WEEK PRIOR TO STREET TREE PLANTING, CONTRACTOR SHALL CONTACT CITY

AND REVIEW PLANTING SPECIFICATIONS WITH THE LANDSCAPER.

BUILDING OUTLINE

EDGE OF PAVEMENT

LEGEND

— · — · — · — · — EASEMENT LINE

---- BUILDING OVERHANG

2450 Rimrock Road — — PAVEMENT SETBACK LINE

Suite 100

STANDARD CURB AND GUTTER MOUNTABLE CURB AND GUTTER 8" CONCRETE RIBBON CURB ASPHALT PAVEMENT

HEAVY DUTY ASPHALT PAVEMENT

CONCRETE PAVEMENT 6. ALL EROSION AND SEDIMENT CONTROL ITEMS SHALL BE INSPECTED WITHIN 24 HOURS OF ALL RAIN [+*+*+*+*+*+*+*+*+**] REINFORCED CONCRETE PAVEMENT PROPOSED 1 FOOT CONTOUR

- — — 960— — — — EXISTING 5 FOOT CONTOUR

DRAINAGE DIRECTION STORMWATER MANAGEMENT AREA RETAINING WALL

> LIGHT POLE (REFER TO PHOTOMETRIC PLAN) ADA PARKING SIGN

BOLLARD WITH ADA PARKING SIGN BIKE RACK TREE REMOVAL SHRUB REMOVAL

FLAG POLE

BOLLARD

SANITARY SEWER

WATERMAIN D STORM SEWER 8'x4'x4" INSULATION (PLAN VIEW) 8'x4'x4" INSULATION (PROFILE VIEW)

EROSION MATTING SPOT ELEVATION

> FG: XXX.XX BOC - BACK OF CURB MATCH - MATCH EXISTING GRADE HP - HIGH POINT SW - SIDEWALK

PROPERTY LINE

DEMOLITION - REMOVAL OF ONSITE CUR SURFACES AND BASE COURSE

> DEMOLITION - REMOVAL OF RETAINING SURFACES

DEMOLITION - REMOVAL OF BUILDINGS/STRUCTURES

SURFACES

PROTECT EXISTING TREE

CONSTRUCTION ENTRANCE

TURF REINFORCEMENT MATTING EP - EDGE OF PAVEMENT FG — FINISH GRADE EC - EDGE OF CONCRETE

DITCH CHECK

INLET PROTECTION - · - · - · - · - EASEMENT LINE

> DEMOLITION - PAVEMENT MILL AND OVFRI AY

DEMOLITION - REMOVAL OF ASPHALT XXXXXXXX

> DEMOLITION - REMOVAL OF UTILITIES DEMOLITION - REMOVAL OF FENCE

> > NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

DRAWN:

APPR:

PROJECT # 23-814

NOTES & LEGEND


Madison, WI 53713 Telephone: 608-258-5580 Fax: 608-258-5599 www.alexandercompany.com

NOT FOR CONSTRUCTION


10-12-23 LAND USE APPLICATION


DEMOLITION - REMOVAL OF CONCRETE


TREE REMOVAL SHRUB REMOVAL












FLEXSTORM CATCH-IT FILTERS FOR TEMPORARY INLET PROTECTION PRODUCT SELECTION AND SPECIFICATION DRAWING

STYLE	FRAME STYLE AND SIZE	Frame P/N:
	Small Round (up to 20.0" dia grates (A) dim)	62SRD
ROUND	Med Round (20.1" - 26.0" dia grates (A) up to 25" dia openings (B))	62MRD
રૂડ	Large Round (26.1" - 32.0" dia grates (A) up to 30" openings (B))	62LRD
_	XL Round (32.1" dia - 39" dia grates (A) up to 37" dia openings (B))	62XLRD
ш	Small Rect / Square (up to 16" (B) x 16" (D) openings or 64" perimeter)	62SSQ
RECT/ SQUARE	Med Rect / Square (up to 24" (B) x 24" (D) openings or 96" perimeter)	62MSQ
RE(Large Rect / Square (up to 36" (B) x 24" (D) openings or 120" perimeter)	62LSQ
<u> </u>	XL Rect / Square (side by side 2 pc set to fit up to 48" (B) x 36" (D) openings)	62XLSQ
0	Small Rect / Square (ref Rect sizing; shipped with Magnetic Curb Flaps)	62SCB
OMBO	Med Rect / Square (ref Rect sizing; shipped with Magnetic Curb Flaps)	62MCB
COMBO	Large Rect / Square (ref Rect sizing; shipped with Magnetic Curb Flaps)	62LCB
	XL Rect / Square (ref Rect sizing; shipped with Magnetic Curb Flaps)	62XLCB
—	12" diameter Nyloplast castings (Stainless Steel Framing standard)	6212NY
AS.	15" diameter Nyloplast castings (Stainless Steel Framing standard)	6215NY
OPI	18" diameter Nyloplast castings (Stainless Steel Framing standard)	6218NY
NYLOPLAST	24" diameter Nyloplast castings (Stainless Steel Framing standard)	6224NY
~	30" diameter Nyloplast castings (Stainless Steel Framing standard)	6230NY

SPECIFICATIONS FOR STANDARD BAGS BY NOMINAL SIZE					
Nominal Bag	Solids Storage	Filtered Flow Rate	e at 50% Max (CFS)		
Size	(CuFt)	FX (Woven)	IL (NonWoven)		
Small	1.6	1.2	0.9		
Medium	2.1	1.7	1.3		
Large	3.8	2.7	1.9		

2. SELECT YOUR BAG PART NUMBER					
FLEXSTORM FILTER BAGS	(22" depth)	(12" depth)	Clean Water Flow	Min A.O.S.	
FLEXSTORIVIFILIER BAGS	STD Bag P/N	Short Bag P/N	Rate (GPM/SqFt)	(US Sieve)	
FX: Standard Woven Bag	FX	FX-S	200	40	
IL: IDOT Non-Woven Bag	IL	IL-S	145	70	



INSTALLATION:

- 1. REMOVE GRATE
- 2. DROP FLEXSTORM INLET FILTER ONTO LOAD BEARING LIP OF CASTING OR CONCRETE STRUCTURE
- 3. REPLACE GRATE

FRAMED INLET PROTECTION

BY INLET & PIPE PROTECTION, INC A DIVISION OF ADS, INC. WWW.INLETFILTERS.COM (866) 287-8655 PH (630) 355-3477 FX INFO@INLETFILTERS.COM

ALL PRODUCTS MANUFACTURED

GALVANIZED) FOR 7 YEAR MINIMUM SERVICE

CALLOUT, PRECAST OR CASTING MAKE AND

BE PROVIDED TO CONFIGURE AND ASSEMBLE

YOUR CUSTOMIZED FLEXSTORM INLET FILTER.


3. FOR WRITTEN SPECIFICATIONS AND MAINTENANCE

PART NUMBER ALONE IS NOT SUFFICIENT.

GUIDELINES VISIT WWW.INLETFILTERS.COM

MODEL, OR DETAILED DIMENSIONAL FORMS MUST

2. UPON ORDERING CONFIRMATION OF THE DOT





GENERAL NOTES:


REV. 12-7-2018

- EXCAVATE A SHALLOW TRENCH SLIGHTLY BELOW BASEFLOW OR A 4" TRENCH ON SLOPE CONTOURS.
- PLACE THE ROLL IN THE TRENCH AND ANCHOR WITH 2" X 2" POSTS PLACED ON BOTH SIDES OF THE ROLL AND SPACED LATERALLY ON 2' TO 4' CENTERS. TRIM THE TOP OF THE POSTS EVEN WITH THE EDGE OF THE ROLL, IF NECESSARY.
- NOTCH THE POSTS AND TIE TOGETHER, ACROSS THE ROLL, WITH 9 GAUGE GALVANIZED WIRE OR 1/8" DIAMETER BRAIDED NYLON ROPE.
- PLACE SOIL EXCAVATED FROM THE TRENCH BEHIND THE ROLL AND HAND TAMP. PLANT WITH SUITABLE HERBACEOUS OR WOODY VEGETATION AS SPECIFIED.

FIBER SILT SOCK







CONCRETE SIDEWALK SECTION

REINFORCED CONCRETE PAVEMENT


GENERAL NOTES:

- 1. REFER TO PAVEMENT RECOMMENDATIONS IN THE GEOTECHNICAL INVESTIGATION REPORT, PREPARED BY ______ TITLED "_____" DATED _____. IF THERE ARE ANY DISCREPANCIES BETWEEN THIS DETAIL AND THE PAVEMENT RECOMMENDATIONS PROVIDED IN THE GEOTECHNICAL INVESTIGATION REPORT, THE GEOTECHNICAL REPORT SHALL GOVERN.
- 2. WISDOT STANDARD SPECIFICATIONS FOR HIGHWAY AND STRUCTURE CONSTRUCTION, INCLUDING SUPPLEMENTAL SPECIFICATIONS, COMPACTION REQUIREMENTS:
- BITUMINOUS CONCRETE: REFER TO SECTION 460-3. - BASE COURSE: REFER TO SECTION 301.3.4.2, STANDARD COMPACTION.
- 3. CONCRETE PADS SHALL HAVE A WIRE REINFORCEMENT MESH (6X6, W2.9XW2.9) FOR CRACK CONTROL.
- 4. AGGREGATE BASE SHALL BE 3" MINUS UP TO 4" BELOW PAVEMENT AND 14" MINUS TO PAVEMENT.

REV. 7-01-2019

PAVEMENT SECTIONS

N.T.S.





10.12.23 I AND LISE APPLICATION

2450 Rimrock Road

Madison, WI 53713

Fax: 608-258-5599

Telephone: 608-258-5580

www.alexandercompany.com


Suite 100

10-12-20	LAND OOL ALL LICATION
DRAWN	: APPR:

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

DETAILS





LEGEND	
	PROPERTY LINE
	RIGHT-OF-WAY
	EASEMENT LINE
	BUILDING OUTLINE
	BUILDING OVERHANG
	EDGE OF PAVEMENT
	STANDARD CURB AND GUTTER
	ASPHALT PAVEMENT
d	CONCRETE PAVEMENT
+ + + + + + + + + + + + + + + + + + + +	HEAVY DUTY CONCRETE PAVEMENT
959	PROPOSED 1 FOOT CONTOUR
960——	PROPOSED 5 FOOT CONTOUR
— ·959· — —	EXISTING 1 FOOT CONTOUR
- -960 -	EXISTING 5 FOOT CONTOUR
SAN	SANITARY SEWER
W	WATERMAIN
ST	STORM SEWER
———Е——	ELECTRIC
G	GAS
SAN	EXISTING SANITARY SEWER
W	EXISTING WATERMAIN
ST	EXISTING STORM SEWER
	RETAINING WALL
X	RAILING
x	FENCE
o-a a-o-a	LIGHT POLE (REFER TO PHOTOMETRIC PLAN)
_	BIKE RACK
	ALLEMENT EDOING

X X X X X X GREEN ROOF

OVERSTORY DECIDUOUS TREES	CODE	BOTANICAL / COMMON NAME
	GIBI	Ginkgo biloba 'Autumn Gold' TM Autumn Gold Maidenhair Tree
DECIDUOUS SHRUBS	CODE	BOTANICAL / COMMON NAME
•	AMEO	Amelanchier alnifolia 'Obelisk' Standing Ovation™ Serviceberry
	ARME	Aronia melanocarpa 'Morton' TM Iroquis Beauty Black Chokeberry
•	HAMV	Hamamelis virginiana Common Witch Hazel
\odot	HYDB	Hydrangea paniculata 'ILVOBO' Bobo® Panicle Hydrangea
+	PHOPA	Physocarpus opulifolius 'Amber Jubilee' Ninebark
	RHOG	Rhododendron x 'Golden Lights' Golden Lights Northern Lights Azalea
5 5 24 2 5 4 5 2	RIBG	Ribes alpinum 'Green Mound' Green Mound Alpine Currant
EVERGREEN SHRUBS	CODE	BOTANICAL / COMMON NAME
	BUGV	Buxus x 'Green Velvet' Green Velvet Boxwood
PERENNIALS & GRASSES	CODE	BOTANICAL / COMMON NAME
\bigcirc	ALSU	Allium x 'Summer Beauty' Summer Beauty Allium
*	ASCHW	Astilbe chinensis 'Vision in White' Vision in White Chinese Astilbe
	HOBA	Hosta x 'Blue Angel' Blue Angel Hosta
	HORS	Hosta x 'Regal Splendor' Regal Splendor Hosta
Sull Victoria	PAVI	Panicum virgatum 'Shenandoah' Shenandoah Switch Grass
*	SPHE	Sporobolus heterolepis Prairie Dropseed

LANDSCAPE MATERIAL NOTES

- 1. ALL DISTURBED AREAS TO RECEIVE SEED, FERTILIZER, AND MULCH UNLESS OTHERWISE SPECIFIED. (SEE SHEET L2.0 SEEDING NOTES)
- 2. ALL PLANTING AREAS TO RECEIVE SHREDDED HARDWOOD BARK MULCH UNLESS OTHERWISE SPECIFIED. (SEE SHEET L2.0 MATERIAL NOTES)

THE RIGHT OF WAY IS THE SOLE JURISDICTION OF THE CITY OF MADISON AND IS SUBJECT TO CHANGE AT ANY TIME PER THE RECOMMENDED PLAN BY TRAFFIC ENGINEERING AND CITY ENGINEERING DEPARTMENT

ALL PROPOSED IMPROVEMENTS WITHIN THE PUBLIC RIGHT-OF-WAY OR CONNECTIONS TO CITY OWNED UTILITIES SHALL BE COMPLETED PER THE CITY ISSUED IMPROVEMENTS PLAN (CONTRACT NO. XXXX, PROJECT NO. XXXXX)



2450 Rimrock Road Suite 100 Madison, WI 53713 Telephone: 608-258-5580 Fax: 608-258-5599




PRELIMINARY NOT FOR CONSTRUCTION


10-12-23 LAND USE APPLICATION DRAWN:

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814


LANDSCAPE PLAN





oofEdge Maxx Aluminum Edge Restraint

Part Number LiveRoof System Dimension Finish



LiveRoof Global, LLC
P.O. Box 533
Spring Lake, MI 49456
www.liveroof.com

NOTE: "LIVEROOF" DETAIL PROVIDED FOR REFERENCE ONLY. FINAL DETAILING, SPECIFICATIONS AND DRAINAGE REQUIREMENTS SHALL BE PROVIDED BY LIVEROOF AND/OR ARCHITECTURAL



2450 Rimrock Road Suite 100 Madison, WI 53713 Telephone: 608-258-5580 Fax: 608-258-5599





10-12-23 LAND USE APPLICATION


DRAWN	: APPR:

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715


PROJECT # 23-814


LANDSCAPE PLAN -GREEN ROOF





V. 01-03-2019





OVERSTORY DECIDUOUS TREES	CODE	BOTANICAL / COMMON NAME	CONT	SIZE	QTY
$\overline{(\cdot)}$	GIBI	Ginkgo biloba 'Autumn Gold' TM Autumn Gold Maidenhair Tree	B & B	2.5" Cal	1
DECIDUOUS SHRUBS	CODE	BOTANICAL / COMMON NAME	CONT	SIZE	QTY
•	AMEO	Amelanchier alnifolia 'Obelisk' Standing Ovation™ Serviceberry	B & B	Min. 24"-36"	3
• 5	ARME	Aronia melanocarpa 'Morton' TM Iroquis Beauty Black Chokeberry	#3	Min. 12"-24"	8
••	HAMV	Hamamelis virginiana Common Witch Hazel	B & B	Min. 36" tall	1
$\overline{\bullet}$	HYDB	Hydrangea paniculata 'ILVOBO' Bobo® Panicle Hydrangea	#3	Min. 12"-24"	11
(+)	PHOPA	Physocarpus opulifolius 'Amber Jubilee' Ninebark	#5	Min. 24" Ht.	6
$\overline{\mathcal{A}}$	RHOG	Rhododendron x 'Golden Lights' Golden Lights Northern Lights Azalea	#3	Min. 24"	11
5 4 4 2 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	RIBG	Ribes alpinum 'Green Mound' Green Mound Alpine Currant	#3	Min. 12"-24"	18
EVERGREEN SHRUBS	CODE	BOTANICAL / COMMON NAME	CONT	SIZE	QTY
£	BUGV	Buxus x 'Green Velvet' Green Velvet Boxwood	#3	Min. 12"-24"	7
PERENNIALS & GRASSES	CODE	BOTANICAL / COMMON NAME	CONT	SIZE	QTY
	ALSU	Allium x 'Summer Beauty' Summer Beauty Allium	#1	Min. 8"-18"	17
*	ASCHW	Astilbe chinensis 'Vision in White' Vision in White Chinese Astilbe	#1	Min. 8"-18"	40
	HOBA	Hosta x 'Blue Angel' Blue Angel Hosta	#1	Min 8"-18"	25
	HORS	Hosta x 'Regal Splendor' Regal Splendor Hosta	#1	Min. 8"-18"	14
man • EEE Annance	PAVI	Panicum virgatum 'Shenandoah' Shenandoah Switch Grass	#1	Min. 8"-18"	25
*	SPHE	Sporobolus heterolepis Prairie Dropseed	#1	Min. 8"-18"	30

zoning lot. There are three methods for calculating landscape points depending on the size of the lot and Zoning District.

(A) For all lots except those described in (B) and (C) below, five (5) landscape points shall be provided for each three hundred (300) square feet of developed area.

Total square footage of developed area:

(B) For lots larger than five (5) acres, points shall be provided at five (5) points per three hundred (300) square feet for the first Five (5) developed acres, and one (1) point per one hundred (100) square feet for all additional acres.

Total square footage of developed area:

Five (5) acres =

First five (5) developed acres =

PLANT SCHEDULE

Remainder of developed area:

Total landscape points required

(C) For the Industrial – Limited (IL) and Industrial – General (IG) districts, one (1) point shall be provided per one hundred (100) square feet of developed area.

Total square footage of developed area:

Total landscape points required:

TABULATION OF LANDSCAPE CREDITS AND POINTS

				/ EXISTING CAPING	NEW / PROPOSED LANDSCAPING	
PLANT TYPE/ELEMENT	MINIMUM INSTALLATION SIZE	POINTS	QUANTITY	POINTS ACHIEVED	QUANTITY	POINTS ACHIEVED
OVERSTORY DECIDUOUS TREE	2.5" CAL MIN.	35	0	0	1	35
TALL EVERGREEN TREE	5-6' TALL MIN.	35	0	0	0	0
ORNAMENTAL TREE	1.5" CAL MIN.	15	0	0	0	0
UPRIGHT EVERGREEN SHRUB	3-4' TALL, MIN.	10	0	0	0	0
SHRUB, DECIDUOUS	#3 CONT., MIN. 12"-24"	3	0	0	58	174
SHRUB, EVERGREEN	#3 CONT., MIN. 12"-24"	4	0	0	7	28
ORNAMENTAL GRASS & PERENNIAL	#1 CONT., MIN. 8"-18"	2	0	0	151	302
ORNAMENTAL / DECORATIVE FENCING OR WALL	4 POINTS / 10 LF	.4	0	0	0	0
EXISTING SIGNIFICANT SPECIMAN TREE	14 POINTS / CAL. (MAXIMUM 200 POINTS PER TREE)	14	0	0	0	0
LANDSCAPE FURNITURE	5 POINTS PER SEAT (WITHIN PUBLICALLY ACCESSIBLE DEVELOPED AREA. CANNOT COMPRISE MORE THAN 5% OF TOTAL REQUIRED POINTS)	5	0	0	0	0
		SUBTOTAL		0		539
TOTAL NUMBER OF POINTS PROVIDED		539				

GENERAL NOTES

- 1. REFER TO THE EXISTING CONDITIONS SURVEY FOR EXISTING CONDITIONS NOTES AND LEGEND.
- 2. JSD SHALL BE HELD HARMLESS AND DOES NOT WARRANT ANY DEVIATIONS BY THE OWNER/CONTRACTOR FROM THE APPROVED CONSTRUCTION PLANS THAT MAY RESULT IN DISCIPLINARY ACTIONS BY ANY OR ALL REGULATORY AGENCIES.
- 3. DRAWING FOR REVIEW NOT FOR CONSTRUCTION UNLESS OTHERWISE NOTED IN THE TITLE BLOCK.
- 4. THE LANDSCAPE CONTRACTOR SHALL COORDINATE ALL FINE GRADING AND TOPSOILING WITH GENERAL
- 5. CONTRACTOR SHALL REVIEW SITE CONDITIONS FOR UTILITY CONFLICTS, DRAINAGE ISSUES, SUBSURFACE ROCK, AND PLANT PLACEMENT CONFLICTS PRIOR TO PLANT INSTALLATION. REPORT ANY CONDITIONS THAT MAY HAVE ADVERSE IMPACT ON PLANTING OPERATIONS TO LANDSCAPE ARCHITECT
- 6. DO NOT COMMENCE PLANTING OPERATIONS UNTIL ALL ADJACENT SITE IMPROVEMENTS, IRRIGATION INSTALLATION (IF APPLICABLE), AND FINISH GRADING ARE COMPLETE
- 7. GENERAL: ALL WORK IN THE R-O-W AND PUBLIC EASEMENTS SHALL BE IN ACCORDANCE WITH LOCAL MUNICIPAL REQUIREMENTS. JSD SHALL BE HELD HARMLESS AND DOES NOT WARRANT ANY DEVIATIONS BY THE OWNER/CONTRACTOR FROM THE APPROVED CONSTRUCTION PLANS THAT MAY RESULT IN DISCIPLINARY ACTIONS BY ANY OR ALL REGULATORY AGENCIES. LOCATE ALL UTILITIES PRIOR TO CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR REPAIRING ANY DAMAGE DONE TO UTILITIES. CONTRACTOR MUST CALL 1-800-242-8511 FOR UTILITY LOCATIONS AT LEAST THREE DAYS PRIOR TO DIGGING. HAND DIG AND INSTALL ALL PLANTS THAT ARE NEAR EXISTING UTILITIES. PROTECT PREVIOUSLY INSTALLED WORK OF OTHER TRADES. CONTRACTOR IS RESPONSIBLE FOR STAKING THE PLANT MATERIALS FOR REVIEW BY OWNER PRIOR TO DIGGING AND PLACEMENT AND SHALL COORDINATE ALL FINE GRADING AND RESTORATION WITH THE GRADING CONTRACTOR.
- 8. DELIVERY AND HANDLING: DO NOT DELIVER MORE PLANT MATERIALS THAN CAN BE PLANTED IN ONE DAY, UNLESS ADEQUATE, APPROPRIATE AND SECURE STORAGE IS PROVIDED AND APPROVED BY OWNER'S REPRESENTATIVE. AT ALL TIMES, PROTECT ALL PLANT MATERIALS FROM WIND AND DIRECT SUN. DELIVER PLANTS WITH LEGIBLE IDENTIFICATION LABELS. PROTECT PLANTS DURING DELIVERY AND DO NOT PRUNE PRIOR TO DELIVERY. ALL TREES AND SHRUBS SHALL BE PLANTED ON THE DAY OF DELIVERY; IF THIS IS NOT POSSIBLE, PROTECT THE PLANT MATERIALS NOT PLANTED BY STORING THEM IN A SHADED, SECURE AREA, PROTECTING THE ROOT MASS WITH WET SOIL, MULCH, HAY OR OTHER SUITABLE MEDIUM. CONTRACTOR TO KEEP ALL PLANT MATERIALS ADEQUATELY WATERED TO PREVENT ROOT DESICCATION. DO NOT REMOVE CONTAINER GROWN STOCK FROM CONTAINERS BEFORE TIME OF PLANTING. DO NOT PICK UP CONTAINER OR BALLED PLANTS BY STEM OR ROOTS. ALL PLANTS SHALL BE LIFTED AND HANDLED FROM THE BOTTOM OF THE CONTAINER OR BALL. PERFORM ACTUAL PLANTING ONLY WHEN WEATHER AND SOIL CONDITIONS ARE SUITABLE IN ACCORDANCE WITH LOCALLY ACCEPTED BEST HORTICULTURAL PRACTICES.
- 9. MATERIALS PLANTS: ALL PLANTS SHALL CONFORM TO THE LATEST VERSION OF THE AMERICAN STANDARD FOR NURSERY STOCK ANSI Z60.1. PLANTS SHALL BE TRUE TO SPECIES AND VARIETY SPECIFIED AND NURSERY GROWN IN ACCORDANCE WITH GOOD HORTICULTURAL PRACTICES UNDER CLIMATIC CONDITIONS SIMILAR TO THOSE IN THE LOCALITY OF THE PROJECT FOR AT LEAST 2 YEARS. PLANTS SHALL BE FRESHLY DUG (DURING THE MOST RECENT FAVORABLE HARVEST SEASON). PLANTS SHALL BE SO TRAINED IN DEVELOPMENT AND APPEARANCE AS TO BE UNQUESTIONABLY SUPERIOR IN FORM, COMPACTNESS, AND SYMMETRY. PLANTS SHALL BE SOUND, HEALTHY, VIGOROUS, WELL BRANCHED AND DENSELY FOLIATED WHEN IN LEAF, AND FREE OF DISEASE AND INSECTS (ADULT EGGS, PUPAE OR LARVAE). THEY SHALL HAVE HEALTHY, WELL-DEVELOPED ROOT SYSTEMS AND SHALL BE FREE FROM PHYSICAL DAMAGE OR OTHER CONDITIONS THAT WOULD PREVENT THRIVING GROWTH OR PREMATURE MORTALITY. PLANTS SHALL BE OF THE HIGHEST QUALITY, POSSESS TYPICAL GROWTH HABITS AND FORM FOR THEIR SPECIES AND BE FREE OF INJURY. PARKWAY TREES AND PARKING LOT TREES SHALL HAVE A MINIMUM BRANCHING HEIGHT OF SIX (6) FEET ABOVE THE GROUND TO ALLOW ADEQUATE VISUAL AND PHYSICAL CLEARANCE.
- 10. PRUNING: THE CONTRACTOR SHALL PRUNE ALL TREES AND REPAIR ANY INJURIES THAT OCCURRED DURING THE PLANTING PROCESS. DOUBLE LEADERS, DEAD BRANCHES, AND LIMBS DAMAGED OR BROKEN DURING THE PLANTING PROCESS, SHALL BE PRUNED. THIS SHALL BE THE ONLY PRUNING ALLOWED AT PLANTING. PRUNING SHALL CONFORM TO THE LATEST VERSION OF THE AMERICAN STANDARD FOR TREE CARE OPERATIONS, ANSI A300. PRUNE TREES IN ACCORDANCE WITH NAA GUIDELINES. DO NOT TOP TREES. PRUNE SHRUBS ACCORDING TO STANDARD HORTICULTURAL PRACTICES. ON CUTS OVER 3/4" IN DIAMETER AND BRUISES OR SCARS ON BARK, TRACE THE INJURED CAMBIUM LAYER BACK TO LIVING TISSUE AND REMOVE. SMOOTH AND SHAPE WOUNDS SO AS NOT TO RETAIN WATER. TREAT THE AREA WITH AN APPROVED INCONSPICUOUS LATEX BASED ANTISEPTIC TREE PAINT, IF PRUNING OCCURS "IN SEASON". DO NOT PRUNE ANY OAK TREES DURING THE MONTHS FROM APRIL TO OCTOBER.
- 11. CLEANUP: THE WORK AREA SHALL BE KEPT SAFE AND NEAT AT ALL TIMES. DISPOSED OF EXCESS SOIL. REMOVE ALL CUTTINGS AND WASTE MATERIALS. SOIL AND BRANCHES. BIND AND WRAP THESE MATERIALS, ANY REJECTED PLANTS, AND ANY OTHER DEBRIS RESULTING FROM ALL PLANTING TASKS AND PROMPTLY CLEAN UP AND REMOVE FROM THE PROJECT SITE. UNDER NO CIRCUMSTANCES SHALL THE ACCUMULATION OF SOIL, BRANCHES OR OTHER DEBRIS BE ALLOWED UPON A PUBLIC PROPERTY IN SUCH A MANNER AS TO RESULT IN A PUBLIC SAFETY HAZARD OR DAMAGE. LIKEWISE, UNDER NO CIRCUMSTANCES SHALL ANY DEBRIS OR INCIDENTAL MATERIALS BE ALLOWED UPON ADJACENT PRIVATE PROPERTY.
- 12. ANY SUBSTITUTIONS IN PLANT TYPE, LOCATION, OR SIZE SHALL BE APPROVED BY LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
- 13. CONTRACTOR TO VERIFY PLANT MATERIAL QUANTITIES AND SQUARE FOOTAGES. QUANTITIES SHOWN ON PLAN TAKE PRECEDENCE OVER THOSE ON SCHEDULE.

LANDSCAPE MATERIAL NOTES

- 1. MATERIALS PLANTING MIXTURE: ALL HOLES EXCAVATED FOR TREES. SHRUBS. PERENNIALS AND ORNAMENTAL GRASSES SHALL BE BACKFILLED WITH TWO (2) PARTS TOPSOIL, ONE (1) PART SAND AND ONE (1) PART COMPOST. SOIL MIXTURE SHALL BE WELL BLENDED PRIOR TO INSTALLATION.
- 2. MATERIALS TOPSOIL: TOPSOIL TO BE CLEAN, FRIABLE LOAM FROM A LOCAL SOURCE, FREE FROM STONES OR DEBRIS OVER 3/4" IN DIAMETER, AND FREE FROM TOXINS OR OTHER DELETERIOUS MATERIALS. TOPSOIL SHALL HAVE A pH VALUE BETWEEN 6 AND 7. TOPSOIL AND PLANTING SOIL SHALL BE TESTED TO ENSURE CONFORMANCE WITH THESE SPECIFICATIONS AND SHALL BE AMENDED TO MEET THESE SPECIFICATIONS. PROVIDE TEST RESULTS TO OWNER'S REPRESENTATIVE PRIOR TO PLACEMENT. DO NOT PLACE FROZEN OR MUDDY TOPSOIL. APPLY SOIL AMENDMENTS TO ALL LANDSCAPE AREAS PER SOIL TEST.
- 3. MATERIALS SHREDDED HARDWOOD BARK MULCH: ALL PLANTING AREAS LABELED ON PLAN SHALL RECEIVE CERTIFIED WEED FREE SHREDDED HARDWOOD BARK MULCH INSTALLED TO A MINIMUM AND CONSISTENT DEPTH OF 3-INCHES. SHREDDED HARDWOOD BARK MULCH SIZE & COLOR TO BE APPROVED BY OWNER'S REPRESENTATIVE PRIOR TO INSTALLATION. FERTILIZER SHALL BE IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY AND STATE REQUIREMENTS. SHREDDED HARDWOOD BARK MULCH AREAS SHALL NOT RECEIVE WOVEN WEED BARRIER FABRIC.
- 4. MATERIALS TREE & SHRUB RINGS: ALL TREES AND/OR SHRUBS PLANTED IN SEEDED LAWN AREAS TO BE INSTALLED WITH A MINIMUM 4' DIAMETER SHREDDED HARDWOOD BARK MULCH TREE RING SPREAD TO A CONSISTENT DEPTH OF 3-INCHES. ALL TREE RINGS SHOULD BE INSTALLED WITH A 5" DEPTH SHOVEL CUT EDGE, ANGLED 45 DEGREES INTO SOIL AT A 5' DIAMETER ABOUT THE CENTER OF THE TREE PLANTING. A PRE-EMERGENT GRANULAR HERBICIDE WEED-PREVENTER SHOULD BE MIXED WITH MULCH USED TO INSTALL TREE RING AS WELL AS TOPICALLY APPLIED TO COMPLETED INSTALLATION OF TREE RING.
- 5. MATERIALS ALUMINUM EDGING: EDGING SHALL BE 1/8" X 4", ALUMINUM EDGING, MILL FINISH. OWNER'S REPRESENTATIVE SHALL APPROVE PRODUCT SPECIFICATION PROVIDED BY LANDSCAPE

CONTRACTOR AND OWNER RESPONSIBILITY NOTES

- GUARANTEE: THE CONTRACTOR SHALL GUARANTEE ALL PLANTS THROUGH ONE (1) YEAR AFTER ACCEPTANCE BY THE OWNER'S REPRESENTATIVE. PLANTS SHALL BE ALIVE AND IN HEALTHY AND FLOURISHING CONDITION AT THE END OF THE GUARANTEE PERIOD. THE CONTRACTOR SHALL REPLACE (AT NO COST TO OWNER) ANY PLANTS THAT ARE DEAD OR NOT IN A VIGOROUS THRIVING CONDITION. REPLACEMENT PLANTS SHALL BE OF THE SAME KIND AND SIZE AS ORIGINALLY SPECIFIED UNLESS OTHERWISE DIRECTED BY OWNER'S REPRESENTATIVE. RESTORE BEDS AS NECESSARY FOLLOWING PLANT REPLACEMENT, INCLUDING BUT NOT LIMITED TO BEDDING, EDGING, MULCH, ETC. REPLACE PLANTS DAMAGED AT TIME OF PLANTING. REPAIR AREAS DISTURBED IN ANY WAY DURING PLANT REPLACEMENT AT NO COST TO OWNER. CONTRACTOR SHALL PROVIDE A ONE (1)—YEAR STRAIGHTENING GUARANTEE FOR ALL TREES.
- CONTRACTOR IS RESPONSIBLE FOR STAKING THE PLANT MATERIALS FOR REVIEW BY OWNER'S REPRESENTATIVE PRIOR TO DIGGING AND PLACEMENT AND SHALL COORDINATE ALL FINE GRADING AND RESTORATION WITH THE GRADING CONTRACTOR.
- MAINTENANCE: (CONTRACTOR) FOR ALL PLANTINGS, SEEDED AND/OR SODDED LAWN AREAS: THE CONTRACTOR SHALL MAINTAIN ALL PLANTINGS AND LAWN AREAS FOR A MINIMUM TIME PERIOD OF 60 DAYS, UNTIL FINAL ACCEPTANCE BY OWNER'S REPRESENTATIVE. THE CONTRACTOR IS RESPONSIBLE FOR ADEQUATELY WATERING PLANTS AND LAWN/TURFGRASS DURING THIS 60 DAY ESTABLISHMENT PERIOD. CONTRACTOR IS RESPONSIBLE FOR THE ESTABLISHMENT OF HEALTHY VIGOROUS PLANT MATERIALS AND LAWN/TURFGRASS GROWTH. CONTRACTOR IS ALSO RESPONSIBLE FOR ANY PRUNING OF PLANT MATERIALS, AND SHAPING AND/OR REPLACEMENT OR SUPPLEMENT OF DEFICIENT SHREDDED HARDWOOD BARK MULCH DURING THIS PERIOD. LONG TERM PLANT MATERIALS AND LAWN/TURFGRASS MAINTENANCE AND ANY PROGRAM FOR SUCH IS THE RESPONSIBILITY OF THE OWNER. ALL PLANTINGS AND LAWN/TURFGRASS AREAS SHALL BE MAINTAINED IN A MANICURED CONDITION UNTIL THE TIME WHEN THE OWNER'S ACCEPTANCE IS GIVEN.
- MAINTENANCE: (OWNER) THE OWNER IS RESPONSIBLE FOR THE CONTINUED MAINTENANCE, REPAIR AND REPLACEMENT OF ALL LANDSCAPING MATERIALS AND WEED BARRIER FABRIC AS NECESSARY FOLLOWING THE ONE (1) YEAR CONTRACTOR GUARANTEE PERIOD.



2450 Rimrock Road Suite 100 Madison, WI 53713 Telephone: 608-258-5580 Fax: 608-258-5599



NOT FOR CONSTRUCTION

10-12-23 LAND USE APPLICATION

APPR: DRAWN:

NEIGHBORHOOD HOUSE 29 S. MILLS STREET MADISON, WI 53715

PROJECT # 23-814

LANDSCAPE **DETAILS & NOTES**



	7		Λ
L		•	U