

XSPW-3MC

OSQ-A-NM-4ME-K-57K-UL-BZ w/OSQ-DABZ OSQK-4ME-2 2 @ 90 DEGREES 17291

All Calc Points

Fixture Mounting Height:

Pole Mounted: 1, 20' AFG (17' Pole + 3.0' Base)


Proposed Poles Meets 140MPH Sustained Winds

(1) - PS4S17C3BZ - (17' X 4" X 0.125", Steel Square Pole, 2@90°)

Customer to verify Color, Mounting, Fixture Location and

ustomer responsible to verify ordering information/ catalogue number prior to placing order. 1200 92nd Street - Sturtevant, WI 53177 /SR-21667 Scale: 1"=10' // Footcandles calculated at grade Filename: 160307NB1CJW.AGI Layout by: Collin Witherow Illumination results shown on this lighting design are based on project parameters provided to Cree, Inc. used in conjunction with luminaire test procedures conducted under laboratory conditions. Actual project conditions differing from these design parameters may affect field results. he customer is responsible for verifying dimensional accuracy along with compliance with any applicable electrical, lighting, or energy code





BSE1908 201-215 N. BLOUNT STREET | RMS | CHAPTER | AND SANTARY SEVER ELEVATION TABLE
| RMST | ELFANTON | ELSANTON | ELSAN STORM SEWER MANAGE STORM SEWER MANAGE ONLY NE PPE VISILE SANDRY SEWER MANAGE CANDRY SEWER MANAGE

	LEGEND			
	1-1/4" SOLID IRON ROD FOUND		BOLLARD	
	1" IRON PIPE FOUND	0	CISTERN	
x	FOUND CHISELED "X" IN CONCRETE	0	WATER VALVE	
	FOUND CHISELED X IN CONCRETE	6	GAS METER	
-	3/4" X 18" SOLID IRON RE-ROD	Ø	UTILITY POLE	
0	SET, WT. 1.50 lbs./ft.		CHAIN LINK FENCE	
— он —	- OVERHEAD UTILITY WIRE		LIGHT POLE	
	BURIED GAS LINE		GUY WRE	
	- WATER MAIN	$\oplus$	DECIDUOUS TREE	
— sa —	- SANITARY SEWER	( )	INDICATES RECORDED AS	
st	STORM SEWER		DISTANCES ARE MEASURED TO THE NEAREST HUNDREDTH OF A	
—-E—	- BURIED ELECTRIC		FOOT, BUILDINGS ARE MEASURED TO THE NEAREST	
855	- MAJOR CONTOUR		TENTH OF A FOOT.	
854	- MINOR CONTOUR			
3(854,0	EXISTING SPOT ELEVATION			

2) No attempt has been made as a part of this survey to obtain or show data concerning condition or capacity of any utility or municipal/public service facility. For information regarding these utilities or facilities, please contact the apprepriate agencies.

3) Dates of field work: August 4-5, August 11-12, 2016

4) Surveyor has made no investigation or independent search for easements of record, encumbrances restrictive covenants, ownership title evidence, or any other facts that an accurate and current title search may disclose.

7) Routing of public utilities is based upon markings provided by Digger's Hatline Ticket Numbers 20163303965, 20163303975, 20163303981 and visible above ground structures. Additional buried utilities/structures may be encounteed. Ne excovations were mode to located utilities. Before excavations are performed contact Digger's Hatline.


8) 201 N. Blount St. parcel area = 8,728 square feet
 207, 209 and 211 N. Blount St. parcel area = X,XXX square feet
 213 and 215 N. Blount St. parcel area = X,XXX square feet


9) Elevations are based upon NAVD88 datum. The Surveyor transferred elevations to the site utilizing the MSCORS network AND RTK GPS surveying methods.





C100





- Erasion control devices and/or structures shall be installed prior to clearing and grubbing perations. These shall be properly maintained for maximum effectiveness until vegetation is re-established.
- Erosion control is the responsibility of the contractor until acceptance of this project. Erosion control measures as shown shall be the minimum precautions that will be allowed. The contractor shall be responsible for recognizing and correcting all erosion control problems that are the result of construction activities. Additional erosion control measures, as requested in wirtling by the state or local inspectors, or the developers, engineer, shall be installed within 124 hours.
- 3. All erasion control measures and structures serving the site must be inspected at least weekly or within 24 hours of the time 0.5 inches of rain is produced. All maintenance will follow an inspection within 24 hours. Inspection schedule and record keeping shall comply with NR 216.46(9), Wis. Adm. Code.
- 4. Construction Entrances Provide a stone tracking pad at each point of access. Install according to WDNR Standard 1057. Refer to WDNR's stormwater web page of technical standards at: http://dn.wi.gov/tapic/stormwater/standards/const\_standards.html. The Tracking Pad must be maintained in a condition that prevents the tracking of material and the public street.
- Temporary stabilization using anionic polymer. After November 1, 20XX, anionic polyacrylamide will be applied to all disturbed areas where the municipality's engineer or WDNR representatives deem stabilization and/or erosion to be problematic. Application of polyacrylamide will be according to WDNR Conservation Proctice standard 1050, Erosion Control Land Application of Anionic Polyacrylamide. Refer to WDNR's starmwater web page of technical standards at http://dnr.wi.gov/topic/stormwater/standards/const\_standards.html
- 6. Deer Tilling Following rough grotting, deep tilling (a.k.a. subspilling) will be performed on all proded proces outside the footprint of street footprints. The operation sould be accomplished using tent straight steel shows drawn by tracked monthings, Zooh shows the 24 to 35 inches long, positioned over the tractor tracks, and spaced 4 to 5 feet aport. Deep tilling shall be done on dry sail and across the slope. Refer to the Dane County Erosian Control and Stormyster Management Monual, Appendix IDI., which is accessible from the Dane County Lickse and Waters Commission web site at: http://www.danewaters.com/business/stormwater.aspx.
- Soil Stockpiles A row of slit fence placed downslope and at least 10 feet away from the stockpile shall protect all stockpiles. Soil stockpiles that are inactive
  for more than 14 consecutive days shall be stabilized with seed & mulch, erasion mat, polymer, or covered with tarps or similar material. No stockpile shall be placed within 20 feet of a drainage way.
- 8. Devotoring Water purpose from the site shall be treated by using a temporary sedimentation basis, no protosis devastering basis, geotestic bag, or an equivalent service. Show on the glant the anticipated locations of devotoring activity, and provide an engineering detail of the devotoring system. Devotes shall comply with WDNR Technical Standards 1051 found at: http://drx.wi.gov/topic/stormwater/standards/const\_standards.html This water shall be discharged in a manner that does not induce erosion of the site or objector troperty.
- 9. Storm Sewer Inlets Provide WDOT Type D "CatchAll" inlet protection or equivalent. Refer to WDOT Product Acceptability List at: http://www.dot.wisconsin.gov/business/engrserv/pal.htm. Inlet protection shall be installed prior to the storm sewer system receiving site runoff. Other than for performing maintenance, these devices shall not be removed until plat—level stabilization is complete.
- 10. Building and waste materials shall be prevented from running-off the site and entering waters of the state in conformance with NR151.12(6m).
- 11. No solid material shall be discharged or deposited into waters of the state in violation of Ch. 30 or 31 of the Wisconsin State Statutes or 33 USC 1344 permits.
- 12. Erosion control devices shall adhere to the technical standards found at: http://dnr.wi.gov/runoff/stormwater/techstds.htm and comply with all City of Madison
- 13. All debris tracked onto public streets shall be be swept or scraped clean by the end of each workday.
- 14. All building and waste material shall be handled properly to prevent runoff of these materials off of the site.
- 15. All disturbed areas shall be seeded immediately after grading activities have been completed.
- 16. All disturbed areas, except paved areas, shall receive a minimum of four (4) inches of topsoli, fertilizer, seed, and mulch. Seed mixtures shall be selected appropriate to the intended function. A qualified Landscaping Contractor, Landscape Architect or Nursery can be consulted for recommendations. Seeding rates shall be based on pounds or ounces of Pure Live Seed per acre and shall be provided by the seed supplier. Fertilizer can be applied to help promote growth, but a soil test is recommended to determine the type and amount of fertilizer to be applied. All seeding and restoration shall be in conformance to WDNR Technical Standard 1059 found at http://dnr.wi.gov/topic/standard/standard/sconst\_standard.html. Seeding and sodding may only be used from May 1st to September 15th of any year. Temporary seed shall be used after September 15. If temporary seeding is used, a permanent cover shall also be required as part of the final site stabilization.
- 17. For the first six (6) weeks after the initial stabilization of a disturbed area, watering shall be performed whenever more than seven (7) days of dry weather

## Emergency Contact

Michael Matty 2132 Fordem Avenue Suite #1400 Madison W 153704 608.301.0000 mmatty@pgrentals.com www.rpgrentals.com


## Schedule:


June 13, 2017 Install silt fence and construction entrance.


June 14, 2017 Begin disturbance of site ground cover.


May 1, 2018 Base course installed. Apply seed and mulch to all disturbed

July 1, 2018 Vegetation established.









Dial 🔐 or (800) 242-8511 www.DiggersHotline.com

-Buree WALS PROJECT DEAMN E LC roup 1/4 POINT
201-215 N. Blount St.
Madison, WI 33704
ance Property Gru
32 Fordem Ave. Suite #14
Madison, WI 53704 Renaissance Pro 2132 Fordem Av Madison, ' Ä Printed 2017 PROJECT #: BSE1908 PLOT DATE: 03-15-201 Mar REVISION DATES: ISSUE DATES: EROSION CONTROL NOTES AND DETAILS

Burse

DRAWING NUMBER

C500

