

# Watershed Study Overview and Stricker's/Mendota Proposed Solutions

by City of Madison Engineering Division April 20, 2022

# **Presentation Overview**

- Phasing and Schedule
- Process (with anecdotal Lessons Learned)
- Proposed Solutions
  - Stricker's/Mendota
- Comments/Questions





# Watershed Study Phasing







# **Round 1 Watershed Studies**



- Madison Pheasant Branch
  - In-House
  - PM/Modeling Lead: Caroline Burger
- Spring Harbor
  - Outsourced
  - PM: Jojo O'Brien
- Stricker's/Mendota
  - Outsourced
  - PM: Lauren Striegl/Caroline Burger
- Wingra West
  - Outsourced
  - PM: Phil Gaebler





#### **Proposed and Actual Schedule**

Round 1 Watershed Studies



Example: Madíson Pheasant Branch



Item	Quantity
Watershed Area (acres)	3,300
Number of Subcatchments (#)	451
Public Stormwater Inlets and Access Structures in Watershed (#)	2,500
Total storm sewer pipes in Watershed (#)	2,200 segments; 31.4 miles
Storm sewer pipes in Model (#; length)	1,452 segments; 27.4 miles
Open channels in Model (#; length)	90 segments; 6.7 miles
Detention Ponds in Model (#)	44



Example: Madíson Pheasant Branch

#### > Data collection

- >Ground/storm sewer survey
- Monitoring rain depth, pond and storm sewer water levels, storm sewer flow
- Flood reports
- Focus groups flooding experiences



Example: Madíson Pheasant Branch

#### Public Information

- Public Input Meeting #1 May 4, 2019
- Focus Groups 9 Focus Groups in September 2019
- Public Input Meeting #2 June 18, 2020
- Project website creation and updates – <u>www.cityofmadison.com/P</u> <u>heasantBranchWatershed</u>





Example: Madíson Pheasant Branch

- Media television, radio, Facebook, Twitter, Podcast
  - Coverage about Watershed studies as a whole on Channels 3, 27, 15, State Journal, Cap Times
  - Flooding awareness, education posts, photos and videos from focus groups on social media
  - Two podcast episodes on Everyday Engineering: Historic Flooding, Watershed studies





Example: Madíson Pheasant Branch

#### Existing Conditions Model Construction and Calibration



#### Working with City Legal Department

- Review Existing Condition Reports
- Provide following disclaimer for inundation mapping

#### LEGAL DISCLAIMER

THE INTENT OF THE FLOOD ZONE MAPS ARE TO ASSIST INDIVIDUALS IN QUICKLY FINDING GENERAL FLOOD ZONE INFORMATION FOR THE INCORPORATED AND UNINCORPORATED AREAS OF THE CITY OF MADISON. FLOOD ZONE MAPS DO NOT NECESSARILY IDENTIFY ALL AREAS SUBJECT TO FLOODING. THE CITY OF MADISON PROVIDES THE MAPS AS AN ADVISORY TOOL FOR FLOOD HAZARD AWARENESS. INDIVIDUALS SHOULD NOT USE FLOOD ZONE MAPS AS THEIR PRIMARY RESOURCE FOR MAKING OFFICIAL FLOOD ZONE DETERMINATIONS FOR INSURANCE, LENDING, OR OTHER RELATED PURPOSES. THIS IS NOT AN OFFICIAL FLOOD MAP.

THE CITY OF MADISON ASSUMES NO LIABILITY FOR ANY ERRORS, OMISSIONS, INACCURACIES, COMPLETENESS OR USEFULNESS OF THE INFORMATION PROVIDED REGARDLESS OF THE CAUSE OR FOR ANY DECISION MADE, ACTION TAKEN, OR ACTION NOT TAKEN BY THE USER IN RELIANCE UPON ANY OF THE MAPS OR INFORMATION PROVIDED.



#### Existing Conditions 1% Chance (100-yr) Event Inundation Mapping



Storm Events Analyzed

- 100% chance (1-year)
- ▶ 50% chance (2-year)
- > 20% chance (5-year)
- 10% chance (10-year)
- 4% chance (25-year)
- 1% chance (100-year)
- 0.2% chance (500-year)
- August 2018



CITY OF MAD

Each storm event takes 2-6 hours of simulation time



Flood Reduction Targets

- 10% Chance Event
  - No surcharging of storm sewer onto roadway (storm sewer pipes are sized for event)
- 4% Chance Event
  - 0.2' at Centerline of Road (roads passable for emergency vehicles)
- 1% Chance Event
  - No structure (home/building) flooding
  - No greenway crossing overflow (stormwater does not come out of greenway and flow over the road)
- 0.2% Chance Event
  - Safe conveyance of overflow



Proposed Solutions - to get to Draft Solutions for Discussion

- Brainstorm ideas
  - Meet with Engineering Staff
- Conceptually size mitigation measures
  - Meeting with Engineering Staff
- Conduct initial analysis of mitigation measures
  - Some computer modeling
  - Some manual analysis
  - Meet with Engineering Staff
- Revise initial analysis based on feedback
  - Mostly computer modeling
  - Meet with Engineering Staff



Proposed Solutions - to Finalize Solutions and Report

- Internal Agency Review
  - Engineering meets with Internal Agency staff to get feedback
  - Revise solutions based on feedback
- 3<sup>rd</sup> Public Information Meeting
  - Present solutions to public
  - Revise solutions based on feedback
- Finalize Draft Report
- 30-day Public Comment Period
  - Revise solutions based on feedback
- City Board and Commission Review and Approvals
- Finalize Report



# Stricker's/Mendota Watershed Proposed Solutions



#### Results

Stricker's/Mendota Watershed

- 10% Chance Target no ponding on streets
  - Existing Conditions: 3.5 miles out of 6.1 miles of storm sewer not meeting target (58%)
  - Proposed Conditions: 0.2 miles out of 6.1 miles of storm sewer not meeting target (4%) - reduced 3.3 miles
- 4% Chance Target streets passable for emergency vehicles
  - Existing Conditions: 4.9 miles out of 17.7 miles of streets not meeting target (28%)
  - Proposed Conditions: 0.5 miles out of 17.7 miles of streets not meeting targets (1%) - reduced 4.4 miles
- 1% Chance Target no structure flooding
  - Existing Conditions: 91 out of 1,470 structures not meeting target (6%)
  - Proposed Conditions: 15 out of 1,470 structures not meeting target (1%) reduced 76 structures



#### Stricker's/Mendota Watershed Proposed Mitigation Measures





#### Stricker's/Mendota Watershed Proposed Mitigation Measures

- Storm Sewer Pipe Size Increases
- Significant increase to conveyance capacity
  - Longmeadow Drive Relief Sewer
    - Parallel 60" relief sewer from existing Harvest Hill connection to Stricker's Forebay
    - Improvements to Stricker's Pond/Tiedemann's Pond outlets
  - Mendota-Grassman Greenway Improvements
    - Improve greenway conditions between University Avenue to Old Middleton Drive and University Ave to Camelot Drive
    - Parallel 72" pipe beneath University Avenue at the crossing
    - Replace and upsize culverts beneath Lake Mendota Drive

#### Longmeadow Relief Storm Sewer

Stricker's/Mendota Watershed

 Install parallel 60" relief sewer from existing Harvest Hill connection along Gammon Road and Longmeadow Drive to Stricker's Forebay

Target: Prevent roadway flooding in 10% event



#### **Stricker's Pond Outfall**

Stricker's/Mendota Watershed

 Install additional 24" outfall from Stricker's Pond to Tiedeman Pond

Target: Prevent increase in WSE in Stricker's Pond due to improvements in Madison

 Project is located in Middleton



#### **Tiedeman Pond Outfall**

Stricker's/Mendota Watershed

 Installed parallel 36" outfall from Tiedeman Pond to Skyview Pond

Target: Prevent increase in WSE in Tiedeman Pond due to improvements in Madison

 Project is partially in Middleton



#### Lake Mendota Greenway (Upstream)

Stricker's/Mendota Watershed

 Improve greenway flow conditions from Old Middleton Road to University Avenue

Target: Prevent structure flooding in 1% event

 Project requires downstream improvements to be effective

In Design



#### **University Avenue Culvert**

Stricker's/Mendota Watershed

- Install parallel 72" RCP culvert next to existing 6'x10' box culvert
- Target: Prevent structure flooding in 1% chance event
- Requires upstream and downstream greenway improvements to be effective

In Design



#### Lake Mendota Greenway (Downstream)

Stricker's/Mendota Watershed

 Improve greenway flow conditions from University Avenue to Camelot Drive

Target: Prevent structure flooding in 1% event

- Project requires upstream and downstream culvert improvements
- In Design



#### Lake Mendota Drive Culvert

Stricker's/Mendota Watershed

- Replace existing culverts with 2 – 4'x8' Box Culverts
- Target: Prevent structure flooding in 1% chance event
- Requires upstream greenway and culvert improvements to be effective
- In Design



# **Comments/Questions/Open Discussion**

