URBAN DESIGN COMMISSION APPLICATION

UDC

City of Madison Planning Division 126 S. Hamilton St. P.O. Box 2985 Madison, WI 53701-2985 (608) 266-4635



Complete all sections of this application, including the desired meeting date and the action requested.

If you need an interpreter, translator, materials in alternate formats or other accommodations to access these forms, please call the phone number above immediately.

Paid	Receipt #
Date received	
Received by	
Aldermanic District	
Zoning District	
Jrban Design District	
Submittal reviewed by	

1. Project Information

1101 E. Washington Ave., Madison, WI 53703 Address: Madison Metro Facility- Phase 1 Project Title: 2. Application Type (check all that apply) and Requested Date November 7, 2018 UDC meeting date requested New development □ Alteration to an existing or previously-approved development Informational \boxtimes Initial approval X Final approval 3. Project Type X Signage Project in an Urban Design District Project in the Downtown Core District (DC), Urban Comprehensive Design Review (CDR) Mixed-Use District (UMX), or Mixed-Use Center District (MXC) Signage Variance (i.e. modification of signage height, Project in the Suburban Employment Center District (SEC), area, and setback) Campus Institutional District (CI), or Employment Campus Other District (EC) Please specify Planned Development (PD) General Development Plan (GDP) □ Specific Implementation Plan (SIP) Planned Multi-Use Site or Residential Building Complex 4. Applicant, Agent, and Property Owner Information Stacey Z. Keller, AIA _____ Company ___ Mead & Hunt Applicant name 2440 Deming Way _____ City/State/Zip ___ Middleton, WI 53598 Street address Email stacey.keller@meadhunt.com 608-443-0590 Telephone Project contact person _____ Company _____ _____City/State/Zip _____ Street address Telephone Email Property owner (if not applicant) Jon Evans - City of Madison Engineering 210 Martin Luther King Jr Blvd City/State/Zip Madison WI 53703 Street address 608-243-5893 jevans@cityofmadison.com Telephone Email

5. Required Submittal Materials

Application Form

Letter of Intent

- If the project is within an Urban Design District, a summary of how the development proposal addresses the district criteria is required
- For signage applications, a summary of how the proposed signage is consistent with the applicable CDR or Signage Variance review criteria is required.
- Development plans (Refer to checklist provided below for plan details)

Filing fee

Electronic Submittal*

Both the paper copies and electronic copies <u>must</u> be submitted prior to the application deadline before an application will be scheduled for a UDC meeting. Late materials will not be accepted. A completed application form is required for each UDC appearance.

For projects also requiring Plan Commission approval, applicants must also have submitted an accepted application for Plan Commission consideration prior to obtaining any formal action (initial or final approval) from the UDC. All plans must be legible when reduced.

*Electronic copies of all items submitted in hard copy are required. Individual PDF files of each item submitted should be compiled on a CD or flash drive, or submitted via email to <u>udcapplications@cityofmadison.com</u>. The email must include the project address, project name, and applicant name. Electronic submittals via file hosting services (such as Dropbox.com) are not allowed. Applicants who are unable to provide the materials electronically should contact the Planning Division at (608) 266-4635 for assistance.

6. Applicant Declarations

- 1. Prior to submitting this application, the applicant is required to discuss the proposed project with Urban Design Commission staff. This application was discussed with <u>Janine Glaeser</u> on <u>Sept 29, 2017</u>.
- 2. The applicant attests that all required materials are included in this submittal and understands that if any required information is not provided by the application deadline, the application will not be placed on an Urban Design Commission agenda for consideration.

Applicant name Stacey Z. Keller, AIA	Relationship to property Architect
Authorized signature of Property Owner	

7. Application Filing Fees

Fees are required to be paid with the first application for either initial or final approval of a project, unless the project is part of the combined application process involving the Urban Design Commission in conjunction with Plan Commission and/or Common Council consideration. Make checks payable to City Treasurer. Credit cards may be used for application fees of less than \$1,000.

Please consult the schedule below for the appropriate fee for your request:

X	Urban Design Districts: \$350 (per §35.24(6) MGO).	A filing fee is not required for the following project				
	Minor Alteration in the Downtown Core District (DC) or Urban Mixed-Use District (UMX) : \$150 (per §33.24(6)(b) MGO)	applications if part of the combined application process involving both Urban Design Commission and Plan Commission:				
	Comprehensive Design Review: \$500 (per §31.041(3)(d)(1)(a) MGO)	 Project in the Downtown Core District (DC), Urban Mixed-Use District (UMX), or Mixed-Use Center District (MXC) 				
	Minor Alteration to a Comprehensive Sign Plan: \$100 (per §31.041(3)(d)(1)(c) MGO)	 Project in the Suburban Employment Center District (SEC), Campus Institutional District (CI), or Employment 				
	All other sign requests to the Urban Design	Campus District (EC)				
	Commission, including, but not limited to: appeals from the decisions of the Zoning Administrator, requests for signage variances (i.e. modifications of	 Planned Development (PD): General Development Plan (GDP) and/or Specific Implementation Plan (SIP) 				
	signage height, area, and setback), and additional sign code approvals: \$300 (per §31.041(3)(d)(2) MGO)	 Planned Multi-Use Site or Residential Building Complex 				

Each submittal must include fourteen (14) 11" x 17" collated paper copies. Landscape and Lighting plans (if required) must be full-sized. Please refrain from using plastic covers or spiral binding. The City of Madison's Urban Design Commission (UDC) has been created to:

- Encourage and promote high quality in the design of new buildings, developments, remodeling, and additions so as to maintain and improve the established standards of property values within the City.
- Foster civic pride in the beauty and nobler assets of the City, and in all other ways possible assure a functionally efficient and visually attractive City in the future.

Types of Approvals

There are three types of requests considered by the UDC:

- <u>Informational Presentation</u>. Applicants may, at their discretion, request to make an Informational Presentation to the UDC prior to seeking any approvals to obtain early feedback and direction before undertaking detailed design. Applicants should provide details on the context of the site, design concept, site and building plans, and other relevant information to help the UDC understand the proposal and provide feedback. (Does not apply to CDR's or Signage Variance requests)
- <u>Initial Approval</u>. Applicants may, at their discretion, request initial approval of a proposal by presenting preliminary design information. As part of their review, the Commission will provide feedback on the design information what should be addressed at Final Approval stage.
- <u>Final Approval</u>. Applicants may request Final Approval of a proposal by presenting all final project details. Recommendations or concerns expressed by the UDC in the initial approval must be addressed at this time.

Presentations to the Commission

Primarily, the UDC is interested in the appearance and design quality of projects. Emphasis should be given to the site plan, landscape plan, lighting plan, building elevations, exterior building materials, color scheme, and graphics.

When presenting projects to the UDC, applicants must fill out a registration slip provided in the meeting room and present it to the Secretary. Presentations should generally be limited to 5 minutes or as extended by motion by consent of the Commission. The Commission will withhold questions until the end of the presentation.

Applicants are encouraged to consider the use of various graphic presentation material including a locator map, photographs, renderings/model, scale drawings of the proposal in context with adjacent buildings/uses/signs, etc., as may be deemed appropriate to describe the project and its surroundings. Graphics should be mounted on rigid boards so that they may be easily displayed. Applicants/presenters are responsible for all presentation materials, AV equipment and easels.

URBAN DESIGN DEVELOPMENT PLANS CHECKLIST

The items listed below are minimal application requirements for the type of approval indicated. Please note that the UDC and/ or staff may require additional information in order to have a complete understanding of the project.

1. Informational Presentation

				neq	unemen	Its for All Flatt Sheets	
	Locator Map Letter of Intent (If the project is within a Urban Design District, a summary of <u>how</u> the development proposal addresses the district criteria is required) Contextual site information, including photographs and layout of adjacent buildings/structures Site Plan Two-dimensional (2D) images of proposed buildings or structures.		Providing additional information beyond these minimums may generate a greater level of feedback from the Commission.	1. 2. 3. 4. 5. 6. ** <i>µ</i> the plan	Title b Sheet North Scale, Date Fully c at 1"= <i>Il plans</i> <i>full-size</i> <i>s (if requ</i>	lock number arrow both written and graphic limensioned plans, scaled 40' or larger <i>must be legible, including</i> <i>d landscape and lighting</i> <i>uired</i>)	
2 1							
2. Initial A	pproval						
	Locator Map)		
凶	Letter of Intent (If the project is within a Urban Design District, a summary of <u>how</u> the development proposal addresses the district criteria is required)						
凶	Contextual site information, including pho buildings/structures	nt		Providing additional			

- Site Plan showing location of existing and proposed buildings, walks, drives, bike lanes, bike parking, and existing trees over 18" diameter
- ☑ Landscape Plan and Plant List (*must be legible*)
- Building Elevations in both black & white and color for all building sides (include material callouts)
- D PD text and Letter of Intent (if applicable)

3. Final Approval

All the requirements of the Initial Approval (see above), plus:

- 🛛 Grading Plan
- □ Proposed Signage (if applicable)
- Lighting Plan, including fixture cut sheets and photometrics plan (*must be legible*)
- Utility/HVAC equipment location and screening details (with a rooftop plan if roof-mounted)
- D PD text and Letter of Intent (if applicable)
- Samples of the exterior building materials (presented at the UDC meeting)

4. Comprehensive Design Review (CDR) and Variance Requests (Signage applications only)

- □ Locator Map
- □ Letter of Intent (a summary of <u>how</u> the proposed signage is consistent with the CDR or Signage Variance criteria is required)
- □ Contextual site information, including photographs of existing signage both on site and within proximity to the project site
- □ Site Plan showing the location of existing signage and proposed signage, dimensioned signage setbacks, sidewalks, driveways, and right-of-ways
- □ Proposed signage graphics (fully dimensioned, scaled drawings, including materials and colors, and night view)
- D Perspective renderings (emphasis on pedestrian/automobile scale viewsheds)
- $\hfill\square$ Graphic of the proposed signage as it relates to what the Ch. 31, MGO would permit

Providing additional information beyond these minimums may generate a greater level of feedback from the Commission.



Madison Metro Transit – Service Lane Addtion & Interior Remodeling Project Redevelopment at 1101 East Washington Ave.

Project Narrative

Every day, over 30,000 riders rely on Madison Metro Transit to get to and from work, school, home, and through their daily lives, with over 13 million trips a year. Forty years ago, the 1101 E Washington property was designed to house and maintain 140 buses, but it is now servicing up to 223 buses to meet current ridership with future goals for expansion. The facilities and infrastructure have had no significant updates since its original construction, and nearly all components and workflows are past their useful life or are entirely deficient. This is creating undue hardship and stress on users of the building, resulting in deterioration of the overall work environment. This critical capital investment will be the first of several phases over the next five years that will bring the facility up to current code, increase operational efficiencies, and allow the facility to continue to operate for at least 20 more years.

This current project will provide a new 10,300 sf addition and 13,255 sf of interior remodeling of the existing 277,257 square foot facility. The addition will house two new bus servicing lines, where the buses will receive new fluids and fuel, get vacuumed, have the cash boxes pulled, and then sent through the new automatic bus wash equipment. The interior remodeling areas will provide the support areas for the service line, house equipment to accommodate the new electric buses, relocate some of the services to provide new efficiencies to the maintenance department, remove the old service line, and allow for a new left-hand turn circulation pattern inside the bus storage areas (considered a priority for increasing safety within the facility). This simple solution eliminates the major contributors to vehicle circulation congestion, increases circulation safety, reduces humidity and temperature problems, and isolates pollution/exhaust fumes.

The addition will be constructed to the "plan-south" of the building, aligned with the property line, meeting the 0-foot side-setback requirements of the zoning code. It will match the building in height and be built of pre-cast concrete panels, clad with metal panel and concrete faces to match the existing building. To the "plan-west" of the building, facing the Ingersoll "front entrance" will be (1) Fiber-Reinforced-Panel (FRP) personnel swing-door and (2) high-speed coiling overhead doors consistent with the (4) other existing high-speed coiling overhead doors. The long 292-foot south side will contain numerous Kalwall transom windows to bring in natural light to the service lane staff, as well as break up the expansive façade. This addition will not be visible from the East Washington Avenue street side. Only slivers of the addition will be visible from the "plan-east" side of the building, and it is completely concealed from the Historic Gisholt buildings to the Northeast by the main building proper.

The addition will be built to the current energy codes, with added insulative values. This project will also assist the city to house and service the green, electric bus initiative. Future grant initiatives are also already being planned to provide solar panels on this facility's expansive roof. Therefore, no additional green initiatives are planned for this project at this time.







I omato Pies valures





















East Washington Ave. Looking West















East Washington Ave. Looking North





Ingersoll St. at East Washington Ave. Looking Southeast

























Baldwin St. Looking Southwest



CITY OF MADISON METRO TRANSIT - SERVICE LANE ADDITION SITE CONTEXT 03 OCTOBER 2018



















CITY OF MADISON **METRO TRANSIT - SERVICE LANE ADDITION** EXISTING SITE 03 OCTOBER 2018

	γ











CITY OF MADISON **METRO TRANSIT - SERVICE LANE ADDITION** PROPOSED SITE 03 OCTOBER 2018

10 10 10 1			
	1		9
		\$	
		\$	
		÷	
		\$	













10	11	12	13	14	5 16	17	18 19	20	21	22	23	24	25	26 27
							•							

EXISTING FIRST FLOOR PLAN









A03







PROPOSED FIRST FLOOR PLAN 1/32" = 1'-0"

	27 28	29	30	31 32	33	34	5 36	
	ew Flyer 2000 40 x 7.5	New Flyer 2000 40 x 7.5	New Fyer 2000 40 × 7.5	New Flyer 2000 40 x 7:5	New Flyer 2000 40 x 7.5	Gillig 2004 40 x 8.5		
	Wew Flyer 2000 40 x 7.5 Gillig 2005 40 x 8.5 3	New Flyer 2000 40 x 7.5 Gillig 2005 40 x 8.5	New Flyer 2000 40 x 7.5 Gillig 2005 40 x 8.5	New Flyer 2000 40 x 7.5 Gillig 2005 40 x 8.5	New Flyer 2000 40 x 7.5 Gillig 2005 40 x 8.5	Gillig 2004 40 x 8.5		{c}
	Orion 1989 39 x 8.5	Orion 1989 39 x 8.5	Orion 1989 39 x 8.5	Orion 1989 39 x 8.5	Orion 1989 39 x 8.5	Orion 1989 39 x 8.5		
	Orion 1989 39 x 8.5	Orion 1989 39 x 8.5 Orion 1992 39 x 8.5	Orion 1989 39 x 8.5	Orion/1992 39 x 8.5	Orion 1992 39 x 8.5	Orion 1992 39 x 8.5 Orion 1992 39 x 8.5		E
	Orion 1992 39 x 8.5	Orion 1992 39 x 8.5	Orion 1992 39 x 8.5	Orion 1992 39 x 8.5	Orion 1992 39 x 8.5	Orion 1992 39 x 8.5		
	Orion 1992-39 x 8.5 Orion 1994 39 x 8.5	Orion 1994 39 x 8.5 Orion 1994 39 x 8.5	Orion 1994 39 x 8.5 Orion 1994 39 x 8.5	Orion 1994 39 x 8.5 Orion 1994 39 x 8.5	Orion 1994 39 x 8.5 Orion 1994 39 x 8.5	Orion 1994 39 x 8.5		
	Orion 1994 39 x 8.5	Orion 1994 39 × 8.5 Orion 1994 39 × 8.5	Orion 1994 39 x 8.5 Orion 1994 39 x 8.5	Orion 1994 39 x 8.5 Gillig 1995 40 x 8.5	Orion/1994,39 × 8:5 Gillig 1995 40 × 8.5	Orion 1994 39 x 8.5		
	Gillig 1995 40 x 8.5	Gillig 1995 40 x 8.5	Gillig 1995 40 × 8.5 Gillig 1995 40 × 8.5	Gillig 1995 40 × 8,5	Gillig 1995 40 x 8.5 Gillig 1995 40 x 8.5	Gillig 1995 40 x 8.5	er 2000 40 x 7.5	
	Gillig 1996 40 x 8.5	Gillig 1996 40 x 8.5	Gillig 1996 40 x 8.5	Gillig 1996 40 x 8 5	Gillig 1996 40 x 8.5 Gillig 1996 40 x 8.5	Gillig 1996 40 x 8.5		– —
	Gillig 1997 40 x 8.5 Gillig 1997 40 x 8.5	Gillig 1997 40 x 8.5	Gillig 1997 40 x 8.5 Gillig 1997 40 x 8.5	Gillig 1997 40 x 8 5	Gillig 1997 40 x 8.5	Gillig 1997 40 x 8.5	2000 40 × 7.5	́к
	Gillig 2004 40 x 8.5 Gillig 2005 40 x 8.5	Gillig 2004 40 x 8.5	Gillig 2004 40 x 8.5 Gillig 2005 40 x 8.5	Gillig 2004 40 x 8 5 Gillig 2005 40 x 8 5	Gillig 2004 40 x 8.5 Gillig 2005 40 x 8.5	Gillig 2004 40 x 8 5 Gillig 2005 40 x 8 5		
								► M >
					AC SHOP		FACILITIES STORAGE	↓ N >
4 							- 	j

A02 Stand KUENY ARCHITECTS, LLC























3 SOUTHEAST BUILDING ELEVATION

1 NORTHEAST BUILDING ELEVATION

1 LONGITUDINAL SECTION 3/32" = 1'-0"

SERVICE LANE ROOF 118'-6"

FIRST FLOOR 100'-0"

3 INTERIOR 3D PERSPECTIVE - WASH BAY

2 INTERIOR 3D PERSPECTIVE - VACUUM AREA

	•
	1. A.
	(a) A set of the se
	the second se
	and the second
and the second secon	all a state of the second s
	and the second
A CONTRACT OF	
 A Constraint of the second se Second second sec second second sec	
 A second s	
Contracting and the second se second second sec	
1 A A A A A A A A A A A A A A A A A A A	
and the second	
and the second	
1	
the second se	
A second seco	· · · · · · · · · · · · · · · · · · ·
· · ·	
A second seco	

	•		. • • • • • • • •				
	ta a ta serena a						
e in second de la factoria. En la seconda da la factoria de la seconda de la seconda da la seconda da la seconda da la seconda da la second	11 - Sector Contractor (Sector)						
a di serie de la constante de l La constante de la constante de							

$\frac{1}{2} \sum_{i=1}^{n} \frac{1}{2} \sum_{i=1}^{n-1} $	
	••••••••••••••••••••••••••••
	······································
ante a su Secondario de Secondario de Secondario de Secondario de	

an an an ann an an Arthur. An ann an Arthur an A	
an an an an an an an Arainn. An Arainn an Arainn	•••••
	••••••
	······································
n an tha an	

and a state of the second state of the second s Second second	
an an an an Anna an An An Anna an Anna An Anna an Anna	····
	······
a an	

an an an an ann an an Arraigh. Anns	en e
	· · · · · · · · · · · · · · · · · · ·

	······································
a a tha an	

	••••••
andra andra Alfred Antonio Alfred Antonio Alfred Antonio Alfred Antonio	••••

and the second second second	
	· ···· · · · · · · · · · · · · · · · ·
	······

	1
	e the group of the
•	
·	

an an an an ann an an an ann an Arainn. An Ann an Arainn an Ann an An Ann an Ann	
n an	· ·· · · · · · · · · · · · · · · ·
	••••••••
	······································
, 11. – Alex Alexandro Mariana, ang	
.	

en e
• •••• • • • • • • • • • • • • • • • •
······································

	I
	and the second sec
	1
	en e
e de la companya de l	
and the second secon	· · · · · · · · · · · · · · · · · · ·
· · · · · · · · · · · · · · · · · · ·	•••••
	······································
	۱
· . ·	
1997 - Sector Construction Construction Construction	

A 2.6 OC1 O 10'-0"

▲ 2.7 ▲ 2.9 ▲ 2.7

*^{2.6} OC1^{*2.5}

<mark>▲</mark> 2.6 16'-0"▲ 2.5

<mark>▲</mark>2.5 ▲2.4

<u>^ 2.5</u>

<mark>^</mark>2.5

<mark>^</mark>2.6

<mark>^</mark>2.5

▲ 2.7 ▲ 2.6

•2.8 OC1 10'-0" O-

▲ 2.3 ▲ 2.2

<mark>▲</mark>2.6

. .

<mark>▲</mark>2.7

	<mark>▲</mark> 2.4	▲ 2.3
	▲2.4 OC	▲ 2.3
	16'-0" ^ 2.5)
	<mark>▲</mark> 2.6	▲ 2.5
**	▲ 2.7	▲ 2.6

an an an an ann an an an ann an an an an	
an an taon ang taong taong Taong taong	·····
	······································
an 11 an Art An Antaine Anna Anna Anna Anna Anna Anna An An	·······
· · · · · · · · · · · · · · · · · · ·	

	I
an a	
an an taon ang taong taong Taong taong	
	· · · · · · · · · · · · · · · · · · ·
	·····
an 1997 - Santa S	
anta 1997 - Marian Andrea, ang	

	an a
an an an an ann an an an an an an an an	
	·
anta ang ang ang ang ang ang ang ang ang an	······································

CITY OF MADISON **METRO TRANSIT - SERVICE LANE ADDITION** SITE LIGHTING PLAN 03 OCTOBER 2018

Height:

lighting facts	20

d"s	eries

Specifications

Luminaire

Width:	13-3/4" (34.9 cm)	Weight:	12 lbs (5.4 kg)
Depth:	10" (25.4 cm)		
Height:	6-3/8" (16.2 cm)		

Ordering Information

Back Box (BBW, ELCW) BBW 13-3/4″ 5 lbs Width: Weight: (2.3 kg) (34.9 cm) 4" ELCW 10 lbs Depth: (10.2 cm) Weight: (4.5 kg) 6-3/8"

(16.2 cm)

Catalog Number

Notes

Туре

Introduction

The D-Series Wall luminaire is a stylish, fully integrated LED solution for building-mount applications. It features a sleek, modern design and is carefully engineered to provide long-lasting, energy-efficient lighting with a variety of optical and control options for customized performance.

With an expected service life of over 20 years of nighttime use and up to 74% in energy savings over comparable 250W metal halide luminaires, the D-Series Wall is a reliable, low-maintenance lighting solution that produces sites that are exceptionally illuminated.

EXAMPLE: DSXW1 LED 20C 1000 40K T3M MVOLT DDBTXD

DSXW1	LED								
Series	LEDs	Drive Current	Color tempera	ature	Distribution	Voltage	Mounting	Control Options	
DSXW1	LED (10C) (10 LEDs (one engine) 20C 20 LEDs (two engines) 1	350 350 mA 530 530 mA 700 700 mA 1000 1000 mA (1 A) 1	30K 300 40K 400 50K 500 AMBPC Amt pho conv	10 K 10 K 10 K ber sphor verted	T2SType II ShortT2MType II MediumT3SType III ShortT3MType III MediumT4MType IV MediumTFTMForward Throw MediumASYDFAsymmetric diffuse	MVOLT? 120 3 208 3 240 3 277 3 347 3.4 480 3.4	Shipped included (blank) Surface mounting bracket BBW Surface- mounted back box (for conduit entry) ⁵	Shipped installed PE Photoe DMG 0-10V outside PIR 180° m PIRH 180° m PIRH 180° m PIRH 180° m PIRHIFC3V Motion ambien PIRH1FC3V ElcW	electric cell, button type ⁶ dimming driver (no controls; wires pulled e fixture)) notion/ambient light sensor, <15' mtg ht ¹⁷ notion/ambient light sensor, 15-30' mtg ht ¹⁷ nambient sensor, 8-15' mounting height, nt sensor enabled at 11c ¹⁷ n/ambient sensor, 15-30' mounting height, nt sensor enabled at 11c ¹⁷ ency battery backup (includes external nent enclosure), non CEC compliant ⁸
Other 0	ptions			Finish (req	quired)				
Shippe SF DF HS SPD	ed installed Single fuse (120, 277 or 347 Double fuse (208, 240 or 48 House-side shield ¹⁰ Separate surge protection	Shipped sepa 7V) ^{3,9} BSW Bird-du 10V) ^{3,9} WG Wire g VG Vandal DDL Diffuse	rately ¹⁰ eterrent spikes Jaard guard d drop lens	<mark>DDBXD</mark> DBLXD DNAXD DWHXD	<mark>(Dark bronze)</mark> Black Natural aluminum White	DSSXD DDBTXD DBLBXD DNATXD	Sandstone Textured dark bronze Textured black Textured natural alumin	DWHGXD DSSTXD um	Textured white Textured sandstone
	Accessories	NOTES							

Ordered and shipped separately

DSXWHS U	House-side shield (one pe light engine)
DSXWBSW U	Bird-deterrent spikes
DSXW1WG U	Wire guard accessory
DSXW1VG U	Vandal guard accessory

20C 1000 is not available with PIR, PIRH, PIR1FC3V or PIRH1FC3V.

- MVOLT driver operates on any line voltage from 120-277V (50/60 Hz). 2
- 3 Single fuse (SF) requires 120, 277 or 347 voltage option. Double fuse (DF) requires 208, 240 or 480 voltage option.
- Only available with 20C, 700mA or 1000mA. Not available with PIR or PIRH. 5 Back box ships installed on fixture. Cannot be field installed. Cannot be ordered as an accessory.
- Photocontrol (PE) requires 120, 208, 240, 277 or 347 voltage option. Not available with motion/ambient light sensors (PIR or PIRH). 6

Reference Motion Sensor table on page 3.

Cold weather (x20C) rated. Not compatible with conduit entry applications. Not available with BBW mounting option. Not available with fusing. Not available with 347 or 480 voltage options. Emergency components located in back box housing. Emergency mode IES files located on product page at www.lithonia.com 8

9 Not available with ELCW. 10 Also available as a separate accessory; see Accessories information.

Lumen Output

Lumen values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. Contact factory for performance data on any configurations not shown here.

	Drive	Sustam		3(DK (300	00 K, 70	OCRI)		4(OK (40	00 K, 7	OCRI)			50K (50	000 K, 70	CRI)		AMBP	C (Amber	Phosphor	Converte	ed)
LEDs	Current (mA)	Watts	Туре	Lumens	В	U	G	LPW	Lumens	В	U	G	LPW	Lumens	В	U	G	LPW	Lumens	В	U	G	LPW
			T2S	1,415	0	0	1	109	1,520	0	0	1	117	1,530	0	0	1	118	894	0	0	1	69
			T2M	1,349	0	0	1	104	1,448	0	0	1	111	1,458	0	0	1	112	852	0	0		66
			T3S	1,399	0	0	1	108	1,503	0	0	1	116	1,512	0	0	1	116	884	0	0	1	68
	350mA	<mark>13W</mark>	13M	1,385	0	0	1	107	1,488	0	0	1	114	1,497	0	0	1	115	8/6	0	0	1	6/
			I4M	1,357	0	0	1	104	1,458	0	0	1	112	1,467	0	0		113	858	0	0		66
				1,411	1	0	1	109	1,515	1			104	1,525	0	0	1	11/	892	0	0		69
				2 052	1	0	1	9/	2 205	1	0	1	104	1,303	1	0	1	105	1 764	0	0	1	67
			T23	2,033	1	0	1	100	2,203	1	0	1	110	2,220	1	0	1	111	1,204	0	0	1	63
			T3S	2 031	1	0	1	105	2,102	1	0	1	115	2,113	1	0	1	115	1,205	0	0	1	66
	530 mA	19W	T3M	2,010	1	0	1	105	2,159	1	0	1	114	2,177	1	0	1	114	1,230	0	0	1	65
	550 1111	1211	T4M	1.970	1	0	1	100	2,115	1	0	1	111	2,129	1	0	1	112	1,237	0	0	1	64
100			TFTM	2.047	0	0	1	108	2,198	1	0	1	116	2.212	1	0	1	116	1,260	0	0	1	66
100			ASYDF	1,831	1	0	1	96	1,966	1	0	1	103	1,978	1	0	1	104	1,127	0	0	1	59
			T2S	2,623	1	0	1	101	2,816	1	0	1	108	2,834	1	0	1	109	1,544	0	0	1	59
(10 LEDs)			T2M	2,499	1	0	1	96	2,684	1	0	1	103	2,701	1	0	1	104	1,472	0	0	1	57
			T3S	2,593	1	0	1	100	2,785	1	0	1	107	2,802	1	0	1	108	1,527	0	0	1	59
	700 mA	26W	T3M	2,567	1	0	1	99	2,757	1	0	1	106	2,774	1	0	1	107	1,512	0	0	1	58
			T4M	2,515	1	0	1	97	2,701	1	0	1	104	2,718	1	0	1	105	1,481	0	0	1	57
			TFTM	2,614	1	0	1	101	2,808	1	0	1	108	2,825	1	0	1	109	1,539	0	0	1	59
			ASYDF	2,337	1	0	1	90	2,510	1	0	1	97	2,525	1	0	1	97	1,376	1	0	1	53
			125	3,685	1	0	1	94	3,957	1	0	1	101	3,982	1	0	1	102	2,235	1	0	1	5/
			12M	3,512	1	0	1	90	3,//1	1	0	1	9/	3,/94	1	0	1	9/	2,130	1	0		55
	1000 m A	2011/	135 T2M	3,044		0	1	93	3,913	1	0	1	100	3,938	1	0		101	2,210	1	0		5/
	1000 111A	2200	TAM	2,524	1	0	2	92	2,0/3	1	0	1	99	2 910	1	0	2	00	2,10/	1	0	1	55
			TETM	3,554	1	0	1	91	3,790	1	0	1	101	3,019	1	0	1	102	2,143	1	0	1	57
			ASYDE	3,284	1	0	2	84	3,545	1	0	2	90	3,549	1	0	2	91	1 997	1	0	1	51
			T2S	2.820	1	0	1	123	3.028	1	0	1	132	3.047	1	0	1	132	1,777	1	0	1	77
			T2M	2,688	1	0	1	117	2,886	1	0	1	125	2,904	1	0	1	126	1.693	1	0	1	74
			T3S	2,789	1	0	1	121	2,994	1	0	1	130	3,014	1	0	1	131	1,757	0	0	1	76
	350mA	23W	T3M	2,760	1	0	1	120	2,965	1	0	1	129	2,983	1	0	1	130	1,739	1	0	1	76
			T4M	2,704	1	0	1	118	2,905	1	0	1	126	2,922	1	0	1	127	1,704	1	0	1	74
			TFTM	2,811	1	0	1	122	3,019	1	0	1	131	3,038	1	0	1	132	1,771	0	0		77
			ASYDF	2,514	1	0	1	109	2,699	1	0	1	117	2,716	1	0	1	118	1,584	1	0		69
			T2S	4,079	1	0	1	117	4,380	1	0	1	125	4,407	1	0	1	126	2,504	1	0	1	72
			T2M	3,887	1	0	1	111	4,174	1	0	1	119	4,201	1	0	1	120	2,387	1	0	1	68
	520 A	2514	135	4,033	1	0	1	115	4,331	1	0	1	124	4,359	1	0		125	2,4//	1	0	1	/1
	530 MA	35W	T 4M	3,993		0	2	114	4,288	1	0	2	123	4,315	1	0	2	123	2,451	1	0		10
200			TETM	3,912	1	0	2	112	4,201	1	0	2	120	4,227	1	0	2	121	2,402	1	0	1	71
20C				3 636	1	0	2	104	3 904	1	0	2	112	3 978	1	0	2	1120	2,490	1	0	1	64
			T2S	5 188	1	0	1	113	5 572	1	0	1	12	5,520	1	0	1	172	3.065	1	0	1	67
(20 LEDs)			T20	4.945	1	0	2	108	5,309	1	0	2	115	5,343	1	0	2	116	2 921	1	0	1	64
			T3S	5,131	1	0	2	112	5,510	1	0	2	120	5,544	1	0	2	121	3.031	1	0	1	66
	700 mA	46W	T3M	5,078	1	0	2	110	5,454	1	0	2	119	5,487	1	0	2	119	3,000	1	0	1	65
			T4M	4,975	1	0	2	108	5,343	1	0	2	116	5,376	1	0	2	117	2,939	1	0	1	64
			TFTM	5,172	1	0	2	112	5,554	1	0	2	121	5,589	1	0	2	122	3,055	1	0	1	66
			ASYDF	4,624	1	0	2	101	4,965	1	0	2	108	4,996	1	0	2	109	2,732	1	0	1	59
			T2S	7,204	1	0	2	99	7,736	2	0	2	106	7,784	2	0	2	107	4,429	1	0	1	61
			T2M	6,865	1	0	2	94	7,373	2	0	2	101	7,419	2	0	2	102	4,221	1	0	1	58
			T3S	7,125	1	0	2	98	7,651	1	0	2	105	7,698	1	0	2	105	4,380	1	0	1	60
	1000 mA	73W	T3M	7,052	1	0	2	97	7,573	2	0	2	104	7,620	2	0	2	104	4,335	1	0	2	59
			14M	6,909	1	0	2	95	7,420	1	0	2	102	7,466	1	0	2	102	4,248	1	0	2	58
				7,182		0	2	98	/,/12		0	2	106	/,/61		0	2	106	4,415	1	0	2	60
			ASYDE	6,421	2	0	2	88	6,896	2	0	3	94	6,938	2	0	3	95	3,947		0	2	54

Performance Data

Lumen Ambient Temperature (LAT) Multipliers

Use these factors to determine relative lumen output for average ambient temperatures from 0-40°C (32-104°F).

Amb		Lumen Multiplier
0°C	32°F	1.02
10°C	50°F	1.01
20°C	68°F	1.00
25°C	77°F	1.00
30°C	86°F	1.00
40°C	104°F	0.98

Projected LED Lumen Maintenance

Data references the extrapolated performance projections for the **DSXW1 LED 20C 1000** platform in a **25°C ambient**, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

To calculate LLF, use the lumen maintenance factor that corresponds to the desired number of operating hours below. For other lumen maintenance values, contact factory.

Operating Hours	0	25,000	50,000	100,000
Lumen Maintenance Factor	1.0	0.95	0.93	0.88

Electrical Load

					Curre	nt (A)		
LEDs	Drive Current (mA)	System Watts	120V	208V	240V	277V	347V	480V
	350	14 W	0.13	0.07	0.06	0.06	-	-
100	530	20 W	0.19	0.11	0.09	0.08	-	-
IUC	700	27 W	0.25	0.14	0.13	0.11	-	-
	1000	40 W	0.37	0.21	0.19	0.16	-	-
	350	24 W	0.23	0.13	0.12	0.10	-	-
200	530	36 W	0.33	0.19	0.17	0.14	-	-
200	700	47 W	0.44	0.25	0.22	0.19	0.15	0.11
	1000	74 W	0.69	0.40	0.35	0.30	0.23	0.17

Motion Sensor Default Settings										
Option	Dimmed State	High Level (when triggered)	Photocell Operation	Dwell Time	Ramp-up Time	Ramp-down Time				
*PIR or PIRH	3V (37%) Output	10V (100%) Output	Enabled @ 5FC	5 min	3 sec	5 min				
PIR1FC3V or PIRH1FC3V	3V (37%) Output	10V (100%) Output	Enabled @ 1FC	5 min	3 sec	5 min				

*for use with Inline Dusk to Dawn or timer

To see complete photometric reports or download .ies files for this product, visit Lithonia Lighting's D-Series Wall Size 1 homepage.

Isofootcandle plots for the DSXW1 LED 20C 1000 40K. Distances are in units of mounting height (15').

Photometric Diagrams

4 3 2 1 0 1 2 3 4 Hit Monoreproduct of the second and the second

Distribution overlay comparison to 250W metal halide.

Options and Accessories

T3M (left), ASYDF (right) lenses

Š

HS - House-side shields

BSW - Bird-deterrent spikes

VG - Vandal guard

DDL - Diffused drop lens

FEATURES & SPECIFICATIONS

INTENDED USE

The energy savings, long life and easy-to-install design of the D-Series Wall Size 1 make it the smart choice for building-mounted doorway and pathway illumination for nearly any facility.

CONSTRUCTION

Two-piece die-cast aluminum housing has integral heat sink fins to optimize thermal management through conductive and convective cooling. Modular design allows for ease of maintenance. The LED driver is mounted to the door to thermally isolate it from the light engines for low operating temperature and long life. Housing is completely sealed against moisture and environmental contaminants (IP65).

FINISH

Exterior parts are protected by a zinc-infused Super Durable TGIC thermoset powder coat finish that provides superior resistance to corrosion and weathering. A tightly controlled multi-stage process ensures a minimum 3 mils thickness for a finish that can withstand extreme climate changes without cracking or peeling. Available in textured and non-textured finishes.

OPTICS

Precision-molded proprietary acrylic lenses provide multiple photometric distributions tailored specifically to building mounted applications. Light engines are available in 3000 K (70 min. CRI), 4000 K (70 min. CRI) or 5000 K (70 min. CRI) configurations.

ELECTRICAL

Light engine(s) consist of 10 high-efficacy LEDs mounted to a metal-core circuit board to maximize heat dissipation and promote long life (L88/100,000 hrs at 25°C). Class 1 electronic drivers have a

power factor >90%, THD <20%, and a minimum 2.5KV surge rating. When ordering the SPD option, a separate surge protection device is installed within the luminaire which meets a minimum Category C Low (per ANSI/IEEE C62.41.2).

INSTALLATION

Included universal mounting bracket attaches securely to any 4" round or square outlet box for quick and easy installation. Luminaire has a slotted gasket wireway and attaches to the mounting bracket via corrosion-resistant screws.

LISTINGS

CSA certified to U.S. and Canadian standards. Rated for -40°C minimum ambient.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org to confirm which versions are qualified.

WARRANTY

Five-year limited warranty. Complete warranty terms located at www.acuitybrands.com/ CustomerResources/Terms_and_conditions.aspx.

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

