SHEET NO. 2901 UNIVERSITY AVE PROJECT NO. 11913 D-2 DETAIL ROW ROW RIDGE STREET TYPICAL SECTION CITY OF MADISON 33' REV. 07/30/2018 AJM ADDED TWO TYPICAL SECTIONS 1.50% VARIES** TO REPRESENT VARIOUS TYPES OF WORK REQUIRED FOR THE 5" CONCRETE SIDEWALK -CRUSHED AGGREGATE BASE COURSE (TYP) * CONSTRUCTION OF RIDGE ST. 6" TOPSOIL, SEED & MAT EX. PAVEMENT ASPHALTIC CONCRETE PAVEMENT_\ UPPER LAYER (TYP) EX. BASE COURSE ASPHALTIC CONCRETE PAVEMENT LOWER LAYER (TYP) * TYPE 'A' CONCRETE **CURB & GUTTER** TYPICAL SECTION RIDGE ST ROW ROW 66' STA 102+75 TO STA 103+50 NOT TO SCALE 6'** VARIES** 5" CONCRETE SIDEWALK 6" TOPSOIL SEED & MAT TYPE 'A' CONCRETE EX. PAVEMENT **CURB & GUTTER** 2" MILL AND OVERLAY _EX. BASE COURSE TYP. TYPE 'A" **PAVEMENT** TYPICAL SECTION RIDGE ST ROW ROW STA 103+50 TO STA 104+42 NOT TO SCALE VARIES** 5" CONCRETE SIDEWALK 6" TOPSOIL TYPE 'A' CONCRETE EX. PAVEMENT **CURB & GUTTER** EX. BASE COURSE AGG. DENSE TYPICAL SECTION RIDGE ST STA 104+42 TO STA 104+68 NOT TO SCALE CITY OF MADISON MINIMUM PAVEMENT DESIGN NOTES: CRUSHED AGG. BASE COURSE ASPHALTIC CONCRETE PAVEMENT TYPICAL SECTIONS NOT TO SCALE UPPER LAYER
TYPE THICKNESS LOWER LAYER UPPER LAYER GRADATION 1 GRADATION 2 TYPE * HARVEY AND RIDGE ST TO BE CONSTRUCTED AS TYPE 'A' PAVEMENT PER CITY OF MADISON MINIMUM PAVEMENT DESIGN 4 LT 58-28 S 4 LT 58-28 S 1.75" 1.75" 4 LT 58-28 S 2.50" 4 LT 58-28 S 2.00" В ** SEE CROSS SECTIONS FOR ELEVATIONS, SLOPES AND OFFSETS. 3 MT 58-28 S/H 3.50" 4 MT 58-28 S/H 2.00" 3 HT 58-28 H 4 HT 58-28 H

110/2018 PATE: 1/10/2018

2901 UNIVERSITY AVE PROJECT NO. 11913 D-3


DETAIL

HARVEY ST & UNIVERSITY AVE


TYPICAL SECTION CITY OF MADISON

REV. 07/30/2018 AJM

HARVEY AND UNIVERSITY TYPICAL SECTIONS MOVED TO ANOTHER SHEET



STA 200+93 TO STA 202+74 NOT TO SCALE



CITY OF MADISON MINIMUM PAVEMENT DESIGN

l		CRUSHED AGG. BASE COURSE		ASPHALTIC CONCRETE PAVEMENT			
ı	TYPE	LOWER LAYER	UPPER LAYER	LOWER LAYER		UPPER LAYER	
ı		GRADATION 1	GRADATION 2	TYPE	THICKNESS	TYPE	THICKNESS
l	Α	6"	6"	4 LT 58-28 S	1.75"	4 LT 58-28 S	1.75"
l	В	6"	6"	4 LT 58-28 S	2.50"	4 LT 58-28 S	2.00"
ı	С	6"	6"	3 MT 58-28 S/H	3.50"	4 MT 58-28 S/H	2.00"
ı	_ [3 HT 58-28 H		4 HT 58-28 H	

NOTES:

TYPICAL SECTIONS NOT TO SCALE

- * HARVEY AND RIDGE ST TO BE CONSTRUCTED AS TYPE 'A' PAVEMENT PER CITY OF MADISON MINIMUM PAVEMENT DESIGN
- ** SEE CROSS SECTIONS FOR ELEVATIONS, SLOPES AND OFFSETS.
- *** 5.7' SIDEWALK EASEMENT. SEE RECORDED DOCUMENT NO. 5404546

FILE NAME: M:\DESIGN\Projects\11913\Streets\DesIgn\11913EN-TypSection2.dgn

ATE: 7/31/201

